

Specifications

Portable Traffic Signal

STANDARD CONFIGURATION

Dimensions

Overall

Deployed Height: Pavement to bottom of upper signal head.17' 0"
Deployed Height: Pavement to bottom of lower signal head.10' 0"
Transport Height: Pavement to top of upper signal head.....9' 2"
Transport Height: Pavement to top of lower signal head.....7' 11"
Height: Transport.....9' 9"
Width: At widest point.....8' 3"
Length: Master Trailer with hitch.....14' 5"
Length: Remote Trailer with hitch.....12' 9"
Length: In tandem tow configuration.....25' 4"
Gross Weight: Master.....3,940 lbs.
Gross Weight: Remote.....3,780 lbs.
Distance: Between signal heads.....10' 0"



Features

- Designed to tow in tandem or individually
- Monitors and manages battery consumption
- Wireless programming & operation
- Embedded conflict monitor
- Multi-level pre-emption
- Electric-hydraulic powered mast – one switch to raise and lower mast – one switch to extend and retract signal arm
- 90 mph wind load certified
- Batteries provide 21 day run-time without solar charging
- 110v ac plug-in alternative
- Completely self contained, no external power source required
- Radio-interconnect up to 30 trailers
- Run up to 16 phases of traffic
- Store 20 pre-set signal programs per two trailer system. Create and store your own custom programs
- Wireless Programming via hand-held PDA
- 4 programmable traffic sensor channels per trailer

Available Options

- Microwave, doppler, video, audio & optical sensors
- Back plates
- GPS, remote monitoring
- Flagger/Remote controller
- Pre-emption (emergency vehicle)
- Pilot car operation
- 3rd signal head

Specifications describe standard products. Variations exist to meet particular project requirements. Specifications are subject to change without notice.

Specifications

Portable Traffic Signal

STANDARD CONFIGURATION

Dimensions

Overall

Deployed Height: Pavement to bottom of upper signal head.17' 0"
Deployed Height: Pavement to bottom of lower signal head.10' 0"
Transport Height: Pavement to top of upper signal head.....9' 2"
Transport Height: Pavement to top of lower signal head.....7' 11"
Height: Transport.....9' 9"
Width: At widest point.....8' 3"
Length: Master Trailer with hitch.....14' 5"
Length: Remote Trailer with hitch.....12' 9"
Length: In tandem tow configuration.....25' 4"
Gross Weight: Master.....3,940 lbs.
Gross Weight: Remote.....3,780 lbs.
Distance: Between signal heads.....10' 0"



Features

- Designed to tow in tandem or individually
- Monitors and manages battery consumption
- Wireless programming & operation
- Embedded conflict monitor
- Multi-level pre-emption
- Electric-hydraulic powered mast – one switch to raise and lower mast – one switch to extend and retract signal arm
- 90 mph wind load certified
- Batteries provide 21 day run-time without solar charging
- 110v ac plug-in alternative
- Completely self contained, no external power source required
- Radio-interconnect up to 30 trailers
- Run up to 16 phases of traffic
- Store 20 pre-set signal programs per two trailer system. Create and store your own custom programs
- Wireless Programming via hand-held PDA
- 4 programmable traffic sensor channels per trailer

Available Options

- Microwave, doppler, video, audio & optical sensors
- Back plates
- GPS, remote monitoring
- Flagger/Remote controller
- Pre-emption (emergency vehicle)
- Pilot car operation
- 3rd signal head

Specifications describe standard products. Variations exist to meet particular project requirements. Specifications are subject to change without notice.



Standard Trailer

Steel Control & Battery Boxes

- Lockable
- Metal boxes
- Sealed weatherstripping
- Non-slip treads on top
- Easy control access
- Operator faces oncoming traffic

Galaxy Controller

- Wireless programming & operation
- Easy to set-up and operate
- Standard traffic programs stored & ready to use
- Increase fleet interoperability
- Operate remotely or from a central location
- Control up to 16-phase intersections
- Progressive flow synchronization
- Weather proof enclosure
- Completely portable

Signal Head

- 12" diameter, standard ITE approved
- Rotate and lock in 10° increments
- Two signal head assemblies
- Outer signal head is permanently mounted
- Inner signal head can be mounted over the roadway or at lower position the on mast
- Multiple horizontal & vertical positioning enhance signal visibility
- Arm extension allows signal to be centered on roadway while trailer sits in the clear zone

Mast

- Electro-hydraulic powered 12VDC
- One switch to raise and lower mast
- One switch to extend and retract arm

Batteries & Solar

- 16, 6V, 225 amp-hour deep cycle HD batteries wired in a 12VDC configuration
- 21 day run time without solar recharging
- Six, 85-90W solar panels standard



Wireless Operation - Proven Performance

Trailer Construction & Materials

Key features:

- Heavy-duty, ASTM A500B, structural steel tubing
- Frame, steel tubing size: 4" x 2" x 3/16"
- MIG welds
- Highway Safety Orange powder coat finish (custom colors available)
- Fenders: Bolt-on, heavy-duty, 10-gauge, steel with non-slip treads
- Drop axle
- Heavy-duty swivel jacks
- Electric brakes
- NATM Certified Trailer
- Custom hitch/coupler/pintle sizes available upon request

Wireless Operation Provides Total Control

Our comprehensive, easy-to-use Galaxy controller is capable of driving a single temporary traffic signal or an entire network. Users can program and store everything from simple flagger functions to complex 16-phase intersections.

Key features:

- Wireless programming and operation
- Manages and monitors power consumption of LED signal heads, sensors and radios
- Library of traffic programs installed & ready to apply