

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
PLAN OF PROPOSED IMPROVEMENT

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
1693-47-70	WISC 2013378	1
2718-01-92	WISC 2013379	1
2718-01-93	WISC 2013080	1
2718-09-70	WISC 2013381	1

Section No.	Title
1	Typical Sections and Details
2	Estimate of Quantities
3	Miscellaneous Quantities
4	Right of Way Plat
5	Plan and Profile
6	Standard Detail Drawings
7	Sign Plates
8	Structure Plans
9	Computer Earthwork Data
9	Cross Sections

TOTAL SHEETS = 76

CBD PROPOSED INTERCONNECT SYSTEM
CITY OF WAUKESHA
CMAQ
LOCAL STREET
WAUKESHA COUNTY

STATE PROJECT NUMBER
1693-47-70

PEDESTRIAN COUNTDOWN TIMERS
2 CONNECTING HIGHWAY INTERSECTIONS
CITY OF WAUKESHA
VARIOUS HIGHWAYS
WAUKESHA COUNTY


STATE PROJECT NUMBER
2718-01-93

PEDESTRIAN COUNTDOWN TIMERS
18 LOCAL STREET INTERSECTIONS
CITY OF WAUKESHA
LOCAL STREET
WAUKESHA COUNTY

STATE PROJECT NUMBER
2718-01-92

LED RETROFIT
12 VARIOUS INTERSECTIONS
CITY OF WAUKESHA
NON-HIGHWAY
WAUKESHA COUNTY

STATE PROJECT NUMBER
2718-09-70



LAYOUT
NOT TO SCALE

TOTAL NET LENGTH OF CENTERLINE = 0.000 MI.

"Coordinates on this plan are referenced to the Wisconsin State Plane Coordinate System (WSPCS), South Zone."

DESIGN DESIGNATION	
A.A.D.T.	= VARIOUS
A.A.D.T.	= N/A
D.H.V.	= N/A
D.D.	= N/A
T.	= N/A
DESIGN SPEED	= VARIOUS
ESALS	= N/A

CONVENTIONAL SYMBOLS

PLAN	
CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE	
GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	

ACCEPTED FOR

CITY _____ of _____ WAUKESHA

6/4/13 (Date) [Signature] (Signature)

(Date) (Signature)

ORIGINAL PLANS PREPARED BY
TRAFFIC ANALYSIS & DESIGN, INC.



6-4-13 (Date) [Signature] (Signature)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY

Surveyor CITY OF WAUKESHA

Designer TRAFFIC ANALYSIS & DESIGN, INC.

Management Consultant DAAR ENGINEERING

C.O. Examiner

APPROVED FOR THE DEPARTMENT

DATE: 6-4-13 [Signature] (Management Consultant Signature)

E

STANDARD ABBREVIATIONS

AP	ACCESS POINT	Y	NORTH GRID COORDINATE
AC	ACRE	NB	NORTHBOUND
AH	AHEAD	NO	NUMBER
AC	ASPHALT CEMENT	OD	OUTSIDE DIAMETER
ASPH	ASPHALTIC	PAVT	PAVEMENT
AVG	AVERAGE	PLE	PERMANENT LIMITED EASEMENT
ADT	AVERAGE DAILY TRAFFIC	PT	POINT
BK	BACK	PC	POINT OF CURVATURE
BAD	BASE AGGREGATE DENSE	PI	POINT OF INTERSECTION
BM	BENCH MARK	PT	POINT OF TANGENCY
CB	CATCH BASIN	PVC	POINT OF VERTICAL CURVE
C/L	CENTER LINE	PVI	POINT OF VERTICAL INTERSECTION
C/L CONST	CENTER LINE CONSTRUCTION	PVT	POINT OF VERTICAL TANGENCY
△	CENTRAL ANGLE OR DELTA	PVC	POLYVINYL CHLORIDE
CONC	CONCRETE	PCC	PORTLAND CEMENT CONCRETE
CONST	CONSTRUCTION	LB	POUND
CMCP	CORRUGATED METAL CULVERT PIPE	PSI	POUNDS PER SQUARE INCH
CSCP	CORRUGATED STEEL CULVERT PIPE	PE	PRIVATE ENTRANCE
CSPA	CORRUGATED STEEL PIPE ARCH	PGL	PROFILE GRADE LINE
CTH	COUNTY TRUNK HIGHWAY	PL	PROPERTY LINE
CABC	CRUSHED AGGREGATE BASE COURSE	Q100	100-YEAR FLOW RATE
CFS	CUBIC FEET PER SECOND	R	RADIUS
CY	CUBIC YARD	RR	RAILROAD
CP	CULVERT PIPE	R	RANGE
C & G	CURB AND GUTTER	R/L	REFERENCE LINE
D	DEGREE OF CURVE	RCAEW	REINFORCED CONCRETE APRON ENDWALL FOR CULVERT PIPE
DHV	DESIGN HOUR VOLUME	RCCP	REINFORCED CONCRETE CULVERT PIPE
DIA	DIAMETER	RCHCP	REINFORCED CONCRETE HORIZONTAL ELLIPTICAL CULVERT PIPE
DD	DIRECTIONAL DISTRIBUTION	RCPSS	REINFORCED CONCRETE PIPE STORM SEWER
DWY	DRIVEWAY	REINF	REINFORCING OR REINFORCEMENT
E	EAST	REOD	REQUIRED
X	EAST GRID COORDINATE	RT	RIGHT
EB	EASTBOUND	R/W	RIGHT-OF-WAY
EL	ELEVATION	RD	ROAD
ESALS	EQUIVALENT SINGLE AXLE LOADS	RDWY	ROADWAY
EXC	EXCAVATION	SEC	SECTION
EBS	EXCAVATION BELOW SUBGRADE	SHLDR	SHOULDER
EXIST	EXISTING	S	SOUTH
FERT	FERTILIZE	SB	SOUTHBOUND
FE	FIELD ENTRANCE	SO	SQUARE
FL	FLOW LINE	SF	SQUARE FEET
FT	FOOT	SW	SIDEWALK
GN	GRID NORTH	SY	SQUARE YARD
HES	HIGH EARLY STRENGTH	SDD	STANDARD DETAIL DRAWINGS
HYD	HYDRANT	STH	STATE TRUNK HIGHWAYS
INL	INLET	STA	STATION
ID	INSIDE DIAMETER	SS	STORM SEWER
I	INTERSECTION ANGLE	ST	STREET
INV	INVERT	STR	STRUCTURE OR STRUCTURAL
IP	IRON PIPE OR PIN	SE	SUPERELEVATION
JT	JOINT	T	TANGENT
LT	LEFT	TEMP	TEMPORARY
L	LENGTH OF CURVE	TI	TEMPORARY INTEREST
LF	LINEAR FOOT	TLE	TEMPORARY LIMITED EASEMENT
LS	LUMP SUM	+	TON
MH	MANHOLE	T	TOWN
MPH	MILES PER HOUR	T/L	TRANSIT LINE
MIN	MINIMUM	T	TRUCKS (PERCENT OF)
MON	MONUMENT	TYP	TYPICAL
NOM	NOMINAL	USH	UNITED STATES HIGHWAY
NC	NORMAL CROWN	VAR	VARIABLE
N	NORTH	V	VELOCITY OF DESIGN SPEED
		VERT	VERTICAL
		VC	VERTICAL CURVE
		VOL	VOLUME
		WM	WATER MAIN
		WV	WATER VALVE
		W	WEST
		WB	WESTBOUND
		YD	YARD

CITY OF WAUKESHA
DEPARTMENT OF PUBLIC WORKS
TRAFFIC SIGNALS ENGINEERING DIVISION
130 DELAFIELD STREET
WAUKESHA, WI 53188-3616
MR. MICHAEL F. GRULKE, PE, PTOE
262-524-3590

PROJECT DESIGNER
TRAFFIC ANALYSIS & DESIGN, INC.
N36 W7505 BUCHANAN COURT
CEDARBURG, WI 53012
414-350-2292

UTILITIES

CITY OF WAUKESHA PARKS,
RECREATION AND FORESTRY DEPARTMENT
MR. PETE TRACZEK
1400 AVIATION DRIVE
WAUKESHA, WI 53188
262-524-3710

WE-ENERGIES
MR. DAN SANDE
REGULATORY AND UTILITY ACCOMMODATIONS
333 W. EVERETT STREET, A279
MILWAUKEE, WI 53203
414-221-4578

WE-ENERGIES (GAS)
MR. JOE DABLE
1830 S. WEST AVENUE
WAUKESHA, WIL 53185
262-574-3057

WE-ENERGIES (ELECTRIC)
MR. TERRY CONNELLY
513 W33800 HWY 18
DELAFIELD, WI 53018
262-968-5771

TDS METROCOM
MR. MICHAEL JOHNSON
20875 CROSSROADS CIRCLE, SUITE 800
WAUKESHA, WI 53186
262-754-3052

WAUKESHA WATER UTILITY
MR. THOMAS KRAUSE
115 DELAFIELD STREET
WAUKESHA, WI 53188
262-521-5272

DNR LIAISON

WIS DNR
CRAIG WEBSTER
ENVIRONMENTAL REVIEW SPECIALIST
262-574-2141

AT & T WISCONSIN
MR. TOM CROWLEY
2005 PEWAUKEE ROAD
WAUKESHA, WI 53188
262-896-7427

AT & T LEGACY T/TCG (TCG MILWAUKEE)
MR. DON DIETSCH
282 WILLIAMSTOWNE, SUITE B
DELAFIELD, WI 53018
262-646-5602


TIME WARNER CABLE
MR. STEVE CRAMER
1320 N. MARTIN LUTHER KING DRIVE
MILWAUKEE, WI 53212
414-277-4045

SANITARY SEWER
CITY OF WAUKESHA DEPARTMENT OF PUBLIC WORKS
MR. CHRIS LANGEMAK
130 DELAFIELD STREET
WAUKESHA, WI 53188-3616
262-524-3598

CITY LIGHTING AND CITY FIBER OPTIC
CITY OF WAUKESHA DEPARTMENT OF PUBLIC WORKS
MR. DALE EVANS
130 DELAFIELD STREET
WAUKESHA, WI 53188-3616
262-524-3583

GENERAL NOTES

1. NO SHRUBS OR TREES ARE TO BE REMOVED WITHOUT APPROVAL OF THE ENGINEER.
2. PERMANENT RESTORATION - ANY DISTURBED AREA WITHIN LANDSCAPED AREAS OF THE RIGHT OF WAY SHALL BE FERTILIZED, SEEDED, AND MULCHED. PAYMENT IS INCIDENTAL TO BID ITEM RESULTING IN DISTURBED AREA.
3. ALL OPENINGS OF HOLES BELOW SUBGRADE RESULTING FROM REMOVALS OR ABANDONMENTS SHALL BE BACKFILLED WITH GRANULAR BACKFILL AND HOT ASPHALTIC MIX.
4. RESTORATION OF EXPOSED AREAS SHALL TAKE PLACE IMMEDIATELY AFTER FINISHED GRADING IS COMPLETED.



Call 811 3 Work Days Before You Dig
or Toll Free (800) 242-8511
Hearing Impaired TDD (800) 542-2289
www.DiggersHotline.com

ADDITIONAL PROJECT IDS: 2718-01-92, 2718-01-93, 2718-09-70

PROJECT NO:1693-47-70	HWY:EAST MAIN STREET	COUNTY:WAUKESHA	GENERAL NOTES	SHEET	E
-----------------------	----------------------	-----------------	---------------	-------	---

LEGEND




SEE CABINET DETAIL SHEETS







EXISTING FIBER INTERCONNECT



PROPOSED 4.9 GHz WIRELESS INTERCONNECT








TO NORTH/ST. PAUL
TO DELAFIELD/SUMMIT


F/O SPLICE ENCLOSURE

TO CENTRAL STATION
TO MADISON/ST. PAUL



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.
5. SEE MISCELLANEOUS QUANTITIES FOR WORK BREAKDOWN BETWEEN PROJECT ID'S.



TRAFFIC	CONTROL	SIGNAL
NW BARSTOW ST & BANK ST		
CITY OF WAUKESHA		
WAUKESHA COUNTY		
CONTROLLER TYPE: EPAC		
DESIGNED BY: TAD, INC.		PAGE 1 OF 2

CONTROLLER LOGIC



PHASE NUMBER	PHASE LOCKING	DUAL ENTRY W / Ø	PHASE RECALL	PHASE ACTIVE
1				X
2				X
3				X
4				
5				
6				
7				
8				

O.L. "A" =	1,2
O.L. "B" =	
O.L. "C" =	
O.L. "D" =	

TYPE OF LIGHTING	
BY OTHER AGENCY	
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	


TRAFFIC CONTROL SIGNAL
NW BARSTOW ST & BANK ST
CITY OF WAUKESHA
WAUKESHA COUNTY

PAGE 2 OF 2


RING 2[illegible]

CHART 1

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1	NONE	2,3
2	NONE	1,3
3	NONE	1,2
4		
5		
6		
7		
8		



NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONTROLLER LOGIC

[illegible]

PHASE NUMBER	PHASE LOCKING	DUAL ENTRY W / Ø	PHASE RECALL	PHASE ACTIVE
1				X
2	X	6	MIN.	X
3				
4		8		X
5				
6	X	2	MIN.	X
7				
8		4		X

```
O.L. "A" =
O.L. "B" =
O.L. "C" =
O.L. "D" =
```

<

TYPE OF INTERCONNECT COMMUNICATION		
NONE		
TBC		
CLOSED LOOP TWISTED PAIR*		
CLOSED LOOP FIBER OPTIC*		
RADIO		x

*LOCATION OF MASTER CONTROLLER NO: S-

SIGNAL SYSTEM #:	SS-	-
------------------	-----	---

TYPE OF PRE-EMPT	
NONE	
RAILROAD	
EMERGENCY VEHICLE	
3M	
TOMAR	
HARDWIRE	
OTHER	
LIFT BRIDGE	
QUEUE DETECTOR	

TYPE OF LIGHTING	
BY OTHER AGENCY	
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	

CHART 1

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1	6	2,4,8
2	6	1,4,8
3		
4	8	1,2,6
5		
6	1,2	4,8
7		
8	4	1,2,6

1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1 AT LEFT.)

TRAFFIC CONTROL SIGNAL
N. BARSTOW ST & W. MAIN ST
CITY OF WAUKESHA
WAUKESHA COUNTY

DESIGNED BY: TAD, INC.

PAGE 2 OF 2



NOT TO SCALE

LEGEND

- ☒ CONTROL CABINET
— TRAFFIC SIGNAL CONDUIT
● (XX) SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
● POLE, TYPE 4 WITH 6-FOOT LUMINAIRE ARM
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
✕ LUMINAIRE, MUNICIPAL W/ BASE
⊕ PULL BOX, 12" X 24"
[] VIDEO VEHICLE DETECTION ZONE
[] VIDEO VEHICLE DETECTION CAMERA MOUNTED ON MAST ARM

- SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓢ YELLOW CIRCULAR INDICATOR
Ⓢ GREEN CIRCULAR INDICATOR
Ⓢ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
Ⓢ COMMUNICATIONS RADIO ANTENNA

NOTE: ALL VEHICULAR LENSES ARE 12-INCH GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.
5. SEE MISCELLANEOUS QUANTITIES FOR WORK BREAKDOWN BETWEEN PROJECT ID'S.

SOUTH ST

SOUTH ST

N. BARSTOW ST

N. BARSTOW ST


W. BROADWAY ST

TRAFFIC CONTROL SIGNAL
N. BARSTOW ST & SOUTH ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 3



TRAFFIC CONTROL SIGNAL
N. BARSTOW ST & SOUTH ST
CITY OF WAUKESHA
WAUKESHA COUNTY

DESIGNED BY: TAD, INC.

PAGE 2 OF 3

CONTROLLER LOGIC





CHART 1

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1		
2	NONE	3,4
3	NONE	2,4
4	NONE	2,3
5		
6		
7		
8		

1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1 AT LEFT.)

DESIGNED BY: TAD, INC.

PAGE 3 OF 3



LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
	LUMINAIRE, MUNICIPAL W/ BASE
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	COMMUNICATIONS RADIO ANTENNA
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	YELLOW ARROW
	GREEN ARROW
	WALK/DON'T WALK INDICATOR 12"

NOTE: GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

BARSTOW STREET

WISCONSIN AVENUE

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
WISCONSIN AVE & BARSTOW ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 1693-47-70

HWY: LOCAL ROAD



















COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
	LUMINAIRE, MUNICIPAL W/ BASE
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	COMMUNICATIONS RADIO ANTENNA
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	WALK/DON'T WALK INDICATOR 12"
	YELLOW ARROW
	GREEN ARROW

NOTE: GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

CB1

SB1

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
ST PAUL & NORTH/WISCONSIN
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE:EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO:1693-47-70

HWY:LOCAL ROAD

COUNTY:WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

CONSTRUCTION NOTES:


1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.
5. SEE MISCELLANEOUS QUANTITIES FOR WORK BREAKDOWN BETWEEN PROJECT ID'S.

LEGEND

- ☒ CONTROL CABINET
- TRAFFIC SIGNAL CONDUIT
- SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- (XX) SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- POLE, TYPE 4 WITH 6-FOOT LUMINAIRE ARM
- LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
- ✕ LUMINAIRE, MUNICIPAL W/ BASE
- ⊕ PULL BOX, 12" X 24"
- [] VIDEO VEHICLE DETECTION ZONE
- 📹 VIDEO VEHICLE DETECTION CAMERA MOUNTED ON MAST ARM
- 📡 COMMUNICATIONS RADIO ANTENNA

- SIGNAL HEAD NUMBER
- Ⓡ RED CIRCULAR INDICATOR
- Ⓢ YELLOW CIRCULAR INDICATOR
- Ⓢ GREEN CIRCULAR INDICATOR
- 🚶 WALK/DON'T WALK INDICATOR 12" WITH COUNTDOWN TIMER 12"

NOTE: ALL LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



NOT TO SCALE

TRAFFIC CONTROL SIGNAL
W. MAIN ST & CLINTON ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 2

N

[illegible]

OVERLAPS

O.L. "A" =

O.L. "B" =

O.L. "C" =

O.L. "D" =

TYPE OF INTERCONNECT COMMUNICATION	
NONE	
TBC	
CLOSED LOOP TWISTED PAIR*	
CLOSED LOOP FIBER OPTIC*	
RADIO	x
*LOCATION OF MASTER CONTROLLER NO: S-	
SIGNAL SYSTEM #: SS- -	

TYPE OF PRE-EMPT	
NONE	
RAILROAD	
EMERGENCY VEHICLE	x
3M	
TOMAR	
HARDWIRE	
OTHER	
LIFT BRIDGE	
QUEUE DETECTOR	

TYPE OF LIGHTING	
BY OTHER AGENCY	x
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	

CHART 1

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1		
2	NONE	4
3		
4	NONE	2
5		
6		
7		
8		

GENERAL NOTES:

1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1 AT LEFT.)

TRAFFIC CONTROL SIGNAL
W. MAIN ST & CLINTON ST
CITY OF WAUKESHA
WAUKESHA COUNTY

DESIGNED BY: TAD, INC.

PAGE 2 OF 2

LEGEND

- ☒ CONTROL CABINET
--- TRAFFIC SIGNAL CONDUIT
● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
● POLE, TYPE 4 WITH 6-FOOT LUMINAIRE ARM
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
✱ LUMINAIRE, MUNICIPAL W/ BASE
⊕ PULL BOX, 12" X 24"
[] VIDEO VEHICLE DETECTION ZONE
[] VIDEO VEHICLE DETECTION CAMERA MOUNTED ON MAST ARM
[] SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓢ YELLOW CIRCULAR INDICATOR
Ⓢ GREEN CIRCULAR INDICATOR
[] WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
▶ COMMUNICATIONS RADIO ANTENNA

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.
5. SEE MISCELLANEOUS QUANTITIES FOR WORK BREAKDOWN BETWEEN PROJECT ID'S.

W. MAIN ST

BUCKLEY STREET

W. MAIN ST

EAST AVENUE

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
W. MAIN ST & N. EAST AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 2

PROJECT NO: 1693-47-70, 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

FILE NAME : East at Main.dgn

PLOT DATE : 6/5/2013


PLOT BY : DSCHNABEL-TADI

PLOT NAME :

PLOT SCALE : 20.0000 / in.

WISDOT/CADDs SHEET 42

CONTROLLER LOGIC



PHASE NUMBER	PHASE LOCKING	DUAL ENTRY W / Ø	PHASE RECALL	PHASE ACTIVE
1				X
2				X
3				
4				X
5				
6				
7				
8				

O.L. "A" =	1,2
O.L. "B" =	
O.L. "C" =	
O.L. "D" =	

RING 2	HEAD NUMBERS	Ø5						Ø6						Ø7						Ø8								
		R/W	CLEAR TO				R/W	CLEAR TO				R/W	CLEAR TO				R/W	CLEAR TO										
			✖	✖				✖	✖				✖	✖				✖	✖									
Ø1	1,3,11,12																											
Ø2	7,8,9																											
Ø3																												
Ø4	1,2,3,4,5,6 1RT, 3RT																											
Ø5																												
Ø6																												
Ø7																												
Ø8																												
OLA	10,11,12																											
Ø2P	02 PED HEADS OLA PED HEADS																											
Ø4P	04 PED HEADS																											
Ø8P																												

NOT
USED

TYPE OF PRE-EMPT	
NONE	
RAILROAD	
EMERGENCY VEHICLE	
3M	
TOMAR	
HARDWIRE	
OTHER	
LIFT BRIDGE	
QUEUE DETECTOR	

TYPE OF LIGHTING	
BY OTHER AGENCY	x
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1	NONE	2,4
2	NONE	1,4
3		
4	NONE	1,2
5		
6		
7		
8		


1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1 AT LEFT.)

TRAFFIC CONTROL SIGNAL
W. MAIN ST & N. EAST AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

PAGE 2 OF 2

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.
5. SEE MISCELLANEOUS QUANTITIES FOR WORK BREAKDOWN BETWEEN PROJECT ID'S.



CONTROLLER LOGIC

[illegible]

PHASE NUMBER	PHASE LOCKING	DUAL ENTRY W / Ø	PHASE RECALL	PHASE ACTIVE
1				
2				X
3				
4				X
5				
6				
7				
8				

O.L. "A" =	
O.L. "B" =	
O.L. "C" =	
O.L. "D" =	

TYPE OF INTERCONNECT COMMUNICATION		
NONE		
TBC		
CLOSED LOOP TWISTED PAIR*		
CLOSED LOOP FIBER OPTIC*		
RADIO		x
*LOCATION OF MASTER CONTROLLER NO: S-		
SIGNAL SYSTEM #:	SS-	-

TYPE OF PRE-EMPT	
NONE	
RAILROAD	
EMERGENCY VEHICLE	
3M	
TOMAR	
HARDWIRE	
OTHER	
LIFT BRIDGE	
QUEUE DETECTOR	

TYPE OF LIGHTING	
BY OTHER AGENCY	
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	

GENERAL NOTES:


1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1 AT LEFT.)

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1		
2	NONE	4
3		
4	NONE	2
5		
6		
7		
8		

TRAFFIC CONTROL SIGNAL
N. EAST AVE & ARCADIAN AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

DESIGNED BY: TAD, INC

PAGE 2 OF 2




LEGEND


- ☒ CONTROL CABINET
--- TRAFFIC SIGNAL CONDUIT
● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
● POLE, TYPE 4 WITH 6-FOOT LUMINAIRE ARM
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
✱ LUMINAIRE, MUNICIPAL W/ BASE
⊕ PULL BOX, 12" X 24"
[] VIDEO VEHICLE DETECTION ZONE
[] VIDEO VEHICLE DETECTION CAMERA MOUNTED ON MAST ARM
▶ COMMUNICATIONS RADIO ANTENNA
🚶 WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

- SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓨ YELLOW CIRCULAR INDICATOR
Ⓢ GREEN CIRCULAR INDICATOR

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

NOT TO SCALE





TRAFFIC CONTROL SIGNAL
W. BROADWAY ST & CLINTON ST
CITY OF WAUKESHA
WAUKESHA COUNTY


DESIGNED BY: TAD, INC.

PAGE 2 OF 3

CONTROLLER LOGIC

[illegible]OVERLAPS

O.L. "A" =
O.L. "B" =
O.L. "C" =
O.L. "D" =

		NOT USED						NOT USED						NOT USED											
		Ø5						Ø6						Ø7						Ø8					
		CLEAR TO						CLEAR TO						CLEAR TO						CLEAR TO					
		R/W	✖	✖				R/W	✖	✖				R/W	✖	✖				R/W	✖	✖			
RING 2	Ø1	10,11,12																							
	Ø2	7,8,9,13,14,15																		R	R	R			
	Ø3	2,3																		R	R	R			
	Ø4	4,5,6																		R	R	R			
	Ø5																								
	Ø6																			R	R	R			
	Ø7																								
	Ø8	1,2,3																		G	Y	R			
	Ø1P																			D	D	D			
	Ø2P	18,19,22,23																		D	D	D			
Ø4P	20,21																		D	D	D				
Ø8P	16,17																		*	D	D				

TYPE OF INTERCONNECT COMMUNICATION		
NONE		
TBC		
CLOSED LOOP TWISTED PAIR*		
CLOSED LOOP FIBER OPTIC*		
RADIO		x
*LOCATION OF MASTER CONTROLLER NO: S-		
SIGNAL SYSTEM **	SS-	-

TYPE OF PRE-EMPT	
NONE	
RAILROAD	
EMERGENCY VEHICLE	
3M	
TOMAR	
HARDWIRE	
OTHER	
LIFT BRIDGE	
QUEUE DETECTOR	

TYPE OF LIGHTING	
BY OTHER AGENCY	
IN TRAFFIC SIGNAL CABINET	
IN SEPARATE DOT LIGHTING CABINET	

- ** CLEARANCE TO A PHASE IN CONFLICT WITH THIS PHASE ON (SEE CHART 1)
- * WHEN CALLED, TIMED STEADY WALK, THEN FLASHING DON'T WALK, THEN GOES TO STEADY DON'T WALK

PHASE ON	NONCONFLICTING PHASE ALLOWED TO TIME CONCURRENTLY	PHASES IN CONFLICT WITH PHASE ON
1	NONE	2,3,4,8
2	NONE	1,3,4,8
3	8	1,2,4
4	8	1,2,3
5		
6		
7		
8	4	1,2,3

GENERAL NOTES:

1. ANY ACTUATED PHASE FOR WHICH THERE IS NO CALL SHALL BE SKIPPED.
2. WHEN ONE PHASE IS ON ALONE, ANY NONCONFLICTING PHASE MAY START TIMING CONCURRENTLY WITHOUT A CLEARANCE INTERVAL.
(SEE CHART 1AT LEFT.)

TRAFFIC CONTROL SIGNAL
W. BROADWAY ST & CLINTON ST
CITY OF WAUKESHA
WAUKESHA COUNTY

DESIGNED BY: TAD, INC

PAGE 3 OF 3

LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
	LUMINAIRE, MUNICIPAL W/ BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	COMMUNICATIONS RADIO ANTENNA
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	WALK/DON'T WALK INDICATOR 12"

NOTE: GRAYSHADE REPRESENTS EXISTING


CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.



WISCONSIN AVENUE

CLINTON STREET



NOT TO SCALE

TRAFFIC CONTROL SIGNAL
WISCONSIN AVE & CLINTON ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC


DESIGNED BY: TAD, INC.

PAGE 1 OF 1

LEGEND

- CONTROL CABINET
- NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
- SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- PEDESTRIAN HEAD
- PUSH BUTTON
- PULL BOX, 12" X 24"
- EVP PRE-EMPTOR HEAD
- SIGNAL HEAD NUMBER
- RED CIRCULAR INDICATOR
- YELLOW CIRCULAR INDICATOR
- GREEN CIRCULAR INDICATOR
- WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



- CONSTRUCTION NOTES:
1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
 2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
 3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

TRAFFIC CONTROL SIGNAL
E MAIN STREET & DAVIDSON ROAD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE:EPAC


DESIGNED BY: TAD, INC.

PAGE 1 OF 1

NOT TO SCALE

LEGEND

- ☒ CONTROL CABINET
 - NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
 - ◀● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
 - LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
 - (XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
 - ⌋ PEDESTRIAN HEAD
 - ⊕ PUSH BUTTON
 - ⊕ EVP PRE-EMPTOR HEAD
 - SIGNAL HEAD NUMBER
 - Ⓡ RED CIRCULAR INDICATOR
 - Ⓢ YELLOW CIRCULAR INDICATOR
 - Ⓢ GREEN CIRCULAR INDICATOR
 - 🚶 WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
- NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
S EAST AVENUE & GARFIELD AVENUE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.


PAGE 1 OF 1

LEGEND

- ☒ CONTROL CABINET
--- NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
←● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
⊥ PEDESTRIAN HEAD
⊥ B PUSH BUTTON
⊕ PULL BOX, 12" X 24"
→ EVP PRE-EMPTOR HEAD
□ SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓢ YELLOW CIRCULAR INDICATOR
Ⓣ GREEN CIRCULAR INDICATOR
Ⓢ WALK/DON'T WALK INDICATOR WITH
COUNTDOWN TIMER 16"
NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.



ROBERTA PLAYGROUND

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
S GRAND AVE & ROBERTA PLAYGROUND
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.


PAGE 1 OF 1



LEGEND

	CONTROL CABINET		RED CIRCULAR INDICATOR
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED		YELLOW CIRCULAR INDICATOR
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE		GREEN CIRCULAR INDICATOR
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM		WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE		
	PEDESTRIAN HEAD		
	PUSH BUTTON		
	PULL BOX, 12" X 24"		
	EVP PRE-EMPTOR HEAD		
	SIGNAL HEAD NUMBER		

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

TRAFFIC CONTROL SIGNAL
S GRAND AVE & W SUNSET DR
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET


E



LEGEND

- ☒ CONTROL CABINET
--- NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
└─ PEDESTRIAN HEAD
└─ PUSH BUTTON
⊕ PULL BOX, 12" X 24"
└─ EVP PRE-EMPTOR HEAD
□ SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓢ YELLOW CIRCULAR INDICATOR
Ⓣ GREEN CIRCULAR INDICATOR
Ⓢ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. ALL NEW POLES, BASES, ARMS, SIGNAL HOUSINGS, ETC. SHALL BE BLACK. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.

TRAFFIC CONTROL SIGNAL
S GRANDVIEW BLVD & KENSINGTON DR
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN


















SHEET


E

CONSTRUCTION NOTES:











1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.









MATCH LINE STA 28+20

CONFIGURATION WITH HEAD NUMBERS		
P  13,14 15,16	3-V    1,4,5,7,8 10,11,12	5-VL      2
3-H    6,9	5-HL      3	



LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, PEDESTAL MOUNT
	SIGNAL HEAD, MAST-ARM MOUNT
	PEDESTRIAN HEAD WITH PUSH BUTTON
	LUMINAIRE
	LOOP DETECTOR CONDUIT 1" NONMETALLIC
	LOOP DETECTOR IN 1" NONMETALLIC CONDUIT
	PULL BOX, 24" X 36"
	MOUNTING CONFIGURATION SIGNALS HEAD NUMBER

	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	YELLOW ARROW
	GREEN ARROW
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	EVP PRE-EMPTOR DESIGNATOR
	EVP PRE-EMPTOR HEAD

NOTE: ALL VEHICULAR LENSES ARE 12-INCH, LED
GRAYSHADE REPRESENTS EXISTING




NOT TO SCALE

TRAFFIC CONTROL SIGNAL
GRANDVIEW BLVD & MEADOW LANE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 2



NOT TO SCALE

TRAFFIC CONTROL SIGNAL
GRANDVIEW BLVD & MEADOW LANE
CITY OF WAUKESHA
WAUKESHA COUNTY


DESIGNED BY: TAD, INC.

PAGE 2 OF 2



NOT TO SCALE

5



LEGEND

- CONTROL CABINET
- NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
- (XX) SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- PEDESTRIAN HEAD
- PUSH BUTTON
- PULL BOX, 12" X 24"
- EVP PRE-EMPTOR HEAD
- SIGNAL HEAD NUMBER

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

- (R) RED CIRCULAR INDICATOR
- (Y) YELLOW CIRCULAR INDICATOR
- (G) GREEN CIRCULAR INDICATOR
- (WALKER) WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
N GRANDVIEW BLVD & SILVERNAIL RD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

CONSTRUCTION NOTES:


1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, PEDESTAL MOUNT
	SIGNAL HEAD, MAST-ARM MOUNT
	PEDESTRIAN HEAD WITH PUSH BUTTON
	LUMINAIRE, 150W HPS
	VIDEO DETECTION ZONE
	PULL BOX, 24" X 42"
	PULL BOX, 24" X 36"
	SIGNAL HEAD NUMBER

	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	YELLOW ARROW
	GREEN ARROW
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	EVP PRE-EMPTOR DESIGNATOR
	EVP PRE-EMPTOR HEAD W/CONFIRMATION LIGHT
	VIDEO DETECTION CAMERA

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



TRAFFIC CONTROL SIGNAL
MAIN ST & NIKE/PARAMOUNT DR
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
SILVERNAIL RD & MARSHVIEW ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

FILE NAME : Marshview at Silvernail.dgn

PLOT DATE : 6/5/2013

PLOT BY : DSCHNABEL-TADI

PLOT NAME :


PLOT SCALE : 20.0000 ' / in.

WISDOT/CADDS SHEET 42

LEGEND

- ☒ CONTROL CABINET
- — — — — NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
- LUMINAIRE, MUNICIPAL W/ BASE
- (XX) SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- ⌋ PEDESTRIAN HEAD
- ⌋ B PUSH BUTTON
- ⊕ PULL BOX, 12" X 24"
- ⌋ EVP PRE-EMPTOR HEAD
- SIGNAL HEAD NUMBER
- Ⓡ RED CIRCULAR INDICATOR
- Ⓨ YELLOW CIRCULAR INDICATOR
- ⓐ GREEN CIRCULAR INDICATOR
- Ⓢ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:


1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

TRAFFIC CONTROL SIGNAL		
MEADOWBROOK RD & ROLLING RIDGE DR		
CITY OF WAUKESHA		
WAUKESHA COUNTY		
CONTROLLER TYPE: EPAC		
DESIGNED BY: TAD, INC.	PAGE 1 OF 1	

LEGEND

	CONTROL CABINET		RED CIRCULAR INDICATOR
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED		YELLOW CIRCULAR INDICATOR
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE		GREEN CIRCULAR INDICATOR
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM		WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE		
	PEDESTRIAN HEAD		
	PUSH BUTTON		
	PULL BOX, 12" X 24"		
	EVP PRE-EMPTOR HEAD		
	SIGNAL HEAD NUMBER		

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
SILVERNAIL RD & MEADOWBROOK RD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

FILE NAME : Meadowbrook at Silvernail.dgn

PLOT DATE : 6/5/2013

PLOT BY : DSCHNABEL-TADI

PLOT NAME :

PLOT SCALE : 40.0000' / in.


WISDOT/CADDs SHEET 42



LEGEND

- ☒ CONTROL CABINET
— — — — — NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
◀● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
⊥ PEDESTRIAN HEAD
⊥ B PUSH BUTTON
⊕ PULL BOX, 12" X 24"
→ EVP PRE-EMPTOR HEAD
□ SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓨ YELLOW CIRCULAR INDICATOR
ⓐ GREEN CIRCULAR INDICATOR
Ⓜ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
W MORELAND BLVD & MICHIGAN AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET


E

LEGEND

- ☒ CONTROL CABINET
— — — — — NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
● SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
● LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
(XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
⌋ PEDESTRIAN HEAD
⌋ B PUSH BUTTON
⊕ PULL BOX, 12" X 24"
⌋ → EVP PRE-EMPTOR HEAD

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.



- SIGNAL HEAD NUMBER
Ⓡ RED CIRCULAR INDICATOR
Ⓢ YELLOW CIRCULAR INDICATOR
Ⓤ GREEN CIRCULAR INDICATOR
Ⓢ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
W SUNSET DR & PRAIRIE AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-01-92


HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E





CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
W SUNSET DR & S SENTRY DR
CITY OF WAUKESHA
WAUKESHA COUNTY
CONTROLLER TYPE: EPAC
DESIGNED BY: TAD, INC. PAGE 1 OF 1





CONSTRUCTION NOTES:

- 1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
- 2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
- 3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

LEGEND

- [Symbol] CONTROL CABINET
- [Symbol] NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- [Symbol] SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- [Symbol] LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
- [Symbol] SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- [Symbol] PEDESTRIAN HEAD
- [Symbol] PUSH BUTTON
- [Symbol] PULL BOX, 12" X 24"
- [Symbol] EVP PRE-EMPTOR HEAD
- [Symbol] SIGNAL HEAD NUMBER
- [Symbol] WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
- (R) RED CIRCULAR INDICATOR
- (Y) YELLOW CIRCULAR INDICATOR
- (G) GREEN CIRCULAR INDICATOR

NOTE: ALL VEHICULAR LENSES ARE 12-INCH GRAYSHADE REPRESENTS EXISTING

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
MORELAND BLVD & WHITE ROCK AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1



LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
	LUMINAIRE, MUNICIPAL W/ BASE
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

WASHINGTON AVENUE

DELAFIELD STREET

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
DELAFIELD ST & WASHINGTON AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-09-70

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

FILE NAME : Delafield at Washington.dgn

PLOT DATE : 6/5/2013

PLOT BY : DSCHNABEL-TADI

PLOT NAME :

PLOT SCALE : 20.0000 ' / in.

WISDOT/CADDS SHEET 42

LEGEND


- — — — — NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- — — — — — SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- — — — — — LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
- (XX) ● — — — — — SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- — — — — PEDESTRIAN HEAD
- — — — — PUSH BUTTON
- ⊕ — — — — — PULL BOX, 12" X 24"
- — — — — — EVP PRE-EMPTOR HEAD
- — — — — — SIGNAL HEAD NUMBER

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

- (R) RED CIRCULAR INDICATOR
- (Y) YELLOW CIRCULAR INDICATOR
- (G) GREEN CIRCULAR INDICATOR
- (W) WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
- (Y) YELLOW ARROW
- (G) GREEN ARROW

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.



MADISON STREET

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
GRANDVIEW BLVD & MADISON ST
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE
	LUMINAIRE, MUNICIPAL W/ BASE
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	YELLOW ARROW
	GREEN ARROW

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
GRANDVIEW BLVD & NORTHVIEW RD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

PROJECT NO: 2718-09-70

HWY: LOCAL ROAD

COUNTY: WAUKESHA

TRAFFIC SIGNAL PLAN

SHEET

E

LEGEND

- ☒ CONTROL CABINET
- NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
- SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
- LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
- (XX) ● SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
- ⊥ PEDESTRIAN HEAD
- ⊕ PUSH BUTTON
- ⊕ PULL BOX, 12" X 24"
- EVP PRE-EMPTOR HEAD
- SIGNAL HEAD NUMBER
- (R) RED CIRCULAR INDICATOR
- (Y) YELLOW CIRCULAR INDICATOR
- (G) GREEN CIRCULAR INDICATOR
- ⤴ WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
- (Y) YELLOW ARROW
- (G) GREEN ARROW

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.

N GRANDVIEW BLVD

WOODBURN ROAD

NOT TO SCALE



TRAFFIC CONTROL SIGNAL
GRANDVIEW BLVD & WOODBURN RD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC


DESIGNED BY: TAD, INC.

PAGE 1 OF 1

LEGEND

- | | | | |
|--|--|--|--|
| | CONTROL CABINET | | RED CIRCULAR INDICATOR |
| | NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED | | YELLOW CIRCULAR INDICATOR |
| | SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE | | GREEN CIRCULAR INDICATOR |
| | LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM | | WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16" |
| | SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE | | |
| | PEDESTRIAN HEAD | | |
| | PUSH BUTTON | | |
| | PULL BOX, 12" X 24" | | |
| | EVP PRE-EMPTOR HEAD | | |
| | SIGNAL HEAD NUMBER | | |

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.

TRAFFIC CONTROL SIGNAL
MORELAND BLVD & HINE AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1


NOT TO SCALE



LEGEND

	CONTROL CABINET		RED CIRCULAR INDICATOR
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED		YELLOW CIRCULAR INDICATOR
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE		GREEN CIRCULAR INDICATOR
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM		WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE		
	PEDESTRIAN HEAD		
	PUSH BUTTON		
	PULL BOX, 12" X 24"		
	EVP PRE-EMPTOR HEAD		
	SIGNAL HEAD NUMBER		

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING



CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
E MAIN ST & PERKINS AVE
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1


LEGEND

	CONTROL CABINET
	NONMETALLIC CONDUIT 2", UNLESS OTHERWISE NOTED
	SIGNAL HEAD, TRAFFIC SIGNAL STANDARD, PEDESTAL BASE
	LUMINAIRE, TRAFFIC POLE, TRANSFORMER BASE, 12' LUMINAIRE ARM
	SIGNAL HEAD, TRAFFIC SIGNAL POLE, TRANSFORMER BASE
	PEDESTRIAN HEAD
	PUSH BUTTON
	PULL BOX, 12" X 24"
	EVP PRE-EMPTOR HEAD
	SIGNAL HEAD NUMBER
	RED CIRCULAR INDICATOR
	YELLOW CIRCULAR INDICATOR
	GREEN CIRCULAR INDICATOR
	YELLOW ARROW
	GREEN ARROW
	WALK/DON'T WALK INDICATOR WITH COUNTDOWN TIMER 16"

NOTE: ALL VEHICULAR LENSES ARE 12-INCH
GRAYSHADE REPRESENTS EXISTING

CONSTRUCTION NOTES:

1. THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS ARE APPROXIMATE. THERE ARE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA WHICH ARE NOT SHOWN. THE CONTRACTOR SHALL IDENTIFY ALL LOCATIONS PRIOR TO EXCAVATING AND/OR REMOVING OR ERECTING POLES OR CONCRETE BASES.
2. THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH EXISTING UTILITY FACILITIES.
3. THIS DRAWING IS NOT TO SCALE AND IS A SCHEMATIC REPRESENTATION OF FIELD CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL LOCATIONS PRIOR TO BEGINNING WORK.
4. LOCATIONS OF NEW POLES SHALL BE APPROVED BY THE CITY OF WAUKESHA PRIOR TO CONSTRUCTION.



MORELAND BLVD

NOT TO SCALE

TRAFFIC CONTROL SIGNAL
MORELAND BLVD & PEWAUKEE RD
CITY OF WAUKESHA
WAUKESHA COUNTY

CONTROLLER TYPE: EPAC

DESIGNED BY: TAD, INC.

PAGE 1 OF 1

DATE 11JUN13			E S T I M A T E O F Q U A N T I T I E S					
LINE NUMBER	ITEM	ITEM DESCRIPTION	UNIT	TOTAL	1693-47-70 QUANTITY	2718-01-92 QUANTITY	2718-01-93 QUANTITY	2718-09-70 QUANTITY
0010	204.0195	REMOVING CONCRETE BASES	EACH	36.000	15.000			21.000
0020	619.1000	MOBILIZATION	EACH	1.000	0.360	0.180	0.050	0.410
0030	643.0100	TRAFFIC CONTROL (PROJECT) 01.	1693-47-70 EACH	1.000	1.000			
0040	643.0100	TRAFFIC CONTROL (PROJECT) 02.	2718-01-92 EACH	1.000		1.000		
0050	643.0100	TRAFFIC CONTROL (PROJECT) 03.	2718-01-93 EACH	1.000			1.000	
0060	643.0100	TRAFFIC CONTROL (PROJECT) 04.	2718-09-70 EACH	1.000				1.000
0070	654.0101	CONCRETE BASES TYPE 1	EACH	3.000				3.000
0080	654.0102	CONCRETE BASES TYPE 2	EACH	34.000	15.000			19.000
0090	657.0100	PEDESTAL BASES	EACH	57.000		35.000		22.000
0100	657.0255	TRANSFORMER BASES BREAKAWAY 11 1/2-INCH BOLT CIRCLE	EACH	34.000	15.000			19.000
0110	657.0305	POLES TYPE 2	EACH	13.000				13.000
0120	657.0310	POLES TYPE 3	EACH	3.000				3.000
0130	657.0315	POLES TYPE 4	EACH	18.000	15.000			3.000
0140	657.0425	TRAFFIC SIGNAL STANDARDS ALUMINUM 15-FT	EACH	57.000		35.000		22.000
0150	657.0585	TROMBONE ARMS 15-FT	EACH	7.000				7.000
0160	657.0590	TROMBONE ARMS 20-FT	EACH	9.000				9.000
0170	657.0614	LUMINAIRE ARMS SINGLE MEMBER 4-INCH CLAMP 8-FT	EACH	19.000	15.000			4.000
0180	657.0709	LUMINAIRE ARMS TRUSS TYPE 4-INCH CLAMP 12-FT	EACH	2.000				2.000
0190	658.0110	TRAFFIC SIGNAL FACE 3-12 INCH VERTICAL	EACH	94.000				94.000
0200	658.0120	TRAFFIC SIGNAL FACE 5-12 INCH VERTICAL	EACH	20.000				20.000
0210	658.0155	TRAFFIC SIGNAL FACE 3-12 INCH HORIZONTAL	EACH	25.000				25.000
0220	658.0165	TRAFFIC SIGNAL FACE 5-12 INCH HORIZONTAL	EACH	7.000				7.000
0230	658.0215	BACKPLATES SIGNAL FACE 3 SECTION 12-INCH	EACH	119.000				119.000
0240	658.0225	BACKPLATES SIGNAL FACE 5 SECTION 12-INCH	EACH	27.000				27.000
0250	658.0416	PEDESTRIAN SIGNAL FACE 16-INCH	EACH	206.000		110.000	16.000	80.000
0260	658.0600	LED MODULES 12-INCH RED BALL	EACH	146.000				146.000
0270	658.0605	LED MODULES 12-INCH YELLOW BALL	EACH	146.000				146.000
0280	658.0610	LED MODULES 12-INCH GREEN BALL	EACH	146.000				146.000
0290	658.0620	LED MODULES 12-INCH YELLOW ARROW	EACH	27.000				27.000
0300	658.0625	LED MODULES 12-INCH GREEN ARROW	EACH	27.000				27.000
0310	658.0635	LED MODULES PEDESTRIAN COUNTDOWN TIMER 16-INCH	EACH	206.000		110.000	16.000	80.000
0320	678.0200	FIBER OPTIC SPLICE ENCLOSURE	EACH	1.000	1.000			
0330	678.0300	FIBER OPTIC SPLICE	EACH	6.000	6.000			
0340	678.0500	COMMUNICATION SYSTEM TESTING	LS	1.000	1.000			
0350	ASP.1T0A	ON-THE-JOB TRAINING APPRENTICE AT \$5.00/HR	HRS	150.000	75.000	23.000	7.000	45.000
0360	ASP.1T0G	ON-THE-JOB TRAINING GRADUATE AT \$5.00/HR	HRS	200.000	100.000	30.000	10.000	60.000
0370	SPV.0060	SPECIAL 01. FURNISH AND INSTALL 4.9 GHZ IP WIRELESS RADIO AND ANTENNAS	EACH	15.000	15.000			
0380	SPV.0060	SPECIAL 02. FURNISH AND INSTALL IP SINGLE PORT TERMINAL SERVER	EACH	9.000	9.000			
0390	SPV.0060	SPECIAL 03. FURNISH AND INSTALL ETHERNET SWITCH	EACH	15.000	15.000			
0400	SPV.0060	SPECIAL 04. FURNISH AND INSTALL RS-232 INTERNAL DATA MODEM	EACH	7.000	7.000			
0410	SPV.0060	SPECIAL 05. VIDEO MONITOR	EACH	7.000	7.000			
0420	SPV.0060	SPECIAL 06. LED LUMINAIRES	EACH	6.000				6.000
0430	SPV.0060	SPECIAL 07. UTILITY LINE OPENING	EACH	13.000	7.000			6.000
0440	SPV.0105	SPECIAL 01. VIDEO VEHICLE DET SYS INTERSEC OF BARSTOW AT BANK	LS	1.000	1.000			
0450	SPV.0105	SPECIAL 02. VIDEO VEHICLE DET SYS INTERSEC OF BARSTOW AT MAIN	LS	1.000	1.000			

DATE 11JUN13		E S T I M A T E O F Q U A N T I T I E S						
LINE NUMBER	ITEM	ITEM DESCRIPTION	UNIT	TOTAL	1693-47-70 QUANTITY	2718-01-92 QUANTITY	2718-01-93 QUANTITY	2718-09-70 QUANTITY
0460	SPV. 0105	SPECIAL 03. VIDEO VEHICLE DET SYS INTERSEC OF BARSTOW AT BROADWAY	LS	1.000	1.000			
0470	SPV. 0105	SPECIAL 04. VIDEO VEHICLE DET SYS INTERSEC OF MAIN AT CLINTON	LS	1.000	1.000			
0480	SPV. 0105	SPECIAL 05. VIDEO VEHICLE DET SYS INTERSEC OF EAST AT MAIN	LS	1.000	1.000			
0490	SPV. 0105	SPECIAL 06. VIDEO VEHICLE DET SYS INTERSEC OF EAST AT ARCADIAN	LS	1.000	1.000			
0500	SPV. 0105	SPECIAL 07. VIDEO VEHICLE DET SYS INTERSEC OF BROADWAY/MADISON AT CLINTON	LS	1.000	1.000			
0510	SPV. 0105	SPECIAL 08. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF BARSTOW AT BANK	LS	1.000	1.000			
0520	SPV. 0105	SPECIAL 09. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF BARSTOW AT MAIN	LS	1.000	1.000			
0530	SPV. 0105	SPECIAL 10. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF BARSTOW AT BROADWAY	LS	1.000	1.000			
0540	SPV. 0105	SPECIAL 11. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF MAIN AT CLINTON	LS	1.000	1.000			
0550	SPV. 0105	SPECIAL 12. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF EAST AT MAIN	LS	1.000	1.000			
0560	SPV. 0105	SPECIAL 13. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF EAST AT ARCADIAN	LS	1.000	1.000			
0570	SPV. 0105	SPECIAL 14. MODIFY TRAFFIC SIGNALS FOR CBD INTERSEC OF BROADWAY/MADISON AT CLINTON	LS	1.000	1.000			
0580	SPV. 0105	SPECIAL 15. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN EAST AT BROADWAY	LS	1.000		1.000		
0590	SPV. 0105	SPECIAL 16. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MAIN AT DAVIDSON	LS	1.000		1.000		
0600	SPV. 0105	SPECIAL 17. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN EAST AT GARFIELD	LS	1.000		1.000		
0610	SPV. 0105	SPECIAL 18. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN BARSTOW AT BROADWAY	LS	1.000		1.000		
0620	SPV. 0105	SPECIAL 19. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN EAST AT MAIN	LS	1.000		1.000		
0630	SPV. 0105	SPECIAL 20. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRAND AT ROBERTA PLAYGROUND	LS	1.000		1.000		
0640	SPV. 0105	SPECIAL 21. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRAND AT SUNSET	LS	1.000		1.000		
0650	SPV. 0105	SPECIAL 22. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRANDVIEW AT KENSINGTON	LS	1.000		1.000		
0660	SPV. 0105	SPECIAL 23. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRANDVIEW AT MEADOW	LS	1.000		1.000		
0670	SPV. 0105	SPECIAL 24. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRANDVIEW AT GRANDVIEW PARK	LS	1.000		1.000		
0680	SPV. 0105	SPECIAL 25. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN GRANDVIEW AT SILVERNAIL	LS	1.000		1.000		
0690	SPV. 0105	SPECIAL 26. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MAIN AT NIKE	LS	1.000		1.000		
0700	SPV. 0105	SPECIAL 27. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MARSHVIEW & SILVERNAIL	LS	1.000		1.000		

DATE 11JUN13		E S T I M A T E O F Q U A N T I T I E S				2718-01-92	2718-01-93	2718-09-70
LINE	ITEM	ITEM DESCRIPTION	UNIT	TOTAL	1693-47-70	QUANTITY	QUANTITY	QUANTITY
0710	SPV. 0105	SPECIAL 28. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MEADOWBROOK AT ROLLING RIDGE	LS	1.000		1.000		
0720	SPV. 0105	SPECIAL 29. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MEADOWBROOK AT SILVERNAIL	LS	1.000		1.000		
0730	SPV. 0105	SPECIAL 30. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MORELAND AT MICHIGAN	LS	1.000		1.000		
0740	SPV. 0105	SPECIAL 31. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN SUNSET AT PRAIRIE	LS	1.000		1.000		
0750	SPV. 0105	SPECIAL 32. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN SUNSET AT SENTRY	LS	1.000		1.000		
0760	SPV. 0105	SPECIAL 33. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MORELAND AT WHITE ROCK	LS	1.000			1.000	
0770	SPV. 0105	SPECIAL 34. MOD TRAF SIG & ST LIGHTING FOR LED & COUNTDOWN MORELAND AT ST PAUL	LS	1.000			1.000	
0780	SPV. 0105	SPECIAL 35. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN EAST AT ARCADIAN	LS	1.000				1.000
0790	SPV. 0105	SPECIAL 36. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN BARSTOW AT BANK	LS	1.000				1.000
0800	SPV. 0105	SPECIAL 37. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN BROADWAY/MADISON AT CLINTON	LS	1.000				1.000
0810	SPV. 0105	SPECIAL 38. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN BARSTOW AT MAIN	LS	1.000				1.000
0820	SPV. 0105	SPECIAL 39. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN MAIN AT CLINTON	LS	1.000				1.000
0830	SPV. 0105	SPECIAL 40. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN DELAFIELD AT WASHINGTON	LS	1.000				1.000
0840	SPV. 0105	SPECIAL 41. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN GRANDVIEW AT MADISON	LS	1.000				1.000
0850	SPV. 0105	SPECIAL 42. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN GRANDVIEW AT NORTHVIEW	LS	1.000				1.000
0860	SPV. 0105	SPECIAL 43. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN GRANDVIEW AT WOODBURN	LS	1.000				1.000
0870	SPV. 0105	SPECIAL 44. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN MORELAND AT HINE	LS	1.000				1.000
0880	SPV. 0105	SPECIAL 45. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN MAIN AT PERKINS	LS	1.000				1.000
0890	SPV. 0105	SPECIAL 46. MODIFY TRAFFIC SIGNALS FOR LED & COUNTDOWN MORELAND AT PEWAUKEE	LS	1.000				1.000
0900	SPV. 0105	SPECIAL 47. SIGNAL COMMUNICATIONS HUB	LS	1.000	1.000			

3

CONCRETE BASES		654.0102
LOCATION	SB NO.	CONCRETE BASES TYPE 2 EACH
BARSTOW AT BANK	SB3	1
	SB6	1
SUBTOTAL		2
BARSTOW AT BROADWAY	SB12	1
SUBTOTAL		1
BARSTOW AT MAIN	SB1	1
SUBTOTAL		1
BROADWAY/MADISON AT CLINTON	SB2	1
	SB4	1
	SB7	1
SUBTOTAL		3
EAST AT ARCADIAN	SB2	1
	SB4	1
	SB5	1
SUBTOTAL		3
EAST AT MAIN	SB1	1
SUBTOTAL		1
MAIN AT CLINTON	SB1	1
	SB3	1
	SB5	1
	SB7	1
SUBTOTAL		4
TOTAL		15
(1) NEW BASES REPLACE EXISTING BASES IN SAME LOCATION		

REMOVING CONCRETE BASES			204.0195 REMOVING CONCRETE BASES EACH
LOCATION	SB NO.		
BARSTOW AT BANK	SB3	1	
	SB6	1	
SUBTOTAL			2
BARSTOW AT BROADWAY	SB12	1	
SUBTOTAL			1
BARSTOW AT MAIN	SB1	1	
SUBTOTAL			1
BROADWAY/MADISON AT CLINTON	SB2	1	
	SB4	1	
	SB7	1	
SUBTOTAL			3
EAST AT ARCADIAN	SB2	1	
	SB4	1	
	SB5	1	
SUBTOTAL			3
EAST AT MAIN	SB1	1	
SUBTOTAL			1
MAIN AT CLINTON	SB1	1	
	SB3	1	
	SB5	1	
	SB7	1	
SUBTOTAL			4
TOTAL			15

SIGNAL BASES, POLES, ARMS, AND LUMINAIRES				
LOCATION	SB NO.	657.0255 TRANSFORMER BASES BREAKAWAY 11 1/2-INCH BOLT CIRCLE EACH	657.0315 POLES TYPE 4 EACH	657.0614 LUMINAIRE ARMS SINGLE MEMBER 4-INCH CLAMP 8-FOOT EACH
BARSTOW AT BANK	SB3	1	1	1
	SB6	1	1	1
SUBTOTAL		2	2	2
BARSTOW AT BROADWAY	SB12	1	1	1
SUBTOTAL		1	1	1
BARSTOW AT MAIN	SB1	1	1	1
SUBTOTAL		1	1	1
BROADWAY/MADISON AT CLINTON	SB2	1	1	1
	SB4	1	1	1
	SB7	1	1	1
SUBTOTAL		3	3	3
EAST AT ARCADIAN	SB2	1	1	1
	SB4	1	1	1
	SB5	1	1	1
SUBTOTAL		3	3	3
EAST AT MAIN	SB1	1	1	1
SUBTOTAL		1	1	1
MAIN AT CLINTON	SB1	1	1	1
	SB3	1	1	1
	SB5	1	1	1
	SB7	1	1	1
SUBTOTAL		4	4	4
TOTAL		15	15	15

3

FIBER OPTIC SPLICE		
LOCATION	678.0200 FIBER OPTIC SPLICE ENCLOSURE EACH	678.0300 FIBER OPTIC SPLICE EACH
MADISON/DELAFIELD AT NORTH	1	6
TOTAL	1	6

INTERCONNECT TESTING AND INTEGRATION	
LOCATION	678.0500 COMMUNICATIONS SYSTEM TESTING LS
CENTRAL STATION	1
TOTAL	1

	SPV.0060.05 VIDEO MONITOR	SPV.0105.01 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.02 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.03 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.04 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.05 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.06 VIDEO VEHICLE DETECTION SYSTEM LS	SPV.0105.07 VIDEO VEHICLE DETECTION SYSTEM LS	NOTE
BARSTOW AT BANK	1	1	-	-	-	-	-	-	3 APPROACHES
BARSTOW AT MAIN	1	-	1	-	-	-	-	-	4 APPROACHES
BARSTOW AT BROADWAY	1	-	-	1	-	-	-	-	5 APPROACHES
MAIN AT CLINTON	1	-	-	-	1	-	-	-	4 APPROACHES
EAST AT MAIN	1	-	-	-	-	1	-	-	4 APPROACHES
EAST AT ARCADIAN	1	-	-	-	-	-	1	-	3 APPROACHES
BROADWAY/MADISON AT CLINTON	1	-	-	-	-	-	-	1	5 APPROACHES
TOTAL	7	1	1	1	1	1	1	1	

ALL ITEMS ARE CATEGORY 0010
SHEET 1 OF 2

COMMUNICATIONS EQUIPMENT

LOCATION	SPV.0060.01 FURNISH AND INSTALL 4.9 GHz IP WIRELESS RADIO AND ANTENNAS EACH	SPV.0060.02 FURNISH AND INSTALL IP SINGLE PORT TERMINAL SERVER EACH	SPV.0060.03 FURNISH AND INSTALL ETHERNET SWITCH EACH	SPV.0060.04 FURNISH AND INSTALL RS-232 INTERNAL DATA MODEM EACH	SPV.0105.47 SIGNAL COMMUNICATION HUB LS
DELAFIELD AT SUMMIT (A)	-	-	1	-	-
EAST AT HARTWELL (A)	-	1	1	-	-
CENTRAL STATION (A)	-	1	1	-	1
MADISON/DELAFIELD AT NORTH (C)	-	-	1	-	-
NORTH AT ST PAUL (D)	1	-	1	-	-
ST PAUL AT BARSTOW (E)	1	-	-	-	-
WISCONSIN AT CLINTON (F)	2	-	1	-	-
WISCONSIN AT EAST (F)	2	-	1	-	-
WISCONSIN AT BARSTOW (F)	2	-	1	-	-
BANK AT BARSTOW (H)	1	1	1	1	-
BROADWAY/MADISON AT CLINTON (H)	1	1	1	1	-
MAIN AT CLINTON (H)	1	1	1	1	-
BARSTOW AT MAIN (H)	1	1	1	1	-
BARSTOW AT BROADWAY (H)	1	1	1	1	-
EAST AT MAIN (H)	1	1	1	1	-
EAST AT ARCADIAN (H)	1	1	1	1	-
TOTAL	15	9	15	7	1

MISCELLANEOUS ITEMS

DESCRIPTION	ITEM NUMBER	UNIT	QUANTITY
MOBILIZATION	619.1000	EACH	0.36
TRAFFIC CONTROL (PROJECT)	643.0100	EACH	1

MODIFY TRAFFIC SIGNALS FOR CBD

	SPV.0105.08 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.09 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.10 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.11 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.12 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.13 MODIFY TRAFFIC SIGNALS FOR CBD LS	SPV.0105.14 MODIFY TRAFFIC SIGNALS FOR CBD LS
BARSTOW AT BANK	1	-	-	-	-	-	-
BARSTOW AT MAIN	-	1	-	-	-	-	-
BARSTOW AT BROADWAY	-	-	1	-	-	-	-
MAIN AT CLINTON	-	-	-	1	-	-	-
EAST AT MAIN	-	-	-	-	1	-	-
EAST AT ARCADIAN	-	-	-	-	-	1	-
BROADWAY/MADISON AT CLINTON	-	-	-	-	-	-	1
TOTAL	1	1	1	1	1	1	1

UTILITY LINE OPENINGS

LOCATION	SPV.0060.07 UTLITY LINE OPENING EACH
BARSTOW AT BANK	1
BARSTOW AT BROADWAY	1
BARSTOW AT MAIN	1
BROADWAY/MADISON AT CLINTON	1
EAST AT ARCADIAN	1
EAST AT MAIN	1
MAIN AT CLINTON	1
TOTAL	7

ALL ITEMS ARE CATEGORY 0010
SHEET 2 OF 2

SIGNAL FACES

	658.0416 * PEDESTRIAN SIGNAL FACES 16-INCH	658.0635 * LED MODULES PEDESTRIAN COUNTDOWN TIMER 16-INCH EACH
LOCATION	EACH	EACH
EAST AT BROADWAY	8	8
MAIN AT DAVIDSON	4	4
EAST AT GARFIELD	8	8
BARSTOW AT BROADWAY	10	10
EAST AT MAIN	8	8
GRAND AT ROBERTA PLAYGROUND	2	2
GRAND AT SUNSET	8	8
GRANDVIEW AT KENSINGTON	8	8
GRANDVIEW AT MEADOW	4	4
GRANDVIEW AT GRANDVIEW PARK	2	2
GRANDVIEW AT SILVERNAIL	8	8
MAIN AT NIKE	2	2
MARSHVIEW AT SILVERNAIL	8	8
MEADOWBROOK AT ROLLING RIDGE	8	8
MEADOWBROOK AT SILVERNAIL	2	2
MORELAND AT MICHIGAN	8	8
SUNSET AT PRAIRIE	8	8
SUNSET AT SENTRY	4	4
TOTAL	110	110

* ADDITIONAL QUANTITIES SHOWN ELSEWHERE

SIGNAL BASES, POLES, ARMS, AND LUMINAIRES

		657.0100 * PEDESTAL BASES	657.0425 * TRAFFIC SIGNAL STANDARDS ALUMINUM 15-FT EACH
LOCATION	SB NO.	EACH	
EAST AT BROADWAY	SB3	1	1
	SB12	1	1
SUBTOTAL		2	2
MAIN AT DAVIDSON	SB2	1	1
	SB7	1	1
SUBTOTAL		2	2
EAST AT GARFIELD	SB1	1	1
	SB4	1	1
	SB7	1	1
	SB10	1	1
SUBTOTAL		4	4
GRAND AT ROBERTA PLAYGROUND	SB2	1	1
	SB7	1	1
SUBTOTAL		2	2
GRANDVIEW AT KENSINGTON	SB1	1	1
	SB7	1	1
	SB10	1	1
	SB14	1	1
SUBTOTAL		4	4
GRANDVIEW AT MEADOW	SB1	1	1
	SB5	1	1
SUBTOTAL		2	2
GRANDVIEW AT SILVERNAIL	SB1	1	1
	SB5	1	1
	SB9	1	1
	SB13	1	1
SUBTOTAL		4	4
MAIN AT NIKE	SB2	1	1
SUBTOTAL		1	1
MARSHVIEW AT SILVERNAIL	SB1	1	1
	SB6	1	1
SUBTOTAL		2	2
MEADOWBROOK AT ROLLING RIDGE	SB1	1	1
	SB5	1	1
	SB10	1	1
	SB14	1	1
SUBTOTAL		4	4
MORELAND AT MICHIGAN	SB2	1	1
	SB8	1	1
	SB12	1	1
	SB18	1	1
SUBTOTAL		4	4
SUNSET AT PRAIRIE	SB1	1	1
	SB3	1	1
	SB5	1	1
	SB7	1	1
SUBTOTAL		4	4
TOTAL		35	35

* ADDITIONAL QUANTITIES SHOWN ELSEWHERE

MISCELLANEOUS ITEMS

DESCRIPTION	ITEM NUMBER	UNIT	QUANTITY
MOBILIZATION	619.1000	EACH	0.18
TRAFFIC CONTROL (PROJECT)	643.0100	EACH	1

ALL ITEMS ARE CATEGORY 0010
SHEET 1 OF 2

MODIFY TRAFFIC SIGNALS FOR CBD

	SPV.0105.15 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.16 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.17 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.18 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.19 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.20 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.21 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.22 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.23 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.24 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.25 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.26 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.27 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.28 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.29 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.30 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.31 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.32 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS
EAST AT BROADWAY	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MAIN AT DAVIDSON	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EAST AT GARFIELD	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BARSTOW AT BROADWAY	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-
EAST AT MAIN	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-
GRAND AT ROBERTA PLAYGROUND	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-
GRAND AT SUNSET	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-
GRANDVIEW AT KENSINGTON	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-
GRANDVIEW AT MEADOW	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-
GRANDVIEW AT GRANDVIEW PARK	-	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-
GRANDVIEW AT SILVERNAIL	-	-	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-
MAIN AT NIKE	-	-	-	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-
MARSHVIEW AT SILVERNAIL	-	-	-	-	-	-	-	-	-	-	-	-	1	-	-	-	-	-
MEADOWBROOK AT ROLLING RIDGE	-	-	-	-	-	-	-	-	-	-	-	-	-	1	-	-	-	-
MEADOWBROOK AT SILVERNAIL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1	-	-	-
MORELAND AT MICHIGAN	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1	-	-
SUNSET AT PRAIRIE	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1	-
SUNSET AT SENTRY	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1
TOTAL	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

ALL ITEMS ARE CATEGORY 0010
SHEET 2 OF 2

SIGNAL FACES

	658.0416 * PEDESTRIAN SIGNAL FACES 16-INCH	658.0635 * LED MODULES PEDESTRIAN COUNTDOWN TIMER 16-INCH EACH
LOCATION	EACH	EACH
MORELAND AT WHITE ROCK	8	8
MORELAND AT ST PAUL	8	8
TOTAL	16	16

* ADDITIONAL QUANTITIES SHOWN ELSEWHERE

MODIFY TRAFFIC SIGNALS FOR CBD

	SPV.0105.33 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.34 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS
MORELAND AT WHITE ROCK	1	-
MORELAND AT ST PAUL	-	1
TOTAL	1	1

MISCELLANEOUS ITEMS

DESCRIPTION	ITEM NUMBER	UNIT	QUANTITY
MOBILIZATION	619.1000	EACH	0.05
TRAFFIC CONTROL (PROJECT)	643.0100	EACH	1

ALL ITEMS ARE CATEGORY 0010
SHEET 1 OF 1

CONCRETE BASES			
LOCATION	SB NO.	654.0101 CONCRETE BASES TYPE 1 EACH	654.0102 CONCRETE BASES TYPE 2 EACH
BARSTOW AT BANK	SB4	-	1
	SB7	-	1
SUBTOTAL		0	2
BARSTOW AT MAIN	SB2	-	1
	SB4	-	1
	SB6	-	1
	SB8	-	1
SUBTOTAL		0	4
DELAFIELD AT WASHINGTON	SB6	1	-
SUBTOTAL		1	0
GRANDVIEW AT MADISON	SB3	-	1
	SB5	1	-
	SB6	-	1
	SB10	-	1
	SB12	-	1
	SB13	-	1
SUBTOTAL		1	5
GRANDVIEW AT NORTHVIEW	SB14	1	-
SUBTOTAL		1	0
MORELAND AT HINE	SB3	-	1
	SB6	-	1
	SB11	-	1
	SB15	-	1
SUBTOTAL		0	4
MAIN AT PERKINS	SB3	-	1
	SB5	-	1
SUBTOTAL		0	2
MORELAND AT PEWAUKEE	SB4	-	1
	SB9	-	1
SUBTOTAL		0	2
TOTAL		3	19

(1) NEW BASES REPLACE EXISTING BASES IN SAME LOCATION

REMOVING CONCRETE BASES		
LOCATION	SB NO.	204.0195 REMOVING CONCRETE BASES EACH
BARSTOW AT BANK	SB4	1
	SB7	1
SUBTOTAL		2
BARSTOW AT MAIN	SB2	1
	SB4	1
	SB6	1
	SB8	1
SUBTOTAL		4
DELAFIELD AT WASHINGTON	SB6	1
SUBTOTAL		1
GRANDVIEW AT MADISON	SB3	1
	SB5	1
	SB6	1
	SB10	1
	SB12	1
	SB13	1
SUBTOTAL		6
MORELAND AT HINE	SB3	1
	SB6	1
	SB11	1
	SB15	1
SUBTOTAL		4
MAIN AT PERKINS	SB3	1
	SB5	1
SUBTOTAL		2
MORELAND AT PEWAUKEE	SB4	1
	SB9	1
SUBTOTAL		2
TOTAL		21

MISCELLANEOUS ITEMS			
DESCRIPTION	ITEM NUMBER	UNIT	QUANTITY
MOBILIZATION	619.1000	EACH	0.41
TRAFFIC CONTROL (PROJECT)	643.0100	EACH	1

UTILITY LINE OPENINGS	
LOCATION	SPV.0060.07 UTILITY LINE OPENING EACH
MORELAND AT PEWAUKEE	1
MAIN AT PERKINS	2
GRANDVIEW AT MADISON	3
TOTAL	6

ALL ITEMS ARE CATEGORY 0010
SHEET 1 OF 3

SIGNAL FACES

	658.0110 TRAFFIC SIGNAL FACES 3-12 INCH VERTICAL R-Y-G	658.0120 TRAFFIC SIGNAL FACES 5-12 INCH VERTICAL R-Y-G<Y<-G	658.0155 TRAFFIC SIGNAL FACES 3-12 INCH HORIZONTAL R-Y-G	658.0165 TRAFFIC SIGNAL FACES 5-12 INCH HORIZONTAL R-Y<-Y<-G-G	658.0215 BACKPLATES SIGNAL FACE 3-SECTION 12-INCH	658.0225 BACKPLATES SIGNAL FACE 5-SECTION 12-INCH	658.0416 PEDESTRIAN SIGNAL FACES 16-INCH	658.0600 LED MODULES 12-INCH RED BALL	658.0605 LED MODULES 12-INCH YELLOW BALL	658.0610 LED MODULES 12-INCH GREEN BALL	658.0620 LED MODULES 12-INCH YELLOW ARROW	658.0625 LED MODULES 12-INCH GREEN ARROW	658.0635 LED MODULES PEDESTRIAN COUNTDOWN TIMER 16-INCH EACH
LOCATION	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH
EAST AT ARCADIAN	9	-	-	-	9	-	6	9	9	9	-	-	6
BARSTOW AT BANK	6	1	1	1	7	2	4	9	9	9	2	2	4
BROADWAY/MADISON AT CLINTON	11	2	2	-	13	2	8	15	15	15	2	2	8
BARSTOW AT MAIN	7	1	3	1	10	2	8	12	12	12	2	2	8
MAIN AT CLINTON	12	-	-	-	12	-	8	12	12	12	-	-	8
DELAFIELD AT WASHINGTON	7	-	2	-	9	-	4	9	9	9	-	-	4
GRANDVIEW AT MADISON	5	3	1	3	6	6	8	12	12	12	6	6	8
GRANDVIEW AT NORTHVIEW	4	6	2	2	6	8	6	14	14	14	8	8	6
GRANDVIEW AT WOODBURN	7	4	4	-	11	4	4	15	15	15	4	4	4
MORELAND AT HINE	8	-	4	-	12	-	8	12	12	12	-	-	8
MAIN AT PERKINS	8	-	4	-	12	-	8	12	12	12	-	-	8
MORELAND AT PEWAUKEE	10	3	2	-	12	3	8	15	15	15	3	3	8
TOTAL	94	20	25	7	119	27	80	146	146	146	27	27	80

MODIFY TRAFFIC SIGNALS FOR CBD

	SPV.0105.35 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.36 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.37 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.38 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.39 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.40 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.41 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.42 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.43 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.44 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.45 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS	SPV.0105.46 MODIFY TRAFFIC SIGNALS AND STREET LIGHTING FOR LED & COUNTDOWN LS
EAST AT ARCADIAN	1	-	-	-	-	-	-	-	-	-	-	-
BARSTOW AT BANK	-	1	-	-	-	-	-	-	-	-	-	-
BROADWAY/MADISON AT CLINTON	-	-	1	-	-	-	-	-	-	-	-	-
BARSTOW AT MAIN	-	-	-	1	-	-	-	-	-	-	-	-
MAIN AT CLINTON	-	-	-	-	1	-	-	-	-	-	-	-
DELAFIELD AT WASHINGTON	-	-	-	-	-	1	-	-	-	-	-	-
GRANDVIEW AT MADISON	-	-	-	-	-	-	1	-	-	-	-	-
GRANDVIEW AT NORTHVIEW	-	-	-	-	-	-	-	1	-	-	-	-
GRANDVIEW AT WOODBURN	-	-	-	-	-	-	-	-	1	-	-	-
MORELAND AT HINE	-	-	-	-	-	-	-	-	-	1	-	-
MAIN AT PERKINS	-	-	-	-	-	-	-	-	-	-	1	-
MORELAND AT PEWAUKEE	-	-	-	-	-	-	-	-	-	-	-	1
TOTAL	1	1	1	1	1	1	1	1	1	1	1	1

ALL ITEMS ARE CATEGORY 0010
SHEET 2 OF 3



SIGNAL BASES, POLES, ARMS, AND LUMINAIRES

		657.0100 PEDESTAL BASES	657.0255 TRANSFORMER BASES BREAKAWAY 11 1/2-INCH	657.0305 POLES, TYPE 2	657.0310 POLES, TYPE 3	657.0315 POLES TYPE 4	657.0425 TRAFFIC SIGNAL STANDARDS ALUMINUM 15-FT	657.0585 TROMBONE ARMS, 15-FOOT	657.0590 TROMBONE ARMS, 20-FOOT	SPV.0060.06 LED LUMINAIRES	657.0614 LUMINAIRE ARMS SINGLE MEMBER 4-INCH CLAMP 8-FOOT	657.0709 LUMINAIRE ARMS, TRUSS TYPE, 4-INCH CLAMP, 12-FOOT
LOCATION	SB NO.	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH
BARSTOW AT BANK	SB4	-	1	1	-	-	-	-	1	-	-	-
	SB7	-	1	1	-	-	-	-	1	-	-	-
SUBTOTAL		0	2	2	0	0	0	0	2	0	0	0
BARSTOW AT MAIN	SB2	-	1	1	-	-	-	1	-	-	-	-
	SB3	1	-	-	-	-	1	-	-	-	-	-
	SB4	-	1	1	-	-	-	1	-	-	-	-
	SB5	1	-	-	-	-	1	-	-	-	-	-
	SB6	-	1	1	-	-	-	1	-	-	-	-
	SB7	1	-	-	-	-	1	-	-	-	-	-
	SB8	-	1	1	-	-	-	-	1	-	-	-
SUBTOTAL		3	4	4	0	0	3	3	1	0	0	0
DELAFIELD AT WASHINGTON	SB2	1	-	-	-	-	1	-	-	-	-	-
	SB3	1	-	-	-	-	1	-	-	-	-	-
	SB6	1	-	-	-	-	1	-	-	-	-	-
	SB8	1	-	-	-	-	1	-	-	-	-	-
SUBTOTAL		4	0	0	0	0	4	0	0	0	0	0
GRANDVIEW AT MADISON	SB1	1	-	-	-	-	1	-	-	-	-	-
	SB3	-	1	-	1	-	-	-	1	1	1	-
	SB5	1	-	-	-	-	1	-	-	-	-	-
	SB6	-	1	-	1	-	-	-	1	1	1	-
	SB9	1	-	-	-	-	1	-	-	-	-	-
	SB10	-	1	-	1	-	-	-	1	1	1	-
	SB12	-	1	-	-	1	-	-	-	1	1	-
	SB13	-	1	1	-	-	-	-	1	-	-	-
SUBTOTAL		3	5	1	3	1	3	0	4	4	4	0
GRANDVIEW AT NORTHVIEW	SB14	1	-	-	-	-	1	-	-	-	-	-
SUBTOTAL		1	0	0	0	0	1	0	0	0	0	0
MORELAND AT HINE	SB1	1	-	-	-	-	1	-	-	-	-	-
	SB3	-	1	1	-	-	-	-	1	-	-	-
	SB5	1	-	-	-	-	1	-	-	-	-	-
	SB6	-	1	1	-	-	-	1	-	-	-	-
	SB9	1	-	-	-	-	1	-	-	-	-	-
	SB11	-	1	1	-	-	-	-	1	-	-	-
	SB14	1	-	-	-	-	1	-	-	-	-	-
	SB15	-	1	1	-	-	-	1	-	-	-	-
SUBTOTAL		4	4	4	0	0	4	2	2	0	0	0
MAIN AT PERKINS	SB3	-	1	-	-	1	-	-	-	1	-	1
	SB5	-	1	-	-	1	-	-	-	1	-	1
SUBTOTAL		0	2	0	0	2	0	0	0	2	0	2
MORELAND AT PEWAUKEE	SB1	1	-	-	-	-	1	-	-	-	-	-
	SB2	1	-	-	-	-	1	-	-	-	-	-
	SB3	1	-	-	-	-	1	-	-	-	-	-
	SB4	-	1	1	-	-	-	1	-	-	-	-
	SB5	1	-	-	-	-	1	-	-	-	-	-
	SB6	1	-	-	-	-	1	-	-	-	-	-
	SB7	1	-	-	-	-	1	-	-	-	-	-
	SB9	-	1	1	-	-	-	1	-	-	-	-
	SB10	1	-	-	-	-	1	-	-	-	-	-
SUBTOTAL		7	2	2	0	0	7	2	0	0	0	0
TOTAL		22	19	13	3	3	22	7	9	6	4	2


ALL ITEMS ARE CATEGORY 0010
SHEET 3 OF 3

Standard Detail Drawing List

09B02-07	CONDUIT
09B04-10	PULL BOX
09C02-06	CONCRETE BASES, TYPES 1, 2 & 5
09C03-03	TRANSFORMER/PEDESTAL BASES
09E01-12A	POLE MOUNTINGS FOR TRAFFIC SIGNALS TYPE 2
09E01-12B	POLE MOUNTINGS FOR TRAFFIC SIGNALS AND LIGHTING UNITS, TYPE 3 (HEAVY DUTY)
09E01-12C	POLE MOUNTINGS FOR TRAFFIC SIGNALS AND LIGHTING UNITS, TYPE 4
09E01-12G	HARDWARE DETAILS FOR POLE MOUNTINGS
09E03-04	NON-FREEWAY LIGHTING UNIT POLE WIRING
09E06-04	TRAFFIC SIGNAL STANDARD POLY BRACKET MOUNTINGS (TYPICAL) 13 FT. OR 15 FT.
09E07-05	TRAFFIC SIGNAL STANDARD PEDESTRIAN AND FLASHER TYPICAL MOUNTING DETAILS
15C12-03	TRAFFIC CONTROL FOR LANE CLOSURE (SUITABLE FOR MOVING OPERATIONS)
15D20-01	TRAFFIC CONTROL, SINGLE LANE CLOSURE, NON-FREEWAY/EXPRESSWAY



ALL CONDUIT RUNS SHALL BE STRAIGHT (WITHOUT BENDS) FROM PULL BOX TO PULL BOX, PULL BOX TO BASE AND BASE TO BASE AS SHOWN ON THE PLANS.



SIDE ELEVATION
DETAIL FOR CONDUIT UNDER PAVED HIGHWAYS

CONDUIT	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED <u>10/23/03</u> DATE	<u>/S/ Balu Ananthanarayanan</u> STATE ELECTRICAL ENGINEER FOR HWYS
FHWA	

TABLE OF NOMINAL DIMENSIONS AND WEIGHTS

DIMENSION IN INCHES		CORRUGATED STEEL PIPE								
PIPE DIAMETER (INSIDE)	A	12	12	12	18	18	18	24	24	24
PIPE LENGTH **	B	24	30	36	24	30	36	36	42	48
WALL THICKNESS	C	0.064	0.064	0.064	0.064	0.064	0.064	0.064	0.064	0.064
COVER	D	10 1/4	10 1/4	10 1/4	16 1/4	16 1/4	16 1/4	22 1/4	22 1/4	22 1/4
FRAME	E	14 1/2	14 1/2	14 1/2	20 1/2	20 1/2	20 1/2	26 1/2	26 1/2	26 1/2
FRAME	F	8 1/2	8 1/2	8 1/2	14 1/2	14 1/2	14 1/2	20 1/2	20 1/2	20 1/2
FRAME	G	11 1/2	11 1/2	11 1/2	17 1/2	17 1/2	17 1/2	23 1/2	23 1/2	23 1/2
WEIGHT IN POUNDS *										
FRAME AND COVER		60	60	60	110	110	110	155	155	155

* THE ACTUAL WEIGHT OF THE MANHOLE FRAME AND COVER MAY VARY WITHIN 5 PERCENT PLUS OR MINUS OF THE WEIGHTS SHOWN.

** NORMALLY USED LENGTHS. THE PROJECT ENGINEER SHALL DETERMINE IF PIPE LENGTHS, OTHER THAN THOSE SPECIFIED, SHALL BE USED, TO A MAXIMUM OF 48" (CONTINUOUS LENGTH, NON-SPLICED). THE ADDITIONAL LENGTH SHALL BE INCIDENTAL TO THE PULL BOX BID PRICE.

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

ALL FRAMES AND COVERS SHALL BE HEAVY DUTY TYPE, SUITABLE FOR VEHICULAR TRAFFIC LOADS.

PULL BOXES LOCATED IN THE ROADWAYS SHALL HAVE LOCKING COVERS.

ENTRANCE HOLES INTO PULL BOXES SHALL BE CUT WITH A CIRCULAR HOLE SAW OR HYDRAULIC CONDUIT PUNCH. HOLE SIZE SHALL BE THE OUTSIDE DIAMETER OF THE CONDUIT THAT IS TO FIT IN THE OPENING PLUS NO MORE THAN 1/4".

THE CONTRACTOR SHALL NOT INSTALL WIRE IN ANY PULL BOX UNTIL ITS INSTALLATION HAS BEEN INSPECTED AND ACCEPTED BY THE ENGINEER.







GROUNDING LUGS (MECHANICAL CONNECTORS) SHALL BE U.L. LISTED AND APPROVED FOR USE WITH COPPER WIRE.

GROUNDING LUGS ARE NOT REQUIRED IN PULL BOXES WHEN VOLTAGES OF LESS THAN 50 VOLTS AC ARE THE ONLY VOLTAGES ENCOUNTERED IN THE BOXES.

ALL METALLIC CONDUIT IN WHICH WIRE AND/OR CABLE IS TO BE INSTALLED, SHALL BE BUSHED BEFORE INSTALLATION OF THE WIRE AND/OR CABLE.


S.D.D. 9B2, "CONDUIT", APPLIES TO THIS DRAWING.

WHEN PULL BOXES ARE INSTALLED FOR FUTURE USE, DO NOT INSTALL THE EQUIPMENT GROUNDING LUG. THE EQUIPMENT GROUNDING LUG, THE EQUIPMENT GROUNDING ELECTRODE AND THE EQUIPMENT GROUNDING CONDUCTOR SHALL BE REQUIRED AND INSTALLED UNDER A FUTURE WIRING CONTRACT.



PULL BOX	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 2-7-2013 DATE	/S/ Ahmet Demirbilek STATE ELECTRICAL ENGINEER
FHWA	

FORM DEPTH SHALL BE NO MORE THAN 6" BELOW GRADE ON THE LOWER SIDE OF BASE



FORMING DETAIL

QUANTITY REQUIREMENTS	CONCRETE BASE TYPE		
	1	2	5
APPROX. CUBIC YARDS OF CONCRETE	0.40	0.57	0.40
LBS. OF HOOP BAR STEEL	NONE	23	16
LBS. OF VERTICAL BAR STEEL	NONE	60	18

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

BASES SHALL BE EXCAVATED BY USE OF A CIRCULAR AUGER.

TOP SURFACES OF CONCRETE BASES SHALL BE TROWEL FINISHED SMOOTH AND LEVEL.

CONDUIT SIZES AND LOCATIONS SHALL BE AS SHOWN ON THE PLANS.

THE FINAL OR TERMINATING CONCRETE BASE IN A CONDUIT RUN SHALL HAVE A 6" EXIT STUB INSTALLED FOR FUTURE CABLING USE. THE EXIT STUB SHALL BE SIZED AS USED THROUGHOUT THE CONDUIT RUN AS SHOWN AT THE ENTRANCE OF THE BASE.

MINIMUM BENDING RADIUS OF CONDUIT IS EQUAL TO 6 X THE DIAMETER.

CONDUIT HEIGHT ABOVE CONCRETE BASES SHALL BE 1 INCH. ALL METALLIC CONDUIT ENDS SHALL BE REAMED AND THREADED.

ALL CONDUIT ENDS AT THE TOP OF CONCRETE BASES SHALL BE CAPPED IF METALLIC OR PLUGGED IF NONMETALLIC IMMEDIATELY AFTER PLACEMENT AND BEFORE CONCRETE IS POURED. CONDUITS IN WHICH WIRE OR CABLE IS NOT INSTALLED SHALL REMAIN CAPPED OR PLUGGED.

GENERAL NOTES (CONTINUED)

BELL ENDS SHALL BE INSTALLED ON ALL PVC CONDUIT EXPOSED AT THE TOP OF CONCRETE BASES BEFORE INSTALLATION OF CABLE OR WIRE.

ENDS OF CONDUIT INSTALLED BELOW GRADE FOR FUTURE USE SHALL BE CAPPED IF METALLIC OR PLUGGED IF NONMETALLIC.

WHEN REQUIRED TO CONNECT NONMETALLIC CONDUIT TO METALLIC CONDUIT, ONLY ADAPTER FITTINGS, U.L. LISTED FOR ELECTRICAL USE, SHALL BE USED.

IF A BASE REQUIRES A DEEP FORM BECAUSE OF LOOSE DIRT OR FILL, THE FORM SHALL BE REMOVED BEFORE BACKFILLING AROUND THE BASE. BACKFILL SHALL BE TAMPED TIGHT AGAINST THE BARE CONCRETE BASE IN LAYERS OF 1 FOOT OR LESS.

A NO. 4 AWG, STRANDED COPPER EQUIPMENT GROUNDING CONDUCTOR SHALL BE EXOTHERMICALLY WELDED TO THE EQUIPMENT GROUNDING ELECTRODE (GROUND ROD) FOR TYPE 2 AND TYPE 5 BASES.

THE EQUIPMENT GROUNDING CONDUCTOR SHALL BE FURNISHED AND INSTALLED TO ENTER THE BASE OF THE TYPE 2 AND TYPE 5 BASES THROUGH A 1 INCH CONDUIT INSTALLED FOR GROUNDING PURPOSES, LEAVING A 4 FOOT COIL OF WIRE ABOVE THE CONCRETE BASE. THE EQUIPMENT GROUNDING CONDUCTOR SHALL BE NEATLY COILED AND THE COILS TIED TOGETHER.

ANCHOR RODS SHALL BE THREADED 12" IN LENGTH ON EACH END OF THE ROD, ANCHOR RODS SHALL BE MANUFACTURED IN ACCORDANCE WITH SECTION 654.2.1 AND 641.2.2 OF THE STANDARD SPECIFICATIONS, ASTM A-449, OR ASTM A-687 (GRADE 105).

WASHERS AND LOCK WASHERS ARE REQUIRED ON ALL ANCHOR RODS.


WHEN ANCHOR RODS USING THE ALTERNATE "L" BEND ARE FURNISHED, THE 4" "L" BEND SHALL BE IN ADDITION TO THE SPECIFIED ANCHOR ROD BAR LENGTH. THE "L" BEND END SHALL NOT BE THREADED.

ANCHOR RODS SHALL BE INSTALLED WITH MISALIGNMENTS OF LESS THAN 1:40 FROM VERTICAL.


WELDING OF THE ANCHOR RODS TO THE CAGE IS UNACCEPTABLE. TIE WIRES SHALL BE USED.

BAR STEEL REINFORCEMENT SHALL BE COATED WITH POWDERED EPOXY RESIN IN ACCORDANCE WITH SECTION 505 OF THE STANDARD SPECIFICATIONS (LATEST EDITION).



- 1 THE MINIMUM DEPTH OF CONDUIT EXITING THE CONCRETE BASE AND INSTALLED BELOW THE TRAVELED WAY SHALL BE 24 INCHES. THE MINIMUM DEPTH OF CONDUIT EXITING THE CONCRETE BASE THAT IS NOT INSTALLED BELOW THE TRAVELED WAY SHALL BE 18 INCHES. THE MAXIMUM DEPTH OF ALL CONDUIT SHALL BE 36 INCHES EXCEPT WITH WRITTEN APPROVAL BY THE ENGINEER.
- 2 (4) 1" DIA. X 3'-6" ANCHOR RODS.
- 3 (4) 1" DIA. X 5'-0" ANCHOR RODS.
- 4 (6) NO. 6 X 6'-8" BAR STEEL REINFORCEMENT.
- 5 (7) NO. 4 X 5'-1" BAR STEEL REINFORCEMENT @ 1'-0" C-C.
- 6 (4) 1" DIA. X 3'-6" ANCHOR RODS.
- 7 (6) NO. 4 X 4'-8" BAR STEEL REINFORCEMENT.
- 8 (5) NO. 4 X 5'-1" BAR STEEL REINFORCEMENT @ 1'-0" C-C.





HALF SECTION IN UNPAVED AREA (TYPICAL FOR TYPES 1, 2 & 5)



TYPE 1



TYPE 2



TYPE 5

CONCRETE BASES

* ANY ANCHOR ROD PROJECTION SHORTER THAN 2 3/4" OR LONGER THAN 3 1/4" SHALL REQUIRE THE BASE TO BE REMOVED AND REPLACED AT THE CONTRACTORS EXPENSE.

** FOR NONBREAKAWAY INSTALLATIONS, 4 1/2" ± ANCHOR ROD PROJECTION WITH THE USE OF LEVELING NUTS. RODENT SCREEN REQUIRED.

CONCRETE BASES, TYPES 1, 2 & 5

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

3/3/10

DATE

FHWA

/S/ Joanna L. Bush

STATE ELECTRICAL ENGINEER FOR HWYS

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

FOUR (4) BOLTS SHALL BE FURNISHED WITH EACH TRANSFORMER BASE. BOLTS SHALL BE 1" DIAMETER, 4" IN LENGTH, WITH WASHERS, LOCK WASHERS AND NUTS. BOLTS, NUTS AND WASHERS SHALL BE MANUFACTURED IN ACCORDANCE WITH SECTION 641.2.2 OF THE STANDARD SPECIFICATIONS, ASTM A-325, (92,000 YIELD) HEAVY HEX NUT AND BE GALVANIZED IN ACCORDANCE WITH ASTM A-153, CLASS C.

LEVELING SHIMS, IF NEEDED, SHALL BE DESIGNED FOR THE PURPOSE AND USED UNDER CAST BASES WHEN PLUMBING POLES OR STANDARDS DURING INSTALLATION. THE USE OF WASHERS IN LIEU OF PROPER LEVELING SHIMS IS NOT ACCEPTABLE.

SHIM LENGTH SHALL BE LONG ENOUGH TO COMPLETELY COVER THE AREA UNDER THE LENGTH AND WIDTH OF THE BASE MOUNTING FLANGE.

DOUBLE NUTTING IS NOT ACCEPTABLE FOR LEVELING OR MOUNTING PURPOSES.

A NEMA APPROVED AND U.L. LISTED MECHANICAL CONNECTOR (LUG) AL/CU RATED AND SIZED TO ACCEPT #10 AWG STRANDED WIRE, SHALL BE FURNISHED AND INSTALLED IN THE PEDESTAL AND TRANSFORMER BASES.



THE MECHANICAL CONNECTOR SHALL BE INSTALLED USING A 1/4" - 20 (TPI) STAINLESS STEEL HEX HEAD BOLT OF SUFFICIENT LENGTH TO FIRMLY ATTACH THE LUG TO THE BASE.

SHOULD THE MANNER OF ATTACHMENT OF THE LUG REQUIRE WASHERS, HEX NUTS, LOCK WASHER - THEY SHALL BE STAINLESS STEEL AS IS THE BOLT. THE MANNER OF ATTACHMENT SHALL NOT BLOCK ACCESSIBILITY TO WIRE PLACEMENT IN THE CONNECTOR.

PEDESTAL BASE COLLAR THREADING SHALL BE TAPERED AND IN ACCORDANCE WITH NATIONAL PIPE THREADING DIMENSIONS.

BASE COLLAR THREADING SHALL EXTEND INTO THE BASE COLLAR WITH SUFFICIENT DEPTH TO ACCEPT THE INSTALLATION OF TRAFFIC SIGNAL STANDARDS TO A DEPTH OF 1 1/2", THEN TIGHTENING TO A POINT OF BEING IMMOVABLE.

THE ACCESS DOOR SHALL BE OF THE SAME MATERIAL AS THE BASE.




TYPICAL MECHANICAL
CONNECTOR LUG
TO BE FURNISHED WITH EACH BASE

TRANSFORMER BASE
INTENDED FOR USE WITH TYPE 2, 3, 4, 5 & 6 POLES

TRANSFORMER/PEDESTAL BASES


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/27/09
DATE /S/ Joanna L. Bush
STATE ELECTRICAL ENGINEER FOR HWYS
FHWA



HORIZONTAL SIGNAL HEAD MOUNTING DETAIL *


* SIGNAL HEAD ATTACHMENT ALSO APPLYS TO MOUNTING AT CROSS BAR



SECTION A-A

(10 DEGREES TILT REQUIREMENT OF
FACE(S) IN THE TROMBONE MOUNTING)

CONDUIT NIPPLE
1 1/2" I.D.
LENGTH PER STANDARD
SPECIFICATION
(SEE SECTION 658)



SIGNAL FACE MOUNTING DETAIL (BANDED)

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

POLES SHALL BE EITHER ALUMINUM OR GALVANIZED STEEL AS CALLED FOR IN THE CONTRACT.

SECTION 657, POLES, OF THE STANDARD SPECIFICATIONS SHALL APPLY TO THIS DRAWING.

A PULL WIRE/ROPE IN ACCORDANCE WITH STANDARD SPECIFICATION 652 SHALL BE INSTALLED IN EACH TROMBONE ARM RACEWAY DURING THE MANUFACTURING PROCESS.

TYPE 2 ALUMINUM POLES SHALL BE CONSTRUCTED OF 6063-T6 ALUMINUM ALLOY. SLEEVING INSIDE THE POLE IS NOT ACCEPTABLE.


WHEN TRANSFORMER BASES ARE USED, WIRE CONNECTIONS SHALL BE MADE IN THE TRANSFORMER BASE.

- ① 4" X 6" REINFORCED HANDHOLE & COVER ASSEMBLY WITH 2 (TWO) 1/4" X 3/4" - 20 TPI HEX HEAD STAINLESS STEEL BOLTS.
- ② SIGNAL FACE MOUNTING BRACKETS. MOUNT WITH CAP SCREWS AND BANDING. (SEE STANDARD SPECIFICATIONS - SEC. 658)
- ③ GROMMETS, 1" CHASE NIPPLES OR 1" CLOSE CONDUIT NIPPLES WITH BUSHINGS SHALL BE PROVIDED FOR 1 1/4" HOLE IN POLE SHAFT FOR WIRING.
- ④ SECURELY MOUNT DULL BLACK POLYCARBONATE BACKPLATES, PROJECTING 5" BEYOND ALL SIDES OF THE SIGNAL FACE HOUSING, PER MANUFACTURER'S RECOMMENDATIONS.
- ⑤ POLE MOUNTED SIGNAL FACES SHALL REQUIRE 10R MORE MOUNTING SPACERS UNDER THE TOP MOUNTING BRACKET(S) AS REQUIRED, TO PLUMB THE SIGNAL FACES.
- ⑥ CAST ALUMINUM TRANSFORMER BASE, WHEN REQUIRED.
- ⑦ MOUNTING BRACKET NIPPLES FOR THE SIGNAL FACE(S) SHALL BE 2 INCHES IN LENGTH AND 1 1/2 INCHES IN DIAMETER. (SEE STANDARD SPECIFICATION - SECTION 658).
- ⑧ VERTICAL STRUT (ADJUSTABLE), ONE (1) SET SCREW (1/4" X 3/4" LONG-20 TPI, STAINLESS STEEL, HEX HEAD) INTO EACH ARM MEMBER IF STRUT IS THE SLIDING TYPE.
- ⑨ FURNISH AND INSTALL VENTILATED, CAST, METALLIC (ALUMINUM ALLOY) CAPS. FASTEN CAPS WITH ONE (1) 1/4" X 3/4" - 20 TPI STAINLESS STEEL, HEX HEAD BOLT.
- ⑩ SHIMMING, IF NEEDED, SHALL BE LOCATED BETWEEN THE CONCRETE FOUNDATION AND THE TRANSFORMER BASE.
- ⑪ USE SERRATED LOCK WASHERS WITH NOTCHES BETWEEN END TEE AND SIGNAL HEAD.

*MOUNTING HEIGHT LIMITATION DIMENSIONS OF THE TROMBONE MAST ARM WILL BE DEPENDENT UPON THE USE/NON-USE OF A TRANSFORMER BASE.

FOR MANUFACTURERS USE ONLY


WELD TO BE 100% R.T. OR U.T. TESTED AS PER THE REQUIREMENTS OF AWS D 1.5-88. RECORDS OF COMPLIANCE OF SUCH TESTING SHALL BE FURNISHED TO THE OFFICE OF DESIGN/BRIDGE FOR VERIFICATION AND APPROVAL.



POLE SPLICE DETAIL


POLE MOUNTINGS FOR TRAFFIC SIGNALS TYPE 2

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




TYPICAL MOUNTING OF BACK TO BACK
3 AND 5 SECTION SIGNAL FACES

TYPE 2 POLE MOUNTING CONFIGURATION



TYPICAL MOUNTING OF 3 SECTION
SIGNAL FACE




FOR MANUFACTURERS USE ONLY


WELD TO BE 100% R.T. OR U.T. TESTED AS PER THE REQUIREMENTS OF AWS D 1.5-88. RECORDS OF COMPLIANCE OF SUCH TESTING SHALL BE FURNISHED TO THE OFFICE OF DESIGN/BRIDGE FOR VERIFICATION AND APPROVAL.

* RISE FOR 4' ARM SHALL BE 2'-0".


POLE SPLICE DETAIL




INTERCHANGEABLE MOUNTING DETAIL




LUMINAIRE
WT. - 50 LBS.
EFFECTIVE PROJECTED
AREA FOR WIND
LOADING = 1.5 SQ. FT.



SIGNAL FACE MOUNTING DETAIL (BANDED)



TYPICAL MOUNTING OF BACK TO BACK
3 AND 5 SECTION SIGNAL FACES



TYPICAL MOUNTING OF 3 SECTION
SIGNAL FACE

TYPE 3 POLE MOUNTING CONFIGURATION

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

ALL TYPE 3 POLE MOUNTINGS SHALL BE DESIGNED TO INCLUDE TWIN 15' ARMS WITH LUMINAIRES.

POLES SHALL BE GALVANIZED STEEL.


SECTION 657, POLES, OF THE STANDARD SPECIFICATIONS SHALL APPLY TO THIS DRAWING.

A PULL WIRE/ROPE IN ACCORDANCE WITH STANDARD SPECIFICATION 652, SHALL BE INSTALLED IN EACH TROMBONE ARM RACEWAY DURING THE MANUFACTURING PROCESS.

THE SLIPFITTER END OF THE LUMINAIRE MAST ARM SHALL BE A NOMINAL 2 3/8" INCHES IN OUTSIDE DIAMETER. THE STRAIGHT PORTION OF THE SLIPFITTER END OF THE LUMINAIRE MAST ARM SHALL BE A NOMINAL 12 INCHES IN LENGTH.

WHEN TRANSFORMER BASES ARE USED, WIRE CONNECTIONS SHALL BE MADE IN THE TRANSFORMER BASE.

- 4" X 6" REINFORCED HANDHOLE & COVER ASSEMBLY WITH 2 (TWO) 1/4" X 3/4" - 20 TPI HEX HEAD STAINLESS STEEL BOLTS.
- SIGNAL FACE MOUNTING BRACKETS, MOUNT WITH CAP SCREWS AND BANDING. (SEE STANDARD SPECIFICATIONS - SEC. 658)
- GROMMETS, 1" CHASE NIPPLES OR 1" CLOSE CONDUIT NIPPLES WITH BUSHINGS SHALL BE PROVIDED FOR 1 3/8" HOLE IN POLE SHAFT FOR WIRING.
- SECURELY MOUNT DULL BLACK POLYCARBONATE BACKPLATES, PROJECTING 5" BEYOND ALL SIDES OF THE SIGNAL FACE HOUSING, PER MANUFACTURER'S RECOMMENDATIONS.
- POLE MOUNTED SIGNAL FACES SHALL REQUIRE 1 OR MORE MOUNTING SPACERS UNDER THE TOP MOUNTING BRACKET(S) AS REQUIRED, TO PLUMB THE SIGNAL FACE.
- TYPE 3 POLE CONFIGURATIONS SHALL BE MOUNTED DIRECTLY TO THEIR CONCRETE BASES.
- MOUNTING BRACKET NIPPLES FOR THE SIGNAL FACE(S) SHALL BE 2 INCHES IN LENGTH AND 1/2" INCHES IN DIAMETER. (SEE STANDARD SPECIFICATION - SECTION 658)
- VERTICAL STRUT (ADJUSTABLE). ONE (1) SET SCREW (1/4" X 3/4" - 20 TPI, STAINLESS STEEL, HEX HEAD) INTO EACH ARM MEMBER IF STRUT IS THE SLIDING TYPE.
- FURNISH AND INSTALL VENTILATED, CAST, METALLIC (ALUMINUM ALLOY) CAPS. FASTEN CAPS WITH ONE (1) 1/4" X 3/4" - 20 TPI STAINLESS STEEL, HEX HEAD BOLT.
- SHIMMING, IF NEEDED, SHALL BE LOCATED BETWEEN THE CONCRETE FOUNDATION AND POLE.
- USE SERRATED LOCK WASHERS WITH NOTCHES BETWEEN END TEE AND SIGNAL HEAD.





HORIZONTAL SIGNAL HEAD MOUNTING DETAIL **

** SIGNAL HEAD ATTACHMENT ALSO APPLYS TO MOUNTING AT CROSS BAR

POLE MOUNTINGS FOR
TRAFFIC SIGNALS AND
LIGHTING UNITS, TYPE 3
(HEAVY DUTY)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

ALL TYPE 4 POLE MOUNTINGS SHALL BE DESIGNED TO INCLUDE TWIN 15' ARMS WITH LUMINAIRES.


POLES SHALL BE GALVANIZED STEEL WITH A MINIMUM WALL THICKNESS OF U.S. STANDARD 11 GAGE (.1196").

SECTION 657, POLES, OF THE STANDARD SPECIFICATIONS SHALL APPLY TO THIS DRAWING.

THE SLIPFITTER END OF THE LUMINAIRE MAST ARM SHALL BE A NOMINAL 2 3/8 INCHES IN OUTSIDE DIAMETER. THE STRAIGHT PORTION OF THE SLIPFITTER END OF THE LUMINAIRE MAST ARM SHALL BE A NOMINAL 12 INCHES IN LENGTH.

WHEN TRANSFORMER BASES ARE USED, CONNECTIONS SHALL BE MADE IN THE TRANSFORMER BASE.

- ① 4" X 6" REINFORCED HANDHOLE & COVER ASSEMBLY WITH 2 (TWO) 1/4" X 3/4" - 20 TPI HEX HEAD STAINLESS STEEL BOLTS.
- ② SIGNAL FACE MOUNTING BRACKETS, MOUNT WITH CAP SCREWS AND BANDING. (SEE STANDARD SPECIFICATIONS - SEC. 658).
- ③ GROMMETS, 1" CHASE NIPPLES OR 1" CLOSE CONDUIT NIPPLES WITH BUSHINGS SHALL BE PROVIDED FOR 1 3/8" HOLE IN POLE SHAFT FOR WIRING.
- ④ SECURELY MOUNT DULL BLACK POLYCARBONATE BACKPLATES, PROJECTING 5" BEYOND ALL SIDES OF THE SIGNAL FACE HOUSING, PER MANUFACTURER'S RECOMMENDATIONS.
- ⑤ POLE MOUNTED SIGNAL FACES SHALL REQUIRE 1 OR MORE MOUNTING SPACERS UNDER THE TOP MOUNTING BRACKET(S) AS REQUIRED, TO PLUMB THE SIGNAL FACE.
- ⑥ CAST ALUMINUM TRANSFORMER BASE, WHEN REQUIRED.
- ⑦ FURNISH AND INSTALL VENTILATED, CAST, METALLIC (ALUMINUM ALLOY) CAPS. FASTEN CAPS WITH ONE (1) 1/4" X 3/4" - 20 TPI STAINLESS STEEL, HEX HEAD BOLT.
- ⑧ SHIMMING, IF NEEDED, SHALL BE LOCATED BETWEEN THE CONCRETE FOUNDATION AND THE TRANSFORMER BASE.




INTERCHANGEABLE MOUNTING DETAIL


TYPE 4 POLE MOUNTING CONFIGURATION

**POLE MOUNTINGS FOR
TRAFFIC SIGNALS AND
LIGHTING UNITS, TYPE 4**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




**FRONT VIEW
RECTANGULAR CLAMP SHIM**
(4 TO A SET)





LEVELING SHIM
SHALL BE ALUMINUM




**TYPICAL APPLICATION OF
GROMMET IN POLE SHAFT**




**TYPICAL APPLICATION OF
CHASE NIPPLE IN POLE SHAFT**




**SECTION A-A
CIRCULAR CLAMP SHIM**
(2 TO A SET)




**TYPICAL TROMBONE MAST ARM AND SINGLE
LUMINAIRE MAST ARM MOUNTING CLAMP**





**TYPICAL LUMINAIRE MAST ARM
(DOUBLE) MOUNTING BRACKETS**




TYPICAL "J" HOOK LOCATION



BASE PLATE



TYPICAL GROUNDING CONNECTIONS
NUT, BOLT AND WASHERS SHALL
BE STAINLESS STEEL



GENERAL NOTES


CLAMP BOLT-NUT TIGHTENING TORQUE SHALL BE INDICATED BY INDENT STAMPING (1/2 INCH NUMERALS AND LETTERS) OR WEATHERPROOF PRINTING ON THE INSIDE OF THE CLAMP THAT IS WELDED TO THE ARM MEMBER.

- ⑩ 4.5" I.D. FOR LUMINAIRE MAST ARM CLAMP.
6.625" I.D. FOR TROMBONE MAST ARM CLAMP.
- ⑪ INDIVIDUAL BASE PLATE ANCHOR ROD COVERS. (4 REQUIRED)
- ⑫ BASE PLATE SLOTTED TO ACCEPT 11" THROUGH 12" BOLT CIRCLE USING 1" DIAMETER ANCHOR RODS.
- ⑬ OUTSIDE SHIM DIAMETER - (4.5" O.D. FOR LUMINAIRE MAST ARM)
(6.625" O.D. FOR TROMBONE MAST ARM)
- ⑭ VARIABLE SHIM THICKNESS - (0.10", 0.25", 0.35", 0.53" OR 0.70")
SHIM THICKNESS FOR TROMBONE MAST ARMS MAY BE TYPICALLY 0.25", 0.35", 0.53" OR 0.70".
SHIM THICKNESS FOR LUMINAIRE MAST ARMS MAY BE TYPICALLY 0.10", 0.25" OR 0.35".
SHIM MATERIAL SHALL BE ALUMINUM ALLOY.
SHIM THICKNESS SHALL BE IMPRESSED INTO EACH SHIM. NUMERALS SHALL BE 1/4" HIGH AND LEGIBLE.
THE CONTRACTOR SHALL SUBMIT TWO COPIES OF ALL SHIM SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL.
- ⑮ LEVELING SHIMS, DESIGNED FOR THE PURPOSE, SHALL BE USED WHEN PLUMBING POLES. THE USE OF WASHERS IN LIEU OF PROPER LEVELING SHIMS IS NOT ACCEPTABLE. LEVELING SHIMS SHALL BE USED ONLY BETWEEN THE TOP OF THE CONCRETE BASE AND A METALLIC BASE PLATE.
SHIMS SHALL BE LONG ENOUGH AND WIDE ENOUGH TO COMPLETELY COVER THE AREA UNDER THE LENGTH AND WIDTH OF THE BASE MOUNTING FLANGE.


HARDWARE DETAILS FOR POLE MOUNTINGS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
2/7/2013
DATE
/S/ Ahmet Demirbilek
STATE ELECTRICAL ENGINEER
FHWA






**LIGHTING UNIT CODE
(TYPICAL)**



**DETAIL "A"
BREAKAWY
DOUBLE POLE WITH
WATERPROOF
INSULATING BOOT**



**DETAIL "B"
BREAKAWY
SINGLE POLE WITH
WATERPROOF
INSULATING BOOT**



TYPICAL GROUNDING CONNECTIONS
NUT, BOLT, WASHERS AND LOCKWASHERS SHALL BE STAINLESS STEEL

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

THE EQUIPMENT GROUNDING CONNECTOR SHALL BE TAPED WITH 3 WRAPS (MINIMUM) OF APPROVED RUBBER TAPE AND THEN 3 WRAPS (MINIMUM) OF APPROVED VINYL TAPE TO COVER SHARP WIRE ENDS AFTER THE CONNECTION IS COMPLETED.

WHEN TRANSFORMER BASES ARE USED, ALL WIRING CONNECTIONS SHALL OCCUR WITHIN THE TRANSFORMER BASES.

ADDITIONAL CONDUCTORS
AND FUSE FOR TWIN
LIGHTING UNITS

EQUIPMENT GROUNDING
CONDUCTOR(S) TO LUMINAIRE(S)

APPROVED MECHANICAL TYPE
CONNECTOR FOR EQUIPMENT
GROUNDING CONDUCTORS.
COMPRESSION, CRIMP OR
WIRE NUT CONNECTORS ARE
NOT ALLOWED.

TYPICAL GROUNDING CONNECTION -
STAINLESS STEEL BOLT,
NUT AND WASHERS
1/2" X 1/2" - 13 TPI

AWG #4 (MIN.) BARE EQUIPMENT
GROUNDING CONDUCTOR.
NOTE: THIS WIRE SHALL BE
CONTINUOUS WITHOUT SPLICES
FROM THE GROUNDING ELECTRODE
TO THE EQUIPMENT GROUNDING
CONDUCTOR SPLICE CONNECTOR.

INSULATED EQUIPMENT GROUNDING
CONDUCTORS FROM SYSTEM RACEWAY

EXOTHERMICALLY WELDED
TO GROUNDING ELECTRODE

CONDUCTORS TO
LUMINAIRES SHALL BE #12 AWG,
COPPER STRANDED, U.S.E. RATED,
XLP INSULATED. SINGLE
LIGHTING UNIT SHOWN

CIRCUIT TAGS, BOTH SIDES
OF ALL FUSES (TYPICAL)

IN LINE SINGLE POLE FUSE ASSEMBLY.
600 VAC, WITH 5 AMP FNO FUSE
(SEE DETAIL "B")
TAPE AND VARNISH
CRIMPED END FERRULES

HANDHOLE & COVER

18" PIGTAIL BETWEEN
CONNECTOR AND FUSEHOLDER

APPROVED INSULATED MULTITAP
TERMINAL BLOCK TYPE CONNECTORS.
COMPRESSION, CRIMP OR WIRE NUT
CONNECTORS ARE NOT ALLOWED.

INSULATED UNGROUNDED CIRCUIT
CONDUCTORS FROM SYSTEM RACEWAY

ALTERNATE PHASE UNGROUNDED
CIRCUIT CONDUCTOR PASSING
THROUGH THIS POLE

**3 WIRE - 120, 240 OR 480 VAC (UNGROUND CONDUCTOR)
WITH GROUNDED CONDUCTOR AND
WITH EQUIPMENT GROUNDING CONDUCTOR**

UNGROUND CONDUCTORS TO
LUMINAIRES SHALL BE #12 AWG,
COPPER STRANDED, U.S.E.
RATED, XLP INSULATED.
SINGLE LIGHTING UNIT SHOWN

TWIN LIGHTING UNITS REQUIRE
INDIVIDUAL SETS OF UNGROUNDED
CONDUCTORS AND FUSE ASSEMBLY.

AWG #4 (MIN.) BARE EQUIPMENT
GROUNDING CONDUCTOR.
NOTE: THIS WIRE SHALL BE
CONTINUOUS WITHOUT SPLICES
FROM THE GROUNDING ELECTRODE
TO THE EQUIPMENT GROUNDING
CONDUCTOR SPLICE CONNECTOR.

EQUIPMENT GROUNDING
CONDUCTOR(S) TO LUMINAIRE(S)

TYPICAL GROUNDING CONNECTION -
STAINLESS STEEL BOLT,
NUT AND WASHERS
1/2" X 1/2" - 13 TPI

APPROVED MECHANICAL TYPE
CONNECTOR FOR EQUIPMENT
GROUNDING CONDUCTORS.
COMPRESSION, CRIMP OR
WIRE NUT CONNECTORS ARE
NOT ALLOWED.

INSULATED EQUIPMENT GROUNDING
CONDUCTORS FROM SYSTEM RACEWAY

EXOTHERMICALLY WELDED
TO GROUNDING ELECTRODE

**2 WIRE - 240 OR 480 VAC (UNGROUND CONDUCTORS)
WITH EQUIPMENT GROUNDING CONDUCTOR**

CIRCUIT TAGS, BOTH SIDES
OF ALL FUSES (TYPICAL)

IN LINE FUSE ASSEMBLY
TWO POLE, 600 VAC,
WITH 5 AMP FNO FUSES
(SEE DETAIL "A")
TAPE AND VARNISH
CRIMPED END FERRULES

HANDHOLE & COVER

18" PIGTAIL BETWEEN
CONNECTORS AND FUSEHOLDERS

APPROVED INSULATED MULTITAP
TERMINAL BLOCK TYPE CONNECTORS.
COMPRESSION, CRIMP OR WIRE NUT
CONNECTORS ARE NOT ALLOWED.

INSULATED UNGROUNDED CIRCUIT
CONDUCTORS FROM SYSTEM RACEWAY

**NON-FREWAY LIGHTING UNIT
POLE WIRING**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

3/2/2011
DATE

FHWA

/S/ Thomas J. Goring
STATE ELECTRICAL ENGINEER FOR HWYS



GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

SEE THE SIGNAL PLAN FOR REQUIRED SIGNAL FACE SIZES.

ALL PEDESTAL BASES SHALL BE MOUNTED ON CONCRETE BASE - TYPE 1.

FOR APPROVED MOUNTING HARDWARE, SEE THE CONTRACT SPECIAL PROVISIONS.

POLYCARBONATE MOUNTING BRACKETS SHALL BE USED.


LENGTH AND LOCATION OF TRAFFIC SIGNAL STANDARDS SHALL BE AS SHOWN ON THE PLANS.

OPTICALLY PROGRAMMED SIGNAL FACES SHALL BE MASKED IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS, AND UNDER THE DIRECTIONS OF THE DISTRICT TRAFFIC ENGINEER.

FOLDING STOP SIGNS SHALL BE IN ACCORDANCE WITH THE MUTCD AND/OR THE LATEST WISCONSIN SUPPLEMENT. THE SIGNS SHALL BE SIZED AND LOCATED AS CALLED FOR IN THE PLANS.

PEDESTRIAN SIGNS SHALL BE AS DESIGNATED IN THE PLANS.

FURNISH AND INSTALL VENTILATED, CAST, METALLIC (ALUMINUM ALLOY) CAPS.
FASTEN CAPS WITH ONE (1) 1/4" X 3/4" - 20 TPI STAINLESS STEEL, HEX HEAD BOLT.






SIGNAL FACE MOUNTING DETAIL (BANDED)




TRAFFIC SIGNAL STANDARD
POLY BRACKET MOUNTINGS
(TYPICAL) 13 FT. OR 15 FT.

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
5/11/10 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA



SIGNAL FACE MOUNTING DETAILS

PEDESTRIAN PUSH BUTTON
TYPICAL MOUNTINGPEDESTRIAN FACE STANDARD-10 FT.
(WALK-DON'T WALK)STANDARD FLASHER.
10 FOOT, 13 FOOT OR 15 FOOT AS REQUIRED

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

SEE THE SIGNAL PLAN FOR REQUIRED SIGNAL FACE SIZES.

LOCATIONS SHALL BE AS SHOWN ON THE PLANS.

ALL PEDESTAL BASES SHALL BE MOUNTED ON CONCRETE BASE - TYPE 1.

FOR APPROVED MOUNTING HARDWARE, SEE THE CONTRACT SPECIFICATIONS.


POLYCARBONATE SIGNAL FACE MOUNTING BRACKETS SHALL BE USED UNLESS ORNAMENTAL POLE CLAMPS ARE SPECIFIED.

LENGTH OF TRAFFIC STANDARDS SHALL BE AS SHOWN ON THE PLANS.

MOUNTINGS AND BRACKETS SHALL BE AS SHOWN ON THE PLANS OR DESCRIBED IN THE SPECIAL PROVISIONS (BY THE DISTRICT TRAFFIC ENGINEER).

PEDESTRIAN SIGNS SHALL BE AS DESIGNATED IN THE PLANS.

FURNISH AND INSTALL VENTILATED, CAST, METALLIC (ALUMINUM ALLOY) CAPS. FASTEN CAPS WITH ONE (1) 1/4" X 3/4" - 20 TPI STAINLESS STEEL, HEX HEAD BOLT.

SINGLE
(OFFSET-SERRATED MOUNTING)DOUBLE
(SERRATED MOUNTING)

SLIPFITTERS

**TRAFFIC SIGNAL STANDARD
PEDESTRIAN AND FLASHER
TYPICAL MOUNTING DETAILS**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED


5/11/10
DATE


FHWA


/S/ John Corbin
STATE ELECTRICAL ENGINEER FOR HWYS

TWO-LANE ROADWAY

SYMBOLS


WORK AREA

FLAGGER, EQUIPPED WITH STOP/SLOW PADDLE FASTENED ON SUPPORT STAFF

SIGN ON PORTABLE OR PERMANENT SUPPORT



USE OF THE "BE PREPARED TO STOP" SIGN IS OPTIONAL. WHEN USED, THIS SIGN SHALL BE LOCATED BETWEEN THE W20-7a AND W20-4 SIGNS. A 500' TYPICAL SPACING SHALL BE PROVIDED BETWEEN THE SIGNS.



GENERAL NOTES


- DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS AND DEVICES (AND THE LOCATION OF ALL FLAGGERS) SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.
- THE FIRST ADVANCE WARNING SIGN SHOULD TYPICALLY BE LOCATED IN ADVANCE OF THE ANTICIPATED TRAFFIC BACKUP OR QUEUE.
- WHEN A SIDE ROAD OR RAMP INTERSECTS THE FACILITY ON WHICH THE WORK IS BEING PERFORMED, ADDITIONAL TRAFFIC CONTROLS SHALL BE PROVIDED AS SPECIFIED IN THE PLANS AND/OR THE SPECIAL PROVISIONS OR AS APPROVED BY THE ENGINEER.
- FLAGGERS SHALL BE IN SIGHT OF EACH OTHER OR IN DIRECT COMMUNICATION AT ALL TIMES. THEY SHALL BE EQUIPPED WITH STOP/SLOW PADDLES FASTENED ON SUPPORT STAFFS. WHEN THE FLAGGING OPERATION IS NOT IN EFFECT, THE "FLAGGER AHEAD", THE "ROAD WORK AHEAD" AND THE ONE LANE ROAD AHEAD" SIGNS SHALL BE COVERED OR REMOVED AND THE HIGHWAY RESTORED TO NORMAL OPERATION.
- ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.

- ① FOR A MOVING WORK OPERATION, SIGNING FOR BOTH DIRECTIONS SHALL BE REESTABLISHED (AS SIMULTANEOUSLY AS PRACTICAL) AT APPROXIMATELY 3500 FOOT INTERVALS IN THE MOVING WORK OPERATION OR AS APPROVED BY THE ENGINEER.
- ② SIGN NOT REQUIRED IF FLAGGING OPERATION OCCURS WITHIN A SIGNED ROAD WORK ZONE AREA.

TRAFFIC CONTROL FOR LANE CLOSURE (SUITABLE FOR MOVING OPERATIONS)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
9/5/06 /S/ Thomas N. Notbohm
DATE STATE TRAFFIC ENGINEER OF DESIGN
FHWA



B=400' AT 25-30 MPH
700' AT 35-40 MPH
1000' AT 45-55 MPH

A=200' AT 25-30 MPH
350' AT 35-40 MPH
500' AT 45-55 MPH

TABLE 1
TAPER AND BUFFER SPACE
FOR 12' LANE WIDTH

S	L	BUFFER SPACE
25	125'	55'
30	180'	85'
35	245'	120'
40	320'	170'
45	540'	220'
50	600'	280'
55	660'	335'

FOR LANE WIDTH OTHER THAN 12':

L = WS AT 45 MPH OR GREATER

$L = \frac{WS^2}{60}$ AT 40 MPH OR LESS


L = TAPER LENGTH IN FEET

S = NON-CONSTRUCTION SPEED LIMIT (MPH)

W = WIDTH OF LANE CLOSURE

(PLACE BARRICADE AND SIGN APPROX.
EVERY 1000' ACROSS THE CLOSED LANE)

*IF ARROWBOARD IS NOT INCLUDED IN
MISCELLANEOUS QUANTITIES, SUBSTITUTE
A TYPE III BARRICADE WITH W01-6 SIGN
IN THE LANE CLOSURE TAPER.



LEGEND

- DRUM WITH/WITHOUT WARNING LIGHT, TYPE C (STEADY-BURN)
- POST MOUNTED SIGN
- ↑ ARROW BOARD
- IC/C TYPE III BARRICADE (8' EQUIVALENT) AND WARNING LIGHTS, TYPE A (FLASHING) WITH/WITHOUT SIGN
- DIRECTION OF TRAFFIC FLOW
- x x x x REMOVING PAVEMENT MARKING (SEE GENERAL NOTES)

GENERAL NOTES

THIS LANE CLOSURE DETAIL IS TYPICAL FOR CLOSING THE LEFT LANE. FOR A RIGHT LANE CLOSURE, REVERSE THE TRAFFIC CONTROL.

THIS DETAIL MAY BE USED FOR ROADWAYS WITH EITHER TWO OR THREE LANES IN EACH DIRECTION.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48"x48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS IN URBAN AREAS, 36" X 36" SIGNS MAY BE USED IF APPROVED BY DISTRICT TRAFFIC UNIT.

"WO" SIGNS ARE THE SAME AS "W" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS, OR THAT WILL BE PLACED IN A CLOSED LANE, MAY BE MOUNTED ON PORTABLE SUPPORTS.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

REMOVE PAVEMENT MARKINGS AND PLACE TEMPORARY PAVEMENT MARKING, REMOVABLE TAPE IF LANE CLOSURE IS TO BE IN PLACE FOR 7 OR MORE CONTINUOUS DAYS AND NIGHTS.

ON UNDIVIDED ROADWAYS, OMIT THE SIGNS SHOWN ON LEFT SIDE OF ROAD.

W20-1, G20-1 AND G20-2A SIGNS ARE NOT REQUIRED IF THE LANE CLOSURE IS WITHIN A LARGER WORK ZONE WHERE THESE SIGNS ARE ALREADY PRESENT.

OMIT G20-1 SIGNS IF LENGTH OF WORK AREA IS 2 MILES OR LESS.

CONSIDER GEOMETRICS WHEN LOCATING SIGNS AND ARROWBOARDS SO THE APPROACHING DRIVER HAS A CLEAR VIEW OF THE ARROWBOARDS AND LANE CLOSURE DRUMS.

PLACE THE ARROWBOARD AS CLOSE AS POSSIBLE TO THE BEGINNING OF THE LANE CLOSURE TAPER, PREFERABLY ON THE SHOULDER OR TERRACE.

CHANNELIZING DEVICES PLACED ADJACENT TO WORK AREA SHALL BE PULLED BACK FROM THE TRAVEL LANE WHEN WORK IS NOT IN PROGRESS.


BARRICADES IN A CLOSED LANE THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION OR, FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

WARNING LIGHTS ARE NOT REQUIRED IF THE LANE CLOSURE IS A DAYTIME ONLY OPERATION.

TRAFFIC CONTROL,
SINGLE LANE CLOSURE,
NON-FREEWAY/EXPRESSWAY

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
5/23/00 /S/ Chester J. Spang
DATE CHIEF SIGNS AND MARKING ENGINEER
FHWA



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>