HIGHWAY WORK PROPOSAL

Proposal Number:

Wisconsin Department of Transportation DT1502 10/2010 s.66.29(7) Wis. Stats.

and Conditions.

COUNTY STATE PROJECT ID FEDERAL PROJECT ID PROJECT DESCRIPTION HIGHWAY

Milwaukee 2984-04-71 Various Highways 3 Connecting Highway Intersections

Var Hwy

This proposal, submitted by the undersigned bidder to the Wisconsin Department of Transportation, is in accordance with the advertised request for proposals. The bidder is to furnish and deliver all materials, and to perform all work for the improvement of the designated project in the time specified, in accordance with the appended Proposal Requirements

Proposal Guaranty Required, \$ 6,000.00	Attach Proposal Guaranty on back of this PAGE.
Payable to: Wisconsin Department of Transportation	
Bid Submittal Due	Firm Name, Address, City, State, Zip Code
Date: May 12, 2015 Time (Local Time): 9:00 AM	SAMPLE
Contract Completion Time	NOT FOR BIDDING PURPOSES
Twenty (20) Working Days	NOT FOR DIDDING FOR OSES
Assigned Disadvantaged Business Enterprise Goal 0 %	This contract is exempt from federal oversight.

This certifies that the undersigned bidder, duly sworn, is an authorized representative of the firm named above; that the bidder has examined and carefully prepared the bid from the plans, Highway Work Proposal, and all addenda, and has checked the same in detail before submitting this proposal or bid; and that the bidder or agents, officer, or employees have not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with this proposal bid.

collusion, or otherwise taken any action in restraint of free competitive bidding in co	onnection with this proposal bid.
Do not sign, notarize, or submit this Highway Work Proposal when s	ubmitting an electronic bid on the Internet.
Subscribed and sworn to before me this date	
(Signature, Notary Public, State of Wisconsin)	(Bidder Signature)
(Print or Type Name, Notary Public, State Wisconsin)	(Print or Type Bidder Name)
(Date Commission Expires)	(Bidder Title)
Notary Seal	
For Department U	se Only
Type of Work	

Type of Work Excavation and installation of concrete bases, monotube poles and mast arms, conduit and control vaults. Notice of Award Dated Date Guaranty Returned

PLEASE ATTACH PROPOSAL GUARANTY HERE

Effective with November 2007 Letting

PROPOSAL REQUIREMENTS AND CONDITIONS

The bidder, signing and submitting this proposal, agrees and declares as a condition thereof, to be bound by the following conditions and requirements.

If the bidder has a corporate relationship with the proposal design engineering company, the bidder declares that it did not obtain any facts, data, or other information related to this proposal from the design engineering company that was not available to all bidders.

The bidder declares that they have carefully examined the site of, and the proposal, plans, specifications and contract forms for the work contemplated, and it is assumed that the bidder has investigated and is satisfied as to the conditions to be encountered, as to the character, quality, and quantities of work to be performed and materials to be furnished, and as to the requirements of the specifications, special provisions and contract. It is mutually agreed that submission of a proposal shall be considered conclusive evidence that the bidder has made such examination.

The bidder submits herewith a proposal guaranty in proper form and amount payable to the party as designated in the advertisement inviting proposals, to be retained by and become the property of the owner of the work in the event the undersigned shall fail to execute the contract and contract bond and return the same to the office of the engineer within fourteen (14) days after having been notified in writing to do so; otherwise to be returned.

The bidder declares that they understand that the estimate of quantities in the attached schedule is approximate only and that the attached quantities may be greater or less in accordance with the specifications.

The bidder agrees to perform the said work, for and in consideration of the payment of the amount becoming due on account of work performed, according to the unit prices bid in the following schedule, and to accept such amounts in full payment of said work.

The bidder declares that all of the said work will be performed at their own proper cost and expense, that they will furnish all necessary materials, labor, tools, machinery, apparatus, and other means of construction in the manner provided in the applicable specifications and the approved plans for the work together with all standard and special designs that may be designed on such plans, and the special provisions in the contract of which this proposal will become a part, if and when accepted. The bidder further agrees that the applicable specifications and all plans and working drawings are made a part hereof, as fully and completely as if attached hereto.

The bidder, if awarded the contract, agrees to begin the work not later than ten (10) days after the date of written notification from the engineer to do so, unless otherwise stipulated in the special provisions.

The bidder declares that if they are awarded the contract, they will execute the contract agreement and begin and complete the work within the time named herein, and they will file a good and sufficient surety bond for the amount of the contract for performance and also for the full amount of the contract for payment.

The bidder, if awarded the contract, shall pay all claims as required by Section 779.14, Statutes of Wisconsin, and shall be subject to and discharge all liabilities for injuries pursuant to Chapter 102 of the Statutes of Wisconsin, and all acts amendatory thereto. They shall further be responsible for any damages to property or injury to persons occurring through their own negligence or that of their employees or agents, incident to the performance of work under this contract, pursuant to the Standard Specifications for Road and Bridge Construction applicable to this contract.

In connection with the performance of work under this contract, the contractor agrees to comply with all applicable state and federal statutes relating to non-discrimination in employment. No otherwise qualified person shall be excluded from employment or otherwise be subject to discrimination in employment in any manner on the basis of age, race, religion, color, gender, national origin or ancestry, disability, arrest or conviction record (in keeping with s.111.32), sexual orientation, marital status, membership in the military reserve, honesty testing, genetic testing, and outside use of lawful products. This provision shall include, but not be limited to the following: employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation, and selection for training, including apprenticeship. The contractor further agrees to ensure equal opportunity in employment to all applicants and employees and to take affirmative action to attain a representative workforce.

The contractor agrees to post notices and posters setting forth the provisions of the nondiscrimination clause, in a conspicuous and easily accessible place, available for employees and applicants for employment.

If a state public official (section 19.42, Stats.) or an organization in which a state public official holds at least a 10% interest is a party to this agreement, this contract is voidable by the state unless appropriate disclosure is made to the State of Wisconsin Ethics Board.

Effective with August 2007 Letting

BID PREPARATION

Preparing the Proposal Schedule of Items

A General

- Obtain bidding proposals as specified in section 102 of the standard specifications prior to 11:45 AM of the last business day preceding the letting. Submit bidding proposals using one of the following methods:
 - 1. Electronic bid on the internet.
 - 2. Electronic bid on a printout with accompanying diskette or CD ROM.
 - 3. Paper bid under a waiver of the electronic submittal requirements.
- (2) Bids submitted on a printout with accompanying diskette or CD ROM or paper bids submitted under a waiver of the electronic submittal requirements govern over bids submitted on the internet.
- (3) The department will provide bidding information through the department's web site at http://www.dot.wisconsin.gov/business/engrserv/bid-letting-information.htm. The contractor is responsible for reviewing this web site for general notices as well as information regarding proposals in each letting. The department will also post special notices of all addenda to each proposal through this web site no later than 4:00 P.M. local time on the Thursday before the letting. Check the department's web site after 5:00 P.M. local time on the Thursday before the letting to ensure all addenda have been accounted for before preparing the bid. When bidding using methods 1 and 2 above, check the Bid Express™ on-line bidding exchange at http://www.bidx.com/ after 5:00 P.M. local time on the Thursday before the letting to ensure that the latest schedule of items Expedite file (*.ebs or *.00x) is used to submit the final bid.
- (4) Interested parties can subscribe to the Bid Express™ on-line bidding exchange by following the instructions provided at the www.bidx.com web site or by contacting:

Info Tech Inc. 5700 SW 34th Street, Suite 1235 Gainesville, FL 32608-5371

email: mailto:customer.support@bidx.com

- (5) The department will address equipment and process failures, if the bidder can demonstrate that those failures were beyond their control.
- (6) Contractors are responsible for checking on the issuance of addenda and for obtaining the addenda. Notice of issuance of addenda is posted on the department's web site at http://www.dot.wisconsin.gov/business/engrserv/bid-letting-information.htm or by calling the department at (608) 266-1631. Addenda can ONLY be obtained from the departments web site listed above or by picking up the addenda at the Bureau of Highway Construction, Room 601, 4802 Sheboygan Avenue, Madison, WI, during regular business hours.

B Submitting Electronic Bids

B.1 On the Internet

- (1) Do the following before submitting the bid:
 - 1. Have a properly executed annual bid bond on file with the department.
 - 2. Have a digital ID on file with and enabled by Info Tech Inc. Using this digital ID will constitute the bidder's signature for proper execution of the bidding proposal.
- (2) In lieu of preparing, delivering, and submitting the proposal as specified in 102.6 and 102.9 of the standard specifications, submit the proposal on the internet as follows:

- 1. Download the latest schedule of items reflecting all addenda from the Bid Express™ web site.
- 2. Use Expedite™ software to enter a unit price for every item in the schedule of items.
- 3. Submit the bid according to the requirements of Expedite[™] software and the Bid Express[™] web site. Do not submit a bid on a printout with accompanying diskette or CD ROM or a paper bid. If the bidder does submit a bid on a printout with accompanying diskette or a paper bid in addition to the internet submittal, the department will disregard the internet bid.
- 4. Submit the bid before the hour and date the Notice to Contractors designates.
- 5. Do not sign, notarize, and return the bidding proposal described in 102.2 of the standard specifications.
- (3) The department will not consider the bid accepted until the hour and date the Notice to Contractors designates.

B.2 On a Printout with Accompanying Diskette or CD ROM

- Ownload the latest schedule of items from the Wisconsin pages of the Bid Express™ web site reflecting the latest addenda posted on the department's web site at http://www.dot.wisconsin.gov/business/engrserv/bid-letting-information.htm. Use Expedite ™ software to prepare and print the schedule of items. Provide a valid amount for all price fields. Follow instructions and review the help screens provided on the Bid Express™ web site to assure that the schedule of items is prepared properly.
- (2) Staple an 8 1/2 by 11 inch printout of the Expedite™ generated schedule of items to the other proposal documents submitted to the department as a part of the bidder's sealed bid. As a separate submittal not in the sealed bid envelop but due at the same time and place as the sealed bid, also provide the Expedite™ generated schedule of items on a 3 1/2 inch computer diskette or CD ROM. Label each diskette or CD ROM with the bidder's name, the 4 character department-assigned bidder identification code from the top of the bidding proposal, and a list of the proposal numbers included on that diskette or CD ROM as indicated in the following example:

Bidder Name

BN00

Proposals: 1, 12, 14, & 22

- (3) If bidding on more than one proposal in the letting, the bidder may include all proposals for that letting on one diskette or CD ROM. Include only submitted proposals with no incomplete or other files on the diskette or CD ROM.
- (4) The bidder-submitted printout of the Expedite™ generated schedule of items is the governing contract document and must conform to the requirements of section 102 of the standard specifications. If a printout needs to be altered, cross out the printed information with ink or typewriter and enter the new information and initial it in ink. If there is a discrepancy between the printout and the diskette or CD ROM, the department will analyze the bid using the printout information.
- (5) In addition to the reasons specified in section 102 of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
 - The check code printed on the bottom of the printout of the Expedite[™] generated schedule of items is not the same on each page.
 - 2. The check code printed on the printout of the Expedite™ generated schedule of items is not the same as the check code for that proposal provided on the diskette or CD ROM.

3. The diskette or CD ROM is not submitted at the time and place the department designates.

C Waiver of Electronic Submittal

- The bidder may request a waiver of the electronic submittal requirements. Submit a written request for a waiver in lieu of bids submitted on the internet or on a printout with accompanying diskette or CD ROM. Use the waiver that was included with the paper bid document sent to the bidder or type up a waiver on the bidder's letterhead. The department will waive the electronic submittal requirements for a bidding entity (individual, partnership, joint venture, corporation, or limited liability company) for up to 4 individual proposals in a calendar year. The department may allow additional waivers for equipment malfunctions.
- (2) Submit a schedule of items on paper conforming to section 102 of the standard specifications. The department charges the bidder a \$75 administrative fee per proposal, payable at the time and place the department designates for receiving bids, to cover the costs of data entry. The department will accept a check or money order payable to: "Wisconsin, Dept. of Transportation."
- (3) In addition to the reasons specified in section 102 of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
 - 1. The bidder fails to provide the written request for waiver of the electronic submittal requirements.
 - 2. The bidder fails to pay the \$75 administrative fee before the time the department designates for the opening of bids unless the bidder requests on the waiver that they be billed for the \$75.
 - 3. The bidder exceeds 4 waivers of electronic submittal requirements within a calendar year.
- (4) In addition to the reasons specified in section 102 of the standard specifications, the department may refuse to issue bidding proposals for future contracts to a bidding entity that owes the department administrative fees for a waiver of electronic submittal requirements.

PROPOSAL BID BOND

DT1303 1/2006

Wisconsin Department of Transportation

Proposal Number	Project Number		Letting Date
Name of Principal			
Name of Surety		State in Which Surety is	Organized

We, the above-named Principal and the above-named Surety, are held and firmly bound unto the State of Wisconsin in the sum equal to the Proposal Guaranty for the total bid submitted for the payment to be made; we jointly and severally bind ourselves, our heirs, executors, administrators, successors and assigns. The condition of this obligation is that the Principal has submitted a bid proposal to the State of Wisconsin acting through the Department of Transportation for the improvement designated by the Proposal Number and Letting Date indicated above.

If the Principal is awarded the contract and, within the time and manner required by law after the prescribed forms are presented for signature, enters into a written contract in accordance with the bid, and files the bond with the Department of Transportation to guarantee faithful performance and payment for labor and materials, as required by law, or if the Department of Transportation shall reject all bids for the work described, then this obligation shall be null and void; otherwise, it shall be and remain in full force and effect. In the event of failure of the Principal to enter into the contract or give the specified bond, the Principal shall pay to the Department of Transportation within 10 business days of demand a total equal to the Proposal Guaranty as liquidated damages; the liability of the Surety continues for the full amount of the obligation as stated until the obligation is paid in full.

The Surety, for value received, agrees that the obligations of it and its bond shall not be impaired or affected by any extension of time within which the Department of Transportation may accept the bid; and the Surety does waive notice of any such extension.

IN WITNESS, the Principal and Surety have agreed and have signed by their proper officers and have caused their corporate seals to be affixed this date: **(DATE MUST BE ENTERED)**

PRINCIPAL

(Company Name) (Affix C	orporate Seal)		
(Signature and Title)			
(Company Name)			
(Signature and Title)			
(Company Name)			
(Signature and Title)		(Name of Surety) (Affix Seal)	
(Company Name)		(Signature of Attorney-in-Fact)	
(Signature and Title)			
NOTA	RY FOR PRINCIPAL	NOTARY FOR	SURETY
	(Date)	(Date))
State of Wisconsin)	State of Wisconsin)
) ss. County)	() ss. County)
On the above date, this instrunamed person(s).	ument was acknowledged before me by the	On the above date, this instrument was named person(s).	acknowledged before me by the
(Signature, Nota	ary Public, State of Wisconsin)	(Signature, Notary Public,	State of Wisconsin)
(Print or Type Name	, Notary Public, State of Wisconsin)	(Print or Type Name, Notary Po	ublic, State of Wisconsin)
(Date	Commission Expires)	(Date Commission	on Expires)

Notary Seal Notary Seal

IMPORTANT: A certified copy of Power of Attorney of the signatory agent must be attached to the bid bond.

CERTIFICATE OF ANNUAL BID BOND

DT1305 8/2003

Wisconsin Department of Transportation

Time Period Valid ((From/To)
Name of Surety	
Name of Contracto	ır
Certificate Holder	Wisconsin Department of Transportation
	y that an annual bid bond issued by the above-named Surety is currently on file with the partment of Transportation.
	is issued as a matter of information and conveys no rights upon the certificate holder amend, extend or alter the coverage of the annual bid bond.
Cancellation:	Should the above policy be cancelled before the expiration date, the issuing surety will give thirty (30) days written notice to the certificate holder indicated above.
	(Signature of Authorized Contractor Representative) (Date

March 2010

LIST OF SUBCONTRACTORS

Section 66.0901(7), Wisconsin Statutes, provides that as a part of the proposal, the bidder also shall submit a list of the subcontractors the bidder proposes to contract with and the class of work to be performed by each. In order to qualify for inclusion in the bidder's list a subcontractor shall first submit a bid in writing, to the general contractor at least 48 hours prior to the time of the bid closing. The list may not be added to or altered without the written consent of the municipality. A proposal of a bidder is not invalid if any subcontractor and the class of work to be performed by the subcontractor has been omitted from a proposal; the omission shall be considered inadvertent or the bidder will perform the work personally.

No subcontract, whether listed herein or later proposed, may be entered into without the written consent of the Engineer as provided in Subsection 108.1 of the Standard Specifications.

Name of Subcontractor	Class of Work	Estimated Value
-		

DECEMBER 2000

CERTIFICATION REGARDING DEBARMENT, SUSPENSION, AND OTHER RESPONSIBILITY MATTERS - PRIMARY COVERED TRANSACTIONS

Instructions for Certification

- 1. By signing and submitting this proposal, the prospective contractor is providing the certification set out below.
- 2. The inability of a person to provide the certification required below will not necessarily result in denial of participation in this covered transaction. The prospective contractor shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective contractor to furnish a certification or an explanation shall disqualify such person from participation in this transaction.
- 3. The certification in this clause is a material representation of fact upon which reliance was placed when the department determined to enter into this transaction. If it is later determined that the contractor knowingly rendered an erroneous certification in addition to other remedies available to the Federal Government the department may terminate this transaction for cause or default.
- 4. The prospective contractor shall provide immediate written notice to the department to whom this proposal is submitted if at any time the prospective contractor learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
- 5. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction," "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of the rules implementing Executive Order 12549. You may contact the department to which this proposal is being submitted for assistance in obtaining a copy of those regulations.
- 6. The prospective contractor agrees by submitting this proposal that, should this contract be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department entering into this transaction.
- 7. The prospective contractor further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," which is included as an addendum to PR-1273 "Required Contract Provisions Federal Aid Construction Contracts," without

modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.

- 8. The contractor may rely upon a certification of a prospective subcontractor/materials supplier that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A contractor may decide the method and frequency by which it determines the eligibility of its principals. Each contractor may, but is not required to, check the Disapproval List (telephone # 608/266/1631).
- 9. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of a contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- 10. Except for transactions authorized under paragraph 6 of these instructions, if a contractor in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department may terminate this transaction for cause or default.

Certification Regarding Debarment, Suspension, and Other Responsibility Matters - Primary Covered Transactions

- (1) The prospective contractor certifies to the best of its knowledge and belief, that it and its principals:
 - (a) Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
 - (b) Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements or receiving stolen property;
 - (c) Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offense enumerated in paragraph (1)(b) of this certification; and
 - (d) Have not within a three-year period preceding this proposal had one or more public transactions (Federal, State or local) terminated for cause or default.
- (2) Where the prospective contractor is unable to certify to any of the statements in this certification, such prospective contractor shall attach an explanation to this proposal.

Special Provisions

Table of Contents

Article	Description Description	Page #
1.	General	2
2.	Scope of Work.	2
3.	Prosecution and Progress.	2
4.	Public Convenience and Safety.	3
5.	Holiday Work Restrictions.	3
6.	Utilities	4
7.	Notice to Contractor – Survey.	6
8.	Erosion Control.	6
9.	Tree and Planting Area Protection.	7
10.	Construction Trenches.	7
11.	Concrete Identification Stamping.	8
12.	Concrete Lighting Conduit Box-Outs.	8
13.	Traffic Control.	
14.	Construction Staking Electrical Installations 2984-04-71, Item 650.8500.01	
15.	Conduit Rigid Nonmetallic Schedule 40 3-Inch, Item 652.0235	
16.	Concrete Bases Type 10, Item 654.0110.	
17.	Concrete Base Type 10 Special, Item SPV.0060.01	
18.	Poles Type 9, Item SPV.0060.02.	
19.	Poles Type 12 Special, Item SPV.0060.03; Poles Type 13 Special, Ite	
	SPV.0060.04.	
20.	Monotube Arms 30-FT, Item SPV.0060.05; Monotube Arms 35-FT, Ite	
	SPV.0060.06.	
21.	Rectangular Polymer Concrete Vault 13-Inch x 24-Inch x 18-Inch, Ite SPV.0060.07.	
22.	Inlet Screen Type M, Item SPV.0060.08.	
23.	Utility Line Opening (ULO), Item SPV.0060.09.	
23. 24.	Management of Solid Waste, Item SPV.0195.01.	
∠ ┯.	management of Sond waste, item St v.01/3.01.	41

2984-04-71 1 of 25

SPECIAL PROVISIONS

1. General.

Perform the work under this construction contract for Project 2984-04-71, Various Highways – 3 Connecting Highway Intersections, located in the City of Milwaukee, Milwaukee County, Wisconsin as the plans show and execute the work as specified in the State of Wisconsin, Department of Transportation, Standard Specifications for Highway and Structure Construction, 2015 Edition, as published by the department, and these special provisions.

If all or a portion of the plans and special provisions are developed in the SI metric system and the schedule of prices is developed in the US standard measure system, the department will pay for the work as bid in the US standard system. 100-005 (20141107)

2. Scope of Work.

The work under this contract shall consist of excavation, installation of concrete bases, monotube poles and mast arms, conduit, control vaults and all incidental items necessary to complete the work as shown on the plans and included in the proposal and contract. 104-005 (20090901)

3. Prosecution and Progress.

Begin work within ten calendar days after the engineer issues a written notice to do so.

Construct the project as to maintain a minimum of one lane of traffic in each direction as shown on the traffic control plan.

Provide the time frame for construction of all work on the project within the 2015 construction season. Provide the time frame to the engineer in writing within a month after executing the contract but at least 14 calendar days before the preconstruction meeting. Assure that the time frame is consistent with the contract completion time. Upon approval, the engineer will issue the notice to proceed within 10 calendar days before the beginning of the approved time frame.

To revise the time frame, submit a written request to the engineer at least two weeks before the beginning of the intended time frame. The engineer will approve or deny that request based on the conditions cited in the request and its effect on the department's scheduled resources.

2984-04-71 2 of 25

Add the following to standard spec 108.9.2:

If the contractor desires to work on Saturday, Sunday, or nationally recognized legal holidays, he must obtain approval from the engineer at least 24 hours in advance. If scheduling changes after approval has been obtained, notify the engineer as soon as possible, but not later than 3:00 PM of the prior day.

Except where noted, keep the intersection accessible at all times. Include any costs associated with staging operations at intersections that are to remain accessible at all times in the unit bid price for Traffic Control (Project).

Maintain or provide pedestrian access to adjacent properties, businesses, and at bus stops where necessary, as directed by the engineer. Provide adequate temporary sidewalk and bridging where the median or walk is impacted by construction activities or as directed by the engineer. The cost of bridging shall be included in the unit bid price for Concrete Sidewalk 5-Inch.

Add the following to standard spec 107.18:

When performing the roadway cleaning operation, use equipment having vacuum or water-spray mechanisms to eliminate the dispersion of dust. If vacuum equipment is employed, it must have suitable, self-contained particulate collectors to prevent discharge from collection bin into the atmosphere.

Store drums, buckets and other containers related to construction operations in a secure area to prevent vandalism, spills, and unwanted dumping. If an abandoned container is discovered on the project site, notify the WDNR at (800) 943-0003.

4. Public Convenience and Safety.

Revise standard spec 107.8(6) as follows:

Check for and comply with local ordinances governing the hours of operation of construction equipment. Do not operate motorized construction equipment from 9:00 PM until the following 7:00 AM, unless prior written approval is obtained from the engineer. 107-0001 (20060512)

5. Holiday Work Restrictions.

Do not perform work on, nor haul materials of any kind along or across any portion of the project, and entirely clear the traveled way and shoulders of such portions of the roadways of equipment, barricades, signs, lights, and any other material that might impede the free flow of traffic during the following holiday periods:

2984-04-71 3 of 25

- From noon Thursday, July 2, 2015 to 6:00 AM Monday, July 6, 2015 for Independence Day;
- From noon Friday, September 4, 2015 to 6:00 AM Tuesday, September 8, 2015 for Labor Day.

107-005 (20050502)

6. Utilities.

This contract does not come under the provision of Administrative Rule Trans 220. 107-065 (20080501)

The City of Milwaukee has notified the department that the following operations necessary for the construction of new facilities and/or adjustment of existing facilities will be coordinated with the contractor's construction operations by each representative utility unless otherwise noted. Coordinate construction activities with a call to Digger's Hotline or a direct call to the utilities that have facilities in the area as required by statutes. Use caution to ensure the integrity of underground facilities and maintain code clearances from overhead facilities at all times.

Note: Bidders are advised to contact each utility company listed in the plans prior to preparing their bid to obtain current information on the status of each utility company's work required in association with the project. Existing trees, street light poles, hydrants and utility poles are to remain in place during construction unless noted on plans. Conduct an on-site visit prior to bidding to determine any special measures required for proper clearance between the trees, hydrants, poles, other utilities and any other physical structures and the construction equipment. During construction operations, keep all manholes accessible to utility companies for emergencies.

A City of Milwaukee

1. Water

The Milwaukee Water Works has facilities within the limits of the project. No work is anticipated on water facilities. Contact Mr. Musa Abu-Khader of the City of Milwaukee at (414) 286-2432 with any concerns or questions.

2. Sewer

The City of Milwaukee has storm sewer and sanitary sewer facilities within the limits of the project. No work is anticipated on storm or sanitary sewer facilities. Contact Mr. Musa Abu-Khader of the City of Milwaukee at (414) 286-2432 for coordination of work, with any concerns or questions.

3. Street Lighting

The City of Milwaukee has street lighting facilities within the limits of the project. No work is anticipated on the street lighting facilities. Contact Mr. Denis Kozelek of the City of Milwaukee at (414) 286-3252 with any concerns or questions.

2984-04-71 4 of 25

4. Underground Conduits and Communications (TES)

The City of Milwaukee has communications. fiber and copper cables in underground conduit located throughout the project limits. These cables will be kept in operation during construction. Take precaution when working near these facilities to prevent damage. Contact Ms. Karen Rogney of the City of Milwaukee at (414) 286-3243 with any concerns or questions.

5. Traffic Signals and Signs

City of Milwaukee Traffic Signals and Signs has facilities located within the limits of the project. Specified PVC Conduits, vaults, bases, and monotube mast arm structures are to be installed by the contractor as part of this project. Prior to construction, any needed pole, signal standard, and control cabinet relocations; and temporary traffic signal work will be completed by City of Milwaukee forces. Coordinate all traffic control staging with the City of Milwaukee.

In coordination with contractor installed facilities, cable and signal hardware will be installed, modified, upgraded, and replaced by City of Milwaukee forces as part of a Local Force Account (LFA) contract that is related to the project.

Provide a 10-working day advance notice to Mr. Al Nichols of the City of Milwaukee's Traffic Signal Field Operations at (414) 286-3687 office or (414) 708-5148 mobile, to coordinate the installation of traffic signal materials. Coordinate all Traffic Signal Operation with Mr. Joseph Blakeman of the City of Milwaukee's Traffic Engineering at (414) 286-8070 as well as any City traffic signal concerns.

B. WE Energies - Gas

WE Energies – Gas has facilities within the limits of the project. No impacts are anticipated at this time. Contact Mr. Tom Minesal of the WE Energies – Gas at (414) 944-5755 with any concerns or questions.

C. WE Energies – Electric

WE Energies - Electric has underground and overhead facilities within the limits of the project. Contact Mr. Ken Franecki of WE Energies – Electric at (414) 944-5531 with any concerns or questions.

D. Time Warner Cable

Time Warner Cable (TWC) has underground facilities within the limits of the project. No conflict is anticipated on Time Warner Cable facilities. Contact Mr. Steve Storm of Time Warner Cable (TWC) at (414) 908-4785 with any concerns or questions.

E. AT&T Wisconsin

AT&T has underground facilities within the limits of the project. No conflict is anticipated on the AT&T facilities. Contact Jay Bulanek (AT&T) at (414) 535-7407 with any concerns or questions.

2984-04-71 5 of 25

F. Mcleod USA/ Windstream

Mcleod USA/ Windstream has underground facilities within the limits of the project. No conflict is anticipated on Mcleod USA/Windstream facilities. Contact Mr. James Kostuch (Windstream) at (262) 792-7938 with any concerns or questions.

G. Level 3 Communication

Level 3 Communication has underground facilities within the project limits. No conflicts with these facilities are anticipated. Contact Ms. Nickey Worthington at (720) 888-0336 with any concerns or questions.

H. American Transmission Company

American Transmission Company has an underground 138kV pipeline running along the south side of W. National Ave. at S. 1st St., and also on the southeast corner of W. McKinley Ave. and N. 6th St., both within the project limits. No conflicts with these facilities are anticipated. All work near an underground transmission pipe type cable must be supervised by an ATC representative. Three day prior notification is required to arrange for ATC presence on site during the construction (call Ron Latus at (262) 364-9048). The contractor is responsible for taking any and all precautions to avoid soil compaction, sinking, and any other circumstances that would cause damage to the 138kV pipe type cable. The pipe type cable must be adequately protected using mats or steel road plating during all work activities over the pipe type cable. When heavy equipment is positioned on soil over the ATC pipe type cable, the entire area under the equipment must be reinforced using appropriate construction matting to equalize the weight over the pipe type cable.

I. TDS Metrocom

TDS Metrocom has underground facilities inside AT&T conduit within the project limits. No conflicts with these facilities are anticipated. Call Matt Schulte at (262) 754-3063 with any questions or concerns.

7. Notice to Contractor – Survey.

Digital design file information/existing surface data, including design surface DTMs and/or coordinate system GPS information will not be available for this project.

8. Erosion Control.

Perform this work in accordance to the requirements of standard spec 107.20 and as hereinafter supplemented.

Take adequate precautions to install and maintain necessary erosion and sediment control during grading and construction operations at curbs and gutters, and at other locations determined by the engineer. Protect storm drain inlets and manholes, as determined by the engineer, with a filter fabric meeting accepted design criteria, standards, and specifications. Maintain all erosion control measures until such time that the engineer determines the measures are no longer necessary.

2984-04-71 6 of 25

Submit the Erosion Control Implementation Plan (ECIP) a minimum of 14 days prior to the preconstruction meeting for approval by the department and concurrence by the Wisconsin Department of Natural Resources (DNR). Contractor will not be allowed to start until written approval has been received from the department.

9. Tree and Planting Area Protection.

Sidewalk Construction

Do not cut the root system on the walk side of the tree deeper than 9 inches below the finished grade of the new walk, and not more than 5 inches from the edge of the new walk. Remove roots in the walk area only to a depth of 9 inches below finished grade of the new walk.

General

Manually perform all cutting for the removal of sod and soil in order to establish a finished grade within 4 feet of existing trees, if necessary. Do not park or store any construction equipment, cars, trucks, and/or materials on tree borders on this project or adjacent roadways. Root foundations must remain adequate to withstand heavy windstorms. Do not cut root systems of street trees for the installation of any type of cable by the contractor or City of Milwaukee department.

Use caution during the construction process to avoid damage to the roots, trunks, and branches of all street trees. The contractor shall be responsible for excessive damage to the roots, trunks, and branches of all street trees.

Refrain from placing or storing any construction materials, sand, soil, or any other materials on the surface of the soil within the root zone of existing City of Milwaukee street trees. Additionally, assure that no construction chemicals, tank rinsates, or petroleum products are deposited within the root zones of the trees. Root zone is defined as that area within the dripline of trees.

Irrigation systems are present at the following locations:

N. 6th St. and W. McKinley Ave.

The water service to these irrigation systems will remain active. Contact Mr. James Kringer at (414) 708-2428 at least 5 working days prior to any work being done at these locations.

10. Construction Trenches.

Upon completion of the normal workday and when work is not in progress, plate all trenches resulting from construction activities, which are not fully backfilled, with steel plates suitable for carrying a vehicle as directed by the engineer. Plating is in addition to the barricades and traffic control devices required for lane closure or traffic control. Cost of steel plates shall be included in the bid prices for the related bid items that are under construction.

2984-04-71 7 of 25

11. Concrete Identification Stamping.

Stamp ends of all monolithic Portland cement concrete surfaces with a stamp bearing the contractor's name and the year of construction. Make all letters 2 inches in height.

Include the cost of this work in the contract unit price for Portland cement concrete items and no additional payment will be made.

12. Concrete Lighting Conduit Box-Outs.

The labor associated with construction of the concrete sidewalk box-outs shown on the lighting conduit plans for street light poles, signal standards, and/or conduit junction boxes will be incidental to bid item 602.0410, Concrete Sidewalk 5-Inch.

13. Traffic Control.

Supplement standard spec 643 with the following:

Permanently label each barricade, sign or other traffic control device with the name and telephone number for 24-hour emergency service, printed in letters at least ¾ inches in height.

No operation may proceed until all traffic control devices for such work are in the proper location.

During the life of this contract, provide 24 hour-a-day availability of equipment and forces to promptly restore barricades, lights, signs or other traffic control devices that are damaged or disturbed. In no case may any barricade, light, sign or other traffic control device be out of service for more than 2 hours. The cost to maintain and restore the above items is incidental to the bid item Traffic Control and no additional payment will be made therefore.

Have available at all times sufficient experienced personnel to promptly install, remove and reinstall the required traffic control devices to route traffic in order to perform the operations.

Provide the City of Milwaukee Police Department and the engineer a current telephone number with which the contractor or his representative can be contacted during non-working hours in the event a safety hazard develops.

Mask out all traffic control signs and have flags removed when not in use.

The traffic requirements are subject to change at the direction of the engineer in the event of an emergency.

2984-04-71 8 of 25

Receive prior approval from the engineer for the location of egress or ingress for construction vehicles to prosecute the work.

Park or store equipment and materials only at work sites approved by the engineer. Do not disturb, remove, or obliterate any traffic control signs, advisory signs, shoulder delineators, or beam guard in place along the traveled roadways without the approval of the engineer.

Install appropriate advance and intermediate warning signs of standard design. Install the signs at locations indicated on the plan and at locations as directed by the engineer in accordance to Part VI of the Manual of Uniform Traffic Control Devices. Sign shape, message and color must be in accordance to Part VI of the Manual of Uniform Traffic Control Devices.

14. Construction Staking Electrical Installations 2984-04-71, Item 650.8500.01.

Supplement standard spec 650 with the following:

The traffic poles, bases and vaults are referenced from the right of way line to the center. See drawing details for any additional information.

15. Conduit Rigid Nonmetallic Schedule 40 3-Inch, Item 652.0235.

Supplement standard spec 652, with the following:

Locations of the conduits where they are required are identified in the plans. However, installation will require integration with existing field conditions. Appropriate adjustment on conduit locations may be made if the field conditions are such that the pipes cannot be installed at the specified locations. Any relocation of greater than 5 feet must be approved by the engineer.

Plan changes must be approved by the City of Milwaukee's electric services supervisor or traffic engineer. The primary contacts are Mr. Dennis Miller, Street Lighting Operations supervisor (414) 286-5942 office, (414) 708-4251 mobile; or Mr. Joseph Blakeman, traffic control engineer (414) 286-8070.

Provide three sets of as-built plans to City of Milwaukee electric services supervisor or engineer upon completion of conduit installation. The plan sets are incidental to the conduit installation, and no extra payment will be made by the department.

2984-04-71 9 of 25

16. Concrete Bases Type **10**, Item **654.0110**.

Replace standard spec 654.2(4) with the following:

Contractor shall supply templates, anchor rods, nuts, and washers for installation as shown on the plans.

Add the following to standard spec 654.3:

Contractor shall contact City of Milwaukee Sewer Engineering five working days prior to excavation for any concrete bases. Contact Bob Brooks at (414) 286-3241 or Nancy Alvarado at (414) 286-2013 to confirm lateral clearance with sewer facilities.

Replace standard spec 654.5(2) with the following:

Payment for the Bases bid items is full compensation for providing concrete bases; for embedded conduit and electrical components; for anchor rods, nuts, and washers; for bar steel reinforcement; and for excavating, brick removals, backfilling and disposing of surplus materials.

17. Concrete Base Type 10 Special, Item SPV.0060.01.

A Description

This special provision describes constructing Concrete Base Type 10 Special with a 36-inch diameter for monotube mast arm structures. All work shall conform with standard spec 654 with modifications as shown on the plans, and as hereinafter provided.

B Materials

Replace standard spec 654.2(4) with the following:

Furnish templates, anchor rods, nuts, and washers for installation as shown on the plans.

C Construction

Construction of this item shall conform with standard spec 654.

Contact City of Milwaukee Sewer Engineering five working days prior to excavation for any concrete bases. Conact Bob Brooks at (414) 286-3241 or Nancy Alvarado at (414) 286-2013 to confirm lateral clearance with sewer facilities.

D Measurement

The department will measure Concrete Base Type 10 Special as each individual concrete base, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

2984-04-71 10 of 25

ITEM NUMBER DESCRIPTION UNIT SPV.0060.01 Concrete Base Type 10 Special Each

Payment for the Bases bid items is full compensation for providing concrete bases; for embedded conduit and electrical components; for anchor rods, nuts, and washers; for bar steel reinforcement; and for excavating, brick removals, backfilling and disposing of surplus materials.

18. Poles Type 9, Item SPV.0060.02.

A Description

Work under this item consists of furnishing and installing monotube poles as shown in the standard detail drawing for Type 9 Pole 15' - 30' Monotube Arm, and as hereinafter specified.

B Materials

Design support structures conforming to the minimum wall thickness the plan details show and to AASHTO design and fabrication standards for structural supports for highway signs, luminaries, and traffic signals. Use a design life to 50 years. Design to withstand a three second gust wind speed of 90 mph (145 km/h). Do not use the methods of Appendix C of those AASHTO standards.

Use category III criteria for 15 to 30-foot arms.

For structures requiring a fatigue analysis, use 45 mph (72 km/h) for truck-induced gusts.

After welding and before zinc coating, clean the exterior surface of each steel pole free of all loose rust and mill scale, dirt, oil or grease, and other foreign substances.

Apply a zinc coating conforming to the process specified for steel sign bridges in standard spec 641.2.8. Ensure that the zinc coating is tight, free from rough areas or slag, and presents a uniform appearance.

After completing manufacturing, clean the exterior surfaces of each pole free of all loose scale, dirt, oil or grease, and other foreign substances.

Provide a reinforced hand hole measuring 4 inches by 6 inches (100 mm by 150 mm) as the plans show. Locate the hand hole 18 inches (450 mm) from the bottom of the pole base to the center of the door.

For the hand hole, include an access cover mounted to the pole by two $\frac{1}{4}$ "-20 x $\frac{3}{4}$ " (m6 x 1.00 x 19 mm) hex-head stainless steel bolts.

Provide a grounding lug complete with mounting hardware, as required, inside the pole as the plans show.

2984-04-71 11 of 25

Provide access to the grounding lug from the hand hole. Weld the ground lug directly opposite the hand hole on the inside wall of the pole.

Equip the top of the shaft with a removable, ventilated cap held securely in place by at least three 1/4" -20 x 3/4" (m6 x 1.00 x 19 mm) hex-head stainless steel set screws.

Ensure that all castings are clean, smooth, and with all details well defined and true to pattern.

Attach base plates firmly to the pole shaft by welding or other approved method.

Include anchor bolts meeting AASHTO standards applicable to the pole type and loading.

Provide a mounting template that ensures correct installation of anchor bolts in foundation.

C Construction

Install poles as specified in the plan details and using appropriate contractor-furnished anchor bolts and hardware. Use the appropriate anchor bolt template to ensure correct installation. Secure pole to anchor assembly and document tensioning procedures conforming to standard spec 657.3.2 and provide completed copies of form DT2321 for each structure to the engineer for inclusion in the permanent record.

After completing erection using normal pole shaft raking techniques, ensure the centerline of the shaft appears vertical.

D Measurement

The department will measure Poles Type 9 as each individual pole, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.02Poles Type 9Each

Payment is full compensation for providing and installing poles including all hardware and fittings necessary to install the poles.

19. Poles Type 12 Special, Item SPV.0060.03; Poles Type 13 Special, Item SPV.0060.04.

A Description

Work under this item consists of furnishing and installing monotube poles as shown on the plans and specified below.

2984-04-71 12 of 25

B Materials

Design support structures conforming to the minimum wall thickness the plan details show and to AASHTO design and fabrication standards for structural supports for highway signs, luminaries, and traffic signals. Use a design life of 50 years. Design to withstand a three second gust wind speed of 90 mph (145 km/h). Do not use the methods of Appendix C of those AASHTO standards.

Use category II criteria for 35 to 55-foot arms.

For structures requiring a fatigue analysis, use 45 mph (72 km/h) for truck-induced gusts.

After welding and before zinc coating, clean the exterior surface of each steel pole free of all loose rust and mill scale, dirt, oil or grease, and other foreign substances.

Apply a zinc coating conforming to the process specified for steel sign bridges in standard spec 641.2.8. Ensure that the zinc coating is tight, free from rough areas or slag, and presents a uniform appearance.

After completing manufacturing, clean the exterior surfaces of each pole free of all loose scale, dirt, oil or grease, and other foreign substances.

Provide a reinforced hand hole measuring 4 inches by 6 inches (100 mm by 150 mm) as the plans show. Locate the hand hole 18 inches (450 mm) from the bottom of the pole base to the center of the door.

For the hand hole, include an access cover mounted to the pole by two $\frac{1}{4}$ "-20 x $\frac{3}{4}$ " (m6 x 1.00 x 19 mm) hex-head stainless steel bolts.

Provide a grounding lug complete with mounting hardware, as required, inside the pole as the plans show.

Provide access to the grounding lug from the hand hole. Weld the ground lug directly opposite the hand hole on the inside wall of the pole.

Equip the top of the shaft with a removable, ventilated cap held securely in place by at least three 1/4" -20 x 3/4" (m6 x 1.00 x 19 mm) hex-head stainless steel set screws.

Ensure that all castings are clean, smooth, and with all details well defined and true to pattern.

Attach base plates firmly to the pole shaft by welding or other approved method.

Include anchor bolts meeting AASHTO standards applicable to the pole type and loading.

Provide a mounting template that ensures correct installation of anchor bolts in foundation.

2984-04-71 13 of 25

C Construction

Install poles as specified in the plan details and using appropriate contractor-furnished anchor bolts and hardware. Use the appropriate anchor bolt template to ensure correct installation. Secure pole to anchor assembly and document tensioning procedures conforming to standard spec 657.3.2 and provide completed copies of form DT2321 for each structure to the engineer for inclusion in the permanent record.

After completing erection using normal pole shaft raking techniques, ensure the centerline of the shaft appears vertical.

D Measurement

The department will measure each Poles Type 12 Special and Poles Type 13 Special as each individual pole, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.03	Poles Type 12 Special	Each
SPV.0060.04	Poles Type 13 Special	Each

Payment is full compensation for providing and installing poles including all hardware and fittings necessary to install the poles.

20. Monotube Arms 30-FT, Item SPV.0060.05; Monotube Arms 35-FT, Item SPV.0060.06.

A Description

Work under this item consists of furnishing and installing monotube arms. Furnish and install Monotube Arms 30-FT Special and Monotube Arms 35-FT Special according to the standard detail drawing for Type 9 Pole 15' – 30' Monotube Arm, Type 12 Pole 35'-55' Monotube Arm, and Type 13 Pole 35' – 55' Monotube Arm.

B Materials

Design support structures conforming to the minimum wall thickness the plan details show and to AASHTO design and fabrication standards for structural supports for highway signs, luminaries, and traffic signals. Use a design life of 50 years. Design to withstand a 3 second gust wind speed of 90 mph (145 km/h). Do not use the methods of appendix C of those AASHTO standards.

Use category III criteria for 15 to 30-foot arms. Use category II criteria for 35 to 55-foot arms.

For structures requiring a fatigue analysis, use 45 mph (72 km/h) for truck-induced gusts.

2984-04-71 14 of 25

Base the designs on the completed maximum loading configuration the standard detail drawing shows. Along with the materials list, submit a certificate of compliance certifying that the arms as furnished conform to the above structural performance requirements. Ensure that the certificate of compliance is on the manufacturer's letterhead, signed by an authorized company officer, and notarized. Send a copy of the certificate and a copy of the monotube arm shop drawings to the department electrical engineer.

Furnish monotube arms conforming to the following:

- 1. Consist of zinc coated steel round or oval members.
- 2. Have a mounting device welded to the pole end of the monotube arm that allows the attachment of the arm to a pole as the plans show.
- 3. Have stiffeners or gussets if required between the arm tube and the arm mounting device to provide adequate strength to resist side loads.
- 4. Have a clean, uniform natural finish. No paint or other corrosion preventive maintenance coating is required.

After welding and before zinc coating, clean exterior surfaces of each arm free of all loose rust and mill scale, dirt, oil or grease, and other foreign substances.

Apply zinc coating as specified for sign bridge components in 641.2.8. Ensure that the zinc coating is tight, free from rough areas or slag, and presents a uniform appearance.

After manufacturing is complete, clean the exterior surfaces of each pole free of all loose scale, dirt, oil, or grease, and other foreign substances.

C Construction

Install monotube arms as specified in the plan details and using appropriate contractor-furnished hardware.

Prior to installation of each monotube arm, a 1 1/4-inch hole shall be drilled into the bottom of the arm approximately centered over each driving lane as shown on the plans. Where emergency vehicle pre-emption (EVP) is installed, a separate 1 1/4-inch hole shall be drilled in the bottom of the arm approximately centered over the roadway approach, but a minimum of four feet from the nearest drilled hole.

The contractor shall provide 9-14 AWG traffic signal cable spooled 5 feet outside the arm from each drilled hole in the arm, including the hole for EVP if applicable, to the base of the pole below the hand hole. A separate nylon pull rope shall also be provided for the EVP hole to the base of the pole below the hand hole where applicable.

2984-04-71 15 of 25

D Measurement

The department will measure Monotube Arm (Length) as each individual arm, acceptably completed.

E Payment

The department will pay for measured quantity at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.05Monotube Arms 30-FTEachSPV.0060.06Monotube Arms 35-FTEach

Payment is full compensation for providing and installing all materials, including all hardware, fittings, mounting devices, shims, and attachments necessary to completely install the arms.

21. Rectangular Polymer Concrete Vault 13-Inch x 24-Inch x 18-Inch, Item SPV.0060.07.

A Description

This special provision describes furnishing and installing Rectangular Polymer Concrete Vaults as shown in the plans and specified herein.

B Materials

Rectangular Polymer Concrete shall be manufactured from one of the general types of grades defined in polymers in concrete structural applications state of the art report, ACI 548.6R-96 for structural uses. Thermoplastics will not be acceptable.

Enclosure walls shall be made from pattern cut structural fiberglass cloths to assure uniform, pre-measurable fiberglass content on all areas. Chopper gun fiberglass construction is not acceptable.

Binding polymers used in the manufacture of the polymer concrete and the fiber reinforced polyester shall be of the same formulation or from formulations with demonstrated chemical compatibility to assure complete chemical bonding of all components. Fiber reinforced polyester wall sections must be cast integrally into and chemically bonded within the upper polymer concrete casting.

1. Testing

Meet ANSI/SCTE 77 2010 (<u>Tier 15 or greater</u>), ASTM C 857, and WUC 3.6 structural requirements.

Compressive Modulus of Elasticity (fiberglass reinforced polymer): $5.6 \times 10^6 \text{ PSI}$ tested in accordance to procedures outlined in ASTM D-695.

2984-04-71 16 of 25

Comprehensive Strength (fiberglass reinforced polymer): 24,300 PSI tested in accordance to procedures outlined in ASTM D-695.

Flexural Strength (fiberglass reinforced polymer): 18,700 PSI tested in accordance to ASTM D-790.

Tensile Strength (fiberglass reinforced polymer) 12,100 PSI tested in accordance to procedures outlined in ASTM D-638.

Tensile Modulus of Elasticity (fiberglass reinforced polymer): 8.6 x 10⁵ PSI tested in accordance to procedures outlined in ASTM D-638.

Splitting Tensile Strength (polymer concrete): Tested in accordance to procedures outlined in ASTM C-496.

Accelerated Service: Tested in accordance to procedure E outlined in ASTM D-756.

Water Absorption: Tested in accordance to ASTM D-570 outlined in sections 6.1 and 6.5.

Impact Resistance (fiberglass reinforced polymer concrete): 72 foot pounds in accordance to ASTM D-2444 administered with a "C" tup.

Skid Resistance: 0.60 coefficient of friction in accordance to ASTM C-1028.

Flammability Test: Tested in accordance to ASTM D-635.

Ultraviolet Exposure: Tested in accordance to ASTM test method G-53.

Chemical Resistance
Sodium Chloride 5%
Sodium Carbonate 0.1 N
Hydrochloric Acid 0.2 N
Acetic Acid 5%
Sulfuric Acid 0.1 N
Sodium Sulfate 0.1 N
Sodium Hydroxide 0.1 N
Kerosene Oil per ASTM D-543
Transformer Oil per ASTM D-543

The street lighting vaults and covers shall be gray in color and shall be Flared Wall as indicated on the Drawings. Covers shall be provided with 2 stainless steel bolts. Each cover shall have the words "STREET LIGHTING" cast into its surface along the longest dimension. The words shall be permanently recessed into the surface.

Underground enclosures must successfully pass numerous material and product performance tests before they can meet ANSI/SCTE 77. These tests include:

2984-04-71 17 of 25

- Three Position Load Testing to Simulate Actual Application
- UV Degradation per ASTM G-53
- Fire Resistance per RUS7CFR 1755.910 and WUC 3.6 Section 5.2.7
- Chemical Resistance per ASTM D-543
- Water Absorption per ASTM D-570
- Load and Deflection Requirements per SCTE Coaxial Practice, Section 5
- Impact Resistance per ASTM D-2444
- Accelerated Service per ASTM D-756

C Construction

Install Rectangular Polymer Concrete Vaults as shown on the plans and specified herein. Provisions for inserting conduit into any side or the bottom of the vault shall be included.

D Measurement

The department will measure Rectangular Polymer Concrete Vault 13-Inch x 24-Inch x 18-Inch by each individual unit, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.07	Rectangular Polymer Concrete Vault	Each
	13-Inch x 24-Inch x 18-Inch	

Payment is full compensation for furnishing labor, equipment, coordination and all materials and incidentals necessary to complete the work.

22. Inlet Screen Type M, Item SPV.0060.08.

A Description

This special provision describes furnishing, installing, and maintaining proper inlet screens as directed by the engineer, as shown on the drawings, and as hereinafter provided.

B Materials

Use woven filtration geotextile fabric with the following physical properties:

Method	Value
ASTM D-4632	180 min.
ASTM D-3786	200 min.
ASTM D-4751	US No. 30 max.
ASTM D-4491	140 min.
ASTM D-4491	1.9 min.
ASTM D-4491	0.14 min.
	ASTM D-4632 ASTM D-3786 ASTM D-4751 ASTM D-4491 ASTM D-4491

2984-04-71 18 of 25

C Construction

C.1 Installation

The control of soil erosion requires flexibility to accommodate changing conditions as the construction project progresses. In general, install the erosion control device at locations as described on the plan.

At all inlet locations, install a Type M screen. If the inlet being protected has a side inlet box, seal the inlet box until inlet protection is no longer needed. These screens must be in place prior to the start of any work, including sawing.

C.2 Maintenance

Continue cleaning and repair of all types of control devices until the engineer accepts the work. All such cleaning and repair, as well as the eventual removal of the devices, is the responsibility of the contractor.

Completely clean out manholes into which dirt or other debris has fallen before the end of each work day. Should the contractor not perform the cleaning as required, his operation may be shut down until the situation is corrected.

Protect all control measures protruding above the normal paved and/or ground surface where vehicular and/or pedestrian traffic is being maintained by barricades with flashing lights.

Inspect the inlet basket within 24 hours after each rainfall or daily during extended periods of precipitation. Make repairs immediately, as necessary, to prevent particles from reaching the sewerage system and/or causing the surface flooding.

Remove sediment deposits after each storm event or as often as the fabric becomes clogged. Failure to maintain clean, debris free inlet baskets may result in the contractor's operations being shut down.

D Measurement

The department will measure Inlet Screen, Type M as each individual unit, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.08Inlet Screen Type MEach

Payment is full compensation for supplying, installing and properly maintaining the devices.

2984-04-71 19 of 25

23. Utility Line Opening (ULO), Item SPV.0060.09.

A Description

This special provision describes excavating to uncover utilities for the purpose of determining elevation or location and potential conflicts as shown on the plans or as directed by the engineer.

B (Vacant)

C Construction

Perform the excavation in such a manner that the utility in question is not damaged and the safety of the workers is not compromised.

Perform the utility line openings as soon as possible and at least 10 days in advance of proposed utility construction to allow any conflicts to be resolved with minimal disruption. Give the engineer a minimum of three working days once utility line opening information is received to review all relevant design information prior to proposed utility construction. Where utilities are within 6 feet of each other at a potential conflict location, only one utility line opening will be called for. In these cases, a single utility line opening will be considered full payment to locate multiple utilities. Utility line openings include a trench up to 10 feet long as measured at the trench bottom, and of any depth required to locate the intended utility.

Approve and coordinate all utility line openings with the engineer. Notify the utility engineers or their agents of this work a minimum of 3 days prior to the work so they may be present when the work is completed.

Replace pavement over utility line opening trenches which are within the staged traffic area as directed by the engineer. Replace pavement and open to traffic within 24 hours of the excavation.

D Measurement

The department will measure Utility Line Opening (ULO) by each individual unit, acceptably completed.

E. Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.09 Utility Line Opening (ULO) Each

Payment is full compensation for the excavation required to expose the utility line; backfilling with existing material removed from the excavation; compacting the backfill; restoring the site; and for cleanup.

2984-04-71 20 of 25

Existing pavement, concrete curb, gutter, and sidewalk removals necessary to facilitate utility line openings are not considered part of or paid for under Utility Line Openings, but are considered separate and measured and paid for separately as removal items. Pavement replacement material, concrete curb, gutter, and sidewalk items will also be considered separate from Utility Line Openings and will be measured and paid for separately.

24. Management of Solid Waste, Item SPV.0195.01.

A General

A.1 Description

This work will conform with the requirements of standard spec 205; to pertinent parts of the Wisconsin Administrative Code, Chapters NR 700-736 Environmental Investigation and "Remediation of Environmental Contamination; Wisconsin Administration Code, Chapters NR 500-538, Solid Waste; and as shown on the plans and as supplemented herein.

Contaminated soil classified as solid waste will be encountered within the construction limits. Impacted waste material excavated during construction which cannot in the opinion of the environmental consultant be managed as common excavation or as petroleum-contaminated solid will be managed as solid waste.

This work consists of excavating, segregating, temporary stockpiling, loading, hauling, and disposing of solid waste material at a WDNR-approved disposal facility. The nearest WDNR-approved disposal facilities are:

Advanced Disposal Emerald Park Landfill, LLC W124 S10629 South 124th Street Muskego, WI 53150 (414) 529-1360

Waste Management Orchard Ridge Landfill N96 W13503 County Line Road Menomonee Falls, WI 53051 (262) 532-6200

Provide information to the environmental consultant and engineer that indicates the WDNR-approved disposal facility that the contractor will use.

A.2 Notice to the Contractor – Solid Waste (Contaminated Soil) Locations

The department and others completed hazardous materials assessment for locations within this project where excavation is required. Investigation for soil contamination was conducted at select locations. Results indicate that contaminated soil classified as solid waste is present at the following locations as shown on the plans:

2984-04-71 21 of 25

Southeast corner at the intersection of W. McKinley Ave. and N. 6th St., 15.5' east of right-of-way and 10.0' north of right-of-way, from approximately 8' to at least 16.5' bgs. Soil at this location is contaminated with lead. Approximately 9 cubic yards (approximately 16 tons at an estimated 1.7 tons per cubic yard) of lead-contaminated soil will be excavated here for traffic light monotube installation.

Southwest corner at the intersection of W. National Ave. and S. 1st St., from approximately 6' to 8' below ground surface. Soil at this location contains non-exempt solid waste (foundry sand and slag). Approximately 4 cubic yards (approximately 7 tons at an estimated 1.7 tons per cubic yard) of soil containing foundry sand and slag will be excavated from this location for traffic light pole installation.

Northeast corner of the intersection of W. National Ave. and S. 1st St., from approximately 4' to 6' below ground surface. Soil at this location contains non-exempt solid waste (foundry sand and slag). Approximately 4 cubic yards (approximately 7 tons at an estimated 1.7 tons per cubic yard) of soil containing foundry sand and slag will be excavated from this location for traffic light pole installation.

Directly load solid waste excavated by the project at the above location into trucks that will transport the material to a WDNR-licensed landfill facility for landfill disposal.

A.3 Notice to the Contractor – Contaminated Soil Beyond the Construction Limits

If obviously contaminated soils or other signs of NR 500 non-exempt solid waste and hazardous materials are unexpectedly encountered elsewhere on the project, terminate excavation activities in the area and notify the engineer. Examples of these unexpected conditions may include, but are not limited to, buried containers or tanks, noxious odors and fumes, stained soils, sheen on ground water, other industrial wastes, and significant volumes of municipal or domestic garbage.

No active groundwater monitoring wells were observed within the construction limits. If active groundwater monitoring wells are encountered during construction, notify engineer and protect them to maintain their integrity. The environmental consultant will determine if monitoring wells need to be maintained. For monitoring wells that do need to be maintained, adjust the wells that do not conflict with structures or curb and gutter to be flush with the final grade. For wells that conflict with the previously mentioned items or if monitoring wells are not required to be maintained, they will be abandoned by others.

If dewatering is required at the above location, conduct the dewatering in accordance to Section C below.

A.4 Excavation Management Plan Approval

The excavation management plan for this project has been designed to minimize the offsite disposal of contaminated waste. The excavation management plan, including these special provisions, has been developed in cooperation with the WDNR. The WDNR concurrence letter is on file at the Wisconsin Department of Transportation. For further

2984-04-71 22 of 25

information regarding previous investigation and remediation activities in these areas contact:

Name: Andrew Malsom

Address: 141 NW Barstow Street, Waukesha, WI 53187-0798

Phone: (262) 548-6705 Fax: (262) 548-6891

E-mail: Andrew.Malsom@dot.wi.gov

A.5 Coordination

Coordinate work under this contract with the environment consultant:

Consultant: TRC Environmental Corporation

Address: 150 N. Patrick Blvd. Ste. 180, Brookfield, WI 53045

Contact: Bryan Bergmann, P.G.

Phone: (262) -879-1212 Fax: (262) 879-1220

E-mail: <u>bbergmann@trcsolutions.com</u>

The role of the environmental consultant will be limited to:

Determining the location and limits of solid waste to be excavated based on soil analytical results from previous investigations, visual observations, and field screening of soil that is excavated:

Identifying soils to be hauled to the landfill facility;

Documenting that activities associated with management of solid waste are in conformance with the solid waste management methods for this project as specified herein; and

Obtaining the necessary approvals for disposal of solid waste from the landfill facility.

Provide at least a 14-calendar day notice of the preconstruction conference date to the environmental consultant. At the preconstruction conference, provide a schedule for all excavation activities in the area of solid waste described in A.2 to the environmental consultant. Identify the WDNR licensed landfill facility that will be used for disposal of solid waste, and provide this information to the environmental consultant no later than 30 calendar days prior to commencement of excavation in the impacted area or at the preconstruction conference, whichever comes first. The environmental consultant will be responsible for obtaining the necessary approvals from the landfill facility for disposal of the solid waste.

Coordinate with the environmental consultant to ensure that the environmental consultant is present during excavation in the impacted areas. Notify the environmental consultant at least three calendar days prior to commencement of excavation in the impacted area.

2984-04-71 23 of 25

Perform excavation in the impacted area on a continuous basis until excavation work is completed. Do not transport soil containing solid waste off-site without prior approval from the environmental consultant.

A.6 Health and Safety Requirements

Supplement standard spec 107.1 with the following:

During excavation activities, expect to encounter soil contaminated with regulated organic compounds and metals. Site workers taking part in activities that will result in the reasonable probability of exposure to safety and health hazards associated with hazardous materials shall have completed health and safety training that meets the Occupational Safety and Health Administration (OSHA) requirements for Hazardous Waste Operations and Emergency Response (HAZWOPER), as provided in 29 CFR 1910.120.

Prepare a site-specific Health and Safety Plan, and develop, delineate and enforce the health and safety exclusion zones for each impacted area as required by 29 CFR 1910.120. Submit the site-specific health and safety plan and written documentation of up-to-date OSHA training to the engineer prior to the start of work.

B (Vacant)

C Construction

Supplement standard spec 205.3 with the following:

Control operations in the impacted area to minimize the quantity of soil excavated.

The environmental consultant will periodically monitor soil excavated from the areas identified in A.2 above. The environmental consultant will evaluate excavated soil based on field screening results, visual observations, and soil analytical results from previous environmental investigations. Assist the environmental consultant in collecting soil samples for evaluation using excavation equipment. The sampling frequency shall be a maximum of one sample for every 20 cubic yards excavated.

Directly load and haul solid waste designated by the environmental consultant for off-site disposal to the WDNR approved landfill facility. Use loading and hauling practices that are appropriate to prevent any spills or releases of the material. Prior to transport, sufficiently dewater soils designated for off-site disposal so as not to contain free liquids.

Verify that the vehicles used to transport material are licensed for such activity in accordance to applicable state and federal regulations. Obtain the necessary disposal facility approvals and WDNR approvals for disposal. Do not transport regulated solid waste off site without obtaining the approval of the environmental consultant and engineer and notifying the disposal facility.

2984-04-71 24 of 25

During excavations in the areas of known contamination, larger chunks of clean concrete (~2 cubic feet), asphalt and bricks will be segregated from the fill, to the extent practical and managed as common excavation. Under NR 500.08 this material is exempt from licensing and requirements of Wisconsin Administrative Code NR 500-539-8 of the solid waste regulations, and will be reused as designated by the engineer as fill on the project, or it will be disposed of off site at the contractor's disposal site(s).

If dewatering is required in areas of known contamination, water generated from dewatering activities may contain VOCs and/or metals. Such water may, with approval of the Milwaukee Metropolitan Sewerage District (MMSD), be discharged to the sanitary sewer as follows:

- 1. Meet all applicable requirements of the MMSD including the control of suspended solids. Perform all necessary monitoring to document compliance with MMSD's requirements. Furnish, install, operate, maintain, disassemble, and remove treatment equipment necessary to comply with MMSD's requirements.
- 2. Ensure continuous dewatering and excavation safety at all times. Provide, operate, and maintain adequate pumping equipment and drainage and disposal facilities.

Notify the engineer of any dewatering activities, and obtain any permits necessary to discharge water. Provide copies of such permits to the engineer. Meet any requirements and pay any costs for obtaining and complying with such permit use. Follow all applicable legislative statutes, judiciary decisions, and regulations of the State of Wisconsin.

Costs associated with excavation dewatering in contaminated areas are considered incidental to this pay item. The Wisconsin Department of Transportation will be the generator of regulated solid waste from this construction project.

D Measurement

The department will measure Management of Solid Waste by the ton of waste accepted by the disposal facility and as documented by weight tickets, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following item:

ITEM NUMBERDESCRIPTIONUNITSPV.0195.01Management of Solid WasteTon

Payment is full compensation for excavating, segregating, loading, hauling, and landfill disposal of solid waste; obtaining solid waste collection and transportation service operating licenses; assisting in the collection of soil samples for field evaluation; and for dewatering of soils prior to transport, if necessary.

2984-04-71 25 of 25

November 2013 ASP-4

ADDITIONAL SPECIAL PROVISION 4

Payment to First-Tier Subcontractors

Within 10 calendar days of receiving a progress payment for work completed by a subcontractor, pay the subcontractor for that work. The prime contractor may withhold payment to a subcontractor if, within 10 calendar days of receipt of that progress payment, the prime contractor provides written notification to the subcontractor and the department documenting "just cause" for withholding payment.

The prime contractor may also withhold routine retainage from payments due subcontractors.

Payment to Lower-Tier Subcontractors

Ensure that subcontracting agreements at all tiers provide prompt payment rights to lower-tier subcontractors that parallel those granted first-tier subcontractors in this provision.

Release of Routine Retainage

After granting substantial completion the department may reduce the routine retainage withheld from the prime contractor to 75 percent of the original total amount retained.

When the Department sends the semi-final estimate the department may reduce the routine retainage withheld from the prime contractor to 10 percent of the original total amount retained.

Within 30 calendar days of receiving the semi-final estimate from the department, submit written certification that subcontractors at all tiers are paid in full for acceptably completed work and that no routine retainage is being withheld. The department will pay the prime contractor in full and reduce the routine retainage withheld from the prime contractor to zero when the department approves the final estimate.

This special provision does not limit the right of the department, prime contractor, or subcontractors at any tier to withhold payment for work not acceptably completed or work subject to an unresolved contract dispute.

ADDITIONAL SPECIAL PROVISION 6

ASP 6 - Modifications to the standard specifications

Make the following revisions to the standard specifications:

450.3.2.1 General

Replace the entire text with the following effective with the January 2015 letting:

- (1) Do not place asphaltic mixture when the air temperature approximately 3 feet above grade, in shade, and away from artificial heat sources is less than 36 F for upper layers or 32 F for lower layers unless the engineer allows in writing. The contractor should place HMA pavement for projects on or north of STH 29 between May 1 and October 15 inclusive and for projects south of STH 29 between April 15 and November 1 inclusive. Notify the engineer at least one business day before paving.
- (2) Unless the contract specifies otherwise, conform to the following:
 - Keep the road open to all traffic during construction.
 - Prepare the existing foundation for treatment as specified in 211.
 - Incorporate loose roadbed aggregate as a part of preparing the foundation, in shoulder construction, or dispose of as the engineer approves.
- (3) Place asphaltic mixture only on a prepared, firm, and compacted base, foundation layer, or existing pavement substantially surface-dry and free of loose and foreign material. Do not place over frozen subgrade or base, or where the roadbed is unstable.

450.5 Payment

Replace the entire text with the following effective with the May 2015 letting:

- (1) All costs of furnishing, maintaining, and operating the truck scale or other weighing equipment and furnishing the weigh tickets are incidental to the contract.
- (2) Nonconforming material allowed to remain in place is subject to price adjustment under 105.3.2.
- (3) Full-depth sawing to remove integrally placed safety edge where not required is incidental to the contract.
- (4) The contractor is responsible for the quality of HMA pavement placed in cold weather. If because of an excusable compensable delay under 108.10.3, the engineer directs the contractor to pave when the temperature is less than 36 F for the upper layer or less than 32 F for lower layers, the department:
 - Will relieve the contractor of responsibility for damage and defects the engineer attributes to cold weather paving.
 - Will not assess disincentives for density or ride.

455.3.2.1 General

Replace the paragraphs one and two with the following effective with the January 2015 letting:

- (1) Apply tack coat only when the air temperature is 32 F or more unless the engineer approves otherwise in writing. Before applying tack coat ensure that the surface is dry and reasonably free of loose dirt, dust, or other foreign matter. Do not apply if weather or surface conditions are unfavorable or before impending rains.
- (2) Use tack material of the type and grade the contract specifies. The contractor may, with the engineer's approval, dilute tack material as allowed under 455.2.4. Provide calculations using the asphalt content as-received from the supplier and subsequent contractor dilutions to show that as-placed material has 50 percent or more residual asphalt content. Apply at 0.050 to 0.070 gallons per square yard, after dilution, unless the contract designates otherwise. The engineer may adjust the application rate based on surface conditions. Limit application each day to the area the contractor expects to pave during that day.

460.2.2.3 Aggregate Gradation Master Range

Replace paragraph one with the following effective with the December 2014 letting:

(1) Ensure that the aggregate blend, including recycled material and mineral filler, conforms to the gradation requirements in table 460-1. The values listed are design limits; production values may exceed those limits.

TABLE 460-1 AGGREGATE GRADATION MASTER RANGE AND VMA REQUIREMENTS

		Р	ERCENTS PA	SSING DESIG	NATED SIEVE	S	
SIEVE	NOMINAL SIZE						
	37.5 mm	25.0 mm	19.0 mm	12.5 mm	9.5 mm	SMA 12.5 mm	SMA 9.5 mm
50.0-mm	100						
37.5-mm	90 –100	100					
25.0-mm	90 max	90 -100	100				
19.0-mm		90 max	90 -100	100		100	
12.5-mm			90 max	90 -100	100	90 - 97	100
9.5-mm				90 max	90 -100	58 - 72	90 - 100
4.75-mm					90 max	25 - 35	35 - 45
2.36-mm	15 – 41	19 - 45	23 - 49	28 - 58	20 - 65	15 - 25	18 - 28
75-µm	0 - 6.0	1.0 - 7.0	2.0 - 8.0	2.0 - 10.0	2.0 - 10.0	8.0 - 12.0	10.0 - 14.0
% MINIMUM VMA	11.0	12.0	13.0	14.0 ^[1]	15.0 ^[2]	16.0	17.0

^{[1] 14.5} for E-0.3 and E-3 mixes.

460.3.4 Cold Weather Paving

Add a new subsection as follows effective with the May 2015 letting:

460.3.4 Cold Weather Paving

460.3.4.1 Cold Weather Paving Plan

- (1) Submit a written cold weather paving plan to the engineer at the preconstruction meeting. In that plan outline material, operational, and equipment changes for paving when the air temperature approximately 3 feet above grade, in shade, and away from artificial heat sources is less than 40 F. Include the following:
 - Use a department-accepted HMA mix design that incorporates a warm mix additive from the department's approved products list. Do not use a foaming process that introduces water into the mix.
 - Use additional rollers.
- (2) Engineer written acceptance is required for the cold weather paving plan. Engineer acceptance of the plan does not relieve the contractor of responsibility for pavement performance except as specified in 450.5(4).

460.3.4.2 Cold Weather Paving Operations

- (1) Do not place asphaltic mixture when the air temperature approximately 3 feet above grade, in shade, and away from artificial heat sources is less than 40 F unless a valid engineer-accepted cold weather paving plan is in effect.
- (2) If the national weather service forecast for the construction area predicts ambient air temperature less than 40 F at the projected time of paving within the next 24 hours, confirm or submit revisions to a previously engineer-accepted cold weather paving plan for engineer validation. Upon validation of the plan, the engineer will allow paving for the next day. Once in effect, pave conforming to the engineeraccepted cold weather paving plan for the balance of that work day or shift regardless of the temperature at the time of paving.

^{[2] 15.5} for E-0.3 and E-3 mixes.

460.4 Measurement

Add paragraph two as follows effective with the January 2015 letting:

(2) The department will measure HMA Cold Weather Paving by the ton of HMA mixture for pavement placed conforming to an engineer-accepted cold weather paving plan.

460.5.1 General

Revise paragraph one as follows effective with the January 2015 letting:

(1) The department will pay for measured quantities at the contract unit price under the following bid items:

ITEM NUMBER	DESCRIPTION	<u>UNIT</u>
460.1100	HMA Pavement Type E-0.3	TON
460.1101	HMA Pavement Type E-1	TON
460.1103	HMA Pavement Type E-3	TON
460.1110	HMA Pavement Type E-10	TON
460.1130	HMA Pavement Type E-30	TON
460.1132	HMA Pavement Type E-30X	TON
460.1700	HMA Pavement Type SMA	TON
460.2000	Incentive Density HMA Pavement	DOL
460.4000	HMA Cold Weather Paving	TON

460.5.2.2 Disincentive for HMA Pavement Density

Revise paragraph two as follows effective with the January 2015 letting:

(2) The department will not assess density disincentives for pavement placed in cold weather because of a department-caused delay as specified in 450.5(4).

460.5.2.4 Cold Weather Paving

Add a new subsection as follows effective with the May 2015 letting:

460.5.2.4 Cold Weather Paving

- (1) Payment for HMA Cold Weather Paving is full compensation for additional materials and equipment specified for cold weather paving under 460.3.4 including costs for preparing, administering, and following the contractor's cold weather paving plan. The department will not pay for HMA Cold Weather Paving for HMA placed on days when the department is assessing liquidated damages.
- (2) If HMA pavement is placed under 460.3.4 and the HMA Cold Weather Paving bid item is not in the contract, the department will pay for the additional costs specified in 460.5.2.4(1) as extra work. The department will pay separately for HMA pavement under the appropriate HMA Pavement bid items.

465.2 Materials

Replace paragraph two with the following effective with the December 2014 letting:

(2) Under the other 465 bid items, the contractor need not submit a mix design. Furnish aggregates mixed with a type AC asphaltic material, except under the Asphaltic Curb bid item furnish PG58-28 asphaltic material. Use coarse and fine mineral aggregates uniformly coated and mixed with the asphaltic material in an engineer-approved mixing plant. The contractor may include reclaimed asphaltic pavement materials in the mixture.

506.3.2 Shop Drawings

Replace the entire text with the following effective with the May 2015 letting:

- (1) Ensure that shop drawings conform to the contract plans and provide additional details, dimensions, computations, and other information necessary for completely fabricating and erecting the work. Include project and structure numbers on each shop drawing sheet.
- (2) Check shop drawings and submit electronically to the department for review before beginning fabrication. For primary fabrication items, also certify that shop drawings conform to quality control standards by submitting department form DT2333. Department review does not relieve the contractor from responsibility for errors or omissions on shop drawings.
- (3) Shop drawings are part of the contract. The department must approve differences between shop drawings and contract plans. The contractor bears the costs of department-approved substitutions. Do not deviate from or revise drawings without notifying the department and resubmitting revised drawings.
- (4) Ensure that the fabricator delivers 3 sets of shop drawings for railroad structures to the railroad company upon contract completion.

Bid Items Added

Add the following new bid item effective with the January 2015 letting:

ITEM NUMBERDESCRIPTION460.4000HMA Cold Weather Paving

<u>UNIT</u> TON

Errata

Make the following corrections to the standard specifications:

501.3.2.4.4 Water Reducer

Correct errata by deleting the reference to footnote 6 for grade D concrete.

(1) Add a water reducing admixture conforming to 501.2.3. Determine the specific type and rate of use based on the atmospheric conditions, the desired properties of the finished concrete and the manufacturer's recommended rate of use. The actual rate of use shall at least equal the manufacturer's recommended rate, and both the type and rate used require the engineer's approval before use.

506.5 Payment

Correct errata by changing the reference to 506.3.22.

(9) The department will limit costs for inspections conducted under 506.3.22 to \$0.05 per pound of material and deduct costs in excess of that amount from payment due the contractor. The department will determine costs for in-house inspections based on hourly rates for department staff plus overhead and use invoiced costs for contracted-out inspections. The department will administer deductions for the contractor's share of the total inspection cost under the Excess Costs For Fabrication Shop Inspection administrative item.

ADDITIONAL SPECIAL PROVISION 7

- A. Reporting 1st Tier and DBE Payments During Construction
 - 1. Comply with reporting requirements specified in the department's Civil Rights Compliance, Contractor's User Manual, Sublets and Payments.
 - 2. Report payments to all DBE firms within 10 calendar days of receipt of a progress payment by the department or a contractor for work performed, materials furnished, or materials stockpiled by a DBE firm. Report the payment as specified in A(1) for all work satisfactorily performed and for all materials furnished or stockpiled.
 - 3. Report payments to all first tier subcontractor relationships within 10 calendar days of receipt of a progress payment by the department for work performed. Report the payment as specified in A(1) for all work satisfactorily performed.
 - 4. All tiers shall report payments as necessary to comply with the DBE payment requirement as specified in A(2).
 - 5. Require all first tier relationships, DBE firms and all other tier relationships necessary to comply with the DBE payment requirement in receipt of a progress payment by contractor to acknowledge receipt of payment as specified in A(1), (2), (3) and (4).
 - 6. All agreements made by a contractor shall include the provisions in A(1), (2), (3), (4) and (5), and shall be binding on all first tier subcontractor relationships and all contractors and subcontractors utilizing DBE firms on the project.
- B. Costs for conforming to this special provision are incidental to the contract.

ADDITIONAL SPECIAL PROVISION 9 Electronic Certified Payroll Submittal

- (1) Use the department's Civil Rights Compliance System (CRCS) to submit certified payrolls electronically. Details are available online through the department's highway construction contractor information (HCCI) site on the Labor, Wages, and EEO Information page at: http://www.dot.wi.gov/business/civilrights/laborwages/index.htm
- (2) Ensure that all tiers of subcontractors, as well as all trucking firms, submit their weekly certified payrolls electronically through CRCS. These payrolls are due within seven calendar days following the close of the payroll period. Every firm providing physical labor towards completing the project is a subcontractor under this special provision.
- (3) Upon receipt of contract execution, promptly make all affected firms aware of the requirements under this special provision and arrange for them to receive CRCS training as they are about to begin payrolls. The department will provide training either in a classroom setting at one of our regional offices or by telephone. Contact Tess Mulrooney at 608-267-4489 to schedule the training.
- (4) The department will reject all paper submittals of forms DT-1816 and DT-1929 for information required under this special provision. All costs for conforming to this special provision are incidental to the contract.
- (5) Firms wishing to export payroll data from their computer system into CRCS should have their payroll coordinator send several sample electronic files to Tess two months before a payroll needs to be submitted. Not every contractor's payroll system is capable of producing export files. For details, see pages 17-22 of the CRCS System Background Information manual available online on the Labor, Wages, and EEO Information page at: http://www.dot.wi.gov/business/civilrights/laborwages/docs/crc-payroll-manual.pdf

Page 1 of 1

DECEMBER 2013

BUY AMERICA PROVISION

All steel and iron materials permanently incorporated in this project shall be domestic products and all manufacturing and coating processes for these materials from smelting forward in the manufacturing process must have occurred within the United States. Coating includes epoxy coating, galvanizing, painting and any other coating that protects or enhances the value of a material subject to the requirements of Buy America. The exemption of this requirement is the minimal use of foreign materials if the total cost of such material permanently incorporated in the product does not exceed one-tenth of one percent (1/10 of 1%) of the total contract cost or \$2,500.00, whichever is greater. For purposes of this paragraph, the cost is that shown to be the value of the subject products as they are delivered to the project. The contractor shall take actions and provide documentation conforming to CMM 2-28.5 to ensure compliance with this "Buy America" provision.

http://roadwaystandards.dot.wi.gov/standards/cmm/cm-02-28.pdf#cm2-28.5

Upon completion of the project certify to the engineer, in writing using department form WS4567, that all steel, iron, and coating processes for steel or iron incorporated into the contract work conform to these "Buy America" provisions. Attach a list of exemptions and their associated costs to the certification form. Department form WS4567 is available at:

http://roadwaystandards.dot.wi.gov/standards/forms/ws4567.doc

1 of 1

WISCONSIN DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS AND TRANSPORTATION FACILITIES

SUPPLEMENTAL REQUIRED CONTRACT PROVISIONS

- I. Wage Rates, Hours of labor and payment of Wages
- II. Payroll Requirements
- III. Postings at the Site of the Work
- IV. Affidavits
- V. Wage Rate Redistribution
- VI. Additional Classifications

I. WAGE RATES, HOURS OF LABOR AND PAYMENT OF WAGES

The schedule of "Minimum Wage Rates" attached hereto and made a part hereof furnishes the prevailing wage rates that have been determined pursuant to Section 103.50 of the Wisconsin Statutes. These wage rates are the minimum required to be paid to the various laborers, workers, mechanics and truck drivers employed by contractors and subcontractors on the construction work embraced by the contract and subject to prevailing hours and wages under Section 103.50, Stats. If necessary to employ laborers, workers, mechanics or truck drivers whose classification is not listed on the schedule, they shall be paid at rates conformable to those listed for similar classifications. Apprentices shall be paid at rates not less than those prescribed in their state indenture contacts.

While the wage rates shown are the minimum rates required by the contract to be paid during its life, this in not a representation that labor can be obtained at these rates. It is the responsibility of bidders to inform themselves as to the local labor conditions and prospective changes or adjustments of wage rates. No increase in the contract price shall be allowed or authorized on account of the payment of wage rates in excess of those listed herein.

Pursuant to Section 103.50 of the Wisconsin Statutes, the prevailing hours of labor have been determined to be up to 10 hours per day and 40 hours per calendar week Monday through Friday. If any laborer, worker, mechanic or truck driver is permitted or required to work more than the prevailing number of hours per day or per calendar week on this contract, they shall be paid for all hours in excess of the prevailing hours at a rate of at least one and one-half (1 1/2) times their hourly rate of pay. All work on Saturday, Sunday and the following holidays is to be paid at time and a half: (1) January 1, (2) the last Monday in May, (3) July 4, (4) the first Monday in September, (5) the fourth Thursday in November, (6) December 25, (7) the day before if January 1, July 4 or December 25 falls on a Saturday and (8) the day following if January 1, July 4 or December 25 falls on a Sunday.

All laborers, workers, mechanics and truck drivers shall be paid unconditionally not less often than once a week. Persons who own and operate their own trucks must receive the prevailing truck driver rate for the applicable type of truck (i.e. 2 axle, 3 or more axle, articulated, eculid or dumptor) he or she operates, plus an agreed upon amount for the use of his or her truck. Every owner-operator MUST be paid separately for their driving and for the use of their truck.

For those projects subject to the requirements of the Davis-Bacon Act, the Secretary of Labor will also have determined "Minimum Wage Rates" for work to be performed under the contract. These rates are, for all or most of the labor, worker, mechanic or truck driver classifications, identical to those established under Section 103.50 of the Wisconsin Statutes. In the event the rates are not identical, the higher of the two rates will govern.

II. PAYROLL REQUIREMENTS

All contractors and subcontractors must submit weekly Certified Payrolls and Compliance Statement verifying that all laborers, workers, mechanics and truck drivers working on the project have been paid the prevailing wage rates for all work performed under the contract required by Section 103.50 of the Wisconsin Statutes.

III. POSTINGS AT THE SITE OF THE WORK

In addition to the required postings furnished by the Department, the contractor shall post the following in at least one conspicuous place at the site of work:

- a. "NOTICE TO EMPLOYEES," which provides information required to be posted by the provisions of Section 103.50 of the Wisconsin Statutes.
- b. A copy of the State of Wisconsin Minimum Wages Rates. (Four pages.)
- c. A copy of the contractor's Equal Employment Opportunity Policy.
- d. On any project involving federal aid, in addition to the furnished postings, the contractor shall post a copy of the "Davis-Bacon Act, Minimum Wage Rates". (Three pages.)

IV. WAGE RATE REDISTRIBUTION

The amount specified as the hourly basic rate of pay and the amount(s) specified as the fringe benefit contribution(s), for all classes of laborers, workers, mechanics or truck drivers may be redistributed, when necessary, to conform to those specified in any applicable collective bargaining agreement, provided that both parties to such agreement

request and receive the approval for any such redistribution from both the Department of Transportation and the Department of Workforce Development prior to the implementation of such redistribution.

V. ADDITIONAL CLASSIFICATIONS

Any unlisted laborer or mechanic classification that is needed to perform work on this project, and is not included within the scope of any of the classifications listed in the application prevailing wage rate determination, may be added after award only if all of the following criteria have been met:

- 1. The affected employer(s) must make a written request to WisDOT Central Office to utilize the unlisted classification on this project.
- 2. The request must indicate the scope of the work to be performed by the unlisted classification and must indicate the proposed wage/fringe benefit package that the unlisted classification is to receive.
- 3. The work to be performed by the unlisted classification must not be performed by a classification that is included in the applicable prevailing wage rate determination.
- 4. The unlisted classification must be commonly employed in the area where the project is located.
- 5. The proposed wage/fringe benefit package must bear a reasonable relationship to those set forth in the applicable prevailing wage rate determination.
- 6. The request should be made prior to the actual performance of the work by the unlisted classification.
- 7. DWD must approve the use of the unlisted classification and the proposed wage/fringe benefit package. USDOL also must approve the use of the unlisted classification and the proposed wage/fringe benefit package on federal aid projects.
- 8. WisDOT and DWD may amend the proposed wage/fringe benefit package, as deemed necessary, and may set forth specific employment ratios and scope of work requirements in the approval document.

The approved wage/fringe benefit package shall be paid to all laborers, workers, mechanics or truck drivers performing work within the scope of that performed by the unlisted classification, from the first day on which such work is performed. In the event that work is performed by the unlisted classification prior to approval, the wage/fringe benefit package to be paid for such work must be in conformance with the wage/fringe

benefit package approved for such work. Under this arrangement a retroactive adjustment in wages and/or fringe benefits may be required to be made to the affected laborers, workers, mechanics or truck drivers by the affected employer(s).

ANNUAL PREVAILING WAGE RATE DETERMINATION FOR ALL STATE HIGHWAY PROJECTS MILWAUKEE COUNTY

Compiled by the State of Wisconsin - Department of Workforce Development for the Department of Transportation
Pursuant to s. 103.50, Stats.
Issued on May 1, 2015

CLASSIFICATION: Contractors are required to call the Department of Workforce Development if there are any questions regarding the proper trade or classification to be used for any worker on a public works project.

OVERTIME: Time and one-half must be paid for all hours worked over 10 hours per day and 40 hours per calendar week and for all hours worked on Saturday, Sunday and the following six (6) holidays: January 1; the last Monday in May; July 4; the 1st Monday in September; the 4th Thursday in November; December 25; the day before if January 1, July 4 or December 25 falls on a Saturday; the day following if January 1, July 4 or December 25 falls on a Sunday.

FUTURE INCREASE: If indicated for a specific trade or occupation, the full amount of such increase MUST be added to the "TOTAL" indicated for such trade or occupation on the date(s) such increase(s) becomes effective.

PREMIUM PAY: If indicated for a specific trade or occupation, the full amount of such pay MUST be added to the "HOURLY BASIC RATE OF PAY" indicated for such trade or occupation, whenever such pay is applicable.

SUBJOURNEY: Wage rates may be available for some of the classifications indicated below. Any employer that desires to use any subjourney classification on a project MUST request the applicable wage rate from the Department of Workforce Development PRIOR to the date such classification is used on such project. Form ERD-10880 is available for this purpose and can be obtained by writing to the Department of Workforce Development, Equal Rights Division, P.O. Box 8928, Madison, WI 53708.

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
	\$	\$	\$
Bricklayer, Blocklayer or Stonemason	35.37	17.99	53.36
Carpenter	33.68	19.99	53.67
Cement Finisher Future Increase(s): Add \$1.87 on 6/1/15; Add \$1.75 on 6/1/16. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic r. Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Department of Transportation or responsible governing agency requiartificial illumination with traffic control and the work is completed after	Day. 2) Add \$1.40/lires that work be pe	nr when the Wisc erformed at night	consin
Electrician	33.93	22.77	56.70
Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate of Independence Day, Labor Day, Thanksgiving Day & Christmas Day.	00.00		
Fence Erector	23.73	19.09	42.82
Ironworker Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate of Independence Day, Labor Day, Thanksgiving Day & Christmas Day.	30.77 on Sunday, New Ye	23.97 ar's Day, Memor	54.74 ial Day,
Line Constructor (Electrical)	37.43	18.19	55.62
Painter	29.22	16.69	45.91
Pavement Marking Operator	30.27	18.79	49.06
Piledriver Future Increase(s): Add \$1.50/hr on 6/1/2015; Add \$1.60/hr on 6/1/20 Premium Pay: Add \$.65/hr for Piledriver Loftsman; Add \$.75/hr for Si two times the hourly basic rate on Sunday, New Year's Day, Memoria Thanksgiving Day & Christmas Day.	heet Piling Loftsma		
Roofer or Waterproofer	29.40	17.05	46.45
Teledata Technician or Installer	24.89	17.15	42.04
Tuckpointer, Caulker or Cleaner	33.76	17.82	51.58

MILWAUKEE COUNTY Page 2

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
	<u> </u>		<u> </u>
Underwater Diver (Except on Great Lakes)	35.40	15.90	51.30
Heavy Equipment Operator - ELECTRICAL LINE CONSTRUCTION ONL	Y 35.55	15.57	51.12
Light Equipment Operator -ELECTRICAL LINE CONSTRUCTION ONLY	31.60	14.64	46.24
Heavy Truck Driver - ELECTRICAL LINE CONSTRUCTION ONLY	27.65	13.44	41.09
Light Truck Driver - ELECTRICAL LINE CONSTRUCTION ONLY	25.68	12.83	38.51
Groundman - ELECTRICAL LINE CONSTRUCTION ONLY	21.75	11.63	33.38
TRUCK DRIVERS			
Single Axle or Two Axle	25.18	18.31	43.49
Future Increase(s): Add \$1.15/hr on 6/1/2015. Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate or Independence Day, Labor Day, Thanksgiving Day & Christmas Day. Three or More Axle	n Sunday, New Ye	ar's Day, Memor 18.31	ial Day, 43.59
Future Increase(s): Add \$1.15/hr on 6/1/2015. Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate or Independence Day, Labor Day, Thanksgiving Day & Christmas Day.	•·	•· 	ial Day,
Articulated, Euclid, Dumptor, Off Road Material Hauler Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/20	30.27	21.15	51.42
Day, Independence Day, Labor Day, Thanksgiving Day & Christmas D See DOT'S website for details about the applicability of this night work business/ civilrights/ laborwages/ pwc. htm. Pavement Marking Vehicle Shadow or Pilot Vehicle Truck Mechanic	23.16 24.37		
LABORERS			
General Laborer	27.06	20.03	47.09
Future Increase(s): Add \$1.05/hr eff. 06/01/2015; Add \$1.00/hr eff. 06/ Premium Pay: Add \$.15/hr for air tool operator, joint sawer and filler (p (mechanical hand operated), chain saw operator and demolition burni bituminous worker (raker and luteman), formsetter (curb, sidewalk and \$.50/hr for line and grade specialist; Add \$.65/hr for blaster and powde \$2.46/hr for bottomman; Add \$3.23/hr for pipelayer. / DOT PREMIUMS on Sunday, New Year's Day, Memorial Day, Independence Day, Labor 2) Add \$1.25/hr for work on projects involving temporary traffic control when work under artificial illumination conditions is necessary as requiprep time prior to and/or cleanup after such time period).	pavement), vibrato ing torch laborer; A d pavement) and s erman; Add \$2.01. S: 1) Pay two time Day, Thanksgivin I setup, for lane ar iired by the projec	or or tamper oper Add \$.35/hr for strike off man; Ad/hr for topman; Ad/hr for topman	ator dd dd c rate as Day. ures, uding
Asbestos Abatement Worker	22.05	18.41	40.46
Landscaper Future Increase(s): Add \$1.05/hr eff. 06/01/2015; Add \$1.00/hr eff. 06/ Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day involving temporary traffic control setup, for lane and shoulder closure conditions is necessary as required by the project provisions (including such time period).	te on Sunday, Nev Pay. 2) Add \$1.25/les, when work und g prep time prior t	w Year's Day, Me hr for work on pro der artificial illumi o and/or cleanup	morial ojects nation o after
Flagperson or Traffic Control Person	22.55	19.37	41.92

MILWAUKEE COUNTY Page 3

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
Fiber Optic Laborer (Outside, Other Than Concrete Encased)	17 71	16.01	33.72
Railroad Track Laborer	17.71 14.50	4.39	18.89
ndiilodu ITack Laborei	14.50	4.55	10.09
HEAVY EQUIPMENT OPERATORS			
Crane, Tower Crane, Pedestal Tower or Derrick, With Boom, Leads &/or Lengths Measuring 176 Ft or Over; Crane, Tower Crane, Pedestal Tower Derrick, With or Without Attachments, With a Lifting Capacity of Over 10 Tons, Self-Erecting Tower Crane With a Lifting Capacity Of Over 4,000 L Crane With Boom Dollies; Traveling Crane (Bridge Type).	er or 00 Lbs.,	21.15	58.87
Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/20 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rad Day, Independence Day, Labor Day, Thanksgiving Day & Christmas See DOT'S website for details about the applicability of this night worbusiness/ civilrights/ laborwages/ pwc. htm.	ate on Sunday, New Day. 2) Add \$1.50/h	Year's Day, Me r night work pre	mium.
Backhoe (Track Type) Having a Mfgr.'s Rated Capacity of 130,000 Lbs. Over; Caisson Rig; Crane, Tower Crane, Portable Tower, Pedestal Tower Derrick, With Boom, Leads &/or Jib Lengths Measuring 175 Ft or Under Crane, Tower Crane, Portable Tower, Pedestal Tower or Derrick, With or Without Attachments, With a Lifting Capacity of 100 Tons or Under, Self-Erecting Tower Crane With A Lifting Capacity Of 4,000 Lbs., & Under Dredge (NOT Performing Work on the Great Lakes); Licensed Boat Pilo (NOT Performing Work on the Great Lakes); Pile Driver. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/20 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic raday, Independence Day, Labor Day, Thanksgiving Day & Christmas See DOT'S website for details about the applicability of this night work.	er or ; er; et 016; Add \$1.25/hr o ate on Sunday, New Day. 2) Add \$1.50/h	Year's Day, Me r night work pre	mium.
business/ civilrights/ laborwages/ pwc. htm. Air Track, Rotary or Percussion Drilling Machine &/or Hammers, Blaster Asphalt Heater, Planer & Scarifier; Asphalt Milling Machine; Asphalt Scre Automatic Subgrader (Concrete); Backhoe (Track Type) Having a Mfgr.' Rated Capacity of Under 130,000 Lbs., Backhoe (Mini, 15,000 Lbs. & Under); Bituminous (Asphalt) Plant & Paver, Screed; Boatmen (NOT Performing Work on the Great Lakes); Boring Machine (Directional, Horizontal or Vertical); Bridge (Bidwell) Paver; Bulldozer or Endloader; Concrete Batch Plant, Batch Hopper; Concrete Breaker (Large, Auto, Vlbratory/Sonic, Manual or Remote); Concrete Bump Cutter, Grinder, Planing or Grooving Machine; Concrete Conveyor System; Concrete Laser/Screed; Concrete Paver (Slipform); Concrete Pump, Concrete Conveyor (Rotec or Bidwell Type); Concrete Slipform Placer Curb & Gut Machine; Concrete Spreader & Distributor; Crane (Carry Deck, Mini) or Truck Mounted Hydraulic Crane (10 Tons or Under); Crane WIth a Lifting Capacity of 25 Tons or Under; Forestry Equipment, Timbco, Tree Shear, Grinder, Processor; Gradall (Cruz-Aire Type); Grader or Motor Patrol; Grump; Hydro-Blaster (10,000 PSI or Over); Loading Machine; Post Hole Digger or Driver; Roller (Over 5 Ton); Scraper (Self Propelled or Tractor	tter g Tub rout r);	21.15	57.87
Drawn) 5 cu yds or More Capacity; Shoulder Widener; Sideboom; Skid l Stabilizing or Concrete Mixer (Self-Propelled or 14S or Over); Straddle Carrier or Travel Lift; Tractor (Scraper, Dozer, Pusher, Loader); Tractor of Truck Mounted Hydraulic Backhoe; Trencher (Wheel Type or Chain Type	or		

MILWAUKEE COUNTY Page 4

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
	\$	\$	\$
Tube Finisher; Tugger (NOT Performing Work on the Great Lakes); Winch & A- Frames. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2019 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day See DOT'S website for details about the applicability of this night work business/ civilrights/ laborwages/ pwc. htm.	6; Add \$1.25/hr e on Sunday, Ne ay. 2) Add \$1.50/	w Year's Day, Me hr night work pre	mium.
Belting, Burlap, Texturing Machine; Broom or Sweeper; Compactor (Self-Propelled or Tractor Mounted, Towed & Light Equipment); Concrete Finishing Machine (Road Type); Environmental Burner; Farm or Industrial Type Tractor; Fireman (Asphalt Plant, Pile Driver & Derrick NOT Performir Work on the Great Lakes); Forklift; Greaser; Hoist (Tugger, Automatic); Je Digger; Joint Sawer (Multiple Blade); Launch (NOT Performing Work on the Great Lakes); Lift Slab Machine; Mechanical Float; Mulcher; Power Subgrader; Robotic Tool Carrier (With or Without Attachments); Roller (Rubber Tire, 5 Ton or Under); Self Propelled Chip Spreader; Shouldering Machine; Skid Steer Loader (With or Without Attachments); Telehandler; Tining or Curing Machine. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016	ng ep ne	21.15 on 6/1/2017.	57.61
Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day See DOT'S website for details about the applicability of this night work business/ civilrights/ laborwages/ pwc. htm.	e on Sunday, Ne ay. 2) Add \$1.50/ premium at: http	w Year's Day, Me /hr night work pre p://www.dot.wi.g	mium. ov/
Air Compressor (&/or 400 CFM or Over); Air, Electric or Hydraulic Jacking System; Augers (Vertical & Horizontal); Automatic Belt Conveyor & Surge Bin; Boiler (Temporary Heat); Concrete Proportioning Plant; Crusher, Screening or Wash Plant; Generator (&/or 150 KW or Over); Heaters (Mechanical); High Pressure Utility Locating Machine (Daylighting Machine Mudjack; Oiler; Prestress Machine; Pug Mill; Pump (3 Inch or Over) or We Points; Rock, Stone Breaker; Screed (Milling Machine); Stump Chipper; Tank Car Heaters; Vibratory Hammer or Extractor, Power Pack. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2019 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate	e); ell 6; Add \$1.25/hr		57.32
Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Da See DOT'S website for details about the applicability of this night work business/ civilrights/ laborwages/ pwc. htm.	ay. 2) Add \$1.50/ premium at: http	hr night work pre	mium.
Fiber Optic Cable Equipment.	28.89	17.95	46.84
Work Performed on the Great Lakes Including Diver; Wet Tender or Hydraulic Dredge Engineer.	41.65	21.71	63.36
Work Performed on the Great Lakes Including 70 Ton & Over Tug Operator Assistant Hydraulic Dredge Engineer; Crane or Backhoe Operator; Hydrau Dredge Leverman or Diver's Tender; Mechanic or Welder.		21.71	63.36
Work Performed on the Great Lakes Including Deck Equipment Operator Machineryman (Maintains Cranes Over 50 Tons or Backhoes 115,000 Lbs or More); Tug, Launch or Loader, Dozer or Like Equipment When Operate on a Barge, Breakwater Wall, Slip, Dock or Scow, Deck Machinery.	S.	17.85	53.57
Work Performed on the Great Lakes Including Deck Equipment Operator, Machineryman or Fireman (Operates 4 Units or More or Maintains Cranes 50 Tons or Under or Backhoes 115,000 Lbs. or Under); Deck Hand, Deck Engineer or Assistant Tug Operator; Off Road Trucks-Great Lakes ONLY.	3	20.40	55.86

Wisconsin Department of Transportation PAGE: 1 DATE: 03/18/15

REVISED: SCHEDULE OF ITEMS

LINE	1	APPROX.	UNIT PRICE	BID AMOUNT
NO	DESCRIPTION	QUANTITY AND UNITS	ļ.	DOLLARS CT
SECTI	ON 0001 Traffic Signal Co	nstruction		
0010	204.0155 Removing Concrete Sidewalk 	 10.000 SY	 	
	209.0100 Backfill Granular 	 17.000 CY	 	 .
0030	213.0100 Finishing Roadway (project) 01. 2984-04-71	 1.000 EACH	 	
	602.0410 Concrete Sidewalk 5-Inch 	 27.000 SF		
0050	619.1000 Mobilization 	 1.000 EACH		
0060	625.0100 Topsoil 	 6.000 SY		
0070	629.0210 Fertilizer Type B 	 0.500 CWT		
0080	631.1000 Sod Lawn 	6.000 SY		
	634.0618 Posts Wood 4x6-Inch X 18-FT	 3.000 EACH	 	
0100	634.0816 Posts Tubular Steel 2x2-Inch X 16-FT 	9.000 EACH	 .	

Wisconsin Department of Transportation PAGE: 2 DATE: 03/18/15

SCHEDULE OF ITEMS

REVISED:

LINE	I	1	PPROX.	UNIT P	RICE	BID AM	OUNT
NO	DESCRIPTION		ANTITY D UNITS	DOLLARS	CTS	DOLLARS	CTS
	637.2210 Signs Type II Reflective H 	 SF	170.063	 		 	
	638.2602 Removing Signs Type II 	 EACH	10.000	 		 	
	638.3000 Removing Small Sign Supports	 EACH	9.000	 		 	
0140	643.0100 Traffic Control (project) 01. 2984-04-71	 EACH	1.000	 		 	
	643.0300 Traffic Control Drums 	 DAY	1,066.000	 		 	
	643.0420 Traffic Control Barricades Type III 	 DAY	338.000	 		 	
	643.0705 Traffic Control Warning Lights Type A 	 DAY	676.000	 		 	
	643.0715 Traffic Control Warning Lights Type C 	 DAY	1,066.000	 		 	
	643.0900 Traffic Control Signs	 DAY	338.000	 		 	
	650.8500 Construction Staking Electrical Installations (project) 01. 2984-04-71	 LUMP 		 LUMP 			

Wisconsin Department of Transportation PAGE: 3 DATE: 03/18/15

SCHEDULE OF ITEMS

REVISED:

LINE	!	APPROX.	UNIT PRICE	BID AMOUNT
NO	DESCRIPTION 	QUANTITY AND UNITS	DOLLARS CTS	DOLLARS CTS
0210	650.9910 Construction Staking Supplemental Control (project) 01. 2984-04-71	 LUMP 	LUMP	
0220	652.0235 Conduit Rigid Nonmetallic Schedule 40 3-Inch	 40.000 LF	 	
0230	654.0110 Concrete Bases Type 10 	 1.000 EACH	 	
0240	690.0250 Sawing Concrete 	 20.000 LF	 	
0250	SPV.0060 Special 01. Concrete Base Type 10 Special	 3.000 EACH	 	 .
	SPV.0060 Special 02. Poles Type 9 	 1.000 EACH	 	 .
	SPV.0060 Special 03. Poles Type 12 Special	 2.000 EACH	 	 .
	SPV.0060 Special 04. Poles Type 13 Special 	 1.000 EACH	 	 .
	SPV.0060 Special 05. Monotube Arms 30-Ft	 1.000 EACH	 	 .
	SPV.0060 Special 06. Monotube Arms 35-Ft	3.000 EACH		

Wisconsin Department of Transportation PAGE: 4 DATE: 03/18/15

SCHEDULE OF ITEMS

REVISED:

LINE NO	TTEM DESCRIPTION	APPROX.	UNIT PRICE	BID AMOUNT	
NO	DESCRIPTION	AND UNITS	DOLLARS CTS	DOLLARS CTS	
0310	SPV.0060 Special 07. Rectangular Polymer Concrete Vault 13-Inch X 24-Inch X 18-Inch	 1.000 EACH			
0320	SPV.0060 Special 08. Inlet Screen Type M	 32.000 EACH	 	 	
	SPV.0060 Special 09. Utility Line Opening (ULO)	 3.000 EACH		 	
0340	SPV.0195 Special 01. Management Of Solid Waste	 30.000 TON		 	
	 SECTION 0001 TOTAL		 	·	
	 TOTAL BID				

PLEASE ATTACH SCHEDULE OF ITEMS HERE