

HIGHWAY WORK PROPOSAL

Wisconsin Department of Transportation
DT1502 10/2010 s.66.29(7) Wis. Stats.

Proposal Number:

Ø 8

<u>COUNTY</u>	<u>STATE PROJECT ID</u>	<u>FEDERAL PROJECT ID</u>	<u>PROJECT DESCRIPTION</u>	<u>HIGHWAY</u>
La Crosse	5121-09-63		La Crosse - Cashton Shady Pines Road to CTH OA)	STH 33
La Crosse	5121-09-73		La Crosse - Cashton Kirschner Rd to Monroe Co Line	STH 33
La Crosse	5820-01-73		La Crosse - Cashton STH 33 - Dutch Creek Bridge STH 33 NLY .57 MI to Dutch Creek Bridge	STH 162

This proposal, submitted by the undersigned bidder to the Wisconsin Department of Transportation, is in accordance with the advertised request for proposals. The bidder is to furnish and deliver all materials, and to perform all work for the improvement of the designated project in the time specified, in accordance with the appended Proposal Requirements and Conditions.

Proposal Guaranty Required, \$ 100,000.00 Payable to: Wisconsin Department of Transportation	Attach Proposal Guaranty on back of this PAGE.
Bid Submittal Due Date: February 9, 2016 Time (Local Time): 9:00 AM	Firm Name, Address, City, State, Zip Code
Contract Completion Time November 15, 2016	SAMPLE NOT FOR BIDDING PURPOSES
Assigned Disadvantaged Business Enterprise Goal 0%	This contract is exempt from federal oversight.

This certifies that the undersigned bidder, duly sworn, is an authorized representative of the firm named above; that the bidder has examined and carefully prepared the bid from the plans, Highway Work Proposal, and all addenda, and has checked the same in detail before submitting this proposal or bid; and that the bidder or agents, officer, or employees have not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with this proposal bid.

Do not sign, notarize, or submit this Highway Work Proposal when submitting an electronic bid on the Internet.

Subscribed and sworn to before me this date _____

(Signature, Notary Public, State of Wisconsin)

(Print or Type Name, Notary Public, State Wisconsin)

(Date Commission Expires)

Notary Seal

(Bidder Signature)

(Print or Type Bidder Name)

(Bidder Title)

For Department Use Only

Type of Work Milling, grading, aggregate base dense, HMA pavement, culverts, storm sewer, concrete curb and gutter, erosion control, signing, pavement marking, and Structure B-32-0215.	Date Guaranty Returned
Notice of Award Dated	

**PLEASE ATTACH
PROPOSAL GUARANTY HERE**

Effective with November 2007 Letting

PROPOSAL REQUIREMENTS AND CONDITIONS

The bidder, signing and submitting this proposal, agrees and declares as a condition thereof, to be bound by the following conditions and requirements.

If the bidder has a corporate relationship with the proposal design engineering company, the bidder declares that it did not obtain any facts, data, or other information related to this proposal from the design engineering company that was not available to all bidders.

The bidder declares that they have carefully examined the site of, and the proposal, plans, specifications and contract forms for the work contemplated, and it is assumed that the bidder has investigated and is satisfied as to the conditions to be encountered, as to the character, quality, and quantities of work to be performed and materials to be furnished, and as to the requirements of the specifications, special provisions and contract. It is mutually agreed that submission of a proposal shall be considered conclusive evidence that the bidder has made such examination.

The bidder submits herewith a proposal guaranty in proper form and amount payable to the party as designated in the advertisement inviting proposals, to be retained by and become the property of the owner of the work in the event the undersigned shall fail to execute the contract and contract bond and return the same to the office of the engineer within fourteen (14) days after having been notified in writing to do so; otherwise to be returned.

The bidder declares that they understand that the estimate of quantities in the attached schedule is approximate only and that the attached quantities may be greater or less in accordance with the specifications.

The bidder agrees to perform the said work, for and in consideration of the payment of the amount becoming due on account of work performed, according to the unit prices bid in the following schedule, and to accept such amounts in full payment of said work.

The bidder declares that all of the said work will be performed at their own proper cost and expense, that they will furnish all necessary materials, labor, tools, machinery, apparatus, and other means of construction in the manner provided in the applicable specifications and the approved plans for the work together with all standard and special designs that may be designed on such plans, and the special provisions in the contract of which this proposal will become a part, if and when accepted. The bidder further agrees that the applicable specifications and all plans and working drawings are made a part hereof, as fully and completely as if attached hereto.

The bidder, if awarded the contract, agrees to begin the work not later than ten (10) days after the date of written notification from the engineer to do so, unless otherwise stipulated in the special provisions.

The bidder declares that if they are awarded the contract, they will execute the contract agreement and begin and complete the work within the time named herein, and they will file a good and sufficient surety bond for the amount of the contract for performance and also for the full amount of the contract for payment.

The bidder, if awarded the contract, shall pay all claims as required by Section 779.14, Statutes of Wisconsin, and shall be subject to and discharge all liabilities for injuries pursuant to Chapter 102 of the Statutes of Wisconsin, and all acts amendatory thereto. They shall further be responsible for any damages to property or injury to persons occurring through their own negligence or that of their employees or agents, incident to the performance of work under this contract, pursuant to the Standard Specifications for Road and Bridge Construction applicable to this contract.

In connection with the performance of work under this contract, the contractor agrees to comply with all applicable state and federal statutes relating to non-discrimination in employment. No otherwise qualified person shall be excluded from employment or otherwise be subject to discrimination in employment in any manner on the basis of age, race, religion, color, gender, national origin or ancestry, disability, arrest or conviction record (in keeping with s.111.32), sexual orientation, marital status, membership in the military reserve, honesty testing, genetic testing, and outside use of lawful products. This provision shall include, but not be limited to the following: employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation, and selection for training, including apprenticeship. The contractor further agrees to ensure equal opportunity in employment to all applicants and employees and to take affirmative action to attain a representative workforce.

The contractor agrees to post notices and posters setting forth the provisions of the nondiscrimination clause, in a conspicuous and easily accessible place, available for employees and applicants for employment.

If a state public official (section 19.42, Stats.) or an organization in which a state public official holds at least a 10% interest is a party to this agreement, this contract is voidable by the state unless appropriate disclosure is made to the State of Wisconsin Ethics Board.

Effective with August 2015 Letting

BID PREPARATION

Preparing the Proposal Schedule of Items

A General

- (1) Obtain bidding proposals as specified in **section 102** of the standard specifications prior to 11:45 AM of the last business day preceding the letting. Submit bidding proposals using one of the following methods:
 1. Electronic bid on the internet.
 2. Electronic bid on a printout with accompanying diskette or CD ROM.
 3. Paper bid under a waiver of the electronic submittal requirements.
- (2) Bids submitted on a printout with accompanying diskette or CD ROM or paper bids submitted under a waiver of the electronic submittal requirements govern over bids submitted on the internet.

- (3) The department will provide bidding information through the department's web site at:
<http://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx>

The contractor is responsible for reviewing this web site for general notices as well as information regarding proposals in each letting. The department will also post special notices of all addenda to each proposal through this web site no later than 4:00 P.M. local time on the Thursday before the letting. Check the department's web site after 5:00 P.M. local time on the Thursday before the letting to ensure all addenda have been accounted for before preparing the bid. When bidding using methods 1 and 2 above, check the Bid Express™ on-line bidding exchange at <http://www.bidx.com/> after 5:00 P.M. local time on the Thursday before the letting to ensure that the latest schedule of items Expedite file (*.ebs or *.00x) is used to submit the final bid.

- (4) Interested parties can subscribe to the Bid Express™ on-line bidding exchange by following the instructions provided at the www.bidx.com web site or by contacting:

Info Tech Inc.
5700 SW 34th Street, Suite 1235
Gainesville, FL 32608-5371
email: <mailto:customer.support@bidx.com>

- (5) The department will address equipment and process failures, if the bidder can demonstrate that those failures were beyond their control.
- (6) Contractors are responsible for checking on the issuance of addenda and for obtaining the addenda. Notice of issuance of addenda is posted on the department's web site at:
<http://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx>

or by calling the department at (608) 266-1631. Addenda can ONLY be obtained from the departments web site listed above or by picking up the addenda at the Bureau of Highway Construction, Room 601, 4802 Sheboygan Avenue, Madison, WI, during regular business hours.

- (7) Addenda posted after 5:00 PM on the Thursday before the letting will be emailed to the eligible bidders for that proposal. All eligible bidders shall acknowledge receipt of the addenda whether they are bidding on the proposal or not. Not acknowledging receipt may jeopardize the awarding of the project.

B Submitting Electronic Bids

B.1 On the Internet

- (1) Do the following before submitting the bid:
 1. Have a properly executed annual bid bond on file with the department.
 2. Have a digital ID on file with and enabled by Info Tech Inc. Using this digital ID will constitute the bidder's signature for proper execution of the bidding proposal.
- (2) In lieu of preparing, delivering, and submitting the proposal as specified in 102.6 and 102.9 of the standard specifications, submit the proposal on the internet as follows:
 1. Download the latest schedule of items reflecting all addenda from the Bid ExpressTM web site.
 2. Use ExpediteTM software to enter a unit price for every item in the schedule of items.
 3. Submit the bid according to the requirements of ExpediteTM software and the Bid ExpressTM web site. Do not submit a bid on a printout with accompanying diskette or CD ROM or a paper bid. If the bidder does submit a bid on a printout with accompanying diskette or a paper bid in addition to the internet submittal, the department will disregard the internet bid.
 4. Submit the bid before the hour and date the Notice to Contractors designates.
 5. Do not sign, notarize, and return the bidding proposal described in 102.2 of the standard specifications.
- (3) The department will not consider the bid accepted until the hour and date the Notice to Contractors designates.

B.2 On a Printout with Accompanying Diskette or CD ROM

- (1) Download the latest schedule of items from the Wisconsin pages of the Bid ExpressTM web site reflecting the latest addenda posted on the department's web site at:
<http://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx>

Use ExpediteTM software to prepare and print the schedule of items. Provide a valid amount for all price fields. Follow instructions and review the help screens provided on the Bid ExpressTM web site to assure that the schedule of items is prepared properly.

- (2) Staple an 8 1/2 by 11 inch printout of the ExpediteTM generated schedule of items to the other proposal documents submitted to the department as a part of the bidder's sealed bid. As a separate submittal not in the sealed bid envelop but due at the same time and place as the sealed bid, also provide the ExpediteTM generated schedule of items on a 3 1/2 inch computer diskette or CD ROM. Label each diskette or CD ROM with the bidder's name, the 4 character department-assigned bidder identification code from the top of the bidding proposal, and a list of the proposal numbers included on that diskette or CD ROM as indicated in the following example:

Bidder

Name

BN00

Proposals: 1, 12, 14, & 22

- (3) If bidding on more than one proposal in the letting, the bidder may include all proposals for that letting on one diskette or CD ROM. Include only submitted proposals with no incomplete or other files on the diskette or CD ROM.
- (4) The bidder-submitted printout of the ExpediteTM generated schedule of items is the governing contract document and must conform to the requirements of section 102 of the standard specifications. If a printout needs to be altered, cross out the printed information with ink or typewriter and enter the new information and initial it in ink. If there is a discrepancy between the printout and the diskette or CD ROM, the department will analyze the bid using the printout information.

- (5) In addition to the reasons specified in [section 102](#) of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
1. The check code printed on the bottom of the printout of the ExpediteTM generated schedule of items is not the same on each page.
 2. The check code printed on the printout of the ExpediteTM generated schedule of items is not the same as the check code for that proposal provided on the diskette or CD ROM.
 3. The diskette or CD ROM is not submitted at the time and place the department designates.

C Waiver of Electronic Submittal

- (1) The bidder may request a waiver of the electronic submittal requirements. Submit a written request for a waiver in lieu of bids submitted on the internet or on a printout with accompanying diskette or CD ROM. Use the waiver that was included with the paper bid document sent to the bidder or type up a waiver on the bidder's letterhead. The department will waive the electronic submittal requirements for a bidding entity (individual, partnership, joint venture, corporation, or limited liability company) for up to 4 individual proposals in a calendar year. The department may allow additional waivers for equipment malfunctions.
- (2) Submit a schedule of items on paper conforming to [section 102](#) of the standard specifications. The department charges the bidder a \$75 administrative fee per proposal, payable at the time and place the department designates for receiving bids, to cover the costs of data entry. The department will accept a check or money order payable to: "Wisconsin, Dept. of Transportation."
- (3) In addition to the reasons specified in [section 102](#) of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
 1. The bidder fails to provide the written request for waiver of the electronic submittal requirements.
 2. The bidder fails to pay the \$75 administrative fee before the time the department designates for the opening of bids unless the bidder requests on the waiver that they be billed for the \$75.
 3. The bidder exceeds 4 waivers of electronic submittal requirements within a calendar year.
- (4) In addition to the reasons specified in [section 102](#) of the standard specifications, the department may refuse to issue bidding proposals for future contracts to a bidding entity that owes the department administrative fees for a waiver of electronic submittal requirements.

PROPOSAL BID BOND

DT1303 1/2006

Wisconsin Department of Transportation

Proposal Number	Project Number	Letting Date
Name of Principal		
Name of Surety	State in Which Surety is Organized	

We, the above-named Principal and the above-named Surety, are held and firmly bound unto the State of Wisconsin in the sum equal to the Proposal Guaranty for the total bid submitted for the payment to be made; we jointly and severally bind ourselves, our heirs, executors, administrators, successors and assigns. The condition of this obligation is that the Principal has submitted a bid proposal to the State of Wisconsin acting through the Department of Transportation for the improvement designated by the Proposal Number and Letting Date indicated above.

If the Principal is awarded the contract and, within the time and manner required by law after the prescribed forms are presented for signature, enters into a written contract in accordance with the bid, and files the bond with the Department of Transportation to guarantee faithful performance and payment for labor and materials, as required by law, or if the Department of Transportation shall reject all bids for the work described, then this obligation shall be null and void; otherwise, it shall be and remain in full force and effect. In the event of failure of the Principal to enter into the contract or give the specified bond, the Principal shall pay to the Department of Transportation **within 10 business days of demand** a total equal to the Proposal Guaranty as liquidated damages; the liability of the Surety continues for the full amount of the obligation as stated until the obligation is paid in full.

The Surety, for value received, agrees that the obligations of it and its bond shall not be impaired or affected by any extension of time within which the Department of Transportation may accept the bid; and the Surety does waive notice of any such extension.

IN WITNESS, the Principal and Surety have agreed and have signed by their proper officers and have caused their corporate seals to be affixed this date: **(DATE MUST BE ENTERED)**

PRINCIPAL

(Company Name) **(Affix Corporate Seal)**

(Signature and Title)

(Company Name)

(Signature and Title)

(Company Name)

(Signature and Title)

(Company Name)

(Signature and Title)

NOTARY FOR PRINCIPAL

(Date)

State of Wisconsin)
) ss.
_____ County)

On the above date, this instrument was acknowledged before me by the named person(s).

(Signature, Notary Public, State of Wisconsin)

(Print or Type Name, Notary Public, State of Wisconsin)

(Date Commission Expires)

Notary Seal

(Name of Surety) **(Affix Seal)**

(Signature of Attorney-in-Fact)

NOTARY FOR SURETY

(Date)

State of Wisconsin)
) ss.
_____ County)

On the above date, this instrument was acknowledged before me by the named person(s).

(Signature, Notary Public, State of Wisconsin)

(Print or Type Name, Notary Public, State of Wisconsin)

(Date Commission Expires)

Notary Seal

IMPORTANT: A certified copy of Power of Attorney of the signatory agent must be attached to the bid bond.

CERTIFICATE OF ANNUAL BID BOND

DT1305 8/2003

Wisconsin Department of Transportation

Time Period Valid (From/To)	
Name of Surety	
Name of Contractor	
Certificate Holder	Wisconsin Department of Transportation

This is to certify that an annual bid bond issued by the above-named Surety is currently on file with the Wisconsin Department of Transportation.

This certificate is issued as a matter of information and conveys no rights upon the certificate holder and does not amend, extend or alter the coverage of the annual bid bond.

Cancellation: Should the above policy be cancelled before the expiration date, the issuing surety will give thirty (30) days written notice to the certificate holder indicated above.

(Signature of Authorized Contractor Representative)

(Date)

March 2010

LIST OF SUBCONTRACTORS

Section 66.0901(7), Wisconsin Statutes, provides that as a part of the proposal, the bidder also shall submit a list of the subcontractors the bidder proposes to contract with and the class of work to be performed by each. In order to qualify for inclusion in the bidder's list a subcontractor shall first submit a bid in writing, to the general contractor at least 48 hours prior to the time of the bid closing. The list may not be added to or altered without the written consent of the municipality. A proposal of a bidder is not invalid if any subcontractor and the class of work to be performed by the subcontractor has been omitted from a proposal; the omission shall be considered inadvertent or the bidder will perform the work personally.

No subcontract, whether listed herein or later proposed, may be entered into without the written consent of the Engineer as provided in Subsection 108.1 of the Standard Specifications.

[illegible]

DECEMBER 2000

**CERTIFICATION REGARDING DEBARMENT, SUSPENSION, AND OTHER
RESPONSIBILITY MATTERS - PRIMARY COVERED TRANSACTIONS**

Instructions for Certification

1. By signing and submitting this proposal, the prospective contractor is providing the certification set out below.
2. The inability of a person to provide the certification required below will not necessarily result in denial of participation in this covered transaction. The prospective contractor shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective contractor to furnish a certification or an explanation shall disqualify such person from participation in this transaction.
3. The certification in this clause is a material representation of fact upon which reliance was placed when the department determined to enter into this transaction. If it is later determined that the contractor knowingly rendered an erroneous certification in addition to other remedies available to the Federal Government the department may terminate this transaction for cause or default.
4. The prospective contractor shall provide immediate written notice to the department to whom this proposal is submitted if at any time the prospective contractor learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
5. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction," "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of the rules implementing Executive Order 12549. You may contact the department to which this proposal is being submitted for assistance in obtaining a copy of those regulations.
6. The prospective contractor agrees by submitting this proposal that, should this contract be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department entering into this transaction.
7. The prospective contractor further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," which is included as an addendum to PR-1273 - "Required Contract Provisions Federal Aid Construction Contracts," without

modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.

8. The contractor may rely upon a certification of a prospective subcontractor/materials supplier that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A contractor may decide the method and frequency by which it determines the eligibility of its principals. Each contractor may, but is not required to, check the Disapproval List (telephone # 608/266/1631).
9. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of a contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
10. Except for transactions authorized under paragraph 6 of these instructions, if a contractor in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department may terminate this transaction for cause or default.

Certification Regarding Debarment, Suspension, and Other Responsibility Matters - Primary Covered Transactions

- (1) The prospective contractor certifies to the best of its knowledge and belief, that it and its principals:
 - (a) Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
 - (b) Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements or receiving stolen property;
 - (c) Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offense enumerated in paragraph (1)(b) of this certification; and
 - (d) Have not within a three-year period preceding this proposal had one or more public transactions (Federal, State or local) terminated for cause or default.
- (2) Where the prospective contractor is unable to certify to any of the statements in this certification, such prospective contractor shall attach an explanation to this proposal.

Special Provisions

Table of Contents

Article	Description	Page #
1.	General.....	2
2.	Scope of Work.	2
3.	Prosecution and Progress.	2
4.	Traffic.	5
5.	Holiday Work Restrictions.	7
6.	Utilities.....	7
7.	Coordination with Other Projects.	9
8.	Environmental Protection, Aquatic Exotic Species Control.....	9
9.	Erosion Control Structures.....	10
10.	Health and Safety Requirements for Workers Remediating Petroleum Contamination.....	11
11.	Notice to Contractor, Notification of Demolition and/or Renovation No Asbestos Found.	13
12.	Public Convenience and Safety.	13
13.	Coordination with Businesses and Residents.	14
14.	Removing Old Structure Over Waterway With Minimal Debris Station 966+44.23, Item 203.0600.S.01.....	14
15.	Select Borrow.....	15
16.	QMP Base Aggregate.	15
17.	QMP Base Aggregate Dense 1 1/4-Inch Compaction, Item 371.1000.S.....	23
18.	Reheating HMA Pavement Longitudinal Joints, Item 460.4110.S.....	34
19.	QMP HMA Pavement Nuclear Density.....	35
20.	Pipe Cattle Pass.....	42
21.	Pipe Cattle Pass Corrugated Steel.....	42
22.	Storm Sewer Pipe Reinforced Concrete.	42
23.	Fence Temporary, Item 616.0600.S.....	42
24.	Locating No-Passing Zones, Item 648.0100.....	43
25.	Removing HMA Pavement Notched Wedge Longitudinal Joint Milling, Item SPV.0090.01.	43
26.	Concrete Curb and Gutter 32-Inch Special, Item SPV.0090.02.	44
27.	Modify Drain Pipe, Item SPV.0105.01.....	44
28.	Rectangular Rapid Flashing Beacon System, Item SPV.0105.02.	45
29.	Wall Modular Block Gravity LRFD Special, Item SPV.0165.01.....	48
30.	Geogrid Reinforcement, Item SPV.0180.01.....	54
31.	Management of Contaminated Soil, Item SPV.0195.01.....	56

SPECIAL PROVISIONS

1. General.

Perform the work under this construction contract for Project 5121-09-63, La Crosse - Cashton, Shady Pines Road to CTH OA, STH 33, Project 5121-09-73, La Crosse – Cashton, Kirschner Rd to Monroe Co Line, STH 33, and Project 5820-01-73, La Crosse – Cashton, STH 33 to Dutch Creek Bridge, STH 33 NLY .57 MI to Dutch Creek Bridge, STH 162, La Crosse County, Wisconsin as the plans show and execute the work as specified in the State of Wisconsin, Department of Transportation, Standard Specifications for Highway and Structure Construction, 2016 Edition, as published by the department, and these special provisions.

If all or a portion of the plans and special provisions are developed in the SI metric system and the schedule of prices is developed in the US standard measure system, the department will pay for the work as bid in the US standard system.
100-005 (20150630)

2. Scope of Work.

The work under this contract shall consist of milling, grading, base aggregate dense, HMA pavement, culverts, storm sewer, concrete curb and gutter, erosion control, signing and pavement marking, and all incidental items necessary to complete the work as shown on the plans and included in the proposal and contract.
104-005 (20090901)

3. Prosecution and Progress.

Begin work within ten calendar days after the engineer issues a written notice to do so.

Provide the start date to the engineer in writing within a month after executing the contract but at least 14 calendar days before the preconstruction conference. Upon approval, the engineer will issue the notice to proceed within ten calendar days before the approved start date.

To revise the start date, submit a written request to the engineer at least two weeks before the intended start date. The engineer will approve or deny that request based on the conditions cited in the request and its effect on the department's scheduled resources.

Construction Staging

The contractor shall stage traffic to minimize the overall inconvenience to traffic and reduce environmental concerns due to dust and erosion. The contractor shall complete one stage of construction, as described below, before beginning operations on the next stage. The contractor shall remove no pavement until the previous stage is completed as described below for each stage. The contractor shall provide access to all properties along the project and to all side roads, unless otherwise noted in the Traffic article of the special provisions.

Stage 1

This stage of construction consists of the portion of the project from the west end of the project (Station 676+75) to STH 162 (South) (Station 785+00). The road shall remain open to local traffic at all times. STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. Existing STH 162 (South) shall remain open to traffic.

Complete all grading, pipes, curb and gutter, base aggregate, and erosion control on Stage 1 before starting work on future stages, except for Stage 2 material/fill operations. The contractor may place borrow/fill material in Stage 2 only in areas completely off existing alignment and that do not interfere with traffic. The contractor shall utilize temporary traffic control devices and flagging operations to control the work area as needed.

Stage 2

This stage of construction consists of the portion of the project from STH 162 (South) (Station 785+00) to CTH G/STH 162 (North) (Station 930+00). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. STH 162 (South) and CTH G/STH 162 (North) shall remain open to traffic.

Complete all grading, pipes, curb and gutter, base aggregate, and erosion control on Stage 2 before starting work on future stages.

Stage 3

This stage of construction consists of the portion of the project from CTH G/STH 162 (North) (Station 930+00) to Korn Coulee Road (Station 1001+00). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. CTH G/STH 162 (North) and Korn Coulee Road shall remain open to traffic.

Complete all grading, pipes, curb and gutter, base aggregate, and erosion control on Stage 3 before starting work on future stages, except for Stage 2 material/fill operations.

Stage 4

This stage of construction consists of the portion of the project from Korn Coulee Road (Station 1001+00) to the east end of the project (Station 1037+55). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. Korn Coulee Road shall remain open to traffic.

Complete all grading, pipes, curb and gutter, base aggregate, and erosion control on Stage 4 before starting work on future stages, except for Stage 2 material/fill operations.

Stage 5

This stage of construction consists of the STH 162 (North) portion of the project from Station 935+45 to the north end of the project (Station 978+71). STH 162 (North) will be closed to through traffic during this construction stage with a detour route as laid out in the plans. STH 162 (North) can only be closed from June 6, 2016 to September 2, 2016. The intersection of CTH JB/STH 33 shall remain open at all times when STH 162 (North) is closed.

Paving operations may begin along the entire project once all stages are complete. STH 33 and STH 162 will be closed to through traffic during this phase of construction with a detour route as laid out in the plans. The contractor shall utilize temporary traffic control devices and flagging operations to control the work area as needed. Shoulder aggregate, beamguard, and permanent signing shall also be completed during this phase of the project.

The contractor may begin the milling and paving project (ID 5121-09-63) at any time during the previously described Stages 1-5. The contractor shall complete all paving and pavement markings for project 5121-09-63 within one week of the completion of the milling.

Northern Long-eared Bat (*Myotis septentrionalis*)

Northern Long-eared Bats (NLEB) have the potential to inhabit the project limits because they roost in trees and structures (bridges, culverts, buildings). Roosts may not have been observed on this project, but conditions to support the species exist. The species and all active roosts are protected by the Federal Endangered Species Act.

In order to avoid adverse impacts upon the NLEBs, no vegetation clearing and grubbing within the identified clearing and grubbing limits will be allowed from April 1 to September 30, both dates inclusive.

If the required clearing and removal is not completed by March 31, the department will suspend all clearing and associated work directly impacted by clearing. The department will issue a notice to proceed with clearing and associated work directly impacted by clearing after consulting with the United States Fish and Wildlife Service (USFWS).

Submit a schedule and description of Clearing and/or Grubbing operations with the ECIP 14 days prior to any Clearing operations. The department will determine, based on schedule and scope of work, what additional erosion control measures shall be implemented prior to the start of Clearing operations, and list those additional measures in the ECIP.

Notify the Project Leader 14 days in advance of any work on box culverts or bridges between April 1 and September 30 to allow time for department to complete the Bat Presence Structure Inspection Form.

If bats or evidence of bats are not found during the inspection, construction may proceed.

If bats or evidence of bats are found during the inspection, construction activities affecting the structure's roosting potential must stop until the WisDOT Regional Environmental Coordinator completes consultation with the Wisconsin Department of Natural Resources (WDNR) and/or United States Fish and Wildlife Service (USFWS).

4. Traffic.

Wisconsin Lane Closure System Advance Notification

Provide the following advance notification to the engineer for incorporation into the Wisconsin Lane Closure System (LCS).

TABLE 108-1 CLOSURE TYPE AND REQUIRED MINIMUM ADVANCE NOTIFICATION

Closure type with height, weight, or width restrictions (available width, all lanes in one direction $\leq 16'$)	MINIMUM NOTIFICATION
Lane and shoulder closures	14 calendar days
Full roadway closures	14 calendar days
System and service ramp closures	14 calendar days
Full system and service ramp closures	14 calendar days
Detours	14 calendar days
Closure type without height, weight, or width restrictions (available width, all lanes in one direction $> 16'$)	MINIMUM NOTIFICATION
Lane and shoulder closures	3 business days
System and service ramp closures	3 business days
Modifying all closure types	3 business days

Discuss LCS completion dates and provide changes in the schedule to the engineer at weekly project meetings in order to manage closures nearing their completion date.

108-057 (20150630)

Close STH 33 and STH 162, on which the project is located, to through traffic during construction operations under this contract.

Coordinate schedules, including flagging operations, with local emergency vehicles to ensure that emergency personnel are aware of local roadways affected by the construction work.

Maintain access to adjacent properties at all times, as well as roadways that only have access to STH 33 or STH 162. This includes, but is not limited to, Kirschner Road, Bina Road, Hass Road, Kneifl Road, Ritter Road, Erickson Road, Korn Clements Road, and AJ Hundt

Road. If construction operations require the temporary closure of entrances, notify property owners of closures. Property owners shall receive a minimum of 48 hours advance notice. The maximum length of closure for private entrances shall be eight hours and 24 hours for field entrances. Entrances with Concrete Sidewalk 4-Inch and/or Concrete Driveway 6-Inch are exempt from this provision.

At the end of operations each day, the closed portion of the roadway shall be made suitable for local traffic to access their property as well as to sideroads with no other access. No equipment shall be parked within the construction area overnight.

For a field entrance that requires closure longer than 24 hours, get written approval from the property owner prior to closure of the entrance. Provide a copy of the written approval to the engineer prior to entrance closure.

The contractor is required to give a minimum of five day notice to all emergency agencies prior to changing any traffic movements.

Stage 1

This stage of construction consists of the portion of the project from the west end of the project (Station 676+75) to STH 162 (South) (Station 785+00). The road shall remain open to traffic at all times. STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. STH 162 (South) shall remain open to traffic.

Stage 2

This stage of construction consists of the portion of the project from STH 162 (South) (Station 785+00) to CTH G/STH 162 (North) (Station 930+00). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. STH 162 (South) and CTH G/STH 162 (North) shall remain open to traffic.

Stage 3

This stage of construction consists of the portion of the project from CTH G/STH 162 (North) (Station 930+00) to Korn Coulee Road (Station 1001+00). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. CTH G/STH 162 (North) and Korn Coulee Road shall remain open to traffic.

Stage 4

This stage of construction consists of the portion of the project from Korn Coulee Road (Station 1001+00) to the east end of the project (Station 1037+55). STH 33 will be closed to through traffic during this construction stage with a detour route as laid out in the plans. Korn Coulee Road shall remain open to traffic.

Stage 5

This stage of construction consists of the STH 162 (North) portion of the project from Station 935+45 to the north end of the project (Station 978+71). STH 162 (North) will be closed to through traffic during this construction stage with a detour route as laid out in the plans. Closure of STH 162 (North) can only occur between June 6, 2016 and September 2,

2016. The intersection of CTH JB/STH 33 shall remain open at all times when STH 162 (North) is closed.

After all grading, pipes, curb and gutter, base aggregate, and erosion control work is complete, paving operations may occur along the entire project. STH 33 and STH 162 will be closed to through traffic during this phase of construction with a detour route as laid out in the plans. The contractor shall utilize temporary traffic control devices and flagging operations to control the work area as needed. Shoulder aggregate, beamguard, and permanent signing shall also be completed during this phase of the project.

At least one lane of traffic shall remain open at all times during the milling and paving project (ID 5121-09-63) with both lanes being open outside of work hours. The contractor shall use flagging operations for traffic control as necessary.

5. Holiday Work Restrictions.

Do not perform work on, nor haul materials of any kind along or across any portion of the highway carrying STH 33 and STH 162 traffic, and entirely clear the traveled way and shoulders of such portions of the highway of equipment, barricades, signs, lights, and any other material that might impede the free flow of traffic during the following holiday periods:

- From noon Friday, May 27, 2016 to 6:00 AM Tuesday, May 31, 2016 for Memorial Day;
- From noon Friday, July 1, 2016 to 6:00 AM Tuesday, July 5, 2016 for Independence Day;
- From noon Friday, September 2, 2016 to 6:00 AM Tuesday, September 6, 2016 for Labor Day.

Work operations will be allowed on any closed portion of the project as long as it does not impede or interrupt the free flow of traffic on STH 33 and STH 162.
107-005 (20050502)

6. Utilities.

Project 5121-09-63

This contract comes under the provisions of Wisconsin Administrative Code Chapter Trans 220.

All utilities within the construction limits of Project 5121-09-63 were coordinated under Project 5121-09-73. There are no other known utility conflicts within the construction limits.

Project 5121-09-73

This contract comes under the provisions of Wisconsin Administrative Code Chapter Trans 220.

Some of the utility work described below is dependent on prior work performed by the contractor at a specific site. In such situations, provide the engineer and the affected utility a good faith notice of when the utility is to start work at the site. Provide this notice 14 to 16 calendar days in advance of when the prior work will be completed and the site will be available to the utility. Follow-up with a confirmation notice to the engineer and the utility not less than 3 working days before the site will be ready for the utility to begin its work.

Underground and overhead utility facilities are located within the project limits. Coordinate construction activities with a call to Diggers Hotline or a direct call to the utilities that have facilities in the area. Use caution to insure the integrity of underground facilities and maintain code clearance from overhead facilities at all times.

When interpreting the term “working days” within the “Utilities” article of these special provisions (and only within this article), use the definition provided in Trans 220.03(20) of the Wisconsin Administrative Code rather than the definition provided in standard spec 101.3.

The following utilities have facilities within the project limits:

CenturyLink (Communication Line) has underground telephone facilities throughout the project from Station 686+25 to 1035+98. Cable and pedestals from 686+25 to 874+00; 880+00 to 922+00; and 941+00 to 1035+98 will be relocated to the edge of the right-of-way. The cable and pedestals from 874+00 to 880+00 and 930+00 to 941+00 will be retained in place. CenturyLink has one pole on STH 162 at Station 967+18 that will be relocated to the edge of the right of way and a new cable will be buried across STH 162. CenturyLink plans to adjust the telephone facilities within the construction limits prior to May 31, 2016.

Coon Valley Telecommunications (Communication Line) has relocated their facilities outside of the right-of-way in 2015 to avoid conflicts with this contract; no further conflicts are anticipated.

Xcel Energy (Electricity) has overhead electric facilities on the north side of STH 33 from Station 688+00 to 744+00. Excel Energy plans to relocate the poles to the edge of the right of way prior to April 1, 2016.

Bangor Municipal Utility (Electricity) has overhead electric facilities from Station 744+00 to 1036+00. Bangor plans to replace the overhead facilities within the project limits with a combination of new overhead and underground facilities.

The overhead facilities on STH 33 from Station 781+00 to 805+00 and from 956+00 to 1036+00 will be replaced with underground facilities at the edge of the right-of-way. This work is anticipated to be completed by January 31, 2016.

The poles along STH 162 from Station 758+00 to 765+00 will be relocated out of conflict near the edge of the right-of-way. The poles along STH 33 from Station 805+00 to 920+00 will be relocated to the edge of the right-of-way. The pole at the southwest corner of CTH G

and STH 33, the pole at Station 935+71 RT, and the pole 943+00 RT will all be relocated to the edge of the right-of-way. The other poles are remaining in place. Bangor anticipates completing the pole moves prior to May 1, 2016.

The utility pole at Station 868+95, 57' LT will be adjusted during construction after final grade has been achieved. Provide Bangor 3 working days' notice when the grade is finalized. Bangor's relocation work will take 5 working days to complete.

Project ID 5820-01-73

This contract comes under the provisions of Wisconsin Administrative Code Chapter Trans 220.

All utilities within the construction limits of Project 5820-01-73 were coordinated under Project 5121-09-73. There are no other known utility conflicts within the construction limits.

7. Coordination with Other Projects.

The following project work will be concurrent with this project:

Project 5820-01-62, Coon Valley - Bangor, Dutch Creek Bridge-STH 16, STH 162, La Crosse County. This is a pavement resurfacing project that is 8.6 miles in length on STH 162 (North) from Dutch Creek Bridge (north limits of 5820-01-73) to STH 16. Major work on this project includes milling, asphaltic paving, beam guard, and grading side slopes. The project is to be completed under traffic through the use of flagging. Work on this project may impact the travel of construction equipment. Contact WisDOT project manager Brian Meyer at (608) 789-5676 or Brian.Meyer@dot.wi.gov for more information.

Project 5140-03-70, Cashton - Sparta, STH 33 Intersection, STH 27, Monroe County. The STH 27/STH 33 intersection will be reconstructed with a single roundabout at the current intersection location. The west leg of STH 33 will be closed to traffic with the east leg of STH 33 and both legs of STH 27 remaining open to traffic utilizing temporary widening as necessary. Construction of Project 5140-03-70 is required to occur while Project 5121-09-03 is under posted detour as it will utilize the same detour route. Contact WisDOT project manager Todd Waldo at (608) 785-9462 or Todd.Waldo@dot.wi.gov for more information.

8. Environmental Protection, Aquatic Exotic Species Control.

Exotic invasive organisms such as VHS, zebra mussels, purple loosestrife, and Eurasian water milfoil are becoming more prolific in Wisconsin and pose adverse effects to waters of the state. Wisconsin State Statutes 30.07, "Transportation of Aquatic Plants and Animals; Placement of Objects in Navigable Waters", details the state law that requires the removal of aquatic plants and zebra mussels each time equipment is put into state waters.

At construction sites that involve navigable water or wetlands, use the follow cleaning procedures to minimize the chance of exotic invasive species infestation. Use these procedures for all equipment that comes in contact with waters of the state and/or infested water or potentially infested water in other states.

Ensure that all equipment that has been in contact with waters of the state, or with infested or potentially infested waters, has been decontaminated for aquatic plant materials and zebra mussels prior to being used in other waters of the state. Before using equipment on this project, thoroughly disinfect all equipment that has come into contact with potentially infested waters. Use the following inspection and removal procedures (guidelines from the Wisconsin Department of Natural Resources http://dnr.wi.gov/topic/fishing/documents/vhs/disinfection_protocols.pdf for disinfection:

1. Prior to leaving the contaminated site, wash machinery and ensure that the machinery is free of all soil and other substances that could possibly contain exotic invasive species;
2. Drain all water from boats, trailers, bilges, live wells, coolers, bait buckets, engine compartments, and any other area where water may be trapped;
3. Inspect boat hulls, propellers, trailers and other surfaces. Scrape off any attached mussels, remove any aquatic plant materials (fragments, stems, leaves, seeds, or roots), and dispose of removed mussels and plant materials in a garbage can prior to leaving the area or invested waters; and
4. Disinfect your boat, equipment and gear by either:
 - a. Washing with ~212° F water (steam clean), or
 - b. Drying thoroughly for five days after cleaning with soap and water and/or high pressure water, or
 - c. Disinfecting with either 200 ppm (0.5 oz per gallon or 1 Tablespoon per gallon) Chlorine for 10-minute contact time or 1:100 solution (38 grams per gallon) of Virkon Aquatic for 20- to 30-minute contact time. Note: Virkon is not registered to kill zebra mussel veligers nor invertebrates like spiny water flea. Therefore this disinfect should be used in conjunction with a hot water (>104° F) application.

Complete the inspection and removal procedure before equipment is brought to the project site and before the equipment leaves the project site.

107-055 (20130615)

9. Erosion Control Structures.

Within seven calendar days after the commencement of work on the bridge superstructure, place all permanent erosion control devices, including riprap, erosion mat, ditch checks, seed, fertilizer, mulch, soil stabilizer, or any other item required by the contract or deemed necessary by the engineer. These devices shall be in place in the area under the bridge and on both sides of the roadway, from the waterway to a point 100-feet behind the backwall of the abutment. Within said limits, place these devices to a height equivalent to the calculated water elevation resulting from a storm that occurs on the average of once every two years (Q2) as shown on the plan, or as directed by the engineer. Prior to initial construction operations, place turbidity barriers, silt screens, and other temporary erosion control

measures as shown on the plans, and remove them after the permanent erosion control devices are in place unless directed otherwise by the engineer.

In the event that construction activity does not disturb the existing ground below the Q2 elevation, the above timing requirements for permanent erosion control shall be waived.
107-070 (20030820)

10. Health and Safety Requirements for Workers Remediating Petroleum Contamination.

Add the following to standard spec 107.1(2):

Soil contamination with gasoline, diesel fuel, fuel oil, or other petroleum related products may be encountered during excavation activities. Prepare a site specific Health and Safety Plan complying with the Occupational Safety and Health Administration (OSHA) standard for Hazardous Waste Operation and Emergency Response (HAZWOPER), 29 CFR 1910.120.

All site workers taking part in remediation activities or who will have the reasonable probability of exposure of safety or health hazards associated with the hazardous material shall have completed Health and Safety training that meets OSHA requirements. Prior to the start of remediation work, submit to the engineer a site specific Health and Safety Plan, and written verification that workers will have completed up-to-date OSHA training.

Develop, delineate, and enforce the health and safety exclusions zones for each contaminated site location pursuant to 29 CFR 1910.120.

A Description

The department and others have completed investigations for soil and groundwater contamination for locations adjacent to, and within, the construction limits where excavation is planned. Investigations indicated that petroleum-contaminated soil is present at and adjacent to the Arentz Property, which is located at the northeast corner of STH 33 and STH 162 in Middle Ridge, Wisconsin. Contaminated soil is present on STH 33 from approximately Station 934+35 to 934+75 from left 20 feet to construction limits left and on STH 162 from approximately Station 934+85 to 935+35 from right 15 feet to construction limits right.

Supply the schedule of operations, including work in the contaminated areas, to the engineer at the preconstruction conference. If contaminated soil, underground storage tanks (USTs), or other waste is encountered elsewhere on the project during excavation, terminate the excavation in the area and notify the engineer and the environmental consultant.

Be advised that there is potential that USTs may be encountered within the construction limits during excavations. If a UST is encountered, stop excavations in that area and notify the environmental consultant and coordinate with the environmental consultant for its removal by others. Assist the environmental consultant in determining if the USTs are present by performing a backhoe pit investigation, as directed by the environmental consultant at the following locations:

- Arentz property (STH 33, Station 934+30 to 934+65)
- South of STH 33 from Station 934+30 to 936+40 from right 20 feet to construction limits right.

The backhoe pit investigation shall be performed as soon as practical after commencement of construction and prior to significant excavations (if any) beginning in those areas.

B Coordination

Coordinate work under this Contract with the environmental consultant retained by the department:

Consultant: RMT, Inc.
Address: 744 Heartland Trail, P.O. Box 8923, Madison, WI 53708-8923
Contacts: Mr. Richard P. Fish (608.662.5248) or Mr. Dan Haak
Fax: (608) 831-3334

The role of the environmental consultant will be limited to field-screening, classifying, directing, and documenting the performance of activities associated with the management of contaminated soil and groundwater according to agreements between the Wisconsin Department of Natural Resources (WDNR) and the department. Provide 14 calendar days advance notice of the preconstruction conference date to the environmental consultant. At the preconstruction conference, provide a proposed schedule for the excavation activities in the area of known contamination. Identify the department-approved solid waste disposal facility to be used for the disposal of contaminated soil at the preconstruction conference. Notify the environmental consultant 10 business days prior to commencement of the initial excavation in an area with known contamination, and again 5 business days prior to commencement of subsequent excavations in an area known for contamination. Coordinate with the environmental consultant to ensure that the environmental consultant is present prior to, and during, contaminated material management activities.

C Excavation Management Plan Approval

The excavation management plan for this project has been designated to minimize the off-site disposal of contaminated material. The excavation management plan, including these special provisions, has been developed in cooperation with the WDNR. The WDNR's concurrence letter is on file at the Wisconsin Department of Transportation. For further information regarding the investigations, including waste characterization within the project limits, contact Jenny Frederickson with the department, at (608) 785-9945.

11. Notice to Contractor, Notification of Demolition and/or Renovation No Asbestos Found.

James Gondeck, License Number All-108099, inspected Structure B-32-0569 for asbestos on June 6, 2014. No regulated Asbestos Containing Material (RACM) was found on this structure. A copy of the inspection report is available from: Todd Waldo, Phone (608) 785-9462.

According to NR447 and DHS159, ensure that DNR or DHS receives a completed Notification of Demolition and/or Renovation (DNR Form 4500-113 (R 4/11), or subsequent revision) via U.S. mail, hand-delivery, or using the online notification system at least 10 working days prior to beginning any construction or demolition. Pay all associated fees. Provide a copy of the completed 4500-113 form to Todd Waldo, Phone (608) 785-9462 and DOT BTS-ESS Attn: Hazardous Materials Specialist PO Box 7965, Madison, WI. 53707-7965. In addition, comply with all local or municipal asbestos requirements.

Use the following information to complete WisDNR form 4500-113:

- Site Name: Structure B-32-0569, STH 162 over Dutch Creek
- Site Address: 0.5M N Jct STH 33 to E; S02 T15N R05W; Town of Washington
- Ownership Information: WisDOT Transportation SW Region, 3550 Mormon Coulee Rd, La Crosse, WI, 54601
- Contact: Todd Waldo
- Phone: (608) 785-9462
- Age: 88 years old. This structure was constructed in 1927.
- Area: 1196 SF of deck

Insert the following paragraph in Section 6.g.:

- If asbestos not previously identified is found or previously non-friable asbestos becomes crumbled, pulverized, or reduced to a powder, stop work immediately, notify the engineer, and the engineer will notify the department's Bureau of Technical Services at (608) 266-1476 for an emergency response according to standard spec 107.24. Keep material wet until it is abated or until it is determined to be non-asbestos containing material.

107-125 (20120615)

12. Public Convenience and Safety.

Revise standard spec 107.8(6) as follows:

Check for and comply with local ordinances governing the hours of operation of construction equipment. Do not operate motorized construction equipment from 9:00 PM until the following 6:00 AM, unless prior written approval is obtained from the engineer.

13. Coordination with Businesses and Residents.

The contractor shall arrange and conduct a meeting between the contractor, the department, affected residents, local officials and business people to discuss the project schedule of operations including vehicular and pedestrian access during construction operations. Hold the first meeting at least one week prior to the start of work under this contract and hold two meetings per month thereafter. The contractor shall arrange for a suitable location for the meeting(s) that provides reasonable accommodation for public involvement. The department will prepare and coordinate publication of the meeting notices and mailings for the meeting(s). The contractor shall schedule the meeting(s) with at least two weeks prior notice to the engineer to allow for these notifications.

108-060 (20141107)

14. Removing Old Structure Over Waterway With Minimal Debris Station 966+44.23, Item 203.0600.S.01.

Conform to standard spec 203 as modified in this special provision.

Add the following to standard spec 203:

203.3.6 Removals Over Waterways and Wetlands

203.3.6.2 Removing Old Structure Over Waterway with Minimal Debris

- (1) Remove the existing Structure B-32-0569 over the Tributary to Dutch Creek in large sections and conforming to the contractor's approved structure removal and clean-up plan. During superstructure removal, prevent all large pieces and minimize the number of small pieces from entering the waterway or wetland. Remove all reinforcing steel, all concrete, and all other debris that falls into the waterway or wetland. The contractor may leave limited amounts of small concrete pieces scattered over the waterway floor or wetland only if the engineer allows.
- (2) Submit a structure removal and clean-up plan as part of the erosion control implementation plan required under standard spec 107.20. Do not start work under the structure removal and clean-up plan without the department's written approval of the plan. Include the following information in the structure removal and clean-up plan:
 - Methods and schedule to remove the structure.
 - Methods to control potentially harmful environmental impacts.
 - Methods for superstructure removal that prevent all large pieces and minimize the number of small pieces from entering the waterway or wetlands.
 - Methods to control dust and contain slurry.
 - Methods for removing piers and abutments. If blasting in water, include restrictions that regulatory agencies and the contract require.
 - Methods for cleaning the waterway or wetlands.
- (3) If stockpiling spoil material, place it on an upland site an adequate distance from the waterway, wetland, or any open water created by excavation. Install silt fence between the spoil pile and the waterway, wetland, or excavation site.

Add the following Removing Old Structure bid item to standard spec 203.5.1:

ITEM NUMBER	DESCRIPTION	UNIT
203.0600.S.01	Removing Old Structure Over Waterway With Minimal Debris Station 966+44.23	LS

203-020 (20080902)

15. Select Borrow.

Conform to the requirements of standard spec 208 and as hereinafter provided.

Material

Furnish and use material that consists of granular material meeting the following requirements: The material used as Selected Borrow shall be a well graded shot rock with a 3 foot maximum rock size. Before any Selected Borrow is placed, the material shall be approved by the engineer.

Measurement

The following factors and conversions will be assumed for measurement if measurement in original position is not feasible. The engineer must approve any alternate measurement methods if measurement in original position is not feasible.

Expansion Factor from original position (rock face) to final position is assumed to be 1.10
A Conversion Factor of 1.75 Ton/CY is assumed (1 CY in final position=1.75 Ton)

16. QMP Base Aggregate.

A Description

A.1 General

- (1) This special provision describes contractor quality control (QC) sampling and testing for base aggregates, documenting those test results, and documenting related production and placement process changes. This special provision also describes department quality verification (QV), independent assurance (IA), and dispute resolution.
- (2) Conform to standard spec 301, standard spec 305, and standard spec 310 as modified here in this special provision. Apply this special provision to material placed under all of the Base Aggregate Dense and Base Aggregate Open Graded bid items, except do not apply this special provision to material classified as reclaimed asphaltic pavement placed under the Base Aggregate Dense bid items.
- (3) Do not apply this special provision to material placed under the Aggregate Detours, Salvaged Asphaltic Pavement Base, Breaker Run, Select Crushed, Pit Run, Subbase, or Riprap bid items.

- (4) Provide and maintain a quality control program, defined as all activities related to and documentation of the following:
 1. Production and placement control and inspection.
 2. Material sampling and testing.
- (5) Chapter 8 of the department's construction and materials manual (CMM) provides additional detailed guidance for QMP work and describes required sampling and testing procedures. The contractor may obtain the CMM from the department's web site at:
<http://roadwaystandards.dot.wi.gov/standards/cmm/index.htm>

A.2 Contractor Testing for Small Quantities

- (1) The department defines a small quantity, for each individual Base Aggregate bid item, as a plan quantity of 9000 tons or less of material as shown in the schedule of items under that bid item.
- (2) The requirements under this special provision apply equally to a small quantity for an individual bid item except as follows:
 1. The contractor need not submit a full quality control plan but shall provide an organizational chart to the engineer including names, telephone numbers, and current certifications of all persons involved in the quality control program for material under affected bid items.
 2. Divide the aggregate into uniformly sized sublots for testing as follows:

Plan Quantity	Minimum Required Testing
≤ 1500 tons	One test from production, load-out, or placement at the contractor's option ^[1]
> 1500 tons and ≤ 6000 tons	Two tests of the same type, either from production, load-out, or placement at the contractor's option ^[1]
> 6000 tons and ≤ 9000 tons	Three placement tests ^{[2] [3]}

- ^[1] If using production tests for acceptance, submit test results to the engineer for review prior to incorporating the material into the work. Production test results are valid for a period of 3 years.
- ^[2] For 3-inch material, obtain samples at load-out.
- ^[3] If the actual quantity overruns 9000 tons, create overrun sublots to test at a rate of one additional placement test for each 3000 tons, or fraction of 3000 tons, of overrun.
3. No control charts are required. Submit aggregate load-out and placement test results to the engineer within one business day of obtaining the sample. Assure that all properties are within the limits specified for each test.
4. Department verification testing is optional for quantities of 6000 tons or less.
- (3) Material represented by a subplot with any property outside the specification limits is nonconforming. The department may reject material or otherwise determine the final disposition of nonconforming material as specified in standard spec 106.5.

B Materials

B.1 Quality Control Plan

- (1) Submit a comprehensive written quality control plan to the engineer at or before the pre-construction meeting. Do not place base before the engineer reviews and comments on the plan. Construct the project as that plan provides.
- (2) Do not change the quality control plan without the engineer's review. Update the plan with changes as they become effective. Provide a current copy of the plan to the engineer and post in each of the contractor's laboratories as changes are adopted. Ensure that the plan provides the following elements:
 1. An organizational chart with names, telephone numbers, current certifications and/or titles, and roles and responsibilities of QC personnel.
 2. The process used to disseminate QC information and corrective action efforts to the appropriate persons. Include a list of recipients, the communication means that will be used, and action time frames.
 3. A list of source and processing locations, section and quarter descriptions, for all aggregate materials requiring QC testing.
 4. Test results for wear, sodium sulfate soundness, freeze/thaw soundness, and plasticity index of all aggregates requiring QC testing. Obtain this information from the region materials unit or from the engineer.
 5. Descriptions of stockpiling and hauling methods.
 6. Locations of the QC laboratory, retained sample storage, and where control charts and other documentation is posted.
 7. An outline for resolving a process control problem. Include responsible personnel, required documentation, and appropriate communication steps.

B.2 Personnel

- (1) Have personnel certified under the department's highway technician certification program (HTCP) perform sampling, testing, and documentation as follows:

Required Certification Level:	Sampling or Testing Roles:
Aggregate Technician IPP Aggregate Sampling Technician Aggregate Assistant Certified Technician (ACT-AGG)	Aggregate Sampling ^[1]
Aggregate Technician IPP Aggregate Assistant Certified Technician (ACT-AGG)	Aggregate Gradation Testing, Aggregate Fractured Particle Testing, Aggregate Liquid Limit and Plasticity Index Testing

^[1] Plant personnel under the direct observation of an aggregate technician certified at level one or higher may operate equipment to obtain samples.

- (2) A certified technician must coordinate and take responsibility for the work an ACT performs. Have a certified technician ensure that all sampling and testing is performed correctly, analyze test results, and post resulting data. No more than one ACT can work under a single certified technician.

B.3 Laboratory

- (1) Perform QC testing at a department-qualified laboratory. Obtain information on the Wisconsin laboratory qualification program from:
Materials Management Section
3502 Kinsman Blvd.
Madison, WI 53704
Telephone: (608) 246-5388
<http://www.dot.state.wi.us/business/engrserv/lab-qualification.htm>

B.4 Quality Control Documentation

B.4.1 General

- (1) Submit base aggregate placement documentation to the engineer within 10 business days after completing base placement. Ensure that the submittal is complete, neatly organized, and includes applicable project records and control charts.

B.4.2 Records

- (1) Document all placement observations, inspection records, and control adjustments daily in a permanent field record. Also include all test results in the project records. Provide test results to the engineer within 6 hours after obtaining a sample. For 3-inch base, extend this 6-hour limit to 24 hours. Post or distribute tabulated results using a method mutually agreeable to the engineer and contractor.

B.4.3 Control Charts

- (1) Plot gradation and fracture on the appropriate control chart as soon as test results are available. Format control charts according to CMM 8.30. Include the project number on base placement control charts. Maintain separate control charts for each base aggregate size, source or classification, and type.
- (2) Provide control charts to the engineer within 6 hours after obtaining a sample. For 3-inch base, extend this 6-hour limit to 24 hours. Post or distribute charts using a method mutually agreeable to the engineer and contractor. Update control charts daily to include the following:
 1. Contractor individual QC tests.
 2. Department QV tests.
 3. Department IA tests.
 4. Four-point running average of the QC tests.
- (3) Except as specified under B.8.2.1 for nonconforming QV tests, include only QC tests in the running average. The contractor may plot process control or informational tests on control charts, but do not include these tests, conforming QV tests, or IA tests in the running average.

B.5 Contractor Testing

- (1) Test gradation, fracture, liquid limit and plasticity index during placement for each base aggregate size, source or classification, and type.
- (2) Test gradation once per 3000 tons of material placed. Determine random sample locations and provide those sample locations to the engineer. Obtain samples after the material has been bladed, mixed, and shaped but before compacting; except collect 3-inch samples from the stockpile at load-out. Do not sample from material used to maintain local traffic or from areas of temporary base that will not have an overlying pavement. On days when placing only material used to maintain local traffic or only temporary base that will not have an overlying pavement, no placement testing is required.
- (3) Split each contractor QC sample and identify it according to CMM 8.30. Retain the split for 7 calendar days in a dry, protected location. If requested for department comparison testing, deliver the split to the engineer within one business day.
- (4) The engineer may require additional sampling and testing to evaluate suspect material or the technician's sampling and testing procedures.
- (5) Test fracture for each gradation test until the fracture running average is above the lower warning limit. Subsequently, the contractor may reduce the frequency to one test per 10 gradation tests if the fracture running average remains above the warning limit.
- (6) Test the liquid limit and plasticity index for the first gradation test. Subsequently, test the liquid limit and plasticity index a minimum of once per 10 gradation tests.

B.6 Test Methods

B.6.1 Gradation

- (1) Test gradation using a washed analysis conforming to the following as modified in CMM 8.60:
Gradation..... AASHTO T 27
Material finer than the No. 200 sieve..... AASHTO T 11
- (2) For 3-inch base, if 3 consecutive running average points for the percent passing the No. 200 sieve are 8.5 percent or less, the contractor may use an unwashed analysis. Wash at least one sample out of 10. If a single running average for the percent passing the No. 200 sieve exceeds 8.5 percent, resume washed analyses until 3 consecutive running average points are again 8.5 percent passing or less.
- (3) Maintain a separate control chart for each sieve size specified in standard spec 305 or standard spec 310 for each base aggregate size, source or classification, and type. Set control and warning limits based on the standard specification gradation limits as follows:

1. Control limits are at the upper and lower specification limits.
2. There are no upper warning limits for sieves allowing 100 percent passing and no lower control limits for sieves allowing 0 percent passing.
3. Dense graded warning limits, except for the No. 200 sieve, are 2 percent within the upper and lower control limits. Warning limits for the No. 200 sieve are set 0.5 percent within the upper and lower control limits.
4. Open graded warning limits for the 1-inch, 3/8-inch, and No. 4 sieves are 2 percent within the upper and lower control limits. Upper warning limits for the No. 10, No. 40, and No. 200 sieves are 1 percent inside the upper control limit.

B.6.2 Fracture

- (1) Test fracture conforming to CMM 8.60. The engineer will waive fractured particle testing on quarried stone.
- (2) Maintain a separate fracture control chart for each base aggregate size, source or classification, and type. Set the lower control limit at the contract specification limit, either specified in another special provision or in table 301-2 of standard spec 301.2.4.5. Set the lower warning limit 2 percent above the lower control limit. There are no upper limits.

B.6.3 Liquid Limit and Plasticity

- (1) Test the liquid limit and plasticity according to AASHTO T 89 and T 90.
- (2) Ensure the material conforms to the limits specified in standard spec table 301-2.

B.7 Corrective Action

B.7.1 General

- (1) Consider corrective action when the running average trends toward a warning limit. Take corrective action if an individual test exceeds the contract specification limit. Document all corrective actions both in the project records and on the appropriate control chart.

B.7.2 Placement Corrective Action

- (1) Do not blend additional material on the roadbed to correct gradation problems.
- (2) Notify the engineer whenever the running average exceeds a warning limit. When 2 consecutive running averages exceed a warning limit, the engineer and contractor will discuss appropriate corrective action. Perform the engineer's recommended corrective action and increase the testing frequency as follows:
 1. For gradation, increase the QC testing frequency to at least one randomly sampled test per 1000 tons placed.
 2. For fracture, increase the QC testing frequency to at least one test per gradation test.
- (3) If corrective action improves the property in question such that the running average after 4 additional tests is within the warning limits, the contractor may return to the testing frequency specified in B.5.3. If corrective action does not improve the property in

question such that the running average after 4 additional individual tests is still in the warning band, repeat the steps outlined above starting with engineer notification.

- (4) If the running average exceeds a control limit, material starting from the first running average exceeding the control limit and ending at the first subsequent running average inside the control limit is nonconforming and subject to pay reduction.
- (5) For individual test results significantly outside the control limits, notify the engineer, stop placing base, and suspend other activities that may affect the area in question. The engineer and contractor will jointly review data, data reduction, and data analysis; evaluate sampling and testing procedures; and perform additional testing as required to determine the extent of potentially unacceptable material. The engineer may direct the contractor to remove and replace that material. Individual test results are significantly outside the control limits if meeting one or more of the following criteria:
 1. A gradation control limit for the No. 200 sieve is exceeded by more than 3.0 percent.
 2. A gradation control limit for any sieve, except the No. 200, is exceeded by more than 5.0 percent.
 3. The fracture control limit is exceeded by more than 10.0 percent.

B.8 Department Testing

B.8.1 General

- (1) The department will conduct verification testing to validate the quality of the product and independent assurance testing to evaluate the sampling and testing. The department will provide the contractor with a listing of names and telephone numbers of all QV and IA personnel for the project, and provide test results to the contractor within 2 business days after the department obtains the sample.

B.8.2 Verification Testing

B.8.2.1 General

- (1) The department will have an HTCP technician, or ACT working under a certified technician, perform QV sampling and testing. Department verification testing personnel must meet the same certification level requirements specified in B.2 for contractor testing personnel for each test result being verified. The department will notify the contractor before sampling so the contractor can observe QV sampling.
- (2) The department will conduct QV tests of each base aggregate size, source or classification, and type during placement conforming to the following:
 1. One non-random test on the first day of placement.
 2. At least one random test per 30,000 tons, or fraction of 30,000 tons, placed.
- (3) The department will sample randomly, at locations independent of the contractor's QC work, collecting one sample at each QV location. The department will collect QV samples after the material has been bladed, mixed, and shaped but before compacting; except, for 3-inch aggregates, the department will collect samples from the stockpile at load-out. The department will split each sample, test half for QV, and retain half.

- (4) The department will conduct QV tests in a separate laboratory and with separate equipment from the contractor's QC tests. The department will use the same methods specified for QC testing.
- (5) The department will assess QV results by comparing to the appropriate specification limits. If QV test results conform to the specification, the department will take no further action. If QV test results are nonconforming, add the QV to the QC test results as if it were an additional QC test.

B.8.3 Independent Assurance

- (1) Independence assurance is unbiased testing the department performs to evaluate the department's QV and the contractor's QC sampling and testing including personnel qualifications, procedures, and equipment. The department will perform an IA review according to the department's independent assurance program. That review may include one or more of the following:
 1. Split sample testing.
 2. Proficiency sample testing.
 3. Witnessing sampling and testing.
 4. Test equipment calibration checks.
 5. Reviewing required worksheets and control charts.
 6. Requesting that testing personnel perform additional sampling and testing.
- (2) If the department identifies a deficiency, and after further investigation confirms it, correct that deficiency. If the contractor does not correct or fails to cooperate in resolving identified deficiencies, the engineer may suspend placement until action is taken. Resolve disputes as specified in B.9.

B.9 Dispute Resolution

- (1) The engineer and contractor should make every effort to avoid conflict. If a dispute between some aspect of the contractor's and the engineer's testing program does occur, seek a solution mutually agreeable to the project personnel. The department and contractor may review the data, examine data reduction and analysis methods, evaluate sampling and testing procedures, and perform additional testing. Use ASTM E 178 to evaluate potential statistically outlying data.
- (2) Production test results, and results from other process control testing, may be considered when resolving a dispute.
- (3) If the project personnel cannot resolve a dispute, and the dispute affects payment or could result in incorporating non-conforming product, the department will use third party testing to resolve the dispute. The department's central office laboratory, or a mutually agreed on independent testing laboratory, will provide this testing. The engineer and contractor will abide by the results of the third party tests. The party in error will pay service charges incurred for testing by an independent laboratory. The department may use third party test results to evaluate the quality of questionable materials and determine the appropriate payment. The department may reject material

or otherwise determine the final disposition of nonconforming material as specified in standard spec 106.5.

C (Vacant)

D (Vacant)

E Payment

- (1) Costs for all sampling, testing, and documentation required under this special provision are incidental to this work. If the contractor fails to perform the work required under this special provision, the department may reduce the contractor's pay. The department will administer pay reduction under the non-performance of QMP administrative item.
- (2) For material represented by a running average exceeding a control limit, the department will reduce pay by 10 percent of the contract price for the affected Base Aggregate bid items listed in subsection A. The department will administer pay reduction under the Nonconforming QMP Base Aggregate Gradation or Nonconforming QMP Base Aggregate Fracture Administrative items. The department will determine the quantity of nonconforming material as specified in B.7.2.

301-010 (20100709)

17. QMP Base Aggregate Dense 1 1/4-Inch Compaction, Item 371.1000.S.

A Description

- (1) This special provision modifies the compaction and density testing and documentation requirements of work done under the Base Aggregate Dense 1 1/4-Inch bid items. Conform to standard spec 305 as modified in this special provision and to the contract QMP Base Aggregate article.
- (2) Provide and maintain a quality management program. A quality management program is defined as all activities, including process control, inspection, sampling and testing, and necessary adjustments in the process related to construction of dense graded base which meets all the requirements of this provision.
- (3) Chapter 8 of the department's construction and materials manual (CMM) provides additional detailed guidance for QMP work and describes sampling and testing procedures. The contractor may obtain the CMM from the department's web site at:
<http://roadwaystandards.dot.wi.gov/standards/cmm/index.htm>
- (4) This special provision applies to Base Aggregate Dense 1 1/4-Inch material placed on the mainline traveled way and adjacent mainline shoulders according to the typical finished sections. Unless otherwise specified by the contract, all Base Aggregate Dense 1 1/4-Inch material placed on side roads, private and public entrances, ramps, tapers, turn lanes, and other locations not described as the mainline traveled way and its adjacent mainline shoulders is exempt from the compaction and density requirement modifications and testing contained within this special provision.

B (Vacant)

C Construction

C.1 General

- (1) The engineer shall approve the grade prior to placement of the base. Approval of the grade shall be according to applicable provisions of the standard specifications.

Add the following to standard spec 305.3.2.2:

- (3) Compact the 1 1/4-Inch dense graded base to a minimum of 93.0% of the material target density. Ensure that adequate moisture is present during placement and compaction operations to prevent segregation and to help achieve compaction.

The material target density will be identified using one of the following methods:

1. For 1 1/4-Inch dense graded base composed of $\leq 20\%$ reclaimed asphaltic pavement (RAP) or crushed concrete (RCA), as determined by classification of material (aggregate or RAP and/or RCA) and percentage by weight of each material type retained on the No. 4 Sieve: maximum dry density according to AASHTO T-180, Method D, with correction for coarse particles as determined by AASHTO T224, and modified to require determination of Bulk Specific Gravity (G_m) according to AASHTO T 85. Bulk Specific Gravities determined according to standard spec 106.3.4.2.2 for aggregate source approval may be utilized
2. For 1 1/4-Inch dense graded base composed of $>20\%$ RAP or RCA, as determined by classification of material (aggregate or RAP and/or RCA) and percentage by weight of each material type retained on the No. 4 Sieve, the contractor may choose from the following options:
 - a. Maximum dry density as determined by AASHTO T-180, Method D, with correction for coarse particles as determined by AASHTO T224, and modified to require determination of Bulk Specific Gravity (G_m) according to AASHTO T 85.
 - b. Maximum wet density as determined by AASHTO T-180, Method D, modified to define *Maximum Density* as the wet density in pounds per cubic foot of soil at optimum moisture content using Method D specified compaction, with correction for coarse particles as determined by AASHTO T224, and modified to require determination of Bulk Specific Gravity (G_m) according to AASHTO T 85.
 - c. Average of 10 random control strip wet density measurements as described in section C.2.5.1.

- (4) Base Aggregate Dense 1 1/4-Inch will be accepted for compaction on a target density lot basis.
- (5) Field density tests on materials using contractor elected target density methods C.1(3).2.b or C.1(3).2.c will not be considered for lot acceptance on the basis of compaction under the requirements of this provisions until the moisture content of the in-place material is less than 2.0 percentage points above the maximum wet density optimum moisture or 2.0 percentage points of the average moisture content of the 10 density tests representing a control strip, respectively.

C.2 Quality Management Program

C.2.1 Quality Control Plan

- (1) Submit a comprehensive written quality control plan to the engineer no later than 10 business days before placement of material. Do not place any dense graded base before the engineer reviews and accepts the plan. Construct the project as the plan provides.
- (2) Do not change the quality control plan without the engineer's review and acceptance. Update the plan with changes as they become effective. Provide a current copy of the plan to the engineer and post in the contractor's laboratory as changes are adopted. Ensure that the plan provides the following elements:
 - 1. An organizational chart with names, telephone numbers, current certifications and/or titles, and roles and responsibilities of QC personnel.
 - 2. The process used to disseminate QC information and corrective action efforts to the appropriate persons. Include a list of recipients, the communication process that will be used, and action time frames.
 - 3. A list of source locations, section and quarter descriptions, for all aggregate materials requiring QC testing.
 - 4. Descriptions of stockpiling and hauling methods.
 - 5. An outline for resolving a process control problem. Include responsible personnel, required documentation, and appropriate communication steps.
 - 6. Location of the QC laboratory, retained sample storage, and other documentation.
 - 7. A summary of the locations and calculated quantities to be tested under this provision.
 - 8. A description of placement methods and operations. Including, but not limited to: staging, construction of an initial working platform, lift thicknesses, and equipment.

C.2.2 Pre-Placement Meeting

A minimum of two weeks prior to the start of placement of Base Aggregate Dense 1 1/4-Inch material, hold a pre-placement meeting at a mutually agreed upon time and location. Present the Quality Control Plan at the meeting. Attendance at the pre-placement meeting is mandatory for the project superintendent, quality control manager, project inspection and testing staff, all appropriate contractor personnel involved in the sampling, testing, and quality control including subcontractors, and the engineer or designated representatives.

C.2.3 Personnel

- (1) Perform the quality control sampling, testing, and documentation required under this provision using technicians certified by the department's Highway Technician Certification Program (HTCP). Have a HTCP Nuclear Density Technician I, or ACT certified technician, perform field density and field moisture content testing.
- (2) If an ACT is performing sampling or testing, a certified technician must coordinate and take responsibility for the work an ACT performs. Have a certified technician ensure that all sampling and testing is performed correctly, analyze test results, and post resulting data. No more than one ACT can work under a single certified technician.

C.2.4 Equipment

- (1) Furnish the necessary equipment and supplies for performing quality control testing. Ensure that all testing equipment conforms to the equipment specifications applicable to the required testing methods. The engineer may inspect the measuring and testing devices to confirm both calibration and condition. Calibrate all testing equipment according to the CMM and maintain a calibration record at the laboratory.
- (2) Furnish nuclear gauges from the department's approved product list at:
<http://www.dot.wisconsin.gov/business/engrserv/approvedprod.htm>
- (3) Ensure that the nuclear gauge manufacturer or an approved calibration service calibrates the gauge the same calendar year it is used on the project. Retain a copy of the calibration certificate with the gauge.
- (4) For all target density methods, conform to ASTM D 6938 and CMM 8.15 for wet density testing and gauge monitoring methods.
- (5) For the specified target density determined using method C.1(3).1, compute the dry densities for the compacted dense graded base, composed of $\leq 20\%$ RAP or RCA, according to ASTM D 6938.
- (6) For contractor elected target density method C.1(3).2.a compute dry densities of dense graded base composed of $>20\%$ RAP or RCA using a moisture correction factor and the nuclear wet density value. Determine the moisture correction value, for each Proctor produced under the requirements of C.2.5, using the moisture bias as shown in CMM 8.15.12.1 and 8.15.12.2, except the one-point Proctor tests of the five random tests is not required. Conduct a moisture bias test for every 9000 tons of Base Aggregate Dense 1 1/4-Inch placed. Determine natural moistures in the laboratory.
- (7) Perform nuclear gauge measurements using gamma radiation in the backscatter or direct transmission position on the same date of placement of the Base Aggregate Dense 1 1/4-Inch material. Backscatter may be used only if the material being tested cannot reliably maintain an undistorted direct transmission test hole. Direct transmission tests must be performed at the greatest possible probe depth of 2 inches, 4 inches, or 6 inches,

but not to exceed the depth of the compacted layer being tested. Perform each test for 4 minutes of nuclear gauge count time.

C.2.5 Contractor Testing

- (1) Perform compaction testing on the mainline dense graded base material, as defined by A.(4). Perform the quality control sampling, testing, and documentation required under this provision using HTCP certified technicians as required in C.2.3. Conform to CMM 8.15 for testing and gauge monitoring methods.
- (2) Select test sites randomly using ASTM Method D3665. Do not test less than 1 ½ feet from the unsupported edge of the dense graded base layer. Test sites must be located within the mainline traveled way or the traveled way's adjacent mainline shoulder.

C.2.5.1 Contractor Required Quality Control (QC) Testing

- (1) Conduct testing at a minimum frequency of one test per lot. A lot will consist of each 1500 tons for each layer with a minimum lift thickness of 2" of Base Aggregate Dense 1 1/4-Inch material placed, regardless of the location of placement. Each lot of in-place mainline, as defined by A.(4), Base Aggregate Dense 1 1/4- Inch material compacted will be accepted when the lot field density meets the required minimum 93.0% of target density. Lots that don't achieve 93.0% of target density must be addressed and approved according to C.2.7.
- (2) Notify the engineer, if a lot field density test falls below the required minimum value. Document and perform corrective actions according to C.2.7. Deliver documentation of all compaction testing results to the engineer at the time of testing.

C.2.5.1.1 Target Density Determination

C.2.5.1.1.1 Density Control Strip Method

- (1) For contractor elected target density method C.1(3).2.c, construct a control strip for each layer of placement to identify the target wet density for the base aggregate dense material. The control strip construction and density testing will occur under the direct observation and/or assistance of the department QV personnel.
- (2) Unless the engineer approves otherwise, construct control strips to a minimum dimension of 300 feet long and one full lane width.
- (3) Completed control strips may remain in-place to be incorporated into the final roadway cross-section.
- (4) Construct additional control strips, at a minimum, when:
 1. The four point moving average gradation on any one sieve differs from the original gradation test result for that sieve by more than 10 percentage points. The original gradation test is defined as the gradation of the material used to construct the control strip. A previously determined Proctor value will remain

valid for any material with gradation for all sieves within 10.0 percentage points of that Proctor's original gradation test.

2. The source of base aggregate changes.
 3. The four point moving average percentage of blended recycled materials, from classification of material retained on the No. 4 sieve in the original gradation test, differs by more than 10 percentage points. The original gradation test is defined as the gradation of the material used to construct the control strip. A previously determined Proctor value will remain valid for any material with gradation for all sieves within 10.0 percentage points of that Proctor's original gradation test.
 4. The layer thickness changes more than 2.0 inches.
 5. The percent target density exceeds 103.0% on two consecutive density measurements.
- (5) Construct control strips using equipments and methods representative of the operations to be used to place and compact the remaining 1 1/4-Inch Base Aggregate Dense material. Wet the base, as mutually agreed upon by the contractor and engineer, to obtain and/or maintain adequate moisture content to ensure proper compaction. Discontinue water placement if the base begins to exhibit signs of saturation or instability.
 - (6) After compacting the control strip with a minimum of 2 passes, mark and take density measurements at 3 random locations, at least 1 ½ feet from the edge of the base. Subsequent density measurements will be taken at the same 3 locations.
 - (7) After each subsequent pass of compaction equipment over the entirety of the control strip, take density measurements at the 3 marked locations. Continue compacting and testing until the increase in density measurements is less than 2.0 lb/ft³, or the density measurements begin to decrease.
 - (8) Upon completion of control strip compaction, take 10 randomly located density measurements within the limits of the control strip, at least 1 ½ feet from the edge of the base. The final measurements recorded at the 3 locations under article C.2.4.1.1.1(6) may be included as 3 of the 10 measurements. Average the 10 measurements to obtain the control strip target density and target moisture for use in contractor elected method C.1(3).2.c.

C.2.5.1.1.2 Maximum Wet and/or Dry Density Methods

- (1) For contractor elected target density methods C.1(3).2.a, C.1(3).2.b, and contractually specified target density method C.1(3).1; perform one gradation and 5-point Proctor test before placement of 1 1/4-Inch dense graded base. Perform additional gradations every 3000 tons. If sampling requirements are identical, samples/testing performed for the QMP Base Aggregate specification may be used to fulfill the gradation testing requirements of this specification.

(2) Perform additional 5-point Proctor tests, at a minimum, when:

1. The four point moving average gradation on any one sieve differs from the original gradation test result for that sieve, by more than 10 percentage points. The original gradation test is defined as the gradation of the material used to create a 5-point Proctor. Each 5-point Proctor test will remain valid for any material with gradation for all sieves within 10.0 percentage points of that Proctor's original gradation test.
 2. The source of base aggregate changes.
 3. The four point moving average percentage of blended recycled materials ; from classification of material retained on the No. 4 sieve; in the original gradation test, differs by more than 10 percentage points. The original gradation test is defined as the gradation of the material used to construct the control strip. A previously determined Proctor value will remain valid for any material with gradation for all sieves within 10.0 percentage points of that Proctor's original gradation test.
 4. Percent target density exceeds 103.0% on two consecutive density tests.
- (3) Provide Proctor test results to the engineer within 48 hours of sampling. Provide gradation test results to the engineer within 24 hours of sampling.
- (4) Split each contractor QC Proctor sample and identify it according to CMM 8.30. Deliver the split to the engineer within one business day for department QV Proctor testing.
- (5) Split each non-Proctor contractor QC sample and identify it according to CMM 8.30. Retain the split for 7 calendar days in a dry, protected location. If requested for department comparison testing, deliver the split to the engineer within one business day.

C.2.5.2 Optional Contractor Assurance (CA) Testing

- (1) CA Testing is optional and is conducted to further validate QC testing. The contractor may submit recorded CA data to provide additional information for the following:
1. Process control decisions.
 2. Troubleshooting possible sampling, splitting, or equipment problems.

C.2.6 Department Testing

C.2.6.1 General

- (1) The department will conduct verification testing to validate the quality of the product and independent assurance testing to evaluate the sampling and testing. The department will provide the contractor with a listing of names and telephone numbers of all QV and IA personnel for the project, and provide test results to the contractor within 2 business days after the department obtains the sample.

C.2.6.2 Quality Verification (QV) Testing

- (1) The department will have an HTCP technician, or ACT working under a certified technician, perform QV sampling and testing. Department verification testing personnel must meet the same certification level requirements specified in C.2.3 for contractor testing personnel for each test result being verified. The department will notify the contractor before sampling so the contractor can observe QV sampling.
- (2) The department will conduct QV tests at the minimum frequency of 30% of the required gradation, density and Proctor contractor tests.
- (3) The department will utilize contractor's QC Proctor results for determination of the material target density. The department will verify QC Proctor values by testing QC Proctor split sample. The department will use QC Proctor value as a target density if the QC and QV Proctor test results meet the tolerance requirements specified in section 2.6.2.(7).
- (4) The department will locate gradation and nuclear density test samples, at locations independent of the contractor's QC work, collecting one sample at each QV location. The department will split each QV sample, test half for QV, and retain the remaining half for seven calendar days.
- (5) The department will conduct QV tests in a separate laboratory and with separate equipment from the contractor's QC tests. The department will use the same methods specified for QC testing.
- (6) The department will utilize control strip target density testing results in lieu of QV Proctor sampling and testing when the contractor elected C.1 (3).2.c target density method is used.
- (7) The department will assess QV results by comparing to the appropriate specification limits. If QV test results conform to this special provision, the department will take no further action. If QV test results are nonconforming, take corrective actions according to C.2.7 until the requirements of this special provision are met. Differing QC and QV nuclear density values of more than 2.0 pcf will be investigated and resolved. Differing QC and QV Proctor values of more than 3.0 pcf will be investigated and resolved.

C.2.6.3 Independent Assurance (IA)

- (1) Independence assurance is unbiased testing the department performs to evaluate the department's QV and the contractor's QC sampling and testing, including personnel qualifications, procedures, and equipment. The department will perform an IA review according to the department's independent assurance program. That review may include one or more of the following:

1. Split sample testing.
 2. Proficiency sample testing.
 3. Witnessing sampling and testing.
 4. Test equipment calibration checks.
 5. Requesting that testing personnel perform additional sampling and testing.
- (2) If the department identifies a deficiency, and after further investigation confirms it, correct that deficiency. If the contractor does not correct or fails to cooperate in resolving identified deficiencies, the engineer may suspend placement until action is taken. Resolve disputes as specified in C.2.6.4.

C.2.6.4 Dispute Resolution

- (1) The engineer and contractor should make every effort to avoid conflict. If a dispute between some aspect of the contractor's and the engineer's testing program does occur, seek a solution mutually agreeable to the project personnel. The department and contractor shall review the data, examine data reduction and analysis methods, evaluate sampling and testing methods/procedures, and perform additional testing. Use ASTM E 178 to evaluate potential statistically outlying data.
- (2) Production test results, and results from other process control testing, may be considered when resolving a dispute.
- (3) If project personnel cannot resolve a dispute, and the dispute affects payment or could result in incorporating non-conforming product or work, the department will use third party testing to resolve the dispute. The department's central office laboratory, or a mutually agreed on independent testing laboratory, will provide this testing. The engineer and contractor will abide by the results of the third party tests. The party in error will pay service charges incurred for testing by an independent laboratory. The department may use third party test results to evaluate the quality of questionable materials and determine the appropriate payment. The department may reject material or otherwise determine the final disposition of nonconforming material as specified in standard spec 106.5.

C.2.7 Corrective Action

- (1) Lots not achieving 93.0% of target density may be addressed and accepted for compaction according to the requirements of this section. Unless otherwise stated, the actions taken to address an unacceptable lot must be applied to the entire lot.

Passing CA test results according to section C.2.5.2 will reduce the limits of lot investigations and/or corrective actions.

- (2) At no additional cost to the department, investigate the moisture content of material in an unacceptable lot. Moisture content testing/samples collected under the QC and/or QV testing articles of this specification may be used to complete this investigation. Obtain moisture content readings according to ASTM D 6938. For material composed of >20% RAP or RCA, correct the moisture content with the moisture correction value

using the moisture bias, as shown in CMM 8.15.12.1 and 8.15.12.2, except the one-point Proctor tests of the 5 random tests is not required.

- (3) Lots with moisture contents within 2.0 percentage points of optimum moisture for target density methods C.1(3).1, C.1(3).2.a, or C.1(3).2.b, or within 2.0 percentage points of the target moisture content for target density method C.1(3).2.c, and exhibiting no signs of deflection when subjected to loading by the heaviest roller used in the placement and compaction operations, shall be, at no additional cost to the department, compacted a minimum of one more pass using equipment and methods representative of the operations used to place and compact the Base Aggregate Dense 1 1/4-Inch, and density tested at the same location (station and offset) as the failing QC and/or QV density tests. If the change in density exceeds 2.0 lb/ft³ continue subsequent compactive efforts and density testing on that lot, at no additional cost to the department. If the change in density is less than or equal to 2.0 lb/ft³, the lot is accepted as satisfying the compaction requirements of this provision.
- (4) Lots with moisture contents within 2.0 percentage points of optimum moisture for target density methods C.1 (3).1, C.1 (3).2.a, or C.1 (3).2.b, or within 2.0 percentage points of the target moisture content for target density method C.1 (3).2.c, and exhibiting signs of deflection when subjected to loading by the heaviest roller used in the placement and compaction operations, will be reviewed by the engineer. The engineer may request subgrade improvement methods, such as excavation below subgrade (EBS), installation of geotextile fabrics, installation of breaker run material or others to be completed and paid for as specified in standard spec 301.5, or may request, at no additional cost to the department, an additional pass of compactive effort using equipment and methods representative of the operations used to place and compact the base aggregate dense and density test.
 1. If, after an additional pass, the change in density at the same location (station and offset) as the failing QC and/or QV density tests exceeds 2.0 lb/ft³ in a lot continue subsequent compactive efforts and density testing on that lot, at no additional cost to the department. If the change in density at the same location (station and offset) as the failing QC and/or QV density tests is less than or equal to 2.0 lb/ft³, and subgrade improvement methods are not requested by the engineer, the lot is accepted as satisfying the compaction requirements of this provision.
 2. If subgrade improvement methods are requested by the engineer, upon completion, including compaction of the restored base material, conduct a density test within the improved subgrade limits. This density test result will replace the prior field density value. If the lot field density equals or exceeds 93.0% of target density the lot is accepted as satisfying the compaction requirements of this provision. If the lot field density fails to achieve 93.0% of target density, at no additional cost to the department, compact the lot a minimum of one more pass using equipment and methods representative of the operations used to place and compact the base aggregate dense; and density test at the same location (station and offset) as the failing QC and/or QV density

tests. If the change in density exceeds 2.0 lb/ft³ continue subsequent compactive efforts and density testing on that lot, at no additional cost to the department. If the change in density is less than or equal to 2.0 lb/ft³, the lot is accepted as satisfying the compaction requirements of this provision.

- (5) Unacceptable lots, with moisture contents in excess of 2.0 percentage points above or below optimum moisture for target density methods C.1(3).1, C.1(3).2.a, or C.1(3).2.b; or in excess of 2.0 percentage points above or below the target moisture content for target density method C.1(3).2.c; shall receive contractor performed and documented corrective action; including additional density testing; at no additional cost to the department.
- (6) Density tests completed subsequent to any corrective action will replace previous field density test results for that lot. Continue corrective actions until 93.0% of target density is achieved, or an alternate compaction acceptance criteria is met according to this section.
- (7) Field moisture contents of materials tested using contractor elected target density methods C.1(3).2.b or C.1(3).2.c cannot exceed 2.0 percentage points of the optimum moisture content or 2.0 percentage points of the target moisture content, respectively. Density tests on materials using contractor elected target density methods C.1(3).2.b or C.1(3).2.c will not be considered for lot compaction acceptance until the moisture content of the corresponding density test of the in-place material is less than 2.0 percentage points above of the optimum moisture content or 2.0 percentage points of the target moisture content, respectively.

D Measurement

- (1) The department will measure QMP Base Aggregate Dense 1 1/4-Inch Compaction by the ton acceptably completed. The measured tons of QMP Base Aggregate Dense 1 1/4-Inch Compaction equals the tons of Base Aggregate Dense 1 1/4-Inch, acceptably completed, regardless of placement location and density testing eligibility.

E Payment

- (1) The department will pay for the measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
371.1000.S	QMP Base Aggregate Dense 1 1/4-Inch Compaction	TON
- (2) Payment is full compensation for performing compaction testing; for sampling and laboratory testing; and for developing, completing, and documenting the compaction quality management program. The department will pay separately for providing the aggregate under the Base Aggregate Dense 1 1/4-Inch bid item.
370-010 (20150630)

18. Reheating HMA Pavement Longitudinal Joints, Item 460.4110.S.

A Description

This special provision describes reheating the abutting edge of the previously compacted layer in the adjacent lane while paving mainline asphalt pavements.

B (Vacant)

C Construction

C.1 Equipment

Provide a self-contained heating unit that heats by convection only. Do not use forced air to enhance the flame. Provide a fireproof barrier between the flame and the heater's fuel source. The heater must produce a uniform distribution of heat within the heat box. Provide automatic controls to regulate the heater output and shutoff the heater when the paver stops or the heater control system loses power.

Mount the heater on the paver inside the paver's automatic leveling device.

C.2 Reheating Joints

Evenly reheat at least an 8 inch (200 mm) wide strip of the previously compacted layer in the adjacent lane as follows:

- Reheat the joint to within 60 degrees F (15 degrees C) of the mix temperature at the paver auger. Measure joint temperature immediately behind the heater.

The engineer may allow the required joint reheat temperatures to be cooler than specified to adjust for weather, wind, and other field conditions. Coordinate the heater output and paver speed to achieve the required joint reheat temperature without visible smoke emission.

D Measurement

The department will measure Reheating HMA Pavement Longitudinal Joints by the linear foot, acceptably completed, as measured along each joint for each layer of asphalt placed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
460.4110.S	Reheating HMA Pavement Longitudinal Joints	LF

Payment is full compensation for furnishing all the work required under this bid item.
460-015 (20140630)

19. QMP HMA Pavement Nuclear Density.

A Description

Replace standard spec 460.3.3.2 (1) and standard spec 460.3.3.2 (4) with the following:

- (1) This special provision describes density testing of in-place HMA pavement with the use of nuclear density gauges. Conform to standard spec 460 as modified in this special provision.
- (2) Provide and maintain a quality control program defined as all activities and documentation of the following:
 1. Selection of test sites.
 2. Testing.
 3. Necessary adjustments in the process.
 4. Process control inspection.
- (3) Chapter 8 of the department's construction and materials manual (CMM) provides additional detailed guidance for QMP work and describes required procedures. Obtain the CMM from the department's web site at:
<http://roadwaystandards.dot.wi.gov/standards/cmm/index.htm>
- (4) The department's Materials Reporting System (MRS) software allows contractors to submit data to the department electronically, estimate pay adjustments, and print selected reports. Qualified personnel may obtain MRS software from the department's web site at:

<http://www.atwoodsystems.com/mrs>

B Materials

B.1 Personnel

- (1) Perform HMA pavement density (QC, QV) testing using a HTCP certified nuclear technician I, or a nuclear assistant certified technician (ACT-NUC) working under a certified technician.
- (2) If an ACT is performing sampling or testing, a certified technician must coordinate and take responsibility for the work an ACT performs. Have a certified technician ensure that all sampling and testing is performed correctly, analyze test results, and post resulting data. No more than one ACT can work under a single certified technician.

B.2 Testing

- (1) Conform to ASTM D2950 and CMM 8.15 for density testing and gauge monitoring methods. Perform nuclear gauge measurements using gamma radiation in the backscatter position. Perform each test for 4 minutes of nuclear gauge count time.

B.3 Equipment

B.3.1 General

- (1) Furnish nuclear gauges from the department's approved product list at <http://www.dot.wisconsin.gov/business/engrserv/approvedprod.htm>.
- (2) Have the gauge calibrated by the manufacturer or an approved calibration service within 12 months of its use on the project. Retain a copy of the manufacturer's calibration certificate with the gauge.
- (3) Prior to each construction season, and following any calibration of the gauge, the contractor must perform calibration verification for each gauge using the reference blocks located in the department's central office materials laboratory. To obtain information or schedule a time to perform calibration verification, contact the department's Radiation Safety Officer at:
Materials Management Section
3502 Kinsman Blvd.
Madison, Wisconsin 53704
Telephone: (608) 243-5998

B.3.2 Correlation of Nuclear Gauges

B.3.2.1 Correlation of QC and QV Nuclear Gauges

- (1) Select a representative section of the compacted pavement prior to or on the first day of paving for the correlation process. The section does not have to be the same mix design.
- (2) Correlate the 2 or more gauges used for density measurement (QC, QV). The QC and QV gauge operators will perform the correlation on 5 test sites jointly located. Record each density measurement of each test site for the QC, QV and back up gauges.
- (3) Calculate the average of the difference in density of the 5 test sites between the QC and QV gauges. Locate an additional 5 test sites if the average difference exceeds 1.0 lb/ft³. Measure and record the density on the 5 additional test sites for each gauge.
- (4) Calculate the average of the difference in density of the 10 test sites between the QC and QV gauges. Replace one or both gauges if the average difference of the 10 tests exceeds 1.0 lb/ft³ and repeat correlation process from B.3.2.1 (2).
- (5) Furnish one of the QC gauges passing the allowable correlation tolerances to perform density testing on the project.

B.3.2.2 Correlation Monitoring

- (1) After performing the gauge correlation specified in B.3.2.1, establish a project reference site approved by the department. Clearly mark a flat surface of concrete or asphalt or other material that will not be disturbed during the duration of the project. Perform correlation monitoring of the QC, QV, and all back-up gauges at the project reference site.

- (2) Conduct an initial 10 density tests with each gauge on the project reference site and calculate the average value for each gauge to establish the gauge's reference value. Use the gauge's reference value as a control to monitor the calibration of the gauge for the duration of the project.
- (3) Check each gauge on the project reference site a minimum of one test per day if paving on the project. Calculate the difference between the gauge's daily test result and its reference value. Investigate if a daily test result is not within 1.5 lb/ft³ of its reference value. Conduct 5 additional tests at the reference site once the cause of deviation is corrected. Calculate and record the average of the 5 additional tests. Remove the gauge from the project if the 5-test average is not within 1.5 lb/ft³ of its reference value established in B.3.2.2(2).
- (4) Maintain the reference site test data for each gauge at an agreed location.

B.4 Quality Control Testing and Documentation

B.4.1 Lot and Sublot Requirements

B.4.1.1 Mainline Traffic Lanes, Shoulders, and Appurtenances

- (1) A lot consists of the tonnage placed each day for each layer and target density specified in standard spec 460.3.3.1. A lot may include partial sublots.
- (2) Divide the roadway into sublots. A sublot is 1500 lane feet for each layer and target density.
- (3) A sublot may include HMA placed on more than one day of paving. Test sublots at the pre-determined random locations regardless of when the HMA is placed. No additional testing is required for partial sublots at the beginning or end of a day's paving.
- (4) If a resulting partial quantity at the end of the project is less than 750 lane feet, include that partial quantity with the last full sublot of the lane. If a resulting partial quantity at the end of the project is 750 lane feet or more, create a separate sublot for that partial quantity.
- (5) Randomly select test locations for each sublot as specified in CMM 8.15 prior to paving and provide a copy to the engineer. Locate and mark QC density test sites when performing the tests. Perform density tests prior to opening the roadway to traffic.
- (6) Use Table 1 to determine the number of tests required at each station, depending on the width of the lane being tested. When more than one test is required at a station, offset the tests 10 feet longitudinally from one another to form a diagonal testing row across the lane.

Lane Width	No. of Tests	Transverse Location
5 ft or less	1	Random
Greater than 5 ft to 9 ft	2	Random within 2 equal widths
Greater than 9 ft	3	Random within 3 equal widths

Table 1

B.4.1.2 Side Roads, Crossovers, Turn Lanes, Ramps, and Roundabouts

- (1) A lot represents a combination of the total daily tonnage for each layer and target density.
- (2) Each side road, crossover, turn lane, ramp, and roundabout must contain at least one subplot for each layer.
- (3) If a side road, crossover, turn lane, or ramp is 1500 feet or longer, determine sublots and random test locations as specified in B.4.1.1.
- (4) If a side road, crossover, turn lane, or ramp is less than 1500 feet long, determine sublots using a maximum of 750 tons per subplot and perform the number of random tests as specified in Table 2.

Side Roads, Turn Lanes, Crossovers, Ramps, Roundabouts: Sublot/Layer tonnage	Minimum Number of Tests Required
25 to 100 tons	1
101 to 250 tons	3
251 to 500 tons	5
501 to 750 tons	7

Table 2

B.4.2 Pavement Density Determination

B.4.2.1 Mainline Traffic Lanes and Appurtenances

- (1) Calculate the average subplot densities using the individual test results in each subplot.
- (2) If all subplot averages are no more than one percent below the target density, calculate the daily lot density by averaging the results of each random QC test taken on that day's material.
- (3) If any subplot average is more than one percent below the target density, do not include the individual test results from that subplot when computing the lot average density and remove that subplot's tonnage from the daily quantity for incentive. The tonnage from any such subplot is subject to disincentive pay according to standard spec 460.5.2.2.

B.4.2.2 Mainline Shoulders

B.4.2.2.1 Width Greater Than 5 Feet

- (1) Determine the pavement density as specified in B.4.2.1.

B.4.2.2.2 Width of 5 Feet or Less

- (1) If all subplot test results are no more than 3.0 percent below the minimum target density, calculate the daily lot density by averaging all individual test results for the day.
- (2) If a subplot test result is more than 3.0 percent below the target density, the engineer may require the unacceptable material to be removed and replaced with acceptable material or allow the nonconforming material to remain in place with a 50 percent pay reduction. Determine the limits of the unacceptable material according to B.4.3.

B.4.2.3 Side Roads, Crossovers, Turn Lanes, Ramps, and Roundabouts

- (1) Determine the pavement density as specified in B.4.2.1.

B.4.2.4 Documentation

- (1) Document QC density test data as specified in CMM 8.15. Provide the engineer with the data for each lot within 24 hours of completing the QC testing for the lot.

B.4.3 Corrective Action

- (1) Notify the engineer immediately when an individual test is more than 3.0 percent below the specified minimum in standard spec 460.3.3.1. Investigate and determine the cause of the unacceptable test result.
- (2) The engineer may require unacceptable material specified in B.4.3(1) to be removed and replaced with acceptable material or allow the nonconforming material to remain in place with a 50 percent pay reduction. Determine limits of the unacceptable area by measuring density of the layer at 50-foot increments both ahead and behind the point of unacceptable density and at the same offset as the original test site. Continue testing at 50-foot increments until a point of acceptable density is found as specified in standard spec 460.5.2.2(1). Removal and replacement of material may be required if extended testing is in a previously accepted subplot. Testing in a previously accepted subplot will not be used to recalculate a new lot density.
- (3) Compute unacceptable pavement area using the product of the longitudinal limits of the unacceptable density and the full subplot width within the traffic lanes or shoulders.
- (4) Retesting and acceptance of replaced pavement will be according to standard spec 105.3.
- (5) Tests indicating density more than 3.0 percent below the specified minimum, and further tests taken to determine the limits of unacceptable area, are excluded from the computations of the subplot and lot densities.
- (6) If 2 consecutive subplot averages within the same paving pass and same target density are more than one percent below the specified target density, notify the engineer and take necessary corrective action. Document the locations of such sublots and the corrective action that was taken.

B.5 Department Testing

B.5.1 Verification Testing

- (1) The department will have a HTCP certified technician, or ACT working under a certified technician, perform verification testing. The department will test randomly at locations independent of the contractor's QC work. The department will perform verification testing at a minimum frequency of 10 percent of the sublots and a minimum of one subplot per mix design. The sublots selected will be within the active work zone. The contractor will supply the necessary traffic control for the department's testing activities.

- (2) The QV tester will test each selected subplot using the same testing requirements and frequencies as the QC tester.
- (3) If the verification subplot average is not more than one percent below the specified minimum target density, use the QC tests for acceptance.
- (4) If the verification subplot average is more than one percent below the specified target density, compare the QC and QV subplot averages. If the QV subplot average is within 1.0 lb/ft³ of the QC subplot average, use the QC tests for acceptance.
- (5) If the first QV/QC subplot average comparison shows a difference of more than 1.0 lb/ft³ each tester will perform an additional set of tests within that subplot. Combine the additional tests with the original set of tests to compute a new subplot average for each tester. If the new QV and QC subplot averages compare to within 1.0 lb/ft³, use the original QC tests for acceptance.
- (6) If the QV and QC subplot averages differ by more than 1.0 lb/ft³ after a second set of tests, resolve the difference with dispute resolution specified in B.6. The engineer will notify the contractor immediately when density deficiencies or testing precision exceeding the allowable differences are observed.

B.5.2 Independent Assurance Testing

- (1) Independent assurance is unbiased testing the department performs to evaluate the department's verification and the contractor's QC sampling and testing including personnel qualifications, procedures, and equipment. The department will perform the independent assurance review according to the department's independent assurance program.

B.6 Dispute Resolution

- (1) The testers may perform investigation in the work zone by analyzing the testing, calculation, and documentation procedures. The testers may perform gauge correlation according to B.3.2.1.
- (2) The testers may use correlation monitoring according to B.3.2.2 to determine if one of the gauges is out of tolerance. If a gauge is found to be out of tolerance with its reference value, remove the gauge from the project and use the other gauge's test results for acceptance.
- (3) If the testing discrepancy cannot be identified, the contractor may elect to accept the QV subplot density test results or retesting of the subplot in dispute within 48 hours of paving. Traffic control costs will be split between the department and the contractor.
- (4) If investigation finds that both gauges are in error, the contractor and engineer will reach a decision on resolution through mutual agreement.

B.7 Acceptance

- (1) The department will not accept QMP HMA Pavement Nuclear Density if a non-correlated gauge is used for contractor QC tests.

C (Vacant)

D (Vacant)

E Payment

E.1 QMP Testing

- (1) Costs for all sampling, testing, and documentation required under this special provision are incidental to the work. If the contractor fails to perform the work required under this special provision, the department may reduce the contractor's pay. The department will administer pay reduction under the Non-performance of QMP administrative item.

E.2 Disincentive for HMA Pavement Density

- (1) The department will administer density disincentives according to standard spec 460.5.2.2.

E.3 Incentive for HMA Pavement Density

- (1) Delete standard spec 460.5.2.3.
- (2) If the lot density is greater than the minimum specified in standard spec table 460-3 and all individual air voids test results for that mixture are within +1.0 percent or -0.5 percent of the design target in standard spec table 460-2, the department will adjust pay for that lot as follows:

Percent Lot Density Above Minimum	Pay Adjustment Per Ton
From -0.4 to 1.0 inclusive	\$0
From 1.1 to 1.8 inclusive	\$0.40
More than 1.8	\$0.80

- (3) The department will adjust pay under the Incentive Density HMA Pavement bid item. Adjustment under this item is not limited, either up or down, to the bid amount shown on the schedule of items.
- (4) If a traffic lane meets the requirements for disincentive, the department will not pay incentive on the integrally paved shoulder.
- (5) Submit density results to the department electronically using the MRS software. The department will validate all contractor data before determining pay adjustments.

460-020 (20100709)

20. Pipe Cattle Pass.

Add the following to standard spec 520.2.2:

Notify the property owner for cattle pass at Station 927+10 two to three weeks prior to removing or extending existing cattle pass. The cattle pass may be closed for up to two weeks at a time, or make other arrangements with the property owner to get cattle across STH 33.

Notify the property owner for cattle pass at Station 841+40 two weeks prior to removing or extending existing cattle pass. The cattle pass may be closed for up to two weeks at a time, or make other arrangements with the property owner to get cattle across STH 33.

21. Pipe Cattle Pass Corrugated Steel.

Add the following to standard spec 521.2:

Pipe cattle pass corrugated steel at Station 759+21'162' shall be 60-inch diameter or match existing cattle pass diameter. Contractor shall verify size of existing cattle pass.

Notify the property owner two weeks prior to removing or extending existing cattle pass. The cattle pass may be closed for up to one week at a time, or make other arrangements with the property owner to get cattle across STH 162.

22. Storm Sewer Pipe Reinforced Concrete.

Replace standard spec 608.3.4(1) with the following:

Make joints for concrete pipe with annular rubber gaskets, as specified below.

23. Fence Temporary, Item 616.0600.S.

A Description

This special provision describes furnishing, erecting, and removing temporary fencing at the locations shown on the plans and as directed by the engineer.

B (Vacant)

C Construction

Construct fence to the minimum strength and height required to contain livestock, as approved by the engineer.

D Measurement

The department will measure Fence Temporary in place by the linear foot from end posts, center to center, along the ground line.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
616.0600.S	Fence Temporary	LF

Payment is full compensation for furnishing all materials; erecting posts and fence; and for removing and disposing of fencing.

616-025 (20101008)

24. Locating No-Passing Zones, Item 648.0100.

For this project, the spotting sight distance in areas with a 55 mph posted speed limit is 0.21 miles (1108 feet).

648-005 (20060512)

25. Removing HMA Pavement Notched Wedge Longitudinal Joint Milling, Item SPV.0090.01.**A Description**

This special provision describes removing the notched wedge longitudinal joint prior to paving the adjacent lane in order to create a vertical longitudinal joint.

B (Vacant)**C Construction**

Remove the notched wedge longitudinal joint constructed according to standard spec 450.3.2.8 prior to paving the adjacent lane. Provide a uniform milled surface that is reasonably plane, free of excessively large scarification marks, and has the grade and transverse slope the plans show or the engineer directs. Do not damage the remaining pavement.

Use a self-propelled milling machine with depth, grade, and slope controls. Shroud the drum to prevent discharging loosened material onto adjacent work areas or live traffic lanes. Provide an engineer-approved dust control system.

Maintain one lane of the roadway for traffic at all times during working hours. Do not windrow or store material on the roadway. Clear the roadway of all materials and equipment during non-working hours.

D Measurement

The department will measure Removing HMA Pavement Notched Wedge Longitudinal Joint Milling by the linear foot, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0090.01	Removing HMA Pavement Notched Wedge Longitudinal Joint Milling	LF

Payment is full compensation for removing HMA pavement; and for hauling and disposal of materials.

26. Concrete Curb and Gutter 32-Inch Special, Item SPV.0090.02.**A Description**

This special provision describes constructing concrete curb and gutter 32-inch special.

B Materials

Furnish materials that are according to the pertinent requirements of standard spec 601.

C Construction

Conform to the requirements of standard spec 601.

D Measurement

The department will measure Concrete Curb and Gutter 32-Inch Special according to the requirements of standard spec 601.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0090.02	Concrete Curb and Gutter 32-Inch Special	LF

Payment is full compensation for concrete curb and gutter bid items under this section conforming to the requirements of standard spec 601.

27. Modify Drain Pipe, Item SPV.0105.01.**A Description**

This special provision describes the abandonment of an existing PVC drain pipe and the modification of the remaining portion of the pipe to allow for surface drainage at the specified location as provided herein and to meet requirements of the Town of Washington.

B Materials

The drain pipe, fittings, and connections shall be replaced with the same type of material and size that was removed or abandoned, unless otherwise directed by the engineer. All joints shall be watertight. All materials and joints shall conform to appropriate ASTM specifications.

C Construction

Abandon and construct drain pipe at the locations and to the dimensions shown on the plan and as directed by the engineer. Coordinate with property owner and give minimum of 72 hours notice to property owner prior to any construction or modification taking place to drain pipe. Contractor shall maintain drainage at all times during construction unless property owner is given a minimum of 72 hours notice prior to halting of drainage. Drainage may only be halted for a maximum of 24 hours unless approved by the property owner and engineer.

Cut off and seal existing drain pipe where shown on plans or specified by the engineer. Remove existing pipe where necessary and construct new pipe at location shown on plans. Be sure that pipe has positive drainage and can freely discharge to surface.

D Measurement

The department will measure Modify Drain Pipe as an individual unit, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0105.01	Modify Drain Pipe	LS

Payment is full compensation for Modify Drain Pipe, disposal of all waste materials including any pipe, fittings and excess materials.

28. Rectangular Rapid Flashing Beacon System, Item SPV.0105.02.

A Description

This work shall consist of furnishing and installing a solar powered rectangular rapid flashing beacon (RRFB) system consisting of multiple assemblies as described herein and as shown in the plans. Each assembly shall be solar powered and pedestrian activated.

The assemblies shall be wirelessly controlled and multiple units shall be synchronized.

Furnish proposed system to engineer for review.

B Materials

Furnish a complete RRFB system with multiple assemblies. Each assembly may consist of, but is not limited to, light indications, wireless communication equipment, solar power equipment, and electrical components (wiring, solid-state circuit boards, etc.). An assembly may include the following items:

Light Indications:

Each indication shall be a minimum size of approximately 5" wide x 2" high. Two indications shall be installed on an assembly facing each direction of approaching vehicular traffic. The two indications shall be aligned horizontally, with the longer dimension of the

indication horizontal, and a minimum space between the two indications of approximately 7” measured from inside edge of one indication to inside edge of second indication.

A single indication shall be installed on an assembly facing in the direction of approaching pedestrian traffic to serve as a confirmation for the pedestrian that the system has been activated.

The outside edges of the two indications, including any housing, shall not protrude beyond the outside edges of the integral signage of the assembly.

The light intensity of the indications shall meet the minimum specifications of the Society of Automotive Engineers (SAE) standard J595 (Directional Flashing Optical Warning Devices for Authorized Emergency, Maintenance, and Service Vehicles) dated January 2005. Contractor shall furnish a Certificate of Compliance for this standard. Specifically, the certificate should state that the indications: “Meet photometry of jurisdictional compliance standard(s) identical to: 2 J595 Class 2 Nov08 Yellow Peak Cd and 2 J595 Class 3 Nov08 Yellow Cds/Min.

Each indication shall be located between the bottom of the crossing warning sign and the top of the supplemental downward diagonal arrow plaque. All exposed hardware shall be anti-vandal.

Signs:

Signage shall include:

R-10-25

The assemblies must be constructed to allow the appropriate space for the installation of the signs in the field.

Control Circuit:

The control circuit shall have the capability of independently flashing up to two independent outputs. The LED light outputs and flash pattern shall be completely programmable.

The flashing output shall have 70 to 80 periods of flashing per minute with a 100 – millisecond duration on time. The output shall reach the output current as programmed for the duration of the pulse.

When two indications are mounted side-by-side, they shall have alternating but approximately equal periods of rapid pulsing light emissions and dark operation. Also, during each of the 70 to 80 flashing periods per minute, one of the indications shall emit two rapid pulses of light and the other indication shall emit three rapid pulses of light.

Flash rates with the frequencies of 5 to 30 flashes/second shall not be used to avoid inducing seizures.

When activated, the RRFB shall operate for a predetermined interval based on MUTCD procedures for timing of pedestrian clearance times for pedestrian signals. Coordinate with the department for this interval.

To prevent continuous activation of the RRFB and to allow vehicular queue clearance, the RRFB shall be programmed to prevent activation within 30 seconds of the termination of a previous activation.

The control circuit shall be installed in an IP67 NEMA rated enclosure. All circuit connectors shall conform to Ingress Protection, IP-67 rating, dust proof, and protected from temporary immersion in water up to 3 feet deep for 30 minutes. Connectors shall be Deutsch DTM series.

Battery:

Battery unit shall be a 4.8 volt 14000mAH Nickel Metal Hydride (NiMH). All batteries shall be sealed in a plastic film to provide moisture and corrosion resistance.

All batteries shall operate between the temperatures of -20°C and +60°C. All battery connectors shall conform to Ingress Protection, IP-67 rating, dust proof, and protected from temporary immersion in water up to 3 feet deep for 30 minutes. Connectors shall be Deutsch DTM series.

Wireless Radio:

Radio control shall operate on 900mhz frequency hopping spread spectrum network.

Radio shall integrate with communication of RRFB system control circuit to activate light indications from pushbutton input.

The Radio shall synchronize all of the remote light indications so they will turn on within 120msec of each other and remain synchronized through-out the duration of the flashing cycle.

Radio systems shall operate from 3.6 vdc to 15vdc.

Solar Panel:

The solar panel shall be up to 13.5"x15" in size and provide up to 13.5 watts peak total output. The panel shall be sized according to the weather and field conditions to maximize performance.

The solar panel shall be mounted to an aluminum plate and bracket at an angle of 45°- 60° to provide maximum output.

All fasteners used shall be anti-vandal.

All solar panel connectors shall conform to Ingress Protection, IP-67 rating, dust proof, and protected from temporary immersion in water up to 1 meter deep for 30 minutes. Connectors shall be Deutsch DTM series.

Pushbutton:

Furnish freeze-proof ADA compliant pedestrian push buttons made by an approved manufacturer to meet requirements of standard spec 658.

Aluminum Pole Standard and Pedestal Base:

The supporting structure (pole, breakaway transformer base, sign supports), shall be constructed of anodized aluminum and meet requirements of standard spec 657.

Concrete Base:

The concrete base and anchor bolts shall be supplied and installed to meet requirements of a Concrete Base Type 1 of standard spec 654.

Hardware:

Furnish all hardware, connections, etc. to make the RRFB system fully operational.

C Construction

The RRFB system will consist of multiple assemblies to be constructed by the contractor as shown on the plans. Make the RRFB system fully operational. Construct and assemble the system per manufacturer's instructions.

D Measurement

The department will measure Rectangular Rapid Flashing Beacon System [Location] as a single lump sum unit of work for each location, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0105.02	Rectangular Rapid Flashing Beacon System	LS

Payment is full compensation for furnishing and installing a fully operational RRFB system.

29. Wall Modular Block Gravity LRFD Special, Item SPV.0165.01.

A Description

This special provision describes designing, furnishing materials, and erecting a permanent earth retention system according to the lines, dimension, elevations and details as shown on the plans and provided in the contract. The design life of the wall and all wall components shall be 75 years.

B Materials

B.1 Proprietary Modular Block Gravity Wall Systems

The supplied wall system must be from the department's approved list of modular block gravity wall systems.

Proprietary wall systems may be used for this work, but must conform to the requirements of this specification and be pre-approved by the departments' Bureau of Structures, Structures Design Section. The department maintains a list of pre-approved systems of retaining walls. To be eligible for use on this project, a system must have been pre-approved and added to that list prior to the bid opening date. The name of the companies supplying pre-approved material shall be furnished within 25 days after the award of contract.

Applications for pre-approval may be submitted at any time. Applications must be prepared according to the requirements of chapter 14 of the department's LRFD Bridge Manual. Information and assistance with the pre-approval process can be obtained by contacting the Structures Design Section in Room 601 of the Hill Farms State Transportation Building in Madison or by calling (608) 266-8494.

B.2 Design Requirements

It is the responsibility of the contractor to supply a design and supporting documentation as required by this special provision for review by the department to show that the proposed wall design is in compliance with the design specifications. The following shall be submitted to the engineer for review and acceptance no later than 21 days before wall construction will begin.

The design/shop plans shall be prepared on reproducible sheets 11 inch x 17 inch, including borders. Each sheet shall have a title block in the lower right corner. The title block shall include the project identification number and structure number. Design calculations and notes shall be on 8½ inch x 11 inch sheets, and shall contain the project identification number, name or designation of the wall, date of preparation, initials of designer and checker, and page number at the top of the page. All plans and calculations shall be signed, sealed, and dated by a professional engineer licensed in the State of Wisconsin.

The wall shall be designed for the heights shown on the plans. The design shall be in compliance with the *AASHTO LRFD Design Specifications 5th Edition 2010* (AASHTO LRFD) with latest interim specifications for Mechanically Stabilized Earth Walls, WisDOT's current *Standard Specifications for Highway and Structure Construction* (Standard Specifications), Chapter 14 of the WisDOT LRFD Bridge Manual and standard design procedures as determined by the department. Loads, load combinations and load and resistance factors shall be as specified in AASHTO LRFD Section 11. The associated resistance factors shall be defined according to Table 11.5.6-1 in AASHTO LRFD.

The design must include analyses at critical sections that clearly show the Capacity Demand Ratio (CDR) for sliding, eccentricity, and bearing check. Internal stability shall also be considered at each block level. The design shall include an overburden surcharge of 100 psf according to Chapter 14 of the WisDOT LRFD Bridge Manual or as shown on the plans.

The width of the modular block from front face to back face of the wall shall be included in the design computations and shown on the wall shop drawings. The minimum embedment to the bottom of the modular block shall be 1 foot 6 inches, or as specified in the plan.

Submit the following to the engineer for review: complete design calculations, explanatory notes, supporting materials, specifications, and detailed plans and shop drawings for the proposed wall system. Sample analyses and hand output shall be submitted to verify the output by the software. The design calculations and notes shall clearly indicate the Capacity to Demand Ratios (CDR) for all internal stabilities as defined in AASHTO LRFD.

The wall submittal package shall be submitted electronically to the engineer and Structures Design Section. Submit all required information no later than 30 days prior to beginning construction of the wall. The detailed plans and shop drawings shall include all details, dimensions, quantities and cross-sections necessary to construct the walls.

B.3 Wall System Components

Materials furnished under this contract shall conform to the requirements of this specification. All certifications related to material and components of the wall systems specified in this subsection shall be submitted to the engineer.

B.3.1 Backfill

Wall Backfill, Type A, shall comply with the requirements for coarse aggregate No. 1 as given in standard spec 501.2.5.4. All backfill placed within a zone from the base of the leveling pad to the top of the final layer of wall facing units and within 1 foot behind the back face of the wall shall be Wall Backfill, Type A. This includes all material used to fill openings in the wall facing units.

A layer of Geotextile Fabric Type “DF” (Schedule B) shall be placed vertically between the retained soil and the Type A backfill. The geotextile fabric shall extend from the top of the leveling pad to 6 inches below the surface of the retained soil. The geotextile shall then wrap across the top of the Type A backfill to the back of the block wall facing.

B.3.2 Wall Facing

Provide wall facing units that consist of precast modular concrete blocks. All units shall incorporate a mechanism or devices that will develop a mechanical connection between vertical block layers. Units that are cracked, chipped or have other imperfections according to ASTM C1372 or excessive efflorescence shall not be used within the wall. A single block type and style shall be used throughout each wall. The color and surface texture of the block shall be as given on the plan, or chosen by the engineer.

The top course of facing units shall be a solid precast concrete unit designed to be compatible with the remainder of the wall unless a cast-in-place concrete cap is shown on the plans. The finishing course shall be bonded to the underlying facing units with a durable, high strength, flexible adhesive compound compatible with the block material. A formed cast-in-place concrete cap may also be used to finish the wall. A cap of this type shall be designed to have color and an appearance that complements the remainder of the wall. Concrete for all

cast-in-place caps shall be Grade A and shall conform to the requirements of standard spec 501. Reinforcement steel shall have a yield of stress of 60 ksi. The vertical dimension of the cap shall not be less than 3½ inches. Expansion joints shall be placed in the cap to correspond with each 24-inch change in vertical wall height and at maximum spacing of 10 feet.

Block dimensions may vary no more than ±1/8 inch from the standard values published by the manufacturer, according to ASTM C1372. Blocks must have a minimum depth (front face to back face) of 8 inches. The minimum front face thickness of blocks shall be 4 inches measured perpendicular from the front face to inside voids greater than 4 square inches. The minimum allowed thickness of any other portion of the block is 1.75 inches. The front face of the blocks shall conform to plan requirements for color, texture, or patterns.

Cementitious materials and aggregates for modular blocks shall conform to the requirements of ASTM C1372 section 4.1 and 4.2. Modular blocks shall meet the following requirements:

Test	Method	Requirement
Compressive Strength (psi)	ASTM C140	5000 min.
Water Absorption (%)	ASTM C140	6 max.
Freeze-Thaw Loss (%) 40 cycles, 5 of 5 samples 50 cycles, 4 of 5 samples	ASTM C1262 ⁽¹⁾	1.0 max. ⁽²⁾ 1.5 max. ⁽²⁾

⁽¹⁾ Test shall be run using a 3% saline solution.

⁽²⁾ Test results that meet either of the listed requirements for Freeze-Thaw Loss are acceptable.

All blocks shall be certified as to strength, absorption, and freeze-thaw requirements unless, due to contract changes after letting, certified blocks are not available when required. At the time of delivery of the certified blocks, furnish the engineer a certified test report from a department-approved independent testing laboratory for each lot of modular blocks. The certified test report shall clearly identify the firm conducting the sampling and testing, the type of block, the date sampled, name of the person conducting the sampling, the represented lot, the number of blocks in the lot, and the specific test results for each of the stated requirements of this specification. A lot shall not exceed 5000 blocks or fraction thereof produced in day. The certified test results will represent all blocks within the lot. Each pallet of blocks delivered shall bear lot identification information. Block lots that do not meet the requirements of this specification or blocks without supporting certified test reports will be rejected and shall be removed from the project at the contractor's expense.

A department-approved independent testing laboratory shall control and conduct all modular block sampling and testing for certification. Prior to sampling, the manufacturer's representative shall identify all pallets of modular blocks contained in each lot. All pallets of blocks within the lot shall be numbered and marked to facilitate random sample selection.

The representative of the independent testing laboratory shall identify five pallets of blocks by random numbers and shall then select one block from each of these pallets. Solid blocks used as a finishing or top course shall not be selected. The selected blocks shall remain under the control of the person who conducted the sampling until shipped or delivered to the testing laboratory. All pallets of blocks within a lot shall be strapped or wrapped to secure the contents and tagged or marked for identification. The engineer will reject any pallet of blocks delivered to the project without intact security measures. The contractor shall remove all rejected blocks from the project at no expense to the department.

The department may conduct testing of certified or non-certified modular blocks lots delivered to the project. The department will not conduct freeze-thaw testing on blocks less than 45 days old. If a random sample of five blocks of any lot tested by the department fails to meet any of the requirements of this specification (nonconforming), the contractor shall remove from the project site all blocks from the failed lot that have not been installed in the finished work at no cost to the department, unless the engineer allows otherwise. Nonconforming blocks installed in the finished work will be considered approved by the department as stated in standard spec 106.5(2) and any adjustment to the contract price will not exceed the price of the blocks charged by the supplier.

B.3.3 Leveling Pad

The leveling pad shall step to follow the general slope of the ground line. The leveling pad steps shall keep the bottom of the wall below the minimum embedment. Additional embedment that is greater than the minimum embedment will not be measured for payment. The bottom row of blocks shall be horizontal and 100% of the block surface shall bear on the leveling pad.

Provide a wall leveling pad that consists of poured concrete masonry, Grade A, A-FA, A-S, A-T, A-IS, or A-IP concrete conforming to standard spec 501 as modified in standard spec 716. Provide QMP for leveling pad concrete as specified in Standard Specification.

The concrete leveling pad shall be 6 inches deep. The leveling pad shall be as wide as the proposed blocks plus six inches, with 6 inches of the leveling pad extending beyond the front face of the blocks. A concrete leveling pad shall be provided in following scenarios:

- a. When the wall height measured from the top of the leveling pad to the top of the wall exceeds 5 feet at any point along the entire wall length.
- b. A structure number has been assigned (such as R-XX-XXX), regardless of wall height.

Additionally, for walls that are less than or equal to 5 feet in height and do not have a wall number assigned to them, a compacted 1 foot(minimum) deep leveling pad made from base aggregate dense 1¼-inch in conformance with standard spec 305, may be used. The aggregate leveling pad shall be as wide as the blocks plus 12 inches, and the modular blocks shall be centered on the leveling pad.

C Construction

C.1 General

Construct the modular block gravity wall according to the manufacturer's instructions, at the locations and to the dimensions shown on the plan and as directed by the engineer. At the end of each working day, provide good temporary drainage such that the backfill shall not become contaminated with run-off soil or water if it should rain. Do not stockpile or store materials or large equipment within 10 feet of the back face of the wall.

Place materials in the areas as indicated on the plans and as detailed in this specification. Backfill lifts shall be no more than 8-inches in depth. Backfilling shall closely follow erection of each course of wall facing units.

Compact each layer of wall backfill Type A with at least three passes of lightweight manually operated compaction equipment acceptable to the engineer.

Conduct backfilling operations in such a manner as to prevent damage or misalignment of the wall facing units. At no expense to the department, correct any such damage or misalignment as directed by the engineer.

Do not operate tracked or wheeled equipment within 3 feet of the back face of the blocks. The engineer may order the removal of any large or heavy equipment that may cause damage or misalignment of the wall facing units.

After construction of the wall, restore the surrounding area located above and below all precast block retaining wall sites to its original condition and to the finished details on the plans.

C.2 Geotechnical Information

Geotechnical data to be used in the design of the wall is given on the wall plan. After completion of excavation, notify the department and allow two days for the Regional Soils Engineer to review the foundation.

D Measurement

The department will measure Wall Modular Block Gravity LRFD Special in area by the square foot, acceptably completed, measured as the vertical area within the pay limits the contract plans show. No other measurement of quantities shall be made in the field unless the engineer directs in writing a change to the limits indicated on the contract plans.

E Payment

The department will pay for plan quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0165.01	Wall Modular Block Gravity LRFD Special	SF

Payment is full compensation for supplying a design and shop drawings; preparing the site, including all necessary excavation and disposal of surplus materials; supplying all necessary wall components to produce a functional system including cap and copings; constructing the retaining system and wall drainage system; providing backfill, backfilling, and compacting the backfill; and furnishing and installing geotextile fabric. Parapets, railings, and other items above the wall cap or coping will be paid for separately.

Any required topsoil, fertilizer, seeding or sodding and mulch will be paid for at the contract unit price of topsoil, fertilizer, seeding or sodding and mulch, respectively.

30. **Geogrid Reinforcement, Item SPV.0180.01.**

A Description

This special provision describes furnishing and installing geogrids for subgrade stabilization, base reinforcement, or pavement structure applications according to the plans, standard spec 645, and as hereinafter provided.

B Materials

Provide geogrid that consists of either single or joined multiple layers of a uniform rectangular grid of bonded, formed, or fused polymer tensile strands crossing with a nominal right angle orientation. The polymer shall consist of polyester, polypropylene, polyamide, or polyethylene. The grid shall maintain dimensional stability during handling, placing, and installation. The geogrid shall be insect, rodent, mildew, and rot resistant. Minimum geogrid width shall be 6.0 feet.

Provide geogrid that complies with the following physical properties:

Test	Method	Value ⁽¹⁾
Tensile Strength at 5% Strain, Both Principal Directions (lb/ft)	ASTM D 4595 ⁽²⁾	450 min.
Flexural Rigidity Both Principal Directions (mg-cm)	ASTM D 1388 ⁽³⁾	150,000 min.
Aperture Area (in ²)	Inside Measurement ⁽⁴⁾	5.0 max.
Aperture Dimension (in)	Inside Measurement ⁽⁴⁾	0.5 min.

⁽¹⁾ All numerical values represent minimum/maximum average roll values, i.e. the average minimum test results on any roll in a lot should meet or exceed the minimum specified value.

⁽²⁾ The tensile strength (T) of a joined multi-layered geogrid shall be computed using the following equation:

$$T = n(f)t$$

where

n = the number of individual layers in the joined multi-layered geogrid,

t = the tensile strength of a single layer of geogrid as determined using testing method ASTM D4595, and

f = reduction factor based on the number of layers comprising the multi-layered system and determined by the equation $f = 1.00 - [0.04(n - 1)]$.

⁽³⁾ Values shall be determined by Option “A” (Cantilever Test) of testing method ASTM D1388 using test specimens that are 36 inches ± 0.04 inch long. Test specimen widths for differing geogrids shall be variable and equal to 1 element plus $\frac{1}{2}$ the aperture width on both sides of that element. An element is defined as the minimum number of parallel strands that form a distinguishable repeating pattern.

⁽⁴⁾ Aperture Area and Aperture Dimension for joined multi-layer geogrids shall be determined based on measurement of a single layer of the geogrid.

Protect the geogrid from ultraviolet radiation and from damage due to shipping and handling. Keep the geogrid dry until it is installed. The geogrid rolls shall be clearly marked to identify the material contained.

Deliver a sample of the geogrid material to the engineer at least 10 days prior to its incorporation into the work. At the same time, furnish a manufacturer’s Certified Report of Test or Analysis that verifies that the geogrid delivered for use on the work meets the above requirements. Samples of geogrid for test purposes will be obtained from the job site for each 10,000 square yards or portions thereof used on the contract.

C Construction

Prior to placement of the geogrid, bring the indicated placement surface to the required lines, grades, and dimensions as shown on the plans. Smooth and shape the surface to eliminate any rocks, clods, roots, or other items that may cause damage to the geogrid during placement or covering.

Place the geogrid on the prepared surface at the locations and to the limits as shown on the plans. After placement, pull the geogrid taut and secure it using pins, clips, staples, or other devices to prevent movement or displacement. Place parallel strips of geogrid with a minimum overlap of 6 inches. Lap butt joints between roll ends a minimum of 12 inches. Fasten all lapped sections together by using ties, straps, clips, or other devices to develop a secure joint that meets the approval of the engineer. No vehicles or construction equipment shall be permitted to operate directly on the geogrid.

Cover small rips, tears, or defects in the geogrid with an additional section of geogrid; secure the additional geogrid in place so that it overlaps the damaged area by at least 3 feet in all directions. Remove and replace geogrid sections with large rips, tears, defects, or other damage at the direction of the engineer. All costs to repair or replace damaged or defective geogrid shall be the responsibility of the contractor.

After placement, cover the geogrid to the indicated depth with the type of material required on the plans or in the special provisions. Placing, spreading, and compacting of this material shall comply with the applicable sections of the standard specifications or special provisions except that the initial lift of material placed on the geogrid must be at least 4 inches. Place, spread, and compact the required backfill material so that the geogrid is not displaced or damaged. The engineer may require changes in equipment and/or operations to prevent such damage or displacement.

D Measurement

The department will measure Geogrid Reinforcement by the square yard of surface area upon which the geogrid has been placed, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0180.01	Geogrid Reinforcement	SY

Payment is full compensation for furnishing, transporting, and installing the geogrid; furnishing and installing all devices and materials necessary to join or secure the geogrid in place.

31. Management of Contaminated Soil, Item SPV.0195.01.

A Description

This work shall conform with the requirements of standard spec 205 to pertinent parts of the Wisconsin Administrative Code, Chapters NR 700-736, Environmental Investigation and Remediation of Environmental Contamination; Wisconsin Administrative Code, Chapters NR 500-538, Solid Waste; and as shown on the plans and as supplemented herein.

This work consists of excavating, segregating, temporarily stockpiling, loading, hauling, and treating and disposing petroleum-contaminated soil at a Department of Natural Resources-licensed treatment disposal facility. The nearest approved treatment and disposal facility is:

La Crosse County Landfill
6500 State Road 165
La Crosse, WI 54601
(608) 875-9572

B (Vacant)

C Construction

Add the following to standard spec 205.3:

The environmental consultant will periodically examine excavated soil during excavations in the areas of known petroleum contamination in the existing soil within the construction limits on STH 33 from approximately Station 934+35 to 934+75 from left 20 feet to construction limits left and on STH 162 from approximately Station 934+85 to 935+35 from right 15 feet to construction limits right. Control construction operations at these locations to ensure that excavations do not extend beyond the minimum required to construct highway improvements unless expressly directed to do so by the engineer.

When material is encountered outside the above-identified limits of known contamination that appears to have been impacted with petroleum or chemical products, or other obvious potentially contaminated materials are encountered or material exhibits characteristics of industrial-type wastes, such as fly ash, foundry sand, and cinders, or if underground storage tanks are encountered, suspend excavation in that area and notify the engineer.

Assist the environmental consultant in collecting soil samples using excavation equipment. The environmental consultant will collect soil samples from the excavations. The sampling frequency will be a maximum of one sample for every 20 cubic yards excavated.

It is anticipated that the majority of the contaminated soil excavated from the areas of known contamination will have low-level impacts and could be designated for reuse as fill on the project. However based on planned cuts, there may not be space to reuse the impacted soil. Excess low-level impacted soil that cannot be reused as fill, low-level impacted soil that is geotechnically unsuitable for reuses as backfill, as determined by the engineer, and soil identified by the environmental consultant as having significant contamination will require disposal at an WDNR-licensed treatment and disposal facility. The environmental consultant will field-screen material during excavations in the areas of known contamination and in other potentially contaminated area encountered during excavations. On the basis of the results of such field-screening, the material will be designated for disposal as:

- Low-level contaminated soil for reuse as backfill in the excavation from which it came;
- Contaminated material for disposal at the approved treatment and disposal facility, or;
- Potentially contaminated for temporary stockpiling and additional characterization prior to disposal.

Some material may require additional characterization prior to disposal. Provide for the temporary stockpiling of up to 50 cubic yards of contaminated soil on-site that require additional characterization. Construct and maintain a temporary stockpile of the material according to NR 718.05(3), including, but not limited to, placing the contaminated soil/fill material on an impervious surface and covering the stockpile with material to prevent the

infiltration of precipitation. The department's environmental consultant will collect representative samples of the stockpiles material, laboratory-analyze the samples, and advise the contractor, within 10 business days of the construction of the stockpile, of disposal requirements. The stockpiled material shall be disposed either at the approved treatment and disposal facility soil/fill material that required additional characterization, the contractor has the option of suspending excavation in those areas where the material is encountered until such time as characterization is completed.

Verify that the vehicles used to transport contaminated material are licensed for such activity according to applicable state and federal regulations.

The environmental consultant will be responsible for obtaining the necessary disposal facility approvals and WDNR approvals for treatment and disposal. Do not transport contaminated soil or regulated solid waste off-site without obtaining the approval of the engineer and notifying the disposal facility.

The department will be the generator of all contaminated soil and regulated solid waste from this construction project. The department or assigned designee will execute all manifests require for the transportation and disposal of such material from the project.

D Measurement

The department will measure Management of Contaminated Soil by the ton of soil accepted by the treatment and disposal facility and as documented by load tickets. Load tickets must be delivered to the engineer within 10 business days of the date on which the soil was accepted by the treatment and disposal facility.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0195.01	Management of Contaminated Soil	Ton

This payment for the Management of Contaminated Soil is full payment for excavating, segregating, loading, transporting, temporarily stockpiling, and treating/disposing contaminated material.

ADDITIONAL SPECIAL PROVISION 4

Payment to First-Tier Subcontractors

Within 10 calendar days of receiving a progress payment for work completed by a subcontractor, pay the subcontractor for that work. The prime contractor may withhold payment to a subcontractor if, within 10 calendar days of receipt of that progress payment, the prime contractor provides written notification to the subcontractor and the department documenting "just cause" for withholding payment.

The prime contractor may also withhold routine retainage from payments due subcontractors.

Payment to Lower-Tier Subcontractors

Ensure that subcontracting agreements at all tiers provide prompt payment rights to lower-tier subcontractors that parallel those granted first-tier subcontractors in this provision.

Release of Routine Retainage

After granting substantial completion the department may reduce the routine retainage withheld from the prime contractor to 75 percent of the original total amount retained.

When the Department sends the semi-final estimate the department may reduce the routine retainage withheld from the prime contractor to 10 percent of the original total amount retained.

Within 30 calendar days of receiving the semi-final estimate from the department, submit written certification that subcontractors at all tiers are paid in full for acceptably completed work and that no routine retainage is being withheld. The department will pay the prime contractor in full and reduce the routine retainage withheld from the prime contractor to zero when the department approves the final estimate.

This special provision does not limit the right of the department, prime contractor, or subcontractors at any tier to withhold payment for work not acceptably completed or work subject to an unresolved contract dispute.

ADDITIONAL SPECIAL PROVISIONS 5**Fuel Cost Adjustment****A Description**

Fuel Cost Adjustments will be applied to partial and final payments for work items categorized in Section B as a payment to the contractor or a credit to the department. ASP-5 shall not apply to any force account work.

B Categories of Work Items

The following items and Fuel Usage Factors shall be used to determine Fuel Cost Adjustments:

(1) Earthwork.		Unit	Gal. Fuel Per Unit
205.0100	Excavation Common	CY	0.23
205.0200	Excavation Rock	CY	0.39
205.0400	Excavation Marsh	CY	0.29
208.0100	Borrow	CY	0.23
208.1100	Select Borrow	CY	0.23
209.0100	Backfill Granular	CY	0.23
350.0102	Subbase	CY	0.28
350.0104	Subbase	Ton	0.14
350.0115	Subbase 6-Inch	SY	0.05
350.0120	Subbase 7-Inch	SY	0.05
350.0125	Subbase 8-Inch	SY	0.06
350.0130	Subbase 9-Inch	SY	0.07
350.0135	Subbase 10-Inch	SY	0.08
350.0140	Subbase 11-Inch	SY	0.09
350.0145	Subbase 12-Inch	SY	0.09

C Fuel Index

A Current Fuel Index (CFI) in dollars per gallon will be established by the Department of Transportation for each month. The CFI will be the price of No. 2 fuel oil, as reported in U.S. Oil Week, using the first issue dated that month. The CFI will be the average of prices quoted for Green Bay, Madison, Milwaukee and Minneapolis.

The base Fuel Index (BFI) for this contract is \$1.90 per gallon.

D Computing the Fuel Cost Adjustment

The engineer will compute the ratio CFI/BFI each month. If the ratio falls between 0.85 and 1.15, inclusive, no fuel adjustment will be made for that month. If the ratio is less than 0.85 a credit to the department will be computed. If the ratio is greater than 1.15 additional payment to the contractor will be computed. Credit or additional payment will be computed as follows:

- (1) The engineer will estimate the quantity of work done in that month under each of the contract items categorized in Section B.
- (2) The engineer will compute the gallons of fuel used in that month for each of the contract items categorized in Section B by applying the unit fuel usage factors shown in Section B.
- (3) The engineer will summarize the total gallons (Q) of fuel used in that month for the items categorized in Section B.
- (4) The engineer will determine the Fuel Cost Adjustment credit or payment from the following formula:

$$FA = \left(\frac{CFI}{BFI} - 1 \right) \times Q \times BFI$$

(plus is payment to contractor; minus is credit to the department)

Where	FA	=	Fuel Cost Adjustment (plus or minus)
	CFI	=	Current Fuel Index
	BFI	=	Base Fuel Index
	Q	=	Monthly total gallons of fuel

E Payment

A Fuel Cost Adjustment credit to the department will be deducted as a dollar amount each month from any sums due to the contractor. A Fuel Cost Adjustment payment to the contractor will be made as a dollar amount each month.

Upon completion of the work under the contract, any difference between the estimated quantities and the final quantities will be determined. An average CFI, calculated by averaging the CFI for all months that fuel cost adjustment was applied, will be applied to the quantity differences. The average CFI shall be applied in accordance with the procedure set forth in Section D.

ADDITIONAL SPECIAL PROVISION 6

ASP 6 - Modifications to the standard specifications

Make the following revisions to the standard specifications:

550.5.2 Piling

Add the following as paragraph three effective with the December 2015 letting:

- (3) The department will not entertain a change order request for a differing site condition under 104.2.2.2 or for a quantity change under 104.2.2.4.3 for the Piling bid items. Instead the department will adjust pay under the Piling Quantity Variation administrative item if the total driven length of each size is less than 85 percent of, or more than 115 percent of the contract quantity as follows:
- | Percent of Contract Length Driven | Pay Adjustment |
|-----------------------------------|--|
| < 85 | (85% contract length - driven length) x 20% unit price |
| > 115 | (driven length - 115% contract length) x 5% unit price |
-

643.2.1 General

Replace paragraph two with the following effective with the December 2015 letting:

- (2) Use reflective sheeting from the department's approved products list on barricades, drums, and flexible tubular marker posts.

Errata

Make the following corrections to the standard specifications:

641.2.9 Overhead Sign Supports

Correct errata adding back accidentally deleted paragraphs one through three.

- (1) Provide commercially fabricated overhead sign supports conforming to AASHTO design and fabrication standards for structural supports for highway signs, luminaires, and traffic signals. Use a design life of 50 years with a wind importance factor of 1.00. Design to withstand a 3 second gust wind speed of 90 mph. Do not use the methods of appendix C of those AASHTO standards.
- (2) Design structures, listed as applicable structure types in the AASHTO standards, to the fatigue category criteria as follows:
 1. Structures carrying variable message signs:
 - Category I criteria for structures over all roadway types.
 2. Structures carrying type II or III signs:
 - Category I criteria for structures used over highways and free flow ramps.
 - Category II criteria for structures with arms greater than 30 feet used over local roads and city streets.
 - Category III criteria for structures with arms 30 feet or less used over local roads and city streets.
- (3) Use the posted speed limit of the roadway beneath the structure for truck-induced gusts.
- (4) Submit shop drawings identified by structure number, design computations, and material specifications, to the engineer before erecting sign supports. Provide tightening procedures for mast arm or luminaire arm to pole shaft connections on the shop drawings. Have a professional engineer registered in the state of Wisconsin sign, seal, and date the shop drawings and certify that the design conforms to AASHTO standards and the contract.
- (5) Provide steel pole shafts and mast arms zinc coated according to ASTM A123. Provide tapered pole and arm shafts with a minimum taper of 0.14 inch per foot for single-member vertical and single-member horizontal structure components. Provide bolts and other hardware conforming to 641.2.2.

ADDITIONAL SPECIAL PROVISION 7

- A. Reporting 1st Tier and DBE Payments During Construction
1. Comply with reporting requirements specified in the department's Civil Rights Compliance, Contractor's User Manual, Sublets and Payments.
 2. Report payments to all DBE firms within 10 calendar days of receipt of a progress payment by the department or a contractor for work performed, materials furnished, or materials stockpiled by a DBE firm. Report the payment as specified in A(1) for all work satisfactorily performed and for all materials furnished or stockpiled.
 3. Report payments to all first tier subcontractor relationships within 10 calendar days of receipt of a progress payment by the department for work performed. Report the payment as specified in A(1) for all work satisfactorily performed.
 4. All tiers shall report payments as necessary to comply with the DBE payment requirement as specified in A(2).
 5. Require all first tier relationships, DBE firms and all other tier relationships necessary to comply with the DBE payment requirement in receipt of a progress payment by contractor to acknowledge receipt of payment as specified in A(1), (2), (3) and (4).
 6. All agreements made by a contractor shall include the provisions in A(1), (2), (3), (4) and (5), and shall be binding on all first tier subcontractor relationships and all contractors and subcontractors utilizing DBE firms on the project.
- B. Costs for conforming to this special provision are incidental to the contract.

ADDITIONAL SPECIAL PROVISION 9

Electronic Certified Payroll Submittal

(1) Use the department's Civil Rights Compliance System (CRCS) to submit certified payrolls electronically. Details are available online through the department's highway construction contractor information (HCCI) site on the Labor, Wages, and EEO Information page at:

<http://wisconsindot.gov/Pages/doing-bus/civil-rights/labornwage/default.aspx>

(2) Ensure that all tiers of subcontractors, as well as all trucking firms, submit their weekly certified payrolls electronically through CRCS. These payrolls are due within seven calendar days following the close of the payroll period. Every firm providing physical labor towards completing the project is a subcontractor under this special provision.

(3) Upon receipt of contract execution, promptly make all affected firms aware of the requirements under this special provision and arrange for them to receive CRCS training as they are about to begin payrolls. The department will provide training either in a classroom setting at one of our regional offices or by telephone. Contact Tess Mulrooney at 608-267-4489 to schedule the training.

(4) The department will reject all paper submittals of forms DT-1816 and DT-1929 for information required under this special provision. All costs for conforming to this special provision are incidental to the contract.

(5) Firms wishing to export payroll data from their computer system into CRCS should have their payroll coordinator send several sample electronic files to Tess two months before a payroll needs to be submitted. Not every contractor's payroll system is capable of producing export files. For details, see pages 17-22 of the CRCS System Background Information manual available online on the Labor, Wages, and EEO Information page at:

<http://wisconsindot.gov/Documents/doing-bus/civil-rights/labornwage/crcs-payroll-manual.pdf>

Effective August 2015 letting

BUY AMERICA PROVISION

All steel and iron materials permanently incorporated in this project shall be domestic products and all manufacturing and coating processes for these materials from smelting forward in the manufacturing process must have occurred within the United States. Coating includes epoxy coating, galvanizing, painting and any other coating that protects or enhances the value of a material subject to the requirements of Buy America. The exemption of this requirement is the minimal use of foreign materials if the total cost of such material permanently incorporated in the product does not exceed one-tenth of one percent (1/10 of 1%) of the total contract cost or \$2,500.00, whichever is greater. For purposes of this paragraph, the cost is that shown to be the value of the subject products as they are delivered to the project. The contractor shall take actions and provide documentation conforming to CMM 2-28.5 to ensure compliance with this "Buy America" provision.

<http://wisconsindot.gov/rdwy/cmm/cm-02-28.pdf>

Upon completion of the project certify to the engineer, in writing using department form WS4567, that all steel, iron, and coating processes for steel or iron incorporated into the contract work conform to these "Buy America" provisions. Attach a list of exemptions and their associated costs to the certification form. Department form WS4567 is available at:

<http://wisconsindot.gov/rdwy/worksheets/ws4567.doc>

Effective with September 2004 Letting

**WISCONSIN DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS AND TRANSPORTATION FACILITIES**

SUPPLEMENTAL REQUIRED CONTRACT PROVISIONS

- I. Wage Rates, Hours of labor and payment of Wages
- II. Payroll Requirements
- III. Postings at the Site of the Work
- IV. Affidavits
- V. Wage Rate Redistribution
- VI. Additional Classifications

I. WAGE RATES, HOURS OF LABOR AND PAYMENT OF WAGES

The schedule of "Minimum Wage Rates" attached hereto and made a part hereof furnishes the prevailing wage rates that have been determined pursuant to Section 103.50 of the Wisconsin Statutes. These wage rates are the minimum required to be paid to the various laborers, workers, mechanics and truck drivers employed by contractors and subcontractors on the construction work embraced by the contract and subject to prevailing hours and wages under Section 103.50, Stats. If necessary to employ laborers, workers, mechanics or truck drivers whose classification is not listed on the schedule, they shall be paid at rates conformable to those listed for similar classifications. Apprentices shall be paid at rates not less than those prescribed in their state indenture contracts.

While the wage rates shown are the minimum rates required by the contract to be paid during its life, this is not a representation that labor can be obtained at these rates. It is the responsibility of bidders to inform themselves as to the local labor conditions and prospective changes or adjustments of wage rates. No increase in the contract price shall be allowed or authorized on account of the payment of wage rates in excess of those listed herein.

Pursuant to Section 103.50 of the Wisconsin Statutes, the prevailing hours of labor have been determined to be up to 10 hours per day and 40 hours per calendar week Monday through Friday. If any laborer, worker, mechanic or truck driver is permitted or required to work more than the prevailing number of hours per day or per calendar week on this contract, they shall be paid for all hours in excess of the prevailing hours at a rate of at least one and one-half (1 1/2) times their hourly rate of pay. All work on Saturday, Sunday and the following holidays is to be paid at time and a half: (1) January 1, (2) the last Monday in May, (3) July 4, (4) the first Monday in September, (5) the fourth Thursday in November, (6) December 25, (7) the day before if January 1, July 4 or December 25 falls on a Saturday and (8) the day following if January 1, July 4 or December 25 falls on a Sunday.

All laborers, workers, mechanics and truck drivers shall be paid unconditionally not less often than once a week. Persons who own and operate their own trucks must receive the prevailing truck driver rate for the applicable type of truck (i.e. 2 axle, 3 or more axle, articulated, eculid or dumptor) he or she operates, plus an agreed upon amount for the use of his or her truck. Every owner-operator MUST be paid separately for their driving and for the use of their truck.

For those projects subject to the requirements of the Davis-Bacon Act, the Secretary of Labor will also have determined "Minimum Wage Rates" for work to be performed under the contract. These rates are, for all or most of the labor, worker, mechanic or truck driver classifications, identical to those established under Section 103.50 of the Wisconsin Statutes. In the event the rates are not identical, the higher of the two rates will govern.

II. PAYROLL REQUIREMENTS

All contractors and subcontractors must submit weekly Certified Payrolls and Compliance Statement verifying that all laborers, workers, mechanics and truck drivers working on the project have been paid the prevailing wage rates for all work performed under the contract required by Section 103.50 of the Wisconsin Statutes.

III. POSTINGS AT THE SITE OF THE WORK

In addition to the required postings furnished by the Department, the contractor shall post the following in at least one conspicuous place at the site of work:

- a. "NOTICE TO EMPLOYEES," which provides information required to be posted by the provisions of Section 103.50 of the Wisconsin Statutes.
- b. A copy of the State of Wisconsin Minimum Wages Rates. (Four pages.)
- c. A copy of the contractor's Equal Employment Opportunity Policy.
- d. On any project involving federal aid, in addition to the furnished postings, the contractor shall post a copy of the "Davis-Bacon Act, Minimum Wage Rates". (Three pages.)

IV. WAGE RATE REDISTRIBUTION

The amount specified as the hourly basic rate of pay and the amount(s) specified as the fringe benefit contribution(s), for all classes of laborers, workers, mechanics or truck drivers may be redistributed, when necessary, to conform to those specified in any applicable collective bargaining agreement, provided that both parties to such agreement

request and receive the approval for any such redistribution from both the Department of Transportation and the Department of Workforce Development prior to the implementation of such redistribution.

V. ADDITIONAL CLASSIFICATIONS

Any unlisted laborer or mechanic classification that is needed to perform work on this project, and is not included within the scope of any of the classifications listed in the application prevailing wage rate determination, may be added after award only if all of the following criteria have been met:

1. The affected employer(s) must make a written request to WisDOT Central Office to utilize the unlisted classification on this project.
2. The request must indicate the scope of the work to be performed by the unlisted classification and must indicate the proposed wage/fringe benefit package that the unlisted classification is to receive.
3. The work to be performed by the unlisted classification must not be performed by a classification that is included in the applicable prevailing wage rate determination.
4. The unlisted classification must be commonly employed in the area where the project is located.
5. The proposed wage/fringe benefit package must bear a reasonable relationship to those set forth in the applicable prevailing wage rate determination.
6. The request should be made prior to the actual performance of the work by the unlisted classification.
7. DWD must approve the use of the unlisted classification and the proposed wage/fringe benefit package. USDOL also must approve the use of the unlisted classification and the proposed wage/fringe benefit package on federal aid projects.
8. WisDOT and DWD may amend the proposed wage/fringe benefit package, as deemed necessary, and may set forth specific employment ratios and scope of work requirements in the approval document.

The approved wage/fringe benefit package shall be paid to all laborers, workers, mechanics or truck drivers performing work within the scope of that performed by the unlisted classification, from the first day on which such work is performed. In the event that work is performed by the unlisted classification prior to approval, the wage/fringe benefit package to be paid for such work must be in conformance with the wage/fringe

benefit package approved for such work. Under this arrangement a retroactive adjustment in wages and/or fringe benefits may be required to be made to the affected laborers, workers, mechanics or truck drivers by the affected employer(s).

**ANNUAL PREVAILING WAGE RATE DETERMINATION
FOR ALL STATE HIGHWAY PROJECTS
LA CROSSE COUNTY**

Compiled by the State of Wisconsin - Department of Workforce Development
for the Department of Transportation
Pursuant to s. 103.50, Stats.
Issued on May 1, 2015

CLASSIFICATION: Contractors are required to call the Department of Workforce Development if there are any questions regarding the proper trade or classification to be used for any worker on a public works project.

OVERTIME: Time and one-half must be paid for all hours worked over 10 hours per day and 40 hours per calendar week and for all hours worked on Saturday, Sunday and the following six (6) holidays: January 1; the last Monday in May; July 4; the 1st Monday in September; the 4th Thursday in November; December 25; the day before if January 1, July 4 or December 25 falls on a Saturday; the day following if January 1, July 4 or December 25 falls on a Sunday.

FUTURE INCREASE: If indicated for a specific trade or occupation, the full amount of such increase MUST be added to the "TOTAL" indicated for such trade or occupation on the date(s) such increase(s) becomes effective.

PREMIUM PAY: If indicated for a specific trade or occupation, the full amount of such pay MUST be added to the "HOURLY BASIC RATE OF PAY" indicated for such trade or occupation, whenever such pay is applicable.

SUBJOURNEY: Wage rates may be available for some of the classifications indicated below. Any employer that desires to use any subjourney classification on a project MUST request the applicable wage rate from the Department of Workforce Development PRIOR to the date such classification is used on such project. Form ERD-10880 is available for this purpose and can be obtained by writing to the Department of Workforce Development, Equal Rights Division, P.O. Box 8928, Madison, WI 53708.

<u>TRADE OR OCCUPATION</u>	<u>HOURLY BASIC RATE OF PAY</u>	<u>HOURLY FRINGE BENEFITS</u>	<u>TOTAL</u>
	\$	\$	\$
Bricklayer, Blocklayer or Stonemason	30.28	18.18	48.46
Carpenter	32.72	16.00	48.72
Future Increase(s): Add \$1.42/hr on 6/1/2015; Add \$1.42/hr on 6/1/2016. Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day.			
Cement Finisher	33.95	18.01	51.96
Future Increase(s): Add \$1.87 on 6/1/15; Add \$1.75 on 6/1/16. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.40/hr when the Wisconsin Department of Transportation or responsible governing agency requires that work be performed at night under artificial illumination with traffic control and the work is completed after sunset and before sunrise.			
Electrician	30.59	18.37	48.96
Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day.			
Fence Erector	18.50	5.34	23.84
Ironworker	31.50	20.01	51.51
Line Constructor (Electrical)	39.50	19.92	59.42
Painter	26.65	16.09	42.74
Pavement Marking Operator	26.04	20.63	46.67
Piledriver	30.11	26.51	56.62
Future Increase(s): Add \$1.50/hr on 6/1/2015; Add \$1.60/hr on 6/1/2016. Premium Pay: Add \$.65/hr for Piledriver Loftsmen; Add \$.75/hr for Sheet Piling Loftsmen. DOT PREMIUM: Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day.			
Rofer or Waterproofer	18.40	11.44	29.84
Teledata Technician or Installer	22.25	12.24	34.49

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
	\$	\$	\$
Tuckpointer, Caulker or Cleaner	23.60	7.10	30.70
Underwater Diver (Except on Great Lakes)	35.40	15.90	51.30
Heavy Equipment Operator - ELECTRICAL LINE CONSTRUCTION ONLY	35.55	15.57	51.12
Light Equipment Operator -ELECTRICAL LINE CONSTRUCTION ONLY	31.60	14.98	46.58
Heavy Truck Driver - ELECTRICAL LINE CONSTRUCTION ONLY	27.65	13.44	41.09
Light Truck Driver - ELECTRICAL LINE CONSTRUCTION ONLY	25.68	12.83	38.51
Groundman - ELECTRICAL LINE CONSTRUCTION ONLY	21.75	11.63	33.38

TRUCK DRIVERS

Single Axle or Two Axle	25.18	18.31	43.49
Future Increase(s): Add \$1.15/hr on 6/1/2015. Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day.			
Three or More Axle	25.28	18.31	43.59
Future Increase(s): Add \$1.15/hr on 6/1/2015. Premium Pay: DOT PREMIUM: Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day.			
Articulated, Euclid, Dumptror, Off Road Material Hauler	30.27	21.15	51.42
Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .			
Pavement Marking Vehicle	23.16	20.01	43.17
Shadow or Pilot Vehicle	24.37	17.77	42.14
Truck Mechanic	24.52	17.77	42.29

LABORERS

General Laborer	30.13	15.14	45.27
Future Increase(s): Add \$1.05/hr eff. 06/01/2015; Add \$1.00/hr eff. 06/01/2016; Add \$1.00/hr eff. 06/01/2017 Premium Pay: Add \$.10/hr for topman, air tool operator, vibrator or tamper operator (mechanical hand operated), chain saw operator and demolition burning torch laborer; Add \$.15/hr for bituminous worker (raker and luteman), formsetter (curb, sidewalk and pavement) and strike off man; Add \$.20/hr for blaster and powderman; Add \$.25/hr for bottomman; Add \$.35/hr for line and grade specialist; Add \$.45/hr for pipelayer. DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.25/hr for work on projects involving temporary traffic control setup, for lane and shoulder closures, when work under artificial illumination conditions is necessary as required by the project provisions (including prep time prior to and/or cleanup after such time period).			
Asbestos Abatement Worker	24.58	14.61	39.19
Landscaper	30.13	15.14	45.27
Future Increase(s): Add \$1.05/hr eff. 06/01/2015; Add \$1.00/hr eff. 06/01/2016; Add \$1.00/hr eff. 06/01/2017 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.25/hr for work on projects involving temporary traffic control setup, for lane and shoulder closures, when work under artificial illumination conditions is necessary as required by the project provisions (including prep time prior to and/or cleanup after such time period).			

TRADE OR OCCUPATION	HOURLY BASIC RATE OF PAY	HOURLY FRINGE BENEFITS	TOTAL
	\$	\$	\$
Flagperson or Traffic Control Person	26.76	15.14	41.90
Future Increase(s): Add \$1.05/hr eff. 06/01/2015; Add \$1.00/hr eff. 06/01/2016; Add \$1.00/hr eff. 06/01/2017 Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.25/hr when the Wisconsin Department of Transportation or responsible governing agency requires that work be performed at night under artificial illumination with traffic control and the work is completed after sunset and before sunrise.			
Fiber Optic Laborer (Outside, Other Than Concrete Encased)	18.33	13.65	31.98
Railroad Track Laborer	14.50	3.52	18.02

HEAVY EQUIPMENT OPERATORS

Crane, Tower Crane, Pedestal Tower or Derrick, With Boom, Leads &/or Jib Lengths Measuring 176 Ft or Over; Crane, Tower Crane, Pedestal Tower or Derrick, With or Without Attachments, With a Lifting Capacity of Over 100 Tons, Self-Erecting Tower Crane With a Lifting Capacity Of Over 4,000 Lbs., Crane With Boom Dollies; Traveling Crane (Bridge Type).	37.72	21.15	58.87
Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .			
Backhoe (Track Type) Having a Mfr.'s Rated Capacity of 130,000 Lbs. or Over; Caisson Rig; Crane, Tower Crane, Portable Tower, Pedestal Tower or Derrick, With Boom, Leads &/or Jib Lengths Measuring 175 Ft or Under; Crane, Tower Crane, Portable Tower, Pedestal Tower or Derrick, With or Without Attachments, With a Lifting Capacity of 100 Tons or Under, Self-Erecting Tower Crane With A Lifting Capacity Of 4,000 Lbs., & Under; Dredge (NOT Performing Work on the Great Lakes); Licensed Boat Pilot (NOT Performing Work on the Great Lakes); Pile Driver.	37.22	21.15	58.37
Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .			
Air Track, Rotary or Percussion Drilling Machine &/or Hammers, Blaster; Asphalt Heater, Planer & Scarifier; Asphalt Milling Machine; Asphalt Screed; Automatic Subgrader (Concrete); Backhoe (Track Type) Having a Mfr.'s Rated Capacity of Under 130,000 Lbs., Backhoe (Mini, 15,000 Lbs. & Under); Bituminous (Asphalt) Plant & Paver, Screed; Boatmen (NOT Performing Work on the Great Lakes); Boring Machine (Directional, Horizontal or Vertical); Bridge (Bidwell) Paver; Bulldozer or Endloader; Concrete Batch Plant, Batch Hopper; Concrete Breaker (Large, Auto, Vibratory/Sonic, Manual or Remote); Concrete Bump Cutter, Grinder, Planing or Grooving Machine; Concrete Conveyor System; Concrete Laser/Screed; Concrete Paver (Slipform); Concrete Pump, Concrete Conveyor (Rotec or Bidwell Type); Concrete Slipform Placer Curb & Gutter Machine; Concrete Spreader & Distributor; Crane (Carry Deck, Mini) or Truck Mounted Hydraulic Crane (10 Tons or Under); Crane With a Lifting Capacity of 25 Tons or Under; Forestry Equipment, Timbco, Tree Shear, Tub Grinder, Processor; Gradall (Cruz-Aire Type); Grader or Motor Patrol; Grout Pump; Hydro-Blaster (10,000 PSI or Over); Loading Machine (Conveyor);	36.72	21.15	57.87

<u>TRADE OR OCCUPATION</u>	<u>HOURLY BASIC RATE OF PAY</u>	<u>HOURLY FRINGE BENEFITS</u>	<u>TOTAL</u>
	\$	\$	\$
Material or Stack Hoist; Mechanic or Welder; Milling Machine; Post Hole Digger or Driver; Roller (Over 5 Ton); Scraper (Self Propelled or Tractor Drawn) 5 cu yds or More Capacity; Shoulder Widener; Sideboom; Skid Rig; Stabilizing or Concrete Mixer (Self-Propelled or 14S or Over); Straddle Carrier or Travel Lift; Tractor (Scraper, Dozer, Pusher, Loader); Tractor or Truck Mounted Hydraulic Backhoe; Trencher (Wheel Type or Chain Type); Tube Finisher; Tugger (NOT Performing Work on the Great Lakes); Winches & A- Frames. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .			
Belting, Burlap, Texturing Machine; Broom or Sweeper; Compactor (Self-Propelled or Tractor Mounted, Towed & Light Equipment); Concrete Finishing Machine (Road Type); Environmental Burner; Farm or Industrial Type Tractor; Fireman (Asphalt Plant, Pile Driver & Derrick NOT Performing Work on the Great Lakes); Forklift; Greaser; Hoist (Tugger, Automatic); Jeep Digger; Joint Sawyer (Multiple Blade); Launch (NOT Performing Work on the Great Lakes); Lift Slab Machine; Mechanical Float; Mulcher; Power Subgrader; Robotic Tool Carrier (With or Without Attachments); Roller (Rubber Tire, 5 Ton or Under); Self Propelled Chip Spreader; Shouldering Machine; Skid Steer Loader (With or Without Attachments); Telehandler; Tining or Curing Machine. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .	36.46	21.15	57.61
Air Compressor (&/or 400 CFM or Over); Air, Electric or Hydraulic Jacking System; Augers (Vertical & Horizontal); Automatic Belt Conveyor & Surge Bin; Boiler (Temporary Heat); Concrete Proportioning Plant; Crusher, Screening or Wash Plant; Generator (&/or 150 KW or Over); Heaters (Mechanical); High Pressure Utility Locating Machine (Daylighting Machine); Mudjack; Oiler; Prestress Machine; Pug Mill; Pump (3 Inch or Over) or Well Points; Rock, Stone Breaker; Screed (Milling Machine); Stump Chipper; Tank Car Heaters; Vibratory Hammer or Extractor, Power Pack. Future Increase(s): Add \$1.25/hr on 6/1/2015; Add \$1.30/hr on 6/1/2016; Add \$1.25/hr on 6/1/2017. Premium Pay: DOT PREMIUMS: 1) Pay two times the hourly basic rate on Sunday, New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day & Christmas Day. 2) Add \$1.50/hr night work premium. See DOT'S website for details about the applicability of this night work premium at: http://www.dot.wi.gov/business/civilrights/laborwages/pwc.htm .	36.17	21.15	57.32
Fiber Optic Cable Equipment.	28.89	17.95	46.84

SCHEDULE OF ITEMS

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS

SECTION 0001 Contract Items

0010	201.0105 Clearing	17.000 STA
0020	201.0205 Grubbing	110.000 STA
0030	203.0100 Removing Small Pipe Culverts	89.000 EACH
0040	203.0200 Removing Old Structure (station) 01. 688+03	LUMP	LUMP	.	.	.
0050	203.0200 Removing Old Structure (station) 02. 700+95	LUMP	LUMP	.	.	.
0060	203.0200 Removing Old Structure (station) 03. 736+00	LUMP	LUMP	.	.	.
0070	203.0200 Removing Old Structure (station) 04. 777+45	LUMP	LUMP	.	.	.
0080	203.0200 Removing Old Structure (station) 05. 827+39	LUMP	LUMP	.	.	.
0090	203.0200 Removing Old Structure (station) 06. 841+40	LUMP	LUMP	.	.	.

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0100	203.0200 Removing Old Structure (station) 07. 864+70	LUMP	LUMP			.
0110	203.0200 Removing Old Structure (station) 08. 897+23	LUMP	LUMP			.
0120	203.0200 Removing Old Structure (station) 09. 927+11	LUMP	LUMP			.
0130	203.0600.S Removing Old Structure Over Waterway With Minimal Debris (station) 01. 966+44.23	LUMP	LUMP			.
0140	204.0100 Removing Pavement	82.000 SY		.		.
0150	204.0120 Removing Asphaltic Surface Milling	9,665.000 SY		.		.
0160	204.0155 Removing Concrete Sidewalk	36.000 SY		.		.
0170	204.0165 Removing Guardrail	5,645.000 LF		.		.
0180	204.0185 Removing Masonry	24.000 CY		.		.
0190	204.0230 Removing Building (station) 01. 972+85	LUMP	LUMP			.

Wisconsin Department of Transportation

PAGE: 3

DATE: 12/01/15

REVISED:

SCHEDULE OF ITEMS

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0200	204.0240 Site Clearance (parcel) 01. Parcel 40	LUMP	LUMP			.
0210	205.0100 Excavation Common	281,694.000 CY	.		.	
0220	205.0200 Excavation Rock	22,808.000 CY	.		.	
0230	206.1000 Excavation for Structures Bridges (structure) 01. B-32-215	LUMP	LUMP			.
0240	208.0100 Borrow	79,193.000 CY	.		.	
0250	208.1100 Select Borrow	2,773.000 CY	.		.	
0260	210.0100 Backfill Structure	345.000 CY	.		.	
0270	213.0100 Finishing Roadway (project) 01. 5121-09-63	1.000 EACH	.		.	
0280	213.0100 Finishing Roadway (project) 02. 5121-09-73	1.000 EACH	.		.	
0290	213.0100 Finishing Roadway (project) 03. 5820-01-73	1.000 EACH	.		.	

Wisconsin Department of Transportation

PAGE: 4

DATE: 12/01/15

REVISED:

SCHEDULE OF ITEMS

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0300	214.0100 Obliterating Old Road	11.000 STA	.		.	
0310	305.0110 Base Aggregate Dense 3/4-Inch	3,798.000 TON	.		.	
0320	305.0120 Base Aggregate Dense 1 1/4-Inch	124,227.000 TON	.		.	
0330	312.0110 Select Crushed Material	133,362.000 TON	.		.	
0340	371.1000.S QMP Base Aggregate Dense 1 1/4-Inch Compaction	109,047.000 TON	.		.	
0350	415.0410 Concrete Pavement Approach Slab	205.000 SY	.		.	
0360	416.0160 Concrete Driveway 6-Inch	125.000 SY	.		.	
0370	416.1010 Concrete Surface Drains	92.000 CY	.		.	
0380	440.4410 Incentive IRI Ride	33,380.000 DOL	1.00000		33380.00	
0390	455.0105 Asphaltic Material PG58-28	2,345.000 TON	.		.	
0400	455.0605 Tack Coat	9,737.000 GAL	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0410	460.1101 HMA Pavement Type E-1	42,407.000 TON	.		.	
0420	460.2000 Incentive Density HMA Pavement	27,150.000 DOL	1.00000		27150.00	
0430	460.4000 HMA Cold Weather Paving	8,255.000 TON	.		.	
0440	460.4110.S Reheating HMA Pavement Longitudinal Joints	82,779.000 LF	.		.	
0450	465.0120 Asphaltic Surface Driveways and Field Entrances	325.000 TON	.		.	
0460	465.0305 Asphaltic Surface Safety Islands	15.000 TON	.		.	
0470	465.0315 Asphaltic Flumes	451.000 SY	.		.	
0480	465.0425 Asphaltic Shoulder Rumble Strips 2-Lane Rural	51,642.000 LF	.		.	
0490	465.0475 Asphalt Center Line Rumble Strips 2-Lane Rural	41,776.000 LF	.		.	
0500	502.0100 Concrete Masonry Bridges	196.000 CY	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0510	502.3200 Protective Surface Treatment	215.000 SY	.		.	
0520	502.3210 Pigmented Surface Sealer	70.000 SY	.		.	
0530	503.0128 Prestressed Girder Type I 28-Inch	306.000 LF	.		.	
0540	504.0900 Concrete Masonry Endwalls	96.000 CY	.		.	
0550	505.0400 Bar Steel Reinforcement HS Structures	5,770.000 LB	.		.	
0560	505.0600 Bar Steel Reinforcement HS Coated Structures	20,210.000 LB	.		.	
0570	506.2605 Bearing Pads Elastomeric Non-Laminated	12.000 EACH	.		.	
0580	506.4000 Steel Diaphragms (structure) 01. B-32-215	5.000 EACH	.		.	
0590	516.0500 Rubberized Membrane Waterproofing	24.000 SY	.		.	
0600	520.1012 Apron Endwalls for Culvert Pipe 12-Inch	1.000 EACH	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0610	520.1018 Apron Endwalls for Culvert Pipe 18-Inch	10.000 EACH	.		.	
0620	520.1024 Apron Endwalls for Culvert Pipe 24-Inch	66.000 EACH	.		.	
0630	520.1030 Apron Endwalls for Culvert Pipe 30-Inch	4.000 EACH	.		.	
0640	520.1036 Apron Endwalls for Culvert Pipe 36-Inch	2.000 EACH	.		.	
0650	520.3312 Culvert Pipe Class III-A 12-Inch	23.000 LF	.		.	
0660	520.8000 Concrete Collars for Pipe	2.000 EACH	.		.	
0670	520.8500 Pipe Cattle Pass	170.000 LF	.		.	
0680	521.0118 Culvert Pipe Corrugated Steel 18-Inch	1,179.000 LF	.		.	
0690	521.1518 Apron Endwalls for Culvert Pipe Sloped Side Drains Steel 18-Inch 6 to 1	74.000 EACH	.		.	
0700	521.1900 Pipe Cattle Pass Corrugated Steel	60.000 LF	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0710	522.0124 Culvert Pipe Reinforced Concrete Class III 24-Inch	635.000 LF	.		.	
0720	522.0324 Culvert Pipe Reinforced Concrete Class IV 24-Inch	402.000 LF	.		.	
0730	522.0524 Culvert Pipe Reinforced Concrete Class V 24-Inch	235.000 LF	.		.	
0740	522.1012 Apron Endwalls for Culvert Pipe Reinforced Concrete 12-Inch	1.000 EACH	.		.	
0750	522.1015 Apron Endwalls for Culvert Pipe Reinforced Concrete 15-Inch	3.000 EACH	.		.	
0760	522.1018 Apron Endwalls for Culvert Pipe Reinforced Concrete 18-Inch	1.000 EACH	.		.	
0770	522.1024 Apron Endwalls for Culvert Pipe Reinforced Concrete 24-Inch	22.000 EACH	.		.	
0780	528.0118 Culvert Pipe Corrugated Steel Polymer Coated 18-Inch	72.000 LF	.		.	
0790	530.0118 Culvert Pipe Corrugated Polyethylene 18-Inch	180.000 LF	.		.	

SCHEDULE OF ITEMS

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0800	530.0124 Culvert Pipe Corrugated Polyethylene 24-Inch	2,502.000 LF	.		.	
0810	530.0130 Culvert Pipe Corrugated Polyethylene 30-Inch	181.000 LF	.		.	
0820	530.0136 Culvert Pipe Corrugated Polyethylene 36-Inch	90.000 LF	.		.	
0830	550.1100 Piling Steel HP 10-Inch X 42 Lb	280.000 LF	.		.	
0840	601.0411 Concrete Curb & Gutter 30-Inch Type D	8,692.000 LF	.		.	
0850	601.0415 Concrete Curb & Gutter 6-Inch Sloped 30-Inch Type J	2,064.000 LF	.		.	
0860	601.0553 Concrete Curb & Gutter 4-Inch Sloped 36-Inch Type D	1,398.000 LF	.		.	
0870	601.0557 Concrete Curb & Gutter 6-Inch Sloped 36-Inch Type D	1,830.000 LF	.		.	
0880	602.0405 Concrete Sidewalk 4-Inch	215.000 SF	.		.	
0890	602.0515 Curb Ramp Detectable Warning Field Natural Patina	24.000 SF	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
0900	602.1500 Concrete Steps	500.000				
		SF	.		.	
0910	606.0300 Riprap Heavy	588.000				
		CY	.		.	
0920	608.0312 Storm Sewer Pipe Reinforced Concrete Class III 12-Inch	515.000				
		LF	.		.	
0930	608.0315 Storm Sewer Pipe Reinforced Concrete Class III 15-Inch	779.000				
		LF	.		.	
0940	608.0318 Storm Sewer Pipe Reinforced Concrete Class III 18-Inch	75.000				
		LF	.		.	
0950	608.0324 Storm Sewer Pipe Reinforced Concrete Class III 24-Inch	1,321.000				
		LF	.		.	
0960	608.0424 Storm Sewer Pipe Reinforced Concrete Class IV 24-Inch	155.000				
		LF	.		.	
0970	611.0535 Manhole Covers Type J-Special	12.000				
		EACH	.		.	
0980	611.0612 Inlet Covers Type C	1.000				
		EACH	.		.	
0990	611.0624 Inlet Covers Type H	26.000				
		EACH	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1000	611.0639 Inlet Covers Type H-S	2.000 EACH	.		.	
1010	611.0642 Inlet Covers Type MS	7.000 EACH	.		.	
1020	611.2004 Manholes 4-FT Diameter	12.000 EACH	.		.	
1030	611.3004 Inlets 4-FT Diameter	5.000 EACH	.		.	
1040	611.3230 Inlets 2x3-FT	24.000 EACH	.		.	
1050	611.3901 Inlets Median 1 Grate	7.000 EACH	.		.	
1060	612.0406 Pipe Underdrain Wrapped 6-Inch	150.000 LF	.		.	
1070	614.0150 Anchor Assemblies for Steel Plate Beam Guard	4.000 EACH	.		.	
1080	614.0200 Steel Thrie Beam Structure Approach	21.000 LF	.		.	
1090	614.0305 Steel Plate Beam Guard Class A	38.000 LF	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1100	614.0345 Steel Plate Beam Guard Short Radius	50.000 LF	.		.	
1110	614.0390 Steel Plate Beam Guard Short Radius Terminal	1.000 EACH	.		.	
1120	614.2300 MGS Guardrail 3	3,245.000 LF	.		.	
1130	614.2330 MGS Guardrail 3 K	1,190.000 LF	.		.	
1140	614.2500 MGS Thrie Beam Transition	200.000 LF	.		.	
1150	614.2610 MGS Guardrail Terminal EAT	13.000 EACH	.		.	
1160	616.0600.S Fence Temporary	350.000 LF	.		.	
1170	618.0100 Maintenance And Repair of Haul Roads (project) 01. 5121-09-63	1.000 EACH	.		.	
1180	618.0100 Maintenance And Repair of Haul Roads (project) 02. 5121-09-73	1.000 EACH	.		.	
1190	618.0100 Maintenance And Repair of Haul Roads (project) 03. 5820-01-73	1.000 EACH	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1200	619.1000 Mobilization	1.000				
		EACH	.		.	
1210	623.0200 Dust Control Surface Treatment	454,284.000				
		SY	.		.	
1220	624.0100 Water	2,538.000				
		MGAL	.		.	
1230	625.0500 Salvaged Topsoil	393,555.000				
		SY	.		.	
1240	627.0200 Mulching	468,014.000				
		SY	.		.	
1250	628.1104 Erosion Bales	1,025.000				
		EACH	.		.	
1260	628.1504 Silt Fence	44,105.000				
		LF	.		.	
1270	628.1520 Silt Fence Maintenance	83,235.000				
		LF	.		.	
1280	628.1905 Mobilizations Erosion Control	16.000				
		EACH	.		.	
1290	628.1910 Mobilizations Emergency Erosion Control	9.000				
		EACH	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1300	628.2004 Erosion Mat Class I Type B	24,052.000 SY	.		.	
1310	628.2023 Erosion Mat Class II Type B	45,161.000 SY	.		.	
1320	628.2039 Erosion Mat Class III Type D	5,648.000 SY	.		.	
1330	628.7005 Inlet Protection Type A	35.000 EACH	.		.	
1340	628.7015 Inlet Protection Type C	35.000 EACH	.		.	
1350	628.7504 Temporary Ditch Checks	350.000 LF	.		.	
1360	628.7555 Culvert Pipe Checks	161.000 EACH	.		.	
1370	629.0210 Fertilizer Type B	390.000 CWT	.		.	
1380	630.0110 Seeding Mixture No. 10	6,846.000 LB	.		.	
1390	630.0140 Seeding Mixture No. 40	778.000 LB	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1400	630.0200 Seeding Temporary	13,692.000 LB	.		.	
1410	633.5100 Markers Row	342.000 EACH	.		.	
1420	633.5200 Markers Culvert End	111.000 EACH	.		.	
1430	634.0612 Posts Wood 4x6-Inch X 12-FT	8.000 EACH	.		.	
1440	634.0614 Posts Wood 4x6-Inch X 14-FT	98.000 EACH	.		.	
1450	634.0616 Posts Wood 4x6-Inch X 16-FT	71.000 EACH	.		.	
1460	634.0618 Posts Wood 4x6-Inch X 18-FT	2.000 EACH	.		.	
1470	637.2210 Signs Type II Reflective H	1,127.330 SF	.		.	
1480	637.2220 Signs Type II Reflective SH	13.500 SF	.		.	
1490	637.2230 Signs Type II Reflective F	315.000 SF	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:
20160209008PROJECT(S):
5121-09-63
5121-09-73
5820-01-73FEDERAL ID(S):
N/A
N/A
N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1500	638.2602 Removing Signs Type II	141.000 EACH	.		.	
1510	638.3000 Removing Small Sign Supports	156.000 EACH	.		.	
1520	642.5201 Field Office Type C	1.000 EACH	.		.	
1530	643.0100 Traffic Control (project) 01. 5121-09-63	1.000 EACH	.		.	
1540	643.0100 Traffic Control (project) 02. 5121-09-73	1.000 EACH	.		.	
1550	643.0100 Traffic Control (project) 03. 5820-01-73	1.000 EACH	.		.	
1560	643.0300 Traffic Control Drums	18,000.000 DAY	.		.	
1570	643.0420 Traffic Control Barricades Type III	13,160.000 DAY	.		.	
1580	643.0705 Traffic Control Warning Lights Type A	20,680.000 DAY	.		.	
1590	643.0900 Traffic Control Signs	15,980.000 DAY	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1600	643.0910 Traffic Control Covering Signs Type I	4.000 EACH	.		.	
1610	643.1000 Traffic Control Signs Fixed Message	68.000 SF	.		.	
1620	643.1050 Traffic Control Signs PCMS	56.000 DAY	.		.	
1630	643.2000 Traffic Control Detour (project) 01. 5121-09-73	1.000 EACH	.		.	
1640	643.3000 Traffic Control Detour Signs	105,820.000 DAY	.		.	
1650	645.0120 Geotextile Fabric Type HR	1,180.000 SY	.		.	
1660	646.0106 Pavement Marking Epoxy 4-Inch	174,765.000 LF	.		.	
1670	646.0126 Pavement Marking Epoxy 8-Inch	1,600.000 LF	.		.	
1680	647.0566 Pavement Marking Stop Line Epoxy 18-Inch	67.000 LF	.		.	
1690	647.0776 Pavement Marking Crosswalk Epoxy 12-Inch	67.000 LF	.		.	

SCHEDULE OF ITEMS

REVISED:

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1700	648.0100 Locating No-Passing Zones	7.000 MI	.		.	
1710	650.4000 Construction Staking Storm Sewer	58.000 EACH	.		.	
1720	650.4500 Construction Staking Subgrade	48,346.000 LF	.		.	
1730	650.5000 Construction Staking Base	48,346.000 LF	.		.	
1740	650.5500 Construction Staking Curb Gutter and Curb & Gutter	13,621.000 LF	.		.	
1750	650.6000 Construction Staking Pipe Culverts	88.000 EACH	.		.	
1760	650.6500 Construction Staking Structure Layout (structure) 01. B-32-215	LUMP	LUMP		.	
1770	650.6500 Construction Staking Structure Layout (structure) 02. R-32-0063	LUMP	LUMP		.	
1780	650.9910 Construction Staking Supplemental Control (project) 01. 5121-09-73	LUMP	LUMP		.	
1790	650.9920 Construction Staking Slope Stakes	96,692.000 LF	.		.	

SCHEDULE OF ITEMS

CONTRACT:

PROJECT(S):

FEDERAL ID(S):

20160209008

5121-09-63

N/A

5121-09-73

N/A

5820-01-73

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1800	690.0150 Sawing Asphalt	1,226.000				
	LF		.		.	
1810	690.0250 Sawing Concrete	40.000				
	LF		.		.	
1820	715.0415 Incentive Strength Concrete Pavement	500.000	1.00000		500.00	
	DOL					
1830	715.0502 Incentive Strength Concrete Structures	1,176.000	1.00000		1176.00	
	DOL					
1840	SPV.0090 Special 01. Removing HMA Pavement Notched Wedge Longitudinal Joint Milling	45,025.000				
	LF		.		.	
1850	SPV.0090 Special 02. Concrete Curb & Gutter 32-Inch Special	40.000				
	LF		.		.	
1860	SPV.0105 Special 01. Modify Drain Pipe	LUMP	LUMP			
					.	
1870	SPV.0105 Special 02. Rectangular Rapid Flashing Beacon System	LUMP	LUMP			
					.	
1880	SPV.0165 Special 01. Wall Modular Block Gravity LRFD Special **p**	460.000				
	SF		.		.	
1890	SPV.0180 Special 01. Geogrid Reinforcement	170,397.000				
	SY		.		.	

SCHEDULE OF ITEMS

CONTRACT:

20160209008

PROJECT(S):

5121-09-63

5121-09-73

5820-01-73

FEDERAL ID(S):

N/A

N/A

N/A

CONTRACTOR : _____

LINE NO	ITEM DESCRIPTION	APPROX. QUANTITY AND UNITS	UNIT PRICE		BID AMOUNT	
			DOLLARS	CTS	DOLLARS	CTS
1900	SPV.0195 Special 01. Management of Contaminated Soil	50.000 TON	.		.	
	SECTION 0001 TOTAL				.	
	TOTAL BID				.	

PLEASE ATTACH SCHEDULE OF ITEMS HERE