

MANITOWOC

2

GENERAL NOTES

THE LOCATIONS OF EXISTING AND PROPOSED UTILITY FACILITIES AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

FILL AS SHOWN ON THE PLANS PERTAINS TO EMBANKMENTS CONSTRUCTED FROM COMMON EXCAVATION. THE ALLOWANCE USED FOR EXPANDING THE FILLS TO COMPUTE THE VOLUME OF MATERIAL REQUIRED IS 25 PERCENT. ALL FILL VOLUMES SHOWN ARE THE ACTUAL VOLUMES.

WHEN THE QUANTITY OF BASE LAYER OR SURFACE LAYER IS MEASURED FOR PAYMENT BY THE TON, THE DEPTH OR THICKNESS OF THE LAYER SHOWN ON THE PLANS IS APPROXIMATE AND THE ACTUAL THICKNESS WILL DEPEND ON THE DISTRIBUTION OF MATERIAL AS DIRECTED BY THE ENGINEER.

ASPHALTIC SURFACE 4" DEPTH
1 3/4" UPPER LAYER (12.5 mm NOMINAL SIZE AGGREGATE)
2 1/4" LOWER LAYER (19 mm NOMINAL SIZE AGGREGATE)

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT THE APPROVAL OF THE ENGINEER.

ALL DISTURBED AREAS, NOT OTHERWISE SURFACED ARE TO BE TOPSOILED, FERTILIZED, TEMPORARY SEEDED, SEEDED AND COVERED WITH EROSION MAT.

SEED MIXTURE NO. 20 SHALL BE USED ON ALL DISTURBED AREAS, EXCEPT WETLANDS SHALL BE SEEDED WITH MIXTURE NO. 60.

FERTILIZER SHALL NOT BE USED NEAR NAVIGABLE WATERWAYS AND WETLANDS.

WETLAND AREAS ARE SHOWN ON THE PLANS. CONTRACTOR SHALL LIMIT CONSTRUCTION ACTIVITIES TO WORK WITHIN THE SLOPE INTERCEPTS IN THE WETLAND AREAS.

THE EXACT LOCATIONS OF ALL EROSION CONTROL ITEMS SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

DISTANCES SHOWN ON THIS PLAN ARE GROUND DISTANCES.

PLAN ELEVATIONS = USGS DATUM, NAVD 88 (2012)

THE WISCONSIN DEPARTMENT OF TRANSPORTATION WILL FURNISH THE CONTRACTOR A MONUMENT WHICH SHALL BE SET IN THE STRUCTURE AS DESIGNATED BY THE ENGINEER.

EROSION CONTROL NOTES

RUNOFF COEFFICIENTS FOR THIS PROJECT: EXISTING PAVEMENT 0.95, EXISTING SLOPES 0.30, NEW PAVEMENT 0.95, NEW SLOPES 0.30.

TOTAL PROJECT AREA = 2.18 ACRES
TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 1.16 ACRES.

CONTACTS

ELECTRIC

WISCONSIN PUBLIC SERVICE CORPORATION
700 NORTH ADAMS STREET, PO BOX 19001
GREEN BAY, WI 54307-9001
ATTN: LORI BUTRY
TELEPHONE: (920) 433-1703
EMAIL: LAButry@integrysgroup.com

TELEPHONE

LOCAL CONTACT (ELECTRIC): JEFF PELISCHEK
TELEPHONE: 920-794-3216 EXT 4216
CELL PHONE: 920-323-4836
EMAIL: jspelischek@wpsr.com

FRONTIER COMMUNICATIONS
118 DIVISION SSTREET
PLYMOUTH, WI 53073
ATTN: DICK ENDSLEY
TELEPHONE: (920)893-7242
CELL: (920) 574-6859
EMAIL: RICHARD.J.ENDSLEY@FTR.COM

DNR LIAISON

MATT SCHAEVE
DEPARTMENT OF NATURAL RESOURCES
2984 SHAWANO AVENUE
GREEN BAY, WI 54313
TELEPHONE: 920-662-5472
EMAIL: matthew.schaeve@wisconsin.gov

DIGGERSHOTLINE

Dial 811 or (800)242-8511

www.DiggersHotline.com

** DENOTES UTILITIES THAT ARE NOT DIGGERS HOTLINE MEMBERS.

PROJECT NO: 4316-08-71

HWY: HILLCREST ROAD

COUNTY: MANITOWOC


GENERAL NOTES

SHEET:


E 2.1



** DENOTES UTILITIES THAT ARE NOT DIGGERS HOTLINE MEMBERS.




TYPICAL EXISTING SECTION - HILLCREST RD
STA 7+00 TO STA 9+39.68
STA 10+80.68 TO STA 12+50




TYPICAL FINISHED SECTION - HILLCREST RD
STA 7+00 TO STA 9+39.68
STA 10+80.68 TO STA 12+50


NOTES:
△ VARIES TO 6' AT POST NO. 1 OF ENERGY ABSORBING TERMINAL



TYPICAL FINISHED SECTION - HILLCREST RD
STA 6+23 TO STA 7+00
STA 12+50 TO STA 12+97, LT







TYPICAL FINISHED SECTION - HILLCREST RD
STA 5+68.5 TO STA 6+23, LT AND RT
STA 12+97 TO STA 13+37, LT
STA 12+50 TO STA 12+75, RT




LEGEND

- MAG SPIKE
- 3/4-INCH REBAR
- POWER POLE







RURAL DRIVEWAY INTERSECTION DETAIL




CONCRETE PAVEMENT APPROACH SLAB



CULVERT PIPE CHECK





PROJECT NO: 4316-08-71	HWY: HILLCREST ROAD	COUNTY: MANITOWOC	EROSION CONTROL	SHEET	E
------------------------	---------------------	-------------------	-----------------	-------	---

DATE 16MAR16		E S T I M A T E O F Q U A N T I T I E S			
LINE					4316-08-71
NUMBER	ITEM	ITEM DESCRIPTION	UNIT	TOTAL	QUANTITY
0010	201.0205	Grubbing	STA	9.000	9.000
0020	203.0100	Removing Small Pipe Culverts	EACH	2.000	2.000
0030	203.0600.S	Removing Old Structure Over Waterway With Minimal Debris (station) 01. 10+00	LS	1.000	1.000
0040	205.0100	Excavation Common	CY	230.000	230.000
0050	206.1000	Excavation for Structures Bridges (structure) 01. B-36-214	LS	1.000	1.000
0060	208.0100	Borrow	CY	7,120.000	7,120.000
0070	210.0100	Backfill Structure	CY	550.000	550.000
0080	213.0100	Finishing Roadway (project) 01. 4316-08-71	EACH	1.000	1.000
0090	305.0110	Base Aggregate Dense 3/4-Inch	TON	300.000	300.000
0100	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	1,150.000	1,150.000
0110	415.0410	Concrete Pavement Approach Slab	SY	94.000	94.000
0120	455.0605	Tack Coat	GAL	90.000	90.000
0130	465.0105	Asphaltic Surface	TON	300.000	300.000
0140	502.0100	Concrete Masonry Bridges	CY	273.000	273.000
0150	502.3200	Protective Surface Treatment	SY	600.000	600.000
0160	503.0172	Prestressed Girder Type I 72W-Inch	LF	568.000	568.000
0170	505.0400	Bar Steel Reinforcement HS Structures	LB	3,740.000	3,740.000
0180	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	32,810.000	32,810.000
0190	506.2605	Bearing Pads Elastomeric Non-Laminated	EACH	8.000	8.000
0200	506.4000	Steel Diaphragms (structure) 01. B-36-214	EACH	6.000	6.000
0210	513.4061	Railing Tubular Type M (structure) 01. B-36-214	LF	292.000	292.000
0220	516.0500	Rubberized Membrane Waterproofing	SY	26.000	26.000
0230	520.1024	Apron Endwalls for Culvert Pipe 24-Inch	EACH	4.000	4.000
0240	521.0124	Culvert Pipe Corrugated Steel 24-Inch	LF	82.000	82.000
0250	550.1120	Piling Steel HP 12-Inch X 53 Lb	LF	280.000	280.000
0260	606.0200	Riprap Medium	CY	55.000	55.000
0270	606.0300	Riprap Heavy	CY	452.000	452.000
0280	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	120.000	120.000
0290	614.0200	Steel Thrie Beam Structure Approach	LF	21.000	21.000
0300	614.0370	Steel Plate Beam Guard Energy Absorbing Terminal	EACH	1.000	1.000
0310	614.0920	Salvaged Rail	LF	970.000	970.000
0320	614.0925	Salvaged Guardrail End Treatments	EACH	4.000	4.000
0330	614.2300	MGS Guardrail 3	LF	425.000	425.000
0340	614.2500	MGS Thrie Beam Transition	LF	118.000	118.000
0350	614.2610	MGS Guardrail Terminal EAT	EACH	3.000	3.000
0360	619.1000	Mobilization	EACH	1.000	1.000
0370	624.0100	Water	MGAL	10.000	10.000
0380	625.0100	Topsoil	SY	4,850.000	4,850.000
0390	628.1504	Silt Fence	LF	820.000	820.000
0400	628.1520	Silt Fence Maintenance	LF	820.000	820.000
0410	628.1905	Mobilizations Erosion Control	EACH	4.000	4.000
0420	628.1910	Mobilizations Emergency Erosion Control	EACH	2.000	2.000
0430	628.2008	Erosion Mat Urban Class I Type B	SY	4,850.000	4,850.000
0440	628.6005	Turbidity Barriers	SY	325.000	325.000
0450	628.7504	Temporary Ditch Checks	LF	40.000	40.000
0460	628.7555	Culvert Pipe Checks	EACH	15.000	15.000
0470	629.0210	Fertilizer Type B	CWT	3.000	3.000
0480	630.0120	Seeding Mixture No. 20	LB	130.000	130.000

DATE 16MAR16		E S T I M A T E O F Q U A N T I T I E S			
LINE					4316-08-71
NUMBER	ITEM	ITEM DESCRIPTION	UNIT	TOTAL	QUANTITY
0490	630.0160	Seeding Mixture No. 60	LB	10.000	10.000
0500	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	4.000	4.000
0510	634.0616	Posts Wood 4x6-Inch X 16-FT	EACH	2.000	2.000
0520	637.2230	Signs Type II Reflective F	SF	12.000	12.000
0530	638.2102	Moving Signs Type II	EACH	4.000	4.000
0540	638.2602	Removing Signs Type II	EACH	4.000	4.000
0550	638.3000	Removing Small Sign Supports	EACH	6.000	6.000
0560	642.5001	Field Office Type B	EACH	1.000	1.000
0570	643.0100	Traffic Control (project) 01. 4316-08-71	EACH	1.000	1.000
0580	643.0420	Traffic Control Barricades Type III	DAY	1,700.000	1,700.000
0590	643.0705	Traffic Control Warning Lights Type A	DAY	2,720.000	2,720.000
0600	643.0900	Traffic Control Signs	DAY	1,190.000	1,190.000
0610	645.0120	Geotextile Fabric Type HR	SY	783.000	783.000
0620	646.0106	Pavement Marking Epoxy 4-Inch	LF	3,080.000	3,080.000
0630	650.4500	Construction Staking Subgrade	LF	625.000	625.000
0640	650.5000	Construction Staking Base	LF	625.000	625.000
0650	650.6500	Construction Staking Structure Layout (structure) 01. B-36-114	LS	1.000	1.000
0660	650.9910	Construction Staking Supplemental Control (project) 01. 4316-08-71	LS	1.000	1.000
0670	650.9920	Construction Staking Slope Stakes	LF	625.000	625.000
0680	690.0150	Sawing Asphalt	LF	280.000	280.000
0690	715.0415	Incentive Strength Concrete Pavement	DOL	500.000	500.000
0700	715.0502	Incentive Strength Concrete Structures	DOL	1,638.000	1,638.000
0710	999.1000.S	Seismograph	LS	1.000	1.000
0720	999.1500.S	Crack and Damage Survey	LS	1.000	1.000

EARTHWORK

DIVISION	FROM / TO STATION	LOCATION	205.0100 EXCAVATION COMMON (CY) NOTE 2	SALVAGED / UNUSABLE PAVEMENT MATERIAL (CY)	AVAILABLE MATERIAL (CY) NOTE 3	UNEXPANDED FILL (CY)	EXPANDED FILL (CY) NOTE 4	MASS ORDINATE +/- (CY) NOTE 5	208.0100 BORROW (CY)
							Factor 1.25		
WEST	5+68.85/09+38.43	HILLCREST RD	140	0	140	4,720	5,900	-5,760	5,760
EAST	10+81.93/13+36.83	HILLCREST RD	90	0	90	1,163	1,450	-1,360	1,360
		TOTALS	230	0	230	5,883	7,350	-7,120	7,120

- 2) SALVAGED / UNUSABLE PAVEMENT MATERIAL IS INCLUDED IN EXCAVATION COMMON
- 3) AVAILABLE MATERIAL = EXCAVATION COMMON - SALVAGED / UNUSABLE PAVEMENT MATERIAL
- 4) EXPANDED FILL = (UNEXPANDED FILL) * FILL FACTOR
- 5) THE MASS ORDINATE + OR - QUANTITY CALCULATED FOR THE DIVISION. PLUS QUANTITY INDICATES AN EXCESS OF MATERIAL WITHIN THE DIVISION. MINUS INDICATES A SHORTAGE OF MATERIAL WITHIN THE DIVISION.

GRUBBING

STATION	LOCATION	201.0205 GRUBBING STATION
5+69 to 9+38	HILLCREST RD	5
10+82 to 13+37	HILLCREST RD	4
TOTALS		9

BASE AGGREGATE DENSE AND WATER

		305.0110 BASE AGGREGATE DENSE 3/4-INCH TON	305.0120 BASE AGGREGATE DENSE 1 1/4-INCH TON	624.0100 WATER MGAL
STATION TO STATION	LOCATION			
5+69 - STRUCTURE	HILLCREST RD	180	700	6.0
STRUCTURE - 13+37	HILLCREST RD	120	450	4.0
TOTALS		300	1,150	10

ASPHALTIC ITEMS

		455.0605 TACK COAT GAL	465.0105 ASPHALTIC SURFACE TON
STATION TO STATION	LOCATION		
5+69 - STRUCTURE	HILLCREST RD	55	180
STRUCTURE - 13+37	HILLCREST RD	35	120
TOTALS		90	300

CONCRETE PAVEMENT

		415.0410 CONCRETE PAVEMENT APPROACH SLAB SY
STATION TO STATION	LOCATION	
9+23 - STRUCTURE	HILLCREST RD	47
STRUCTURE - 10+97	HILLCREST RD	47
TOTALS		94

CULVERT PIPES

		203.0100 REMOVING SMALL PIPE CULVERTS	520.1024 APRON ENDWALL FOR CULVERT PIPE 24-IN	521.0124 CULVERT PIPE CORRUGATED STEEL 24-IN			
STATION	LOCATION	EA	EA	LF	STEEL THICKNESS	UP INVERT	DN INVERT
6+44, RT	HILLCREST RD	1	2	44	0.064	790.50	789.55
11+80, RT	HILLCREST RD	1	2	38	0.064	780.20	778.00
TOTALS		2	4	82			

STEEL PLATE BEAM GUARD

		614.0200 STEEL THRIE BEAM STRUCTURE APPROACH	614.0370 STEEL PLATE BEAM GUARD EAT EAT	614.2300 MGS GUARDRAIL 3 LF	614.2500 MGS THRIE BEAM TRANSITION LF	614.2610 MGS GUARDRAIL TERMINAL EAT EACH
STATION TO STATION	LOCATION	LF	EAT	LF	LF	EACH
6+74 - STRUCTURE, RT	HILLCREST RD	---	---	175	39.4	1
6+74 - STRUCTURE, LT	HILLCREST RD	---	---	175	39.4	1
STRUCTURE - 11+50, RT	HILLCREST RD	20.7	1	---	---	
STRUCTURE - 12+47, LT	HILLCREST RD	---	---	75	39.4	1
TOTALS		20.7	1	425	118.2	3
ROUNDED TOTALS		21	1	425	118	3

LANDSCAPING

		625.0100 TOPSOIL	630.0120 SEEDING NO 20	630.0160 SEEDING NO 60	629.0210 FERTILIZER TYPE B
STATION TO STATION	LOCATION	SY	LB	LB	CWT
5+69 - STRUCTURE, RT	HILLCREST	1750	48	-	1.1
5+69 - STRUCTURE, LT	HILLCREST	1020	28	-	0.6
STRUCTURE - 12+75, RT	HILLCREST	640	17	-	0.4
STRUCTURE - 13+37, LT	HILLCREST	480	13	-	0.4
UNDISTRIBUTED	HILLCREST	960	24	10	0.5
TOTALS		4,850	130	10	3.0

SALVAGED GUARDRAIL

		614.0920 SALVAGED RAIL	614.0925 SALVAGED GUARDRAIL END TREATMENTS
STATION	LOCATION	LF	EACH
6+73 - 11+80, LT	HILLCREST RD	510	2
7+10 - 11+68, RT	HILLCREST RD	460	2
TOTALS		970	4

TURBIDITY BARRIER

STATION	LOCATION	628.6005 SY
10+00	HILLCREST RD	170
10+50	HILLCREST RD	155
TOTAL		325

EROSION CONTROL ITEMS

		628.1504 SILT FENCE	628.1520 SILT FENCE MAINTENANCE	628.1905 MOBILIZATIONS EROSION CONTROL	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL	628.2008 EROSION MAT URBAN CLASS I TYPE B	628.7504 TEMPORARY DITCH CHECKS	628.7555 CULVERT PIPE CHECKS
STATION TO STATION	LOCATION	LF	LF	EACH	EACH	SY	LF	EACH
5+69 - STRUCTURE, RT	HILLCREST RD	60	60	---	---	1750	20	5
5+69 - STRUCTURE, LT	HILLCREST RD	375	375	---	---	1020	---	---
STRUCTURE - 13+37, RT	HILLCREST RD	100	100	---	---	640	10	5
STRUCTURE - 13+37, LT	HILLCREST RD	120	120	---	---	480	---	---
UNDISTRIBUTED	HILLCREST RD	165	165	4	2	960	10	5
TOTALS		820	820	4	2	4,850	40	15

RIPRAP

		606.0200 RIPRAP MEDIUM	645.0120 GEOTEXTILE FABRIC TYPE HR
STATION	LOCATION	CY	SY
11+50, RT	HILLCREST RD	8	16
TOTAL		8	16

NOTE: ADDITIONAL QUANTITIES SHOWN ELSEWHERE

3

3

ALL ITEMS ARE CATEGORY 0010 UNLESS OTHERWISE NOTED

SIGNS REFLECTIVE TYPE II & POSTS WOOD

STATION	LOCATION	CODE	SIGN SIZE HORIZ X VERT IN X IN	634.0614 POSTS WOOD 4X6-INCH X 14-FT EACH	637.2230 SIGNS TYPE II RELFECTIVE F SF
9+35, RT	HILLCREST RD	W5-52R	12 X 36	1	3
9+35, LT	HILLCREST RD	W5-52L	12 X 36	1	3
10+85, RT	HILLCREST RD	W5-52L	12 X 36	1	3
10+85, LT	HILLCREST RD	W5-52R	12 X 36	1	3
TOTALS				4	12

MOVING SIGNS

FROM STATION	LOCATION	TO STATION	FACE DIR.	DESCRIPTION	638.2102 MOVING SIGNS TYPE II EACH	634.0616 POSTS WOOD 4X6-INCH X 16-FT EACH
9+00 , RT	HILLCREST RD	9+00 , RT	EB	FRIENDS OF BRANCH RIVER, REPORT SPLIIS	2	1
11+10 , LT	HILLCREST RD	11+10 , LT	WB	FRIENDS OF BRANCH RIVER, REPORT SPLIIS	2	1
TOTALS					4	2

REMOVING SIGNS TYPE II AND REMOVING SMALL SIGN SUPPORTS

STATION	LOCATION	DESCRIPTION	638.2602 REMOVING SIGNS TYPE II EACH	638.3000 REMOVING SMALL SIGN SUPPORTS EACH
9+00, RT	HILLCREST RD	FRIENDS OF BRANCH RIVER	---	1
9+45, RT	HILLCREST RD	OBJECT MARKER	1	1
9+45, LT	HILLCREST RD	OBJECT MARKER	1	1
10+55, RT	HILLCREST RD	OBJECT MARKER	1	1
10+55, LT	HILLCREST RD	OBJECT MARKER	1	1
11+10, LT	HILLCREST RD	FRIENDS OF BRANCH RIVER	---	1
TOTALS			4	6

CONSTRUCTION STAKING

STATION TO STATION	LOCATION	650.4500	650.5000	CATEGORY 0020 650.6500 STRUCTURE LAYOUT	650.9910 SUPPLEMENTAL CONTROL	650.9920 SLOPE STAKES
		SUBGRADE LF	BASE LF	LS	LS	LF
5+68 - STRUCTURE	HILLCREST RD	370	370	---	---	370
STRUCTURE B-36-214	HILLCREST RD	---	---	1	---	---
STRUCTURE - 13+37	HILLCREST RD	255	255	---	---	255
TOTALS		625	625	1	1	625

TRAFFIC CONTROL ROAD CLOSURE

LOCATION	APROX. SERVICE PERIOD	643.0420 BARRICADES TYPE III		643.0705 WARNING LIGHTS TYPE A		643.0900 SIGNS	
		EACH		EACH		EACH	
		NO.	DAYS	NO.	DAYS	NO.	DAYS
WEST OF PROJECT	85	10	850	16	1360	7	595
EAST OF PROJECT	85	10	850	16	1360	7	595
TOTALS			1,700		2,720		1,190

PAVEMENT MARKING EPOXY

STATION	LOCATION	646.0106	
		4-INCH DOUBLE YELLOW LF	4-INCH WHITE EDGE LINE LF
5+68 - 13+37	HILLCREST RD	1,540	1,540
TOTAL		3,080	

SAWING ASPHALT

STATION	LOCATION	690.0150 SAWING ASPHALT LF
6+25-7+00	HILLCREST RD	180
12+50-13+00	HILLCREST RD	100
TOTAL		280

SEISMOGRAPH

	999.1000.s
LOCATION	LS
HILLCREST RD	1
TOTAL	1

CRACK & DAMAGE SURVEY

	999.1500.s
LOCATION	LS
HILLCREST RD	1
TOTAL	1

LEVELS ON = 01.02.03.04.05.06.07.08.09.10.11.12.13.14.15.16.17.18.19.20.21.22.23.24.25.26.27.28.29.30.31.32.33.34.35.36.37.38.39.40.41.42.43.44.45.46.47.48.49.50.51.52.53.54.55.56.57.58.59.60.61.62.63.

Conventional Signs and Abbreviations

	SECTION LINE	AC	ACRES	R	RADIUS
	QUARTER LINE	Δ	CENTRAL ANGLE	R.	RANGE
	TOWNSHIP AND RANGE LINE	C/L	CENTERLINE	R/L	REFERENCE LINE
	PROPOSED OR NEW CENTERLINE	COR.	CORNER	R/W	RIGHT OF WAY
	PROPOSED OR NEW R/W LINE	CTH	COUNTY TRUNK HIGHWAY	1/4 LINE	QUARTER LINE
	EXISTING R/W LINE	D	DEGREE OF CURVE	1/2 LINE	SIXTEENTH LINE
	LOT LINE	E.	EAST	S.	SOUTH
	PROPERTY LINE	L	LENGTH OF CURVE	SEC	SECTION
	COUNTY LIMITS LINE	LC	LONG CHORD	SEC LINE	SECTION LINE
	SLOPE INTERCEPTS	LCB	LONG CHORD BEARING	STH	STATE TRUNK HIGHWAY
	EXISTING MONUMENTATION	M	MILE	SF	SQUARE FEET
	FENCE	N.	NORTH	STA	STATION
	SECTION OR QUARTER CORNER	N.T.S.	NOT TO SCALE	T.	TOWN
	TELEPHONE	PC	POINT OF CURVATURE	T	TANGENT LENGTH OF CURVE
	GAS	PI	POINT OF INTERSECTION	TLE	TEMPORARY LIMITED EASEMENT
	WATER	PT	POINT OF TANGENCY	USH	UNITED STATES HIGHWAY
	ELECTRIC	PLE	PERMANENT LIMITED EASEMENT	W.	WEST
	FIBER OPTIC	P/L	PROPERTY LINE		
	SANITARY	PC LINE	PRIVATE CLAIM LINE		
	STORM SEWER				

BEGIN RELOCATION ORDER
STA 5+50.00
0.01' SOUTH OF AND 372.38' EAST OF THE
SOUTH QUARTER CORNER OF SECTION 14,
T20N, R22E, TOWN OF FRANKLIN, MANITOWOC
COUNTY, WISCONSIN
Y: 339072.444
X: 188509.973

TOWN

BRANCH

OF

END RELOCATION ORDER
STA 13+00.00
5.92' SOUTH OF AND 1122.36' EAST
OF THE SOUTH QUARTER CORNER,
SEC 14, T20N, R22E, TOWN OF
FRANKLIN, MANITOWOC COUNTY,
WISCONSIN
Y: 339066.529
X: 189259.949

R/W COORDINATE TABLE		
POINT #	Y	X
5	339012.595	189129.520
9	339029.527	188734.655
10	338994.284	188784.391
12	338992.815	189084.363
16	339119.892	188660.335
17	339154.647	188710.599
18	339153.762	188891.289
24	339153.545	188935.732
25	339123.475	188950.095

MAG NAIL
FOUND
Y: 339059.606
X: 190761.931

LINE TABLE		
LINE	BEARING	DISTANCE
L1	N00°16'49"E	55.00'
L2	N25°31'53"W	33.32'
L3	S55°20'18"W	61.1'
L4	S00°16'49"W	50.00'
L5	S00°16'49"W	55.00'
L6	S66°20'47"W	49.30'
L7	N54°40'40"W	60.96'
L8	N00°16'49"E	40.00'

SCHEDULE OF LANDS AND INTERESTS OF LAND INTERESTS TO THE TOWN OF FRANKLIN						
PARCEL NUMBER	OWNER	INTEREST REQUIRED	AREA ACRES REQUIRED			TLE AREA
			NEW	EXISTING	TOTAL	
1	JAMES C. HYNK	FEE	0.19 AC	0.36 AC	0.55 AC	-----
2	SCOTT R. HASTREITER	FEE	0.12 AC	0.31 AC	0.43 AC	-----
3	ROBERT J. HASTREITER	FEE	0.05 AC	0.18 AC	0.23 AC	-----

UTILITY INTEREST REQUIRED		
PARCEL NUMBER	OWNER	INTEREST REQUIRED
90	FRONTIER COMMUNICATIONS	RELEASE OF RIGHTS

SCALE 0 100' 200'

LAYOUT

TOTAL NET LENGTH OF CENTERLINE = 0.142 MI.

Notes:
POSITIONS SHOWN ON THIS PLAT ARE WISCONSIN COUNTY COORDINATES, MANITOWOC COUNTY, NAD 83 (2007) IN US SURVEY FEET. VALUES SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.
RIGHT OF WAY MONUMENTS ARE TYPE 2 MONUMENTS (TYPICALLY 3/4 X 24" REBAR) AND WILL BE PLACED PRIOR TO THE COMPLETION OF THE PROJECT.
RIGHT OF WAY BOUNDARIES ARE DEFINED WITH COURSES OF THE PERIMETER OF THE HIGHWAY LANDS REFERENCED TO THE U.S. PUBLIC LAND SURVEY OR OTHER SURVEYS OF PUBLIC RECORD.
PROPERTY LINES SHOWN ON THIS PLAT ARE DRAWN FROM DATA DERIVED OF MAPS AND DOCUMENTS OF PUBLIC RECORD AND/ OR EXISTING OCCUPATION LINES. EXCLUDING RIGHT-OF-WAY BOUNDARIES, THIS PLAT MAY NOT BE A TRUE REPRESENTATION OF EXISTING PROPERTY LINES AND SHOULD NOT BE USED AS A SUBSTITUTE FOR AN ACCURATE FIELD SURVEY.
DIMENSIONS FOR THE NEW RIGHT-OF-WAY ARE MEASURED ALONG AND PERPENDICULAR TO THE NEW REFERENCE LINE.
HILLCREST ROAD IS DEFINED FROM R/W CONVEYANCES DOC NO'S 421914, 421915, 421916



ACCEPTED FOR
TOWN OF FRANKLIN

6/30/15 *[Signature]*
(Date) (Signature & Title of Official)

ORIGINAL PLANS PREPARED BY
OMNI ASSOCIATES
APPLETON, WISCONSIN


WISCONSIN
DAVID A. YURK
S-2648
OSHKOSH, WI
PROFESSIONAL LAND SURVEYOR

6-19-2015 *[Signature]*
(Date) (Signature)



Standard Detail Drawing List



08E08-03	TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
08F01-11	APRON ENDWALLS FOR CULVERT PIPE
12A03-10	NAME PLATE (STRUCTURES)
13B02-08A	CONCRETE PAVEMENT APPROACH SLAB
13B02-08B	STRUCTURAL APPROACH SLAB AND CONCRETE PAVEMENT APPROACH SLAB
14B15-08A	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-08B	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-08C	STEEL PLATE BEAM GUARD, CLASS "A", INSTALLATION & ELEMENTS
14B20-11A	STEEL THRIE BEAM STRUCTURE APPROACH
14B20-11F	STEEL THRIE BEAM STRUCTURE APPROACH, CONNECTION TO BRIDGE RAILING TYPE "M"
14B24-08A	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
14B24-08B	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
14B24-08C	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
14B42-03A	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-03B	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-03C	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B44-02A	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-02B	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-02C	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B45-04A	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04B	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04C	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04H	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
15C02-05A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-05B	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C06-07	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-16A	PAVEMENT MARKING (MAINLINE)



GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

- ① TEMPORARY DITCH CHECKS EITHER EROSION BALES OR MANUFACTURED SHALL BE PAID FOR UNDER THE BID ITEM OF TEMPORARY DITCH CHECK. THE DEPARTMENT WILL NOT PAY FOR TEMPORARY DITCH CHECKS CONSTRUCTED OF A SINGLE ROW OF EROSION BALES.


TYPICAL INSTALLATIONS OF
EROSION BALES / TEMPORARY
DITCH CHECKS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED

6/04/02
DATE/S/ Beth Canestra
CHIEF ROADWAY DEVELOPMENT ENGINEER


FHWA




PLAN VIEW
TYPICAL APPLICATION OF SILT FENCE



SILT FENCE



PLAN VIEW
SILT FENCE AT MEDIAN SURFACE DRAINS




JOINING TWO LENGTHS OF SILT FENCE^⑤


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1 1/8" X 1 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL



SILT FENCE TIE BACK
(WHEN REQUIRED BY THE ENGINEER)

SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 4-29-05 DATE	/S/ Beth Canestra CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA	




GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SANDBAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT, H, EXCEEDS 8 FT., POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE 02 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BED ROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



TURBIDITY BARRIER DETAIL SHOWING TYPICAL PLACEMENT AT STRUCTURES

TURBIDITY BARRIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

6/04/02


DATE

FHWA


/S/ Beth Canestra
CHIEF ROADWAY DEVELOPMENT ENGINEER

METAL APRON ENDWALLS												
PIPE DIA. (IN.)	MIN. THICK. (Inches)		DIMENSIONS (Inches)							APPROX. SLOPE		BODY
	STEEL	ALUM.	A (±1")	B (MAX.)	H (±1")	L (±1 1/2")	L1 ①	L2 ①	W (±2")			
12	.064	.060	6	6	6	21	12	17 1/2	24	2 1/2 to 1		1 Pc.
15	.064	.060	7	8	6	26	14	21 3/4	30	2 1/2 to 1		1 Pc.
18	.064	.060	8	10	6	31	15	28 1/4	36	2 1/2 to 1		1 Pc.
21	.064	.060	9	12	6	36	18	29 5/8	42	2 1/2 to 1		1 Pc.
24	.064	.075	10	13	6	41	18	37 1/4	48	2 1/2 to 1		1 Pc.
30	.079	.075	12	16	8	51	18	52 1/4	60	2 1/2 to 1		1 Pc.
36	.079	.105	14	19	9	60	24	59 3/4	72	2 1/2 to 1		2 Pc.
42	.109	.105	16	22	11	69	24	75 5/8	84	2 1/2 to 1		2 Pc.
48	.109	.105	18	27	12	78	24	81	90	2 1/4 to 1		3 Pc.
54	.109	.105	18	30	12	84	30	85 1/2	102	2 1/4 to 1		3 Pc.
60	.109x	.105x	18	33	12	87	—	—	114	2 to 1		3 Pc.
66	.109x	.105x	18	36	12	87	—	—	120	2 to 1		3 Pc.
72	.109x	.105x	18	39	12	87	—	—	126	2 to 1		3 Pc.
78	.109x	.105x	18	42	12	87	—	—	132	1 1/2 to 1		3 Pc.
84	.109x	.105x	18	45	12	87	—	—	138	1 1/2 to 1		3 Pc.
90	.109x	.105x	18	37	12	87	—	—	144	1 1/2 to 1		3 Pc.
96	.109x	.105x	18	35	12	87	—	—	150	1 1/2 to 1		3 Pc.

* EXCEPT CENTER PANEL
SEE GENERAL NOTES




REINFORCED
EDGE (SEE
SECTION A-A)



END CORNER PLATES MAY
BE FASTENED TO APRON
PROPER BY BOLTS, RIVETS,
OR RESISTANCE SPOT
WELDS WHICH WILL HOLD
THE SURFACES TIGHTLY
TOGETHER


TOE PLATE (SAME THICKNESS
AND METAL AS APRON) SHALL
BE FURNISHED WHEN CALLED
FOR ON THE PLANS




SIDE ELEVATION
METAL ENDWALLS

REINFORCED CONCRETE APRON ENDWALLS												
PIPE DIA. (IN.)	DIMENSIONS (Inches)							APPROX. SLOPE				
	T	A	B	C	D	E	G					
12	2	4	24	48 1/8	72 1/8	24	2	3 to 1				
15	2 1/4	6	27	46	73	30	2 1/4	3 to 1				
18	2 1/2	9	27	46	73	36	2 1/2	3 to 1				
21	2 3/4	9	36	37 1/2	73 1/2	42	2 3/4	3 to 1				
24	3	9 1/2	43 1/2	30	73 1/2	48	3	3 to 1				
27	3 1/4	10 1/2	49 1/2	24	73 1/2	54	3 1/4	3 to 1				
30	3 1/2	12	54	19 3/4	73 1/2	60	3 1/2	3 to 1				
36	4	15	63	34 3/4	97 3/4	72	4	3 to 1				
42	4 1/2	21	63	35	98	78	4 1/2	3 to 1				
48	5	24	72	26	98	84	5	3 to 1				
54	5 1/2	27	65	33 1/4-35	98 1/4-100	90	5 1/2	2 1/2 to 1				
60	6	30-35	60	39	99	96	5	2 to 1				
66	6 1/2	24-30	72-78	21-27	99	102	5 1/2	2 to 1				
72	7	24-36	78	21	99	108	6	2 to 1				
78	7 1/2	24-36	78	21	99	114	6 1/2	2 to 1				
84	8	36	90 1/2	21	111 1/2	120	6 1/2	1 1/2 to 1				
90	8 1/2	41	87 1/2	24	111 1/2	132	6 1/2	1 1/2 to 1				


* MINIMUM
** MAXIMUM



PLAN




END VIEW




LONGITUDINAL SECTION
CONCRETE ENDWALLS


1" WIDE, 12 GA. (0.109"
THICK) GALVANIZED STRAP
WITH STANDARD 6" X 1/2"
BAND BOLT AND NUT




ALTERNATE FOR TYPE 1 CONNECTION
END SECTION CONNECTOR STRAP




TYPE 1
FOR 12" THRU 24" CORR. PIPE



TYPE 2
FOR 30" THRU 96" CORR. PIPE



TYPE 3
FOR 42" THRU 96" CORR. PIPE



TYPE 5
ALTERNATE FOR:
ALL SIZES CORRUGATED CIRCULAR PIPE


NOTE: DIMPLED BAND FITS OVER OUTSIDE OF ENDWALL,
AND CORRUGATED BAND FITS INSIDE ENDWALL.
DIMPLED BAND MAY BE USED WITH HELICALLY
CORRUGATED PIPE.

FOR CIRCUMFERENTIALLY CORRUGATED PIPE USE
ENDWALL CONNECTION DETAILS 1, 2, 3 OR 5
AS APPLICABLE.

FOR HELICALLY CORRUGATED PIPE USE ENDWALL
CONNECTION DETAILS 1, 2 OR 5.

FOR HELICALLY CORRUGATED PIPES WITH TWO
CIRCUMFERENTIAL CORRUGATIONS AT EACH END
USE ENDWALL CONNECTION DETAILS 1, 2 OR 3.

CONNECTION DETAILS



SECTION A-A

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON
THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE
STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

CONCRETE CULVERT ENDWALLS MAY NOT BE USED WITH GALVANIZED STEEL
OR ALUMINUM CULVERT PIPE OR VISE VERSA. GALVANIZED STEEL OR
ALUMINUM ENDWALLS SHALL NORMALLY BE INSTALLED ON CULVERT PIPE
OF THE SAME METAL.


ALL THREE PIECE STEEL APRON ENDWALLS FOR 60" DIAMETER PIPE AND
LARGER SHALL HAVE 0.109" SIDES AND 0.138" CENTER PANELS. ALL
THREE PIECE ALUMINUM APRON ENDWALLS FOR 60" DIAMETER PIPE AND
LARGER SHALL HAVE 0.105" SIDES AND 0.134" CENTER PANELS. THE WIDTH
OF CENTER PANELS SHALL BE GREATER THAN 20 PERCENT OF THE PIPE
PERIMETER.

LAP SEAMS SHALL BE TIGHTLY JOINED BY GALVANIZED RIVETS OR BOLTS
FOR STEEL UNITS AND ALUMINUM RIVETS AND BOLTS FOR ALUMINUM UNITS.
FOR THE 60" THROUGH 96" DIAMETER APRON ENDWALL SIZES, THE REINFORCED
EDGES AND CENTER PANEL SEAMS SHALL BE FURTHER REINFORCED WITH
GALVANIZED STEEL OR ALUMINUM STIFFENER ANGLES. THE ANGLES SHALL BE
ATTACHED BY GALVANIZED NUTS AND BOLTS FOR STEEL UNITS AND ALUMINUM
NUTS AND BOLTS FOR ALUMINUM UNITS.


WHERE TWO OR MORE PIPES WITH APRON ENDWALLS ARE LAID ADJACENT
TO EACH OTHER, THEY SHALL BE SEPARATED BY A DISTANCE SUFFICIENT
TO PROVIDE A MINIMUM CLEARANCE OF 6 INCHES BETWEEN APRON ENDWALLS.

① FOR PIPE SIZES UP TO 60" DIAMETER, A 180° ROLLED EDGE MAY BE USED
INSTEAD OF STEEL ROD REINFORCEMENT. SEE SECTION A-A.

APRON ENDWALLS FOR CULVERT PIPE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 11/30/94 DATE	/S/ Rory L. Rhinesmith CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA	



TYPICAL NAME PLATE
(BRIDGES, CULVERTS, AND RETAINING WALLS)




**NUMBERING DESIGNATION
MULTI-UNIT STRUCTURES**

GENERAL NOTES


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.




SECTION A-A



ALTERNATE LUG

- ① ADHERE ANCHOR LUG TO PRECAST RETAINING WALL WITH EPOXY RESIN.




ALTERNATE LUG
(FOR ATTACHMENT TO PRECAST STRUCTURES)


**NAME PLATE
(STRUCTURES)**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
3/26/10
DATE
/S/ Scot Becker
CHIEF STRUCTURAL DEVELOPMENT ENGINEER
FHWA



**SKewed APPROACH
(PAVEMENT MORE THAN 2 LANES)**



**SKews > 20°
(PAVEMENT WIDTH ≤ 30')**




**SKews ≤ 20°
(PAVEMENT WIDTH ≤ 30')
APPROACH SLAB AND ADJACENT PAVEMENT**


* (RS) = REINFORCED CONCRETE SLAB
* (PS) = PAVED CONCRETE SHOULDER OR CONCRETE DRAINAGE SLAB
(SEE DETAILS ELSEWHERE IN THE PLAN)
* (NRS) = NON-REINFORCED CONCRETE SLAB

*** STANDARD DOWEL BAR DIAMETER
(SEE SDD 13C11, & SDD 13C13)


- (A) STANDARD CONTRACTION JOINT NORMAL TO ℓ OR ℓ_c
(B) STANDARD LONGITUDINAL JOINT WITH TIE BARS.
(C) 1½" EXPANSION JOINT WITH DOWEL BARS NORMAL TO ℓ OR ℓ_c



**SECTION A-A
REINFORCEMENT POSITIONING DETAIL**



**SECTION C-C
TRANSITION DETAIL
APPROACH SLAB TO ADJACENT PAVEMENT**




**SECTION D-D
CONTRACTION JOINT**

GENERAL NOTES


THE CONTRACTOR MAY SPLICE NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLICE PER BAR. THE LENGTH OF LAP IS 20 INCHES.

TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.

- THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2'-0" C-C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
- THE CONTRACTOR MAY OMIT TIE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
- DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
- USE A JOINT SEALANT MEETING THE REQUIREMENTS OF ASTM D6690.
- PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.



**SECTION B-B
BEND DETAIL
BOTTOM REINFORCEMENT**




EXPANSION JOINT DETAIL

CONCRETE PAVEMENT APPROACH SLAB


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June, 2015
DATE
FWHA

/S/ Peter Kemp, P.E.
PAVEMENT SUPERVISOR



BRIDGE APPROACHES



SECTION E-E
FOOTING DETAIL
STRUCTURAL APPROACH SLAB TO CONCRETE BRIDGE APPROACH

GENERAL NOTES

ALL PROJECTS THAT INVOLVE A STRUCTURAL APPROACH SLAB WILL ALSO HAVE A CONCRETE PAVEMENT APPROACH SLAB.

- ① SEE BRIDGE PLAN.
- ② CONFORM TO SHEET 13 B 2(A) FOR CONCRETE PAVEMENT APPROACH SLAB DETAILS.
- ③ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.

- ③ 1 1/2" EXPANSION JOINT WITH DOWEL BARS NORMAL TO R_L OR C_L
- ④ 1 1/2" EXPANSION JOINT (NO DOWELS)

STRUCTURAL APPROACH SLAB
AND CONCRETE PAVEMENT
APPROACH SLAB

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June, 2015
DATE
/S/ Peter Kemp, P.E.
PAVEMENT SUPERVISOR
FHWA

6

S.D.D. 14 B 15-8a

- 6

S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a




S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a

S.D.D. 14 B 15-8a



S.D.D. 14 B 15-8a




FRONT VIEW

POST SPACING STANDARD INSTALLATION

SECTION THRU W BEAM




FRONT VIEW
BEAM SPLICE AT WOOD POST
AND POST MOUNTING DETAIL




FRONT VIEW

POST SPACING FOR LONGER POST
AT HALF POST SPACING W BEAM (LHW)



FRONT VIEW
BEAM SPLICE AT STEEL POST

TYPICAL SPLICING DETAILS
OF STEEL PLATE BEAM GUARD




NESTED W BEAM (NW)


USE ALL OTHER STANDARD BEAM GUARD DETAILS FOR
CONSTRUCTING NESTED W BEAM (NW)

REFLECTOR SPACING^⑨

	BEAM GUARD LENGTH	REFLECTOR SPACING	NO. SURFACES REFLECTORIZED	MIN. NO. REFLECTORS
ONE WAY TRAFFIC	< 200'	50' C-C	1	3
	> 200'	100' C-C	1	3
TWO WAY TRAFFIC	< 200'	25' C-C	1 ^⑩	6
	> 200'	50' C-C	1 ^⑩	6
TWO WAY TRAFFIC	< 200'	50' C-C	2 ^⑪	3
	> 200'	100' C-C	2 ^⑪	3



ONE SIDED REFLECTOR DETAIL AND TYPICAL INSTALLATION




STEEL PLATE BEAM GUARD,
CLASS "A",
INSTALLATION & ELEMENTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


GENERAL NOTES

- ⑧ PROVIDE SILVER REFLECTIVE SHEETING ON ALL REFLECTORS EXCEPT THOSE LOCATED ALONG THE LEFT EDGE OF ONE-WAY ROADWAYS, WHICH SHALL BE PROVIDED WITH YELLOW REFLECTIVE SHEETING. SHEETING IS TYPE H. SEE STANDARD SPECIFICATION 637.
- ⑨ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
- ⑩ REVERSE EVERY OTHER REFLECTOR FOR 2-WAY VISIBILITY. THE CONTRACTOR MAY FURNISH TWO-SIDED REFLECTORS IN LIEU OF ONE-SIDED REFLECTORS.
- ⑪ PROVIDE AN ANGLE OF BEND OF 90° ± 1° FOR TWO-SIDED REFLECTORS.
- ⑫ 8 - 5/8" φ X 2" BUTTON HEAD BOLTS WITH OVAL SHOULDERS & RECESS NUTS.
- ⑬ 5/8" DIA. BUTTON HEAD BOLT AND RECESS NUT WITH 5/8" DIA. F844 FLAT WASHER UNDER NUT.



DETAIL FOR DOUBLE BLOCKS

THE NUMBER OF DOUBLE BLOCK POSTS
WITHIN A BARRIER RUN IS UNLIMITED




DETAIL FOR TRIPLE BLOCKS


TRIPLE BLOCK DETAIL IS LIMITED TO ONE
LOCATION WITHIN A BEAM GUARD RUN.

NOTES: USE DOUBLE OR TRIPLE BLOCKS WHEN UNDERGROUND OBSTACLES
PREVENT THE POST FROM BEING INSTALLED.

DO NOT USE EXTRA BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND
SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION
DISTANCE OF THE BARRIER.



PLAN VIEW BEAM LAPPING DETAIL





POST DRIVING FOR CONTINUOUS UNDERGROUND OBSTRUCTION

STEEL PLATE BEAM GUARD,
CLASS "A",
INSTALLATION & ELEMENTS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2014
DATE
FHWA


/S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER



TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE



THRIE BEAM TERMINAL CONNECTOR



THRIE BEAM SPLICE





PLATE WASHER DETAIL



SECTION THRU THRIE BEAM RAIL ELEMENT


GENERAL NOTES

BOLT THE THRIE BEAM TO ALL POSTS AND BLOCKOUTS. DRILL OR PUNCH BOLT HOLES IN THE BEAM IF THE POST SPACING IS LESS THAN 6'-3".

DO NOT USE STEEL POSTS AND NOTCHED PLASTIC BLOCKOUTS IN THE STEEL THRIE BEAM STRUCTURAL APPROACH AND THE TRANSITION SECTION OF STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATIONS.

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2 1/2", AND 12" DIAMETER AROUND POST. SEE 14B15 FOR MORE DETAILS.

- ① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.
- ② MINIMUM EMBEDMENT SHALL BE 4'-0". WHERE EXISTING CONDITIONS DO NOT PERMIT THE APPROPRIATE EARTHWORK SHOWN ON THE PLAN TYPICAL SECTIONS OR DETAILS, THE ENGINEER MAY ALLOW THE REDUCTION OR ELIMINATION OF THE 2 FOOT DISTANCE TO THE HINGE POINT. OTHERWISE BUILD AS THE PLAN SHOWS OR AS THE ENGINEER DIRECTS. IF THE 2 FOOT DISTANCE TO THE HINGE POINT IS REDUCED OR ELIMINATED, INCREASE THE POST EMBEDMENT DEPTH TO 4'-6" OR MORE.
- ③ POST BOLTS ARE 5/8" DIAMETER ASTM A307 BUTTON HEAD BOLT. A POST BOLT REQUIRES A 5/8" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX AND A 5/8" DIAMETER F844 FLAT WASHER. LENGTH OF POST BOLT MAY VARY.
- ④ ALL WOOD POSTS MUST BE 6" X 8" AND AT LEAST 7'-0" LONG.



STEEL THRIE BEAM STRUCTURE APPROACH

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED


8/31/2012
DATE

FHWA


/s/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER

GENERAL NOTES


① VARY THIS DIMENSION DEPENDING ON ABUTMENT TYPE, WINGWALL DETAILS, AND ANGLE OF SKEW. PLACE THE FIRST WOOD POST OFF THE BRIDGE SHALL BE AS CLOSE AS FEASIBLE TO THE STEEL END POST.




FRONT VIEW




PLAN VIEW
BACK-UP PLATE DETAIL, TYPE "M"




FRONT VIEW
ANCHOR PLATE DETAIL, TYPE "M"




SECTION I-I




SECTION H-H



FRONT VIEW
ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"



FRONT VIEW



PLAN VIEW
THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"

**STEEL THRIE BEAM STRUCTURE
APPROACH CONNECTION TO
BRIDGE RAILING TYPE "M"**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
8/31/2012
DATE
/S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER
FHWA

BILL OF MATERIALS

NOTE NO.	QTY.	DESCRIPTION
①	4	WOOD BREAKAWAY TERMINAL POST: 5 1/2" X 7 1/2" X 3'-9"
②	**	STEEL TUBE: OPTION 1 - QUANTITY OF 4 TS 8" X 6" X 0.188", 4'-6" LONG OR OPTION 2 - QUANTITY OF 2 TS 8" X 6" X 0.188", 6'-0" AND 2 TS 8" X 6" X 0.188", 4'-6" LONG
③	2	SOIL PLATE: 2'-0" X 1'-6" X 1/4" **
④	4	WOOD BREAKAWAY CRT POST: 6" X 8" X 6'-0"
⑤	6	WOOD OFFSET BLOCKS: 6' X 8" X 1'-2"
⑥	1	PIPE SLEEVE: 2" X 5 1/2" STANDARD PIPE
⑦	1	BEARING PLATE
⑧	1	BCT CABLE ASSEMBLY
⑨	1	CABLE ANCHOR BOX
⑩	1	STRUT & YOKE
⑪	1	STEEL PLATE BEAM, END PANEL 12 GA. 13'-6 1/2" LONG FOR SKT-350, ET-2000 AND ET-2000 PLUS
⑫	3	STEEL PLATE BEAM: 12 GA. 13'-6 1/2"
⑬	1	ET-2000/ET-2000 PLUS GUARDRAIL EXTRUDER OR SKT-350 IMPACT HEAD: AS FURNISHED BY MANUFACTURER
⑭	1	0.040" ALUMINUM SHEET WITH REFLECTIVE SHEETING TYPE F PER SECTION 637 OF THE STANDARD SPECIFICATIONS
⑮	1	E.A.T. MARKER POST

GENERAL NOTES

FOLLOW MANUFACTURE'S BOLTING RECOMMENDATIONS, IF NONE ARE AVAILABLE, INSTALL 3/8" ϕ X 1'-6" BUTTON HEAD BOLTS AT ALL POSTS EXCEPT FOR POST 1.

(A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL), AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.

(B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED.

(C) THE 13 SLOT FIRST RAIL PANEL MAY BE USED IN LIEU OF THE 3 SLOT RAIL PANEL ON SKT-350 ONLY.

(D) THE TOP OF THE STEEL TUBE ON POSTS 1 THROUGH 4 SHALL NOT BE MORE THAN 3" ABOVE THE FINISH GROUND ELEVATION.

(E) THE CENTER OF THE UPPER 3/2" DIAMETER HOLE ON POST 5 THROUGH 8 SHALL BE 3/4" ABOVE THE FINISHED GROUND LINE.


(F) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF-TAPPING SCREWS, ONE SCREW PER CORNER.

STEEL POSTS SHALL NOT BE ALLOWED FOR USE WITH ENERGY ABSORBING TERMINALS.


DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.

* DO NOT ATTACH BLOCKOUTS TO POSTS 1 AND 2.


** SDD SHOWS 4 - 54 INCH STEEL TUBES WITH SOIL PLATES INSTALLED ON POST 1 AND POST 2. POST 3 AND 4 DO NOT NEED SOIL PLATES. AN ALTERNATIVE INSTALLATION WOULD CONSIST OF 2 - 72 INCH STEEL TUBES ON POST 1 AND POST 2 AND 54 INCH SOIL TUBES ON POSTS 3 AND 4. THE ALTERNATIVE INSTALLATION DOES NOT REQUIRE SOIL PLATES.




SECTION C-C
TYPICAL AT POST NOS. 6, 8




SECTION B-B
TYPICAL AT POST NO. 2 *




PLAN




ELEVATION



DETAIL "A"




SECTION A-A
TYPICAL AT POST NO. 1 *




DETAIL "B"

STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




⑩ STRUT DETAIL (SKT-350)




⑨ CABLE ANCHOR BOX (SKT-350)


(SKT-350)



SECTION B-B




⑨ CABLE ANCHOR BOX (ET-2000/ET-2000 PLUS)




⑩ STRUT DETAIL (ET-2000/ET-2000 PLUS)

(ET-2000/ET-2000 PLUS)




③ SOIL PLATE
(SKT-350, ET-2000/ET-2000 PLUS)




⑦ STEEL BEARING PLATE
(SKT-350, ET-2000/ET-2000 PLUS)

STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



② **72" STEEL TUBE**
(POSTS NO. 1-4)




② **54" STEEL TUBE**
(POSTS NO. 1-4)



① **TERMINAL POST**
(POSTS NO. 1-4)

WOOD BREAKAWAY POSTS




④ **CRT POST**
(POSTS NO'S 5-8)

GENERAL NOTES

WHEN ROCK IS ENCOUNTERED DURING EXCAVATION, A 12 INCH DIA. POST HOLE EXTENDING 20 INCHES DEEP INTO THE ROCK MAY BE USED IF APPROVED BY THE ENGINEER. GRANULAR MATERIAL SHALL BE PLACED IN THE BOTTOM OF THE HOLE APPROXIMATELY 2 1/2" INCHES DEEP TO PROVIDE DRAINAGE. THE SOIL TUBES SHALL BE FIELD CUT TO LENGTH, PLACED IN THE HOLE AND BACKFILLED WITH ADEQUATELY COMPACTED MATERIAL EXCAVATED FROM THE HOLE.


SEE APPROVED PRODUCTS LIST FOR ACCEPTABLE E. A. T. MARKER POST.

ⓐ 1/2" DIA. X 3" LAG BOLT WITH WASHER.




⑤ **WOOD OFFSET BLOCK**
REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 & 2

TYPE H
YELLOW REFLECTIVE
SHEETING 3" X 9"
SEE STANDARD
SPECIFICATION 637




ET-2000 PLUS ONLY




ET-2000 AND SKT-350

⑭ **REFLECTIVE SHEETING DETAILS**




FRONT VIEW




SIDE VIEW

⑮ **E.A.T. MARKER POST**



TYPICAL INSTALLATION OF E.A.T. MARKER POST BACKSIDE OF POST NO. 1
(E.A.T. AND RAIL REMOVED FOR CLARITY)



SECTION A-A

**STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2014
DATE
FHWA

/S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER

6


- S.D.D. 14 B 42-3a**



S.D.D. 14 B 42-3a




S.D.D. 14 B 42-3a




FRONT VIEW

POST SPACING STANDARD INSTALLATION




FRONT VIEW

HALF POST SPACING (HS) AND HALF POST SPACING WITH LONGER POSTS (K)




FRONT VIEW



QUARTER POST SPACING (QS)



FRONT VIEW AT WOOD POST



FRONT VIEW AT STEEL POST




ONE SIDED REFLECTOR DETAIL AND TYPICAL INSTALLATION

GENERAL NOTES


- ⑦ PROVIDE SILVER REFLECTIVE SHEETING ON ALL REFLECTORS EXCEPT THOSE LOCATED ALONG THE LEFT EDGE OF ONE-WAY ROADWAYS, WHICH SHALL BE PROVIDED WITH YELLOW REFLECTIVE SHEETING. SHEETING IS TYPE H. SEE STANDARD SPECIFICATION 637.
- ⑧ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL. RAIL SPLICE LOCATIONS ARE THE ONLY ACCEPTABLE LOCATIONS FOR REFLECTORS.
- ⑨ REVERSE EVERY OTHER REFLECTOR FOR 2-WAY VISIBILITY. THE CONTRACTOR MAY FURNISH TWO-SIDED REFLECTORS IN LIEU OF ONE-SIDED REFLECTORS.
- ⑩ PROVIDE AN ANGLE OF BEND OF $90^\circ \pm 1^\circ$ FOR TWO-SIDED REFLECTORS.
- ⑪ 25 FEET OF HALF POST SPACING IS REQUIRED ON APPROACH AND DEPARTURE ENDS OF QUARTER POST SPACING.

POST BOLTS ARE A $\frac{5}{8}$ " DIAMETER ASTM A307 GUARDRAIL BOLT. A POST BOLT REQUIRES $\frac{5}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT AND $\frac{5}{8}$ " DIAMETER F844 FLAT WASHER. POST BOLTS MAY BE LONGER IF MULTIPLE BLOCKOUTS ARE BEING USED.

GUARD RAIL SPLICE BOLTS ARE A $\frac{5}{8}$ " DIAMETER ASTM A307 GUARDRAIL HEAD BOLT. A GUARDRAIL SPLICE BOLT REQUIRES $\frac{5}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT.



FRONT VIEW
MID-SPAN BEAM SPLICE




SECTION THRU W-BEAM RAIL

REFLECTOR SPACING

	BEAM GUARD LENGTH	REFLECTOR SPACING	NO. SURFACES REFLECTORIZED	MIN. NO. REFLECTORS
ONE WAY TRAFFIC	< 200'	50' C-C	1	3
	> 200'	100' C-C	1	
TWO WAY TRAFFIC	< 200'	25' C-C	1 ⑨	6
	> 200'	50' C-C	1	
TWO WAY TRAFFIC	< 200'	50' C-C	2 ⑩	3
	> 200'	100' C-C	2	


MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



DETAIL FOR 16" BLOCKOUT DEPTH


IT IS ACCEPTABLE TO USE BLOCKOUTS UP TO 16" DEEP TO INCREASE THE POST OFFSET TO AVOID UNDERGROUND OBSTACLES. THERE IS NO LIMIT TO THE NUMBER OF POSTS THAT CAN HAVE ADDITIONAL BLOCKOUTS UP TO 16" DEEP.




DETAIL FOR 36" BLOCKOUT DEPTH

NOTES: UNDER SPECIAL CIRCUMSTANCES, SUCH AS AVOIDING OBSTACLES THAT ARE NOT RELOCATED, IT IS ACCEPTABLE TO INSTALL ADDITIONAL BLOCKOUTS TO OBTAIN UP TO 36" DEPTH FOR ONE OR TWO POSTS IN A SECTION OF GUARDRAIL.


DO NOT USE 16" OR 36" BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION DISTANCE OF THE BARRIER.




POST BOLT TABLE




ALTERNATE BOLT HEAD




POST BOLT
AND RECESS NUT




PLAN VIEW
BEAM LAPPING DETAIL



POST DRIVING FOR CONTINUOUS
UNDERGROUND OBSTRUCTION



SIDE VIEW



TOP VIEW

ALTERNATE WOOD
BLOCKOUT DETAIL

MIDWEST GUARDRAIL SYSTEM
(MGS) GUARDRAIL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2014
DATE /S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER
FHWA

GENERAL NOTES

- (A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL), AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.
- (B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED.
- (C) DIFFERENT MANUFACTURES REQUIRE DIFFERENT PERFORATED W-BEAM RAIL END PANELS. SEE MANUFACTURES INFORMATION.
- (D) THE TOP OF THE STEEL TUBE ON POST 1 AND POST 2 SHALL NOT BE MORE THAN 3" ABOVE THE FINISH GROUND ELEVATION.
- (E) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF-TAPPING SCREWS, ONE SCREW PER CORNER.
- (G) 1/2" DIAMETER X 3" LONG LAG BOLT AND WASHER.
- (H) HARDWARE VARIES BETWEEN DIFFERENT MANUFACTURES. SEE MANUFACTURE'S DRAWING FOR INFORMATION.
- (I) DIMENSIONS MAY VARY. SEE MANUFACTURE'S INFORMATION.


SEE SDD 14B42 FOR MORE INFORMATION.


* DO NOT ATTACH BLOCKOUTS TO POSTS 1 AND 2.

DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.




W-BEAM RAIL SPLICES ARE LOCATED AT POST NUMBER 3, AND BETWEEN POST 5 AND 6, BETWEEN POSTS 7 AND 8, AND MIDDLE OF THE SPAN AFTER POST 9.

THE CENTER OF THE UPPER 3/2" DIAMETER HOLE ON POST NUMBER 3 THROUGH POST 9 IS TO BE FLUSH WITH THE GROUND LINE UP TO A MAXIMUM OF 2" ABOVE GROUND LINE.






9 H
GENERIC GROUND STRUT




8 H
GENERIC ANCHOR CABLE BOX

BILL OF MATERIALS


PART NO.	DESCRIPTION
MATERIALS PROVIDED BY MGS EAT MANUFACTURER. SEE MANUFACTURER'S DETAILS FOR MORE INFORMATION.	
①	WOOD BREAKAWAY POST
②	6" X 8" X 0.188", 6'-0" LONG FOUNDATION TUBE AT POSTS 1 AND 2
③	WOOD CRT
④	WOOD BLOCKOUT
⑤	PIPE SLEEVE
⑥	BEARING PLATE
⑦	BCT CABLE ASSEMBLY
⑧	ANCHOR CABLE BOX
⑨	GROUND STRUT
⑩	PERFORATED W-BEAM RAIL END PANEL, 12'-6" LONG.
⑪	STANDARD W-BEAM RAIL. MULTIPLE SECTIONS REQUIRED. SECTIONS VARY IN LENGTH.
⑫	END SECTION EAT
⑬	0.040" ALUMINUM SHEET WITH REFLECTIVE SHEETING TYPE F PER SECTION 637 OF THE STANDARD SPECIFICATIONS
⑭	EAT MARKER POST - YELLOW (SEE APPROVED PRODUCTS LIST)




⑥
BEARING PLATE




FOUNDATION TUBE ②




POSTS NUMBER 1 AND 2
WOOD BREAKAWAY POST ①



POSTS NUMBER 3-9
WOOD CRT POST ③




SIDE VIEW




TOP VIEW

ALTERNATE WOOD
BLOCKOUT DETAIL





WOOD BLOCKOUT ④
REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 & 2


TYPE H
YELLOW REFLECTIVE
SHEETING 3" X 9".
SEE STANDARD
SPECIFICATION 637.




GENERIC REFLECTIVE SHEETING ⑬ ①



FRONT VIEW
SIDE VIEW
E.A.T. MARKER POST ⑭



TYPICAL INSTALLATION OF E.A.T.
MARKER POST BACKSIDE OF POST NO. 1
(E.A.T. AND RAIL REMOVED FOR CLARITY)




SECTION A-A


MIDWEST GUARDRAIL SYSTEM
ENERGY ABSORBING TERMINAL
(MGS)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2014 /S/ Jerry H. Zogg
DATE ROADWAY STANDARDS DEVELOPMENT
ENGINEER
FHWA



TWO WAY TRAFFIC



ONE WAY TRAFFIC

Ⓣ THRIE BEAM CONNECTION

Ⓦ W-BEAM CONNECTION WHEN REQUIRED

GENERAL NOTES

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2½", AND 12" DIAMETER AROUND POST. SEE 14B42 FOR MORE DETAILS.


TRANSITION USES STEEL POSTS ONLY.

SEE STANDARD DETAIL DRAWING 14 B 42 FOR MORE INFORMATION.


① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.

② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.

TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE



PLAN VIEW



ELEVATION VIEW


MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES


- 2 OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- 3 WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 10D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- 4 TOLERANCE FOR TOP OF W-BEAM RAIL IS $\pm 1"$.




SECTION A-A
POSTS 1-5



SECTION D-D
POSTS 12-17



SECTION B-B
POST 6



SECTION C-C
POSTS 7-11







PLATE WASHER DETAIL



SPlice DETAIL




THRIE BEAM
TERMINAL CONNECTOR




SECTION THRU THRIE
BEAM RAIL ELEMENT

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




W-BEAM TO THRIE BEAM TRANSITION SECTION




6'-3" THRIE BEAM SECTION




12'-6" THRIE BEAM SECTION




STEEL POSTS 1-5



STEEL POSTS 6-17



BLOCKOUT POSTS 1-5



BLOCKOUT POSTS 6-17


GENERAL NOTES

STEEL POSTS ARE W6X9 OR W6X8.5.

BOLT HOLES FOR POST ARE ON FRONT AND OF SIDE OF POST.

③ WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.

⑤ WOOD BLOCKS MAY BE CONSTRUCTED OUT OF 2 WOOD BLOCKS. SEE ALTERNATE WOOD BLOCK DETAIL.




MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES

④ TOLERANCE FOR TOP OF W-BEAM RAIL IS $\pm 1"$.




FRONT VIEW




PLAN VIEW

BACK-UP PLATE DETAIL, TYPE "M"




FRONT VIEW


ANCHOR PLATE DETAIL, TYPE "M"



SECTION M-M




SECTION L-L




FRONT VIEW

ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"



FRONT VIEW




PLAN VIEW

THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June, 2015
DATE
/S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER
FHWA



DETAIL A
MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE GREATER THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

DETAIL B
MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE LESS THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

LEGEND

- SIGN ON PERMANENT SUPPORT
- ⊥ TYPE III BARRICADE
- ⊥ TYPE III BARRICADE WITH ATTACHED SIGN
- Ⓐ TYPE "A" WARNING LIGHT (FLASHING)


WORK AREA

DETOUR EAST
M4-8
M3-X
M1-4
M1-5A
M1-6

M05-1
M06-1

FLAGS, 16" X 16" MIN., (ORANGE)

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750




DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦


**BARRICADES AND SIGNS
FOR
MAINLINE CLOSURES**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

8/2013 DATE /S/ Travis Feltes
STATE TRAFFIC ENGINEER OF DESIGN
FHWA



DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW



DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW

SEE SDD 15C2-SHEET "a" FOR LEGEND

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION OR, FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL D FOR FULL ROAD CLOSURES.

TYPE "A" LOW-INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11-2, R11-3, M4-9, R11-4 AND R10-61 SIGNS PLACED ON BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE OR BOTTOM RAILS.

"WO AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11-2 SHALL BE 48" X 30".

R11-3, R11-4 AND R10-61 SHALL BE 60" X 30".

M4-9 SHALL BE 30" X 24".

M3-X SHALL BE 24" X 12". (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS.)

M4-8 SHALL BE 24" X 12". (30" X 15" IF NEEDED TO MATCH EXISTING SIGNS.)

M1-4, M1-5A, AND M1-6 SHALL BE 24" X 24". (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS.)

M05-1 AND M06-1 SHALL BE 21" X 21". (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS.)

D1-X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.


R1-1 SHALL BE 36" X 36".

- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8-FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL D.
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE LANE CLOSURE BARRICADE DETAIL E.
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11-2 AND R11-3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

8/2013 /S/ Travis Feltes
DATE STATE TRAFFIC ENGINEER OF DESIGN
FHWA




SITUATION 1

WARRANTING CRITERIA:

BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET

DISTANCE TABLE

POSTED OR 85th PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	750'




*OMIT ON ONE-WAY TRAVELLED WAYS

SITUATION 2

WARRANTING CRITERIA:

1. BRIDGE WIDTH IS AT LEAST 24 FEET AND
2. BRIDGE IS LESS THAN 6 FEET WIDER (ON EACH SIDE) THAN APPROACH TRAVEL LANES.




OBJECT MARKER PLACEMENT

GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

PAVEMENT MARKING SHOWN ON THIS DRAWING IS NOT REQUIRED UNLESS OTHERWISE SPECIFIED IN THE CONTRACT. WHEN SPECIFIED, PAVEMENT MARKING SHALL CONFORM TO THIS DRAWING AND OTHER CONTRACT REQUIREMENTS.

- ① MINIMUM DISTANCE UNLESS OTHERWISE SHOWN ON THE PLAN.
- ② FACE OF OBJECT MARKERS W5-52R, AND W5-52L SHALL BE COVERED WITH TYPE F REFLECTIVE SHEETING.
- ③ LOCATE OBJECT MARKER POST(S) BEHIND GUARDRAIL WHEN PRESENT.



SIGN PLACEMENT

SIGNING & MARKING FOR TWO LANE BRIDGES


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED


3-2014
DATE

FHWA

/S/ Travis Fettes
STATE TRAFFIC ENGINEER OF DESIGN




TWO WAY TRAFFIC




ONE WAY TRAFFIC

PERMANENT PAVEMENT MARKING



TWO WAY TRAFFIC



ONE WAY TRAFFIC

TEMPORARY (INTERMEDIATE) PAVEMENT MARKING
(SHOWS CYCLE FOR TEMPORARY CENTER LINE OR TEMPORARY LANE LINE MARKING)


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

- 1 HALF CYCLE LENGTHS (25'±) WITH 2' MINIMUM STRIPE LENGTHS SHALL BE PROVIDED ON ROADWAYS (INCLUDING TEMPORARY TRAVELED WAYS) WITH REVERSE CURVATURE, CURVATURE OF OVER 5 DEGREES OR WHEN DIRECTED BY THE ENGINEER TO MARK UNUSUAL ALIGNMENT OF THE TRAVELED WAY.
- 2 NO PASSING ZONE TEMPORARY PAVEMENT MARKING IS REQUIRED TO BE PLACED, WHERE APPROPRIATE, ALONG WITH CENTERLINE TEMPORARY PAVEMENT MARKING WHEN A SAME DAY PERMANENT PAVEMENT MARKING ITEM IS INCLUDED IN THE CONTRACT.
- 3 NO PASSING ZONE MARKINGS ARE PLACED ACCORDING TO "T" MARKINGS. IF EXISTING NO PASSING ZONE W14-3 SIGNS ARE BEYOND 50 FEET IN EITHER DIRECTION, THE SIGNS SHALL BE MOVED TO THE "T" MARKINGS.
- 4 CONCRETE ONLY.

NOTE

ARROW SYMBOL (→) SHOWS DIRECTION OF TRAVEL



WET REFLECTIVE TAPE SUPPLEMENT TO
SPRAYED OR NON WET REFLECTIVE TAPE LANE LINE

LEGEND


- "T" MARKING
- POST MOUNTED SIGN

PAVEMENT MARKING
(MAINLINE)




STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
5-13-2013 /S/ Travis Feltes
DATE STATE TRAFFIC ENGINEER
FHWA

URBAN AREA



RURAL AREA (See Note 2)



POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

GENERAL NOTES

1. Signs wider than 4 feet, 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on barrier wall, see A4-10 sign plate.
3. For expressways and freeways, mounting height is 7'- 3" (±) or 6'-3" (±) depending upon existence of a sub-sign.
4. Minimum mounting height for J assemblies (A2-1S) is 7'-3" (±) or 6'-3" (±) per urban or rural detail respectively.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'- 3" (±).
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. The (±) tolerance for mounting height is 3 inches.
8. Folding signs shall be mounted at a height of 5'-3" (±) or as directed by the Engineer.
9. The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (±). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±).

✖✖ The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION
OF PERMANENT TYPE II
SIGNS ON SINGLE POSTS


WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew R. Rauch
for State Traffic Engineer

DATE 11/12/14

PLATE NO. A4-3.19



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

WOOD POSTS (4" x 4" or 4" x 6")

LAG SCREWS - 3/8" X 3"

MACHINE BOLTS - 5/16" X 6-1/2" or 7" Length w/ nuts

SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS - 3/8" X 3-1/4" Length w/ nuts


RIVETS - 9/32" (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

WASHERS (ALL POSTS) -

1-1/4" O.D. X 3/8" I.D. X 1/16" STEEL

1-1/4" O.D. X 3/8" I.D. X .080 NYLON for all Type H signs.



Washer Placement when Sign Has Other Than Type H or Type F Face



* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.

ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
for State Traffic Engineer

DATE 3/23/10 PLATE NO. A4-8.7



SIDE VIEW

GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two 1½" diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Chester J. Spang
for State Traffic Engineer

DATE 3/27/97

PLATE NO. A4-11.2

PROJECT NO: 4316-08-71

HWY: HILLCREST ROAD

COUNTY: MANITOWOC


SIGNS

SHEET NO:

E

NOTES


- 1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
- 2. Color:
 - Background - White
 - Message - Black
- 3. Message Series - D
- 4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.



R11-2B

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	48	30	1 3⁄8	1⁄2	5⁄8	8	5	4	19 3⁄4	9 3⁄4	9 7⁄8																10.0
2M	48	30	1 3⁄8	1⁄2	5⁄8	8	5	4	19 3⁄4	9 3⁄4	9 7⁄8																10.0
3	48	30	1 3⁄8	1⁄2	5⁄8	8	5	4	19 3⁄4	9 3⁄4	9 7⁄8																10.0
4	48	30	1 3⁄8	1⁄2	5⁄8	8	5	4	19 3⁄4	9 3⁄4	9 7⁄8																10.0
5	48	30	1 3⁄8	1⁄2	5⁄8	8	5	4	19 3⁄4	9 3⁄4	9 7⁄8																10.0

STANDARD SIGN	
R11-2B	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R. Rauch</i> For State Traffic Engineer
DATE 4/1/11	PLATE NO. R11-2B.2



R11-3B


NOTES

1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:
Background - White
Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals and optically adjust spacing to achieve proper balance.

** See Note 5

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	18	1 3⁄8	1⁄2	5⁄8	4	3	2 1⁄2	2	2	13 1⁄4	2 1⁄4	3	8	8	1 1⁄2	2	10 3⁄4	8 3⁄8	4 3⁄4	6 1⁄2	2	6 3⁄4				4.5
2S	60	30	1 3⁄8	1⁄2	5⁄8	6	5	4	4 1⁄4	3 3⁄8	20 1⁄8	3	5	12	13 1⁄4	1 3⁄4	3	17 3⁄8	13 1⁄8	8	10	3 1⁄2	11				12.5
2M	60	30	1 3⁄8	1⁄2	5⁄8	6	5	4	4 1⁄4	3 3⁄8	20 1⁄8	3	5	12	13 1⁄4	1 3⁄4	3	17 3⁄8	13 1⁄8	8	10	3 1⁄2	11				12.5
3																											
4																											
5																											

STANDARD SIGN R11-3B	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R. Rauch</i> for State Traffic Engineer
DATE 4/1/11	PLATE NO. R11-3B.2



R11-3C

NOTES

1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:
Background - White
Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals and optically adjust spacing to achieve proper balance.

** See Note 5

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	15	1 3/8	1/2	5/8	4	3	2 1/2	13 1/4	2 1/4	3	8	8	1 1/2	2	10 3/4											3.75
2S	60	24	1 3/8	1/2	5/8	6	5	4	20 1/8	3	5	12	13 1/4	1 3/4	3	17 3/8											10.0
2M	60	24	1 3/8	1/2	5/8	6	5	4	20 1/8	3	5	12	13 1/4	1 3/4	3	17 3/8											10.0
3																											
4																											
5																											



STANDARD SIGN
R11-3C

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
For State Traffic Engineer

DATE 4/1/11 PLATE NO. R11-3C.2

7



NOTES

- 1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
- 2. Color:
Background - Yellow
Message - Black
- 3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
- 4. Alternate colors of stripes as shown.

7


SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36				4 3⁄8	3 1⁄2	5 5⁄8	45°	4	4																3.0
2M	12	36				4 3⁄8	3 1⁄2	5 5⁄8	45°	4	4																3.0
3	18	54				6	5 1⁄2	8 1⁄2	45°	6	6 5⁄6																6.75
4																											
5																											

STANDARD SIGN
W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
for State Traffic Engineer

DATE 5/29/12 PLATE NO. W5-52.9



W20-3A

500 FT

W20-3D

1000 FT

W20-3C

1500 FT

W20-3B

1/2 MILE

W20-3G

1 MILE

W20-3F

NOTES

1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:
Background - Orange
Message - Black
3. Message Series - see note 5
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Lines 1 and 2 are Series D.
Line 3 is Series D for AHEAD and Series C for all other distances.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36		1 5/8	5/8	3/4	5	3 3/8	3 1/2	1 1/8	4	8 3/8	8 7/8	12 1/2	11	9	6	10 1/8	2 1/2	1 7/8	5 5/8	8	1 3/8	4 1/2	3 1/2	10 3/4	1 3/4	9.0
2S	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
2M	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
3	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
4	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
5	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0

STANDARD SIGN
W20-3A, B, C, D, F & G

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
For State Traffic Engineer

DATE 3/18/11 PLATE NO. W20-3.7

PROJECT NO: 4316-08-71

HWY: HILLCREST ROAD

COUNTY: MANITOWOC

SIGNS

SHEET NO:

E

TRAFFIC DATA

ADT = 590 (2016)
650 (2036)
RDS = 40 M.P.H.

DESIGN DATA

STRUCTURE IS DESIGNED FOR FUTURE WEARING
SURFACE OF 20"/SO. FT.

LIVE LOAD:

DESIGN LOADING ——— HL-93
INVENTORY RATING FACTOR ——— RF = 1.40
OPERATING RATING FACTOR ——— RF = 1.84
WISCONSIN STANDARD
PERMIT VEHICLE (Wis-SPV) ——— 250 KIPS

MATERIAL PROPERTIES:

CONCRETE MASONRY
SUPERSTRUCTURE ——— f'_c = 4,000 PSI
ALL OTHER ——— f'_c = 3,500 PSI
HIGH STRENGTH BAR STEEL
REINFORCEMENT, GRADE 60 ——— f_y = 60,000 PSI
36W" PRESTRESSED GIRDERS
CONCRETE MASONRY ——— f'_c = 8,000 PSI
STRANDS, 0.6" ϕ ULTIMATE
TENSILE STRENGTH ——— f_y = 270,000 PSI

HYDRAULIC DATA

Q_{100} ——— 2,300 C.F.S.
VELOCITY ——— 4.11 F.P.S.
HIGH WATER ——— EL. 763.83 (100 YEAR)
HIGH WATER ——— EL. 761.06 (2 YEAR)
WATERWAY AREA ——— 560 S.F.
DRAINAGE AREA ——— 82.6 SQ. MILES
OVERTOPPING FREQUENCY = N/A
SCOUR CRITICAL CODE = 8

FOUNDATION DATA

ABUTMENTS TO BE SUPPORTED ON HP 12 X 53 STEEL
PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF
220 TONS** PER PILE. ESTIMATED LENGTH = 20' AT
EACH ABUTMENT.

** THE FACTORED AXIAL RESISTANCE OF PILES IN
COMPRESSION USED FOR DESIGN IS THE REQUIRED
DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE
FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE
DRIVEN PILE CAPACITY.

LIST OF DRAWINGS

1. GENERAL PLAN
2. CROSS SECTION & QUANTITIES
3. SUBSURFACE EXPLORATION
4. WEST ABUTMENT
5. WEST ABUTMENT DETAILS
6. EAST ABUTMENT
7. EAST ABUTMENT DETAILS
8. 72W" PRESTRESSED GIRDER DETAILS
9. STEEL DIAPHRAGMS
10. SUPERSTRUCTURE
11. SUPERSTRUCTURE DETAILS
12. TUBULAR STEEL RAILING TYPE 'M'

PLAN
SINGLE SPAN 72W" PRESTRESSED GIRDER BRIDGE

ELEVATION
(LOOKING NORTH)





CONSULTANT CONTACT

KRISTOFER OLSON
OMNI ASSOCIATES, INC.
(920) 735-6900

BRIDGE OFFICE CONTACT

WILLIAM DREHER
(608) 266-8489


NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED	<i>William C. Dreher</i>	02/08/16	DATE
CHIEF STRUCTURES DESIGN ENGINEER			
STRUCTURE B-36-214			
HILLCREST ROAD OVER BRANCH RIVER			
COUNTY	MANITOWOC	TOWN	FRANKLIN
DESIGN SPEC.	AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS		LOAD HL-93
DESIGNED BY	BRE	CK'D.	KRO
DRAWN BY	BRE	CK'D.	KRO
GENERAL PLAN			SHEET 1 OF 12






NO.	STATION	DESCRIPTION	ELEV.
BM1	12+48, 29' LT	60D SPIKE IN PP* 202214 R3/2ND POLE EAST OF BRIDGE NORTH SIDE OF ROAD	791.39
BM2	6+25, 28' LT.	60D SPIKE IN PP* 202214 R7/2ND POLE WEST OF BRIDGE NORTH SIDE OF ROAD	787.68
BM3	3+81, 27' LT.	60D SPIKE IN PP* 202214 R8/3RD POLE WEST OF BRIDGE NORTH SIDE OF ROAD	796.20

ITEM NO.	BID ITEMS	UNIT	SUPER.	WEST ABUT.	EAST ABUT.	TOTALS
203.0600.S	REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS (STA 10+00)	LS	----	----	----	1
206.1000	EXCAVATION FOR STRUCTURES BRIDGES (B-36-214)	LS	----	----	----	1
210.0100	BACKFILL STRUCTURE	CY	----	275	275	550
502.0100	CONCRETE MASONRY BRIDGES	CY	195	39	39	273
502.3200	PROTECTIVE SURFACE TREATMENT	SY	600	----	----	600
503.0172	PRESTRESSED GIRDER TYPE 172W-INCH	LF	568	----	----	568
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	----	1,870	1,870	3,740
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	28,990	1,910	1,910	32,810
506.2605	BEARING PADS ELASTOMERIC NON-LAMINATED	EACH	8	----	----	8
506.4000	STEEL DIAPHRAGMS (B-36-214)	EACH	6	----	----	6
513.4061	RAILING TUBULAR TYPE M (B-36-214)	LF	292	----	----	292
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	----	13	13	26
550.1120	PILING STEEL HP 12-INCH X 53 LB	LF	----	140	140	280
606.0200	RIPRAP MEDIUM	CY	----	25	22	47
606.0300	RIPRAP HEAVY	CY	----	223	229	452
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	----	60	60	120
645.0120	GEOTEXTILE FABRIC TYPE HR	SY	----	389	378	767
	NON-BID ITEMS					
	FILLER	SIZE	—	—	—	1/2" & 3/4"



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CKD. KRO
CROSS SECTION & QUANTITIES		SHEET 2 OF 12	



ABBREVIATIONS
F—Fine M—Medium C—Coarse
Ws—Weathered So—Sound


MATERIAL SYMBOLS
Topsoil Silt Sandstone
Sand Peat Limestone
Gravel Clay Igneous Rock

LEGEND OF PROBING
Probing No.
Sta.
Elevation
95/6=95 Blows for 6" Penetration
Probing taken with a 350*wt. Falling 18" on a 2" O.D. Point.
7 Average Blows Per Foot
Refusal 95/6

LEGEND OF BORING
Boring No.
Sta.
Elev.
Unconfined Strength—7.7
Blows Per Ft. Using 140* Wt. Falling 30"
Wash Sample
Shelby Tube — S.T.
Ground Water Elevation
No Ground Water Observed Above This Elevation
Sandy Gravel
F. Boulders or Cobbles
Sand
Silty Clay
So Limestone


Unless otherwise specified, the blows per foot at the locations indicated are based on driving a 0.0x1.4" I.D. split spoon sampler with a 140* hammer having a free fall of 30". The blow count is taken in undisturbed soil immediately below a cased or open hole eliminating side friction on the drive pipe.

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION
To obtain relative data concerning the character of material in and upon which the foundation might be built, borings and/or soundings were made at points approximately as indicated on this drawing. The data presented herein represents the findings of the subsurface explorations made. However, because the depths investigated are limited and the area of the borings and/or soundings is very small in relation to the entire area, the Division of Highways does not warrant conditions below the depths investigated or that the classification of material encountered in these investigations is necessarily typical of the entire site.




LEGEND
CAVE
FIRST WATER ENCOUNTERED
COMPLETION WATER ENCOUNTERED

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CK'D. KRO
SUBSURFACE EXPLORATION		SHEET 3 OF 12	





NOTE: SPACE A503 TO MISS PILING

ELEVATION
(LOOKING WEST)



PLAN



PILE PLAN

LEGEND

- (A05) CONSTRUCTION JOINT-FORMED BY BEVELED 2 x 6 BETWEEN BEAM SEATS.
- (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SOUTH SLOPE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN (SEE SHEET 5 FOR DETAILS).
- (A17) 1/2" FILLER INCLUDED IN WING LENGTH, SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE.)
- (A19) 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- (A22) A506 BARS SPACED @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
- (IX) DENOTES WING NUMBER

ABUTMENTS TO BE SUPPORTED ON HP 12 X 53 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 220 TONS PER PILE. ESTIMATED LENGTH = 20' AT THE WEST ABUTMENT.

SEE SHEET 5 FOR SECTION THRU ABUTMENT, WINGWALL DETAILS, BILL OF BARS, AND BAR BENDING DIAGRAMS.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CK'D. KRO
WEST ABUTMENT		SHEET 4 OF 12	

BILL OF BARS


BAR MARK	CONT	NO. REQ'D.	LENGTH	BENT	LOCATION
A401		7	28'-0"	X	BODY - ONE PER PILE
A402		14	2'-3"		BODY - TWO PER PILE
A503		38	15'-6"	X	BODY - STIRRUPS
A604		11	30'-2"		BODY - HORIZONTAL
A805		7	30'-2"		BODY - HORIZONTAL B.F.
A506	X	15	2'-0"		BODY - VERTICAL, DOWEL
A407	X	8	14'-1"	X	WINGS - STIRRUPS
A408	X	60	10'-9"	X	WINGS - STIRRUPS
A509	X	10	17'-7"		WINGS - HORIZONTAL, F.F.
A910	X	14	20'-5"		WINGS - HORIZONTAL
A411	X	28	9'-3"		WINGS - HORIZONTAL
A412	X	4	17'-1"	X	WINGS - HORIZONTAL, TOP
A613		8	3'-8"	X	BODY - END

BAR SERIES

BAR NO.	NO. REQ'D.	LENGTH
A408	4 SERIES OF 15	7'-6" TO 14'-0"
A411	4 SERIES OF 7	2'-11" TO 15'-7"



BAR BENDING DIAGRAMS




RODENT SCREEN DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SCREEN, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SCREEN SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SCREEN TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SCREEN SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH SHEET METAL SCREWS.




SECTION THRU BODY


HORIZ. BARS NOT OTHERWISE IDENTIFIED ARE A604 BARS

LEGEND


- (A05) KEYED CONSTRUCTION JOINT FORMED BY BEVELED 2" x 6".
- (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SOUTH SLOPE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.
- (A19) 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- (A22) A506 BARS SPACED @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
- ☆ 3/4" "V" GROOVE ON F.F. OF WING WALL. NOT REQUIRED IF CONST. JOINT IS NOT USED.




WING 1




WING 2



SECTION A-A




SECTION B-B



STEEL 'HP' SHAPES


STEEL 'HP' PILE MATERIAL SHALL BE A.S.T.M. DESIGNATION A36.




HP WELD DETAIL

FLANGE SHOWN, WEB SIMILAR



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CK'D. KRO
WEST ABUTMENT DETAILS		SHEET 5 OF 12	



ELEVATION
(LOOKING EAST)



PLAN



PILE PLAN


LEGEND

- (A05) CONSTRUCTION JOINT FORMED BY BEVELED 2" x 6".
 - (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SOUTH SLOPE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN (SEE SHEET 7 FOR DETAILS).
 - (A17) 1/2" FILLER INCLUDED IN WING LENGTH, SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE.)
 - (A19) 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
 - (A22) B506 BARS SPACED @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
 - (X) DENOTES WING NUMBER
- ABUTMENTS TO BE SUPPORTED ON HP 12 X 53 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 220 TONS PER PILE. ESTIMATED LENGTH = 20' AT THE EAST ABUTMENT.
- SEE SHEET 7 FOR SECTION THRU ABUTMENT, WINGWALL DETAILS, BILL OF BARS, AND BAR BENDING DIAGRAMS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
		DRAWN BY	BRE
		PLANS CK'D.	KRO
EAST ABUTMENT		SHEET 6 OF 12	

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	LOCATION
B401		7	28'-0"	X	BODY - ONE PER PILE
B402		14	2'-3"		BODY - TWO PER PILE
B503		38	15'-6"	X	BODY - STIRRUPS
B604		11	30'-2"		BODY - HORIZONTAL
B805		7	30'-2"		BODY - HORIZONTAL B.F.
B506	X	15	2'-0"		BODY - VERTICAL, DOWEL
B407	X	8	14'-1"	X	WINGS - STIRRUPS
B408	X	60	10'-9"	X	WINGS - STIRRUPS
B509	X	10	17'-7"		WINGS - HORIZONTAL, F.F.
B910	X	14	20'-5"		WINGS - HORIZONTAL
B411	X	28	9'-3"		WINGS - HORIZONTAL
B412	X	4	17'-1"	X	WINGS - HORIZONTAL, TOP
B613		8	3'-8"	X	BODY - END

BAR NO.	NO. REQ'D.	LENGTH
B408	4 SERIES OF 15	7'-6" TO 14'-0"
B411	4 SERIES OF 7	2'-11" TO 15'-7"



6" NOMINAL


SECTION B-B

3/8" MAX.

1/2"


* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SCREEN SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SCREEN TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SCREEN SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH SHEET METAL SCREWS.



HORIZ. BARS NOT OTHERWISE
IDENTIFIED ARE B604 BARS

- (A05) KEYED CONSTRUCTION JOINT FORMED BY BEVELED 2" x 6".
- (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SOUTH SLOPE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.
- (A19) 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- (A22) B506 BARS SPACED @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
- ☆ ¾" "V" GROOVE ON F.F. OF WING WALL. NOT REQUIRED IF CONST. JOINT IS NOT USED.



2'-0"

14'-0"

7'-1 1/2"

6 SPA. @ 1'-0"

B411

B412

B407

B910 TOP & B.F.

B509 F.F.

5'-0"

14 SPA. @ ± 1'-0"

B408

3" CL.


Technical drawing of a vertical section of a wall or partition. The drawing shows two vertical profiles with various dimensions and components labeled.

- Dimensions:**
 - B411:** Total height of the upper section.
 - B910:** Height of the lower section, labeled as "5 EQ. SPA." (5 equal spaces).
 - B509:** Height of the lower section, labeled as "5 EQ. SPA." (5 equal spaces).
- Components and Labels:**
 - B412:** Points to the top edge of the upper profile.
 - B407, B408:** Points to the middle section of the upper profile.
 - B910:** Points to the middle section of the lower profile.
 - B509:** Points to the middle section of the lower profile.
 - F.F.:** Points to the face of the wall/partition.
 - A05:** A circled label pointing to a star symbol on the right side, labeled "OPTIONA".

Diagram illustrating the vertical section of a wall or partition, showing dimensions and components:

- Dimensions:**
 - B412:** Top width dimension.
 - B411:** Upper height dimension.
 - B407, B408:** Middle width dimension.
 - B910:** Lower height dimension.
 - B509:** Lower width dimension.
 - 5 EQ. SPA.:** Lower height dimension.
- Components:**
 - F.F.:** Face Finish.
 - B.F.:** Back Finish.
 - B412:** Top edge component.
 - B407, B408:** Middle edge component.
 - B910:** Lower edge component.
 - A05 (OPTIONAL):** Optional component.
- Star Symbol:** Located at the bottom left corner.

STEEL 'HP' PILE MATERIAL SHALL BE A.S.T.M. DESIGNATION A36.



FLANGE SHOWN, WEB SIMILAR

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
		DRAWN BY	BRE
		PLANS CK'D.	KRO
EAST ABUTMENT DETAILS		SHEET 7 OF 12	

TOP OF GIRDER TO BE ROUGH FLOATED AND BROOMED TRANSVERSELY, EXCEPT THE OUTSIDE 15" OF GIRDER, WHICH SHALL RECEIVE A SMOOTH FINISH, AN APPROVED CONCRETE SEALER SHALL BE APPLIED TO ALL SMOOTH SURFACES INCLUDING THE OUTSIDE 15" OF THE TOP FLANGE.

THE GIRDERS SHALL BE PROVIDED WITH A SUITABLE LIFTING
DEVICE FOR HANDLING AND ERECTING THE GIRDERS.


STRANDS SHALL BE FLUSH WITH END OF GIRDER. FOR GIRDER ENDS EMBEDDED COMPLETELY IN CONCRETE, END OF STRANDS SHALL BE COATED WITH NON-BITUMINOUS JOINT SEALER. FOR GIRDER ENDS THAT ARE FINALLY EXPOSED, COAT THE GIRDER ENDS, EXPOSED STRAND ENDS AND ALL NON-BONDING SURFACES WITHIN 2 FEET OF THE GIRDER ENDS WITH A NON-PIGMENTED EPOXY CONFORMING TO AASHTO M-235 TYPE III, GRADE 2, CLASS B OR C. THE EPOXY SHALL BE APPLIED AT LEAST 3 DAYS AFTER MOIST CURING HAS CEASED AND PRIOR TO THE APPLICATION OF THE SEALER.

SPACING SHOWN FOR #4 STIRRUPS IS FOR GRADE 60 REINFORCEMENT.


AN ALTERNATE EQUIVALENT OF WELDED WIRE FABRIC (WWF)
ASTM A497 MAY BE SUBSTITUTED FOR THE STIRRUP
REINFORCEMENT SHOWN, UPON APPROVAL OF THE STRUCTURES
DEVELOPMENT SECTION.

PRESTRESSING STRANDS SHALL BE (0.6" DIA.)-7 WIRE
LOW-RELAXATION STRANDS WITH AN ULTIMATE STRENGTH OF
270,000 PSI.

FOR DIAPHRAGM INSERT & CONNECTION DETAILS SEE "STEEL DIAPHRAGM" SHEET.



TOP FLANGE




DRAPED STRAND PROFILE

*THE THEORETICAL INITIAL CAMBER VALUE AT THE TIME OF STRAND RELEASE AT MIDSPAN MULTIPLIED BY A FACTOR OF 1.4 TO ACCOUNT FOR CAMBER GROWTH FROM THE TIME OF STRAND RELEASE TO JOBSITE PLACEMENT.

SPAN	CAMBER (IN.)
1	3.46



THESE VALUES ARE NOT TO BE USED IN DETERMINING 'T'.
USE ACTUAL GIRDER SHOTS.
THESE VALUES ARE FOR INFORMATIONAL PURPOSES ONLY.



SIDE VIEW & TYP. SECTION IN SPAN

- (A) DETAIL TYP. AT EACH END
- (B) 6 #4 BARS, FULL LENGTH, MIN. LAP = 1'-11"

* MINIMUM CYLINDER STRENGTH OF CONCRETE @ TIME OF TRANSFER OF PRESTRESS FORCE.

[illegible]

NO.	DATE	REVISION	BY
-----	------	----------	----

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

STRUCTURE B-36-214

DRAWN BY	BRE	PLANS CK'D	KRO
-------------	-----	---------------	-----

72W" PRESTRESSED GIRDER DETAILS

SHEET 8 OF 12

ALL DIAPHRAGM STRUCTURAL STEEL SHOWN SHALL BE HOT-DIPPED GALVANIZED. ALL BOLTS, NUTS AND WASHERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A153 CLASS C. GALVANIZED NUTS SHALL BE TAPPED OVERSIZED IN ACCORDANCE WITH THE REQUIREMENTS OF ASTM A563 AND SHALL MEET THE REQUIREMENTS OF SUPPLEMENTARY REQUIREMENT SI OF ASTM A563, LUBRICANT AND TEST FOR COATED NUTS.



ALL PATTERNS
ARE SYM. ABOUT
GIRDER

TOTAL NO.
OF STRANDS
00 - 000

TOTAL INITIAL
PRESTRESS
FORCE IN KIPS

FOR DRAPED PATTERN ONLY.
DRAPE ALL STRANDS ON
THESE TWO LINES

1"

7.5"

2"



13 SPA. @ 2"

9 SPA. @ 2"


2"

40-1758

TYP. STRAND PATTERN




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CK'D. KRO
STEEL DIAPHRAGM		SHEET 9 OF 12	




SLAB PLAN

☆ PAIR WITH FIRST 28 STIRRUPS FROM GIRDER END



SECTION S-S


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
		DRAWN BY	BRE PLANS CK'D. KRO
SUPERSTRUCTURE		SHEET 10 OF 12	




FRAMING PLAN

BILL OF BARS


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	LOCATION
S501	X	405	30'-2"		TRANS. TOP & BOT.
S402	X	261	40'-0"		LONG. TOP & BOTTOM
S403	X	87	28'-2"		LONG. TOP & BOTTOM
S604	X	92	12'-0"	X	AT RAIL POST
S605	X	168	6'-0"		AT INTERIOR RAIL POST
S606	X	16	4'-10"	X	AT END RAIL POST
S607	X	18	30'-2"		DIAPH. HORIZONTAL, B.F. & TOP
S608	X	72	4'-10"		DIAPH. HORIZONTAL, F.F.
S509	X	50	18'-4"	X	DIAPH. STIRRUPS VERTICAL
S510	X	32	14'-10"	X	DIAPH. STIRRUPS VERTICAL
S511	X	50	5'-7"	X	DIAPH. TOP
S612	X	20	6'-6"	X	DIAPH. HORIZONTAL, ENDS
S613	X	4	1'-2"		DIAPH. HORIZONTAL, ENDS
S414	X	224	6'-0"	X	HAUNCH AT GIRDER ENDS
S415	X	16	15'-6"		HAUNCH AT GIRDER ENDS




SECTION THRU GIRDER HAUNCH

SEE SLAB PLAN ON SHEET 10
FOR LOCATION OF S414


PART LONGIT. SECTION




DEAD LOAD DEFLECTION DIAGRAM



BEARING PAD DETAIL



BAR BEND DIAGRAMS



DECK HAUNCH DETAIL

IF 1/4" MINIMUM HAUNCH HEIGHT AT EDGE OF GIRDER CANNOT BE MAINTAINED, THE GRADE LINE MAY BE REVISED BY THE ENGINEER AT THE OPTION OF THE CONTRACTOR, THE PLAN DECK THICKNESS SHALL BE HELD. NOTIFY THE STRUCTURES SECTION IF THE GRADE LINE IS RAISED FROM THE PLAN PROFILE BY MORE THAN 1/2" OR, ** IF 3" MINIMUM DECK EMBEDMENT OF TIE BAR CANNOT BE OBTAINED.

TO DETERMINE 'T', ELEV. OF TOP OF GIR'S. AT CL OF SUBSTRUCTURE UNITS & AT 1/10 POINTS OF EACH SPAN SHALL BE TAKEN. THEN FOLLOW THIS PROCESS:

TOP OF DECK ELEV. AT FINAL GRADE
- TOP OF GIRDER ELEVATION
+ DEAD LOAD DEFLECTION
- DECK THICKNESS
= HAUNCH HEIGHT 'T'

NOTE: AN AVERAGE HAUNCH ('T') OF 4 5/8" WAS USED IN THE QUANTITY "CONCRETE MASONRY BRIDGES".

TOP OF DECK ELEVATIONS

LOCATION	W.ABUT.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	E. ABUT.
N. EDGE	783.40	783.27	783.18	783.12	783.09	783.09	783.12	783.18	783.27	783.40	783.55
GIRDER 1	783.45	783.33	783.23	783.17	783.14	783.14	783.17	783.23	783.33	783.45	783.61
GIRDER 2	783.62	783.49	783.40	783.34	783.31	783.31	783.34	783.40	783.49	783.62	783.77
GIRDER 3	783.62	783.49	783.40	783.34	783.31	783.31	783.34	783.40	783.49	783.62	783.77
GIRDER 4	783.45	783.33	783.23	783.17	783.14	783.14	783.17	783.23	783.33	783.45	783.61
S. EDGE	783.40	783.27	783.18	783.12	783.09	783.09	783.12	783.18	783.27	783.40	783.55





NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CK'D. KRO
SUPERSTRUCTURE DETAILS		SHEET 11 OF 12	

LEGEND

- ① W6 x 25 WITH 1/8" x 1/2" HORIZONTAL SLOTS ON EACH SIDE OF POST FOR BOLT NO. 6. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1/4" x 11 3/4" x 1'-8" WITH 1 5/8" x 1 5/8" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN. SLOTS PARALLEL TO SHORT SIDE OF PLATE
- ③ ASTM A449 - 1/8" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED), 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1'-9" LONG IN ABUTMENT WINGS. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1'-3" LONG. USE 10 3/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTIBILITY.)
- ④ 5/8" x 11" x 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 5/8" DIA. HOLES FOR ANCHOR BOLTS NO. 3
- ⑤ TS 5 x 4 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑤A TS 5 x 5 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH NUT, 3/8" x 1 5/8" x 1 5/8" WASHER, AND LOCK WASHER (2 REQ'D. AT EACH RAIL TO POST LOCATION.)
- ⑦ 1/2" THK. BACK-UP PLATE WITH 2 - 7/8" x 1/2" THREADED SHOP WELDED STUDS (ITEM 12). BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑧ 1" DIA. HOLES IN PLATE NO. 7 & TUBES NO. 5A FOR 7/8" DIA. A325 BOLTS WITH HEX NUTS AND WASHERS. 6 HOLES IN TUBES AND PLATE NO. 7.
- ⑨ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- ⑩ 3/8" x 3 5/8" x 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- ⑩A 3/8" x 2 5/8" x 2'-4" PLATE USED IN NO. 5, 3/8" x 3 5/8" x 2'-4" PLATE USED IN NO. 5A. 2 PER RAIL.
- ⑪ 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. USE 1 5/8" x 1/4" LONGIT. SLOTTED HOLES AT FIELD JOINTS AND 1 5/8" x 2 1/4" MIN. LONGIT. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 10A.
- ⑫ 7/8" DIA. x 1 1/2" LONG THREADED SHOP WELDED STUDS (2 REQ'D.).
- ⑬ 3/8" x 8" x 1'-6" PLATE. BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑭ 7/8" DIA. x 2" LONG A325 HEX BOLT WITH NUT AND WASHER. (5 REQ'D.)
- ⑮ 1" DIA. HOLES IN TUBES NO. 5A FOR 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. 4 HOLES IN TUBES.










GENERAL NOTES

1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M (B-36-214)" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8 TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE. RAILS SHALL BE SPLICED IN A PANEL OVER EXPANSION JOINTS.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY S.S.P.C. SPECIFICATIONS.
10. WHEN PAINTING IS REQUIRED, ALL MATERIAL EXCEPT ANCHORAGE DETAIL (NO. 3 & 4) SHALL BE PAINTED OVER GALVANIZING WITH APPROVED TIE COAT AND TOP COAT.
11. THIS RAILING MEETS NCHRP REPORT 350 EVALUATION CRITERIA FOR TEST LEVEL 4 (TL-4).
12. PLACE FIRST BOTTOM LONGITUDINAL BAR CLEAR OF DRIP GROOVE.

**SECTION B-B****SECTION THRU POST WEB****SECTION THRU RAIL**

NOTE: CONNECTIONS AT LOWER RAILS SHOWN. CONNECTIONS AT TOP RAIL SIMILAR.

TYPICAL RAIL TO POST CONNECTIONS

**SECTION C-C****SECTION D-D****POST SHIM DETAIL**

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-214			
DRAWN BY		BRE	PLANS CKD. KRO
TUBULAR STEEL RAILING TYPE 'M'		SHEET 12 OF 12	


HILLCREST ROAD WEST


STATION	AREA (SF)			INCREMENTAL VOLUME (CY) (UNADJUSTED)			CUMULATIVE VOLUME (CY)		MASS ORDINATE
	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	
	NOTE 1			NOTE 1			1.00	1.25	
05+68.5	0	0	0	0	0	0	0	0	0
06+00	13	0	16	8	0	9	8	12	-4
06+42	17	0	19	24	0	28	32	46	-15
06+73.51	15	0	49	19	0	40	50	96	-46
06+98.51	14	0	72	13	0	56	64	166	-102
07+00	38	0	73	1	0	4	65	171	-106
07+23.51	25	0	162	27	0	102	93	299	-206
07+50	13	0	297	19	0	225	111	580	-469
08+00	3	0	569	15	0	802	126	1,582	-1,456
08+50	3	0	635	6	0	1,114	132	2,975	-2,843
09+00	3	0	753	6	0	1,285	137	4,582	-4,444
09+38.43	3	0	729	4	0	1,055	142	5,900	-5,759


HILLCREST ROAD EAST


STATION	AREA (SF)			INCREMENTAL VOLUME (CY) (UNADJUSTED)			CUMULATIVE VOLUME (CY)		MASS ORDINATE
	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	
	NOTE 1			NOTE 1			1.00	1.25	
10+81.93	3	0	426	0	0	0	0	0	0
11+00	3	0	489	2	0	306	2	383	-381
11+34.36	3	0	306	4	0	506	6	1015	-1009
11+50	3	0	228	2	0	155	8	1208	-1200
11+59.36	3	0	155	1	0	66	9	1291	-1282
11+84.36	3	0	42	3	0	91	11	1405	-1394
11+96.86	6	0	21	2	0	15	14	1423	-1410
12+21.86	22	0	12	13	0	15	27	1443	-1416
12+46.86	40	0	3	29	0	7	55	1451	-1396
12+50	42	0	2	5	0	0	60	1451	-1391
12+51	18	0	2	1	0	0	61	1452	-1390
12+72	15	0	0	13	0	1	74	1452	-1378
13+00	7	0	0	11	0	0	86	1452	-1366
13+36.83	6	0	1	9	0	1	95	1453	-1359


NOTE 1: CUT INCLUDES REMOVING EXISTING PAVEMENT.
EXISTING PAVEMENT IS NOT SHOWN IN CROSS SECTIONS.
















Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>