

GRE
PROJECT ID:
WITH: N/A

4316-09-71

COUNTY:
MANITOWOC

FEBRUARY 2018

ORDER OF SHEETS

- Section No. 1 Title
Section No. 2 Typical Sections and Details (Includes Erosion Control)
Section No. 3 Estimate of Quantities
Section No. 3 Miscellaneous Quantities
Section No. 4 Right of Way Plat
Section No. 5 Plan and Profile
Section No. 6 Standard Detail Drawings
Section No. 7 Sign Plates
Section No. 8 Structure Plans
Section No. 9 Computer Earthwork Data
Section No. 9 Cross Sections

TOTAL SHEETS = 78

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT

T FRANKLIN, HILLCREST RD

BRANCH RIVER BRIDGE

LOC STR

MANITOWOC COUNTY

STATE PROJECT NUMBER

4316-09-71

STATE PROJECT

4316-09-71

FEDERAL PROJECT

PROJECT

WISC 2018091

CONTRACT

1

STRUCTURE B-36-220

END PROJECT 4316-09-71
STA 11+80.00

BEGIN PROJECT 4316-09-71
STA 8+00.00

Y = 339062.638
X = 185584.060

DESIGN DESIGNATION

A.A.D.T. 2018 = 590
A.A.D.T. 2038 = 650
D.H.V. = 96
D.D. = 60/40
T. = 4.0%
DESIGN SPEED = 40 MPH
ESALS = 59,000

CONVENTIONAL SYMBOLS

PLAN

CORPORATE LIMITS

PROPERTY LINE

LOT LINE

LIMITED HIGHWAY EASEMENT

EXISTING RIGHT OF WAY

PROPOSED OR NEW R/W LINE

SLOPE INTERCEPT

REFERENCE LINE

EXISTING CULVERT

PROPOSED CULVERT
(Box or Pipe)

COMBUSTIBLE FLUIDS

WETLAND AREA

WOODED OR SHRUB AREA

PROFILE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE
(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER


TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE



LAYOUT

SCALE 0 2 MI

TOTAL NET LENGTH OF CENTERLINE = 0.072 MILES

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COUNTY COORDINATES, MANITOWOC COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. VALUES ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.


ACCEPTED FOR
MANITOWOC COUNTY

DATE: 6/27/17

(Signature)

ORIGINAL PLANS PREPARED BY

OMNI
ASSOCIATES



6/27/2017

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY

Surveyor

OMNI ASSOCIATES

Designer

OMNI ASSOCIATES

Management Consultant

JT ENGINEERING

APPROVED FOR THE DEPARTMENT

DATE: 6/27/17

MANAGEMENT CONSULTANT SIGNATURE

E

GENERAL NOTES

THE LOCATIONS OF EXISTING AND PROPOSED UTILITY FACILITIES AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

FILL AS SHOWN ON THE PLANS PERTAINS TO EMBANKMENTS CONSTRUCTED FROM COMMON EXCAVATION. THE ALLOWANCE USED FOR EXPANDING THE FILLS TO COMPUTE THE VOLUME OF MATERIAL REQUIRED IS 25 PERCENT. ALL FILL VOLUMES SHOWN ARE THE ACTUAL VOLUMES.

CONSTRUCT ASPHALTIC SURFACE 4" DEPTH AS FOLLOWS:

- 1 3/4" UPPER LAYER (12.5 mm NOMINAL SIZE AGGREGATE)
- 2 1/4" LOWER LAYER (19 mm NOMINAL SIZE AGGREGATE)

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT THE APPROVAL OF THE ENGINEER.

ALL DISTURBED AREAS, NOT OTHERWISE SURFACED ARE TO BE TOPSOILED, FERTILIZED, TEMPORARY SEEDED, SEEDED AND COVERED WITH EROSION MAT.

SEED MIXTURE NO. 30 SHALL BE USED ON ALL DISTURBED AREAS, EXCEPT WETLANDS SHALL BE SEEDED WITH MIXTURE NO. 60.

FERTILIZER SHALL NOT BE USED WITHIN 10-FEET OF NAVIGABLE WATERWAYS AND WETLANDS.

WETLAND AREAS ARE SHOWN ON THE PLANS. CONTRACTOR SHALL LIMIT CONSTRUCTION ACTIVITIES TO WORK WITHIN THE SLOPE INTERCEPTS IN THE WETLAND AREAS.

THE EXACT LOCATIONS OF ALL EROSION CONTROL ITEMS SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

DISTANCES SHOWN ON THIS PLAN ARE GROUND DISTANCES.

PLAN ELEVATIONS = USGS DATUM, NAVD 88 (2012)

THE WISCONSIN DEPARTMENT OF TRANSPORTATION WILL FURNISH THE CONTRACTOR A MONUMENT WHICH SHALL BE SET IN THE STRUCTURE AS DESIGNATED BY THE ENGINEER.

EROSION CONTROL NOTES

RUNOFF COEFFICIENTS FOR THIS PROJECT: EXISTING PAVEMENT 0.95, EXISTING SLOPES 0.30,
NEW PAVEMENT 0.95, NEW SLOPES 0.30.

TOTAL PROJECT AREA = 1.39 ACRES
TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.95 ACRES.

CONTACTS

ELECTRIC WISCONSIN PUBLIC SERVICE CORPORATION
700 NORTH ADAMS STREET, PO BOX 19001
GREEN BAY, WI 54307-9001
ATTN: LORI BUTRY
TELEPHONE: (920) 433-1703
EMAIL: LAButry@integrysgruop.com

LOCAL CONTACT (ELECTRIC): JEFF PELISCHEK
TELEPHONE: 920-794-3216 EXT 4216
CELL PHONE: 920-323-4836
EMAIL: jspelischek@wpsr.com

TELEPHONE FRONTIER COMMUNICATIONS
118 DIVISION STREET
PLYMOUTH, WI 53073
ATTN: RYAN OSNESS
TELEPHONE: 920-893-7455
CELL: 920-246-3530
EMAIL: ryan.d.osness@ftr.com

DNR LIAISON MATT SCHAEVE
DEPARTMENT OF NATURAL RESOURCES
2984 SHAWANO AVENUE
GREEN BAY, WI 54313
TELEPHONE: 920-662-5472
EMAIL: matthew.schaeve@wisconsin.gov







Dial **811** or (800)242-8511
www.DiggersHotline.com

RYAN

** DENOTES UTILITIES THAT ARE NOT DIGGERS HOTLINE MEMBERS.

2





TYPICAL FINISHED SECTION - HILLCREST RD


STA 8+19.3 TO STA 9+31.25 LT
STA 8+44.3 TO STA 9+31.25 RT
STA 10+68.25 TO STA 11+55.8

NOTES:

△ VARIES TO 6' AT POST NO. 1 OF ENERGY ABSORBING TERMINAL


* 4:1 MAX WITHIN LIMITS OF ENERGY ABSORBING TERMINAL (EAT)

▽ VARIES WITHIN LIMITS OF EAT




TYPICAL FINISHED SECTION - HILLCREST RD


STA 9+31.75 TO STA 9+45.75
STA 10+53.25 TO STA 10+68.25



LEGEND


- MAG SPIKE
- 3/4-INCH REBAR
- POWER POLE
- BENCH MARK






PLAN VIEW

ONLY THE ASPHALT DRIVEWAY USED IN THIS CONTRACT




TYPICAL CROSS SECTION




PROFILE VIEW


RURAL DRIVEWAY INTERSECTION DETAIL




CONCRETE PAVEMENT APPROACH SLAB



CULVERT PIPE CHECK




SIDE VIEW (SINGLE LAYER)




*LENGTH AND NUMBER OF BAGS MAY VARY
DEPENDING ON DESIRED DEPTH OF WATER POOL

SIDE VIEW (MULTIPLE LAYER)

ROCK BAGS DITCH CHECK
PAID AS ROCK BAGS



SUBGRADE DETAIL AT CONCRETE
PAVEMENT APPROACH SLAB



Estimate Of Quantities

4316-09-71

Line	Item	Item Description	Unit	Total	Qty
0002	201.0205	Grubbing	STA	5.000	5.000
0004	203.0100	Removing Small Pipe Culverts	EACH	1.000	1.000
0006	203.0600.S	Removing Old Structure Over Waterway With Minimal Debris (station) 01. 10+00	LS	1.000	1.000
0008	205.0100	Excavation Common	CY	490.000	490.000
0010	206.1000	Excavation for Structures Bridges (structure) 01. B-36-220	LS	1.000	1.000
0012	208.0100	Borrow	CY	1,800.000	1,800.000
0014	209.2100	Backfill Granular Grade 2	CY	260.000	260.000
0016	210.1500	Backfill Structure Type A	TON	620.000	620.000
0018	213.0100	Finishing Roadway (project) 01. 4316-09-71	EACH	1.000	1.000
0020	305.0110	Base Aggregate Dense 3/4-Inch	TON	140.000	140.000
0022	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	740.000	740.000
0024	415.0410	Concrete Pavement Approach Slab	SY	80.000	80.000
0026	416.1010	Concrete Surface Drains	CY	8.000	8.000
0028	455.0605	Tack Coat	GAL	55.000	55.000
0030	465.0105	Asphaltic Surface	TON	185.000	185.000
0032	465.0120	Asphaltic Surface Driveways and Field Entrances	TON	15.000	15.000
0034	502.0100	Concrete Masonry Bridges	CY	208.000	208.000
0036	502.3200	Protective Surface Treatment	SY	450.000	450.000
0038	503.0155	Prestressed Girder Type I 54W-Inch	LF	420.000	420.000
0040	505.0400	Bar Steel Reinforcement HS Structures	LB	3,160.000	3,160.000
0042	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	23,400.000	23,400.000
0044	506.2605	Bearing Pads Elastomeric Non-Laminated	EACH	8.000	8.000
0046	506.4000	Steel Diaphragms (structure) 01. B-36-220	EACH	6.000	6.000
0048	513.4061	Railing Tubular Type M (structure) 01. B-36-220	LF	218.000	218.000
0050	516.0500	Rubberized Membrane Waterproofing	SY	22.000	22.000
0052	520.1018	Apron Endwalls for Culvert Pipe 18-Inch	EACH	2.000	2.000
0054	521.3118	Culvert Pipe Corrugated Steel 18-Inch	LF	32.000	32.000
0056	550.0020	Pre-Boring Rock or Consolidated Materials	LF	91.000	91.000
0058	550.1100	Piling Steel HP 10-Inch X 42 Lb	LF	210.000	210.000
0060	606.0200	Riprap Medium	CY	80.000	80.000
0062	606.0300	Riprap Heavy	CY	280.000	280.000
0064	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	106.000	106.000
0066	614.0200	Steel Thrie Beam Structure Approach	LF	21.000	21.000
0068	614.0305	Steel Plate Beam Guard Class A	LF	28.000	28.000
0070	614.0345	Steel Plate Beam Guard Short Radius	LF	44.000	44.000
0072	614.0390	Steel Plate Beam Guard Short Radius Terminal	EACH	1.000	1.000
0074	614.0920	Salvaged Rail	LF	410.000	410.000
0076	614.0925	Salvaged Guardrail End Treatments	EACH	4.000	4.000

Estimate Of Quantities

4316-09-71

Line	Item	Item Description	Unit	Total	Qty
0078	614.2300	MGS Guardrail 3	LF	63.000	63.000
0080	614.2500	MGS Thrie Beam Transition	LF	118.000	118.000
0082	614.2610	MGS Guardrail Terminal EAT	EACH	3.000	3.000
0084	619.1000	Mobilization	EACH	1.000	1.000
0086	624.0100	Water	MGAL	5.000	5.000
0088	625.0100	Topsoil	SY	2,650.000	2,650.000
0090	628.1504	Silt Fence	LF	1,210.000	1,210.000
0092	628.1520	Silt Fence Maintenance	LF	1,210.000	1,210.000
0094	628.1905	Mobilizations Erosion Control	EACH	4.000	4.000
0096	628.1910	Mobilizations Emergency Erosion Control	EACH	2.000	2.000
0098	628.2008	Erosion Mat Urban Class I Type B	SY	2,650.000	2,650.000
0100	628.6005	Turbidity Barriers	SY	170.000	170.000
0102	628.7555	Culvert Pipe Checks	EACH	4.000	4.000
0104	628.7570	Rock Bags	EACH	50.000	50.000
0106	629.0210	Fertilizer Type B	CWT	1.700	1.700
0108	630.0130	Seeding Mixture No. 30	LB	50.000	50.000
0110	630.0160	Seeding Mixture No. 60	LB	10.000	10.000
0112	630.0200	Seeding Temporary	LB	35.000	35.000
0114	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	4.000	4.000
0116	634.0616	Posts Wood 4x6-Inch X 16-FT	EACH	1.000	1.000
0118	637.2230	Signs Type II Reflective F	SF	12.000	12.000
0120	638.2102	Moving Signs Type II	EACH	2.000	2.000
0122	638.2602	Removing Signs Type II	EACH	4.000	4.000
0124	638.3000	Removing Small Sign Supports	EACH	4.000	4.000
0126	642.5001	Field Office Type B	EACH	1.000	1.000
0128	643.0420	Traffic Control Barricades Type III	DAY	1,500.000	1,500.000
0130	643.0705	Traffic Control Warning Lights Type A	DAY	2,400.000	2,400.000
0132	643.0900	Traffic Control Signs	DAY	1,050.000	1,050.000
0134	643.5000	Traffic Control	EACH	1.000	1.000
0136	645.0111	Geotextile Type DF Schedule A	SY	90.000	90.000
0138	645.0120	Geotextile Type HR	SY	555.000	555.000
0140	646.1020	Marking Line Epoxy 4-Inch	LF	1,520.000	1,520.000
0142	650.4500	Construction Staking Subgrade	LF	400.000	400.000
0144	650.5000	Construction Staking Base	LF	400.000	400.000
0146	650.6500	Construction Staking Structure Layout (structure) 01. B-36-220	LS	1.000	1.000
0148	650.9910	Construction Staking Supplemental Control (project) 01. 4316-09-71	LS	1.000	1.000
0150	650.9920	Construction Staking Slope Stakes	LF	400.000	400.000
0152	690.0150	Sawing Asphalt	LF	44.000	44.000

Estimate Of Quantities

4316-09-71

Line	Item	Item Description	Unit	Total	Qty
0154	715.0415	Incentive Strength Concrete Pavement	DOL	500.000	500.000
0156	715.0502	Incentive Strength Concrete Structures	DOL	1,248.000	1,248.000
0158	999.1000.S	Seismograph	LS	1.000	1.000
0160	999.1500.S	Crack and Damage Survey	LS	1.000	1.000
0162	ASP.1T0A	On-the-Job Training Apprentice at \$5.00/HR	HRS	300.000	300.000
0164	ASP.1T0G	On-the-Job Training Graduate at \$5.00/HR	HRS	600.000	600.000

EARTHWORK

Location	From/To Station	205.0100			Available Material (5)	Unexpanded Fill	Expanded Fill (13)	Mass Ordinate +/- (14)	208.0100	209.2100
		Common Excavation (1)	EBS Excavation (3)	Salvaged/Unusable Pavement Material (4)					Borrow	Granular Backfill Grade 2
		CY	CY	CY	CY	CY	Factor 1.25 CY	CY	CY	Factor 1.25 CY
HILLCREST RD WEST	7+25/9+46.75	166	143	25	141	1,083	1,354	-1,213	1,213	179
HILLCREST RD EAST	10+53.25/12+75	116	65	27	89	553	691	-602	602	81
Grand Total		282	208	52	230	1,636	2,045	-1,815	1,815	260
ROUNDED TOTALS		490							1,800	260

- 1) Common Excavation includes Salvaged/Unusable Pavement Material. Item number 205.0100
- 3) EBS Excavation to be backfilled with Granular Backfill Grade 2. EBS is considered waste material.
- 5) Available Material = Cut - Salvaged/Unusable Pavement Material
- 14) The Mass Ordinate + or - Qty calculated for the Division. Plus quantity indicates an excess of material within the Division.
Minus indicates a shortage of material within the Division.

ALL ITEMS ARE CATEGORY 0010 UNLESS OTHERWISE NOTED

GRUBBING

STATION	LOCATION	201.0205 GRUBBING STATION
7+00 - 12+00	HILLCREST RD	5
TOTAL		5

BASE AGGREGATE DENSE AND WATER

		305.0110 BASE AGGREGATE DENSE 3/4-INCH TON	305.0120 BASE AGGREGATE DENSE 1 1/4-INCH TON	624.0100 WATER MGAL
STATION TO STATION	LOCATION			
7+40 - STRUCTURE	HILLCREST RD	60	410	2.8
STRUCTURE - 12+50	HILLCREST RD	50	330	2.3
DRIVEWAY	HILLCREST RD	30	---	---
TOTAL		140	740	5

ASPHALTIC ITEMS

		455.0605 TACK COAT GAL	465.0105 ASPHALTIC SURFACE TON	465.0120 ASPHALTIC SURFACE DRIVEWAY & FIELD ENTERANCES TON
STATION TO STATION	LOCATION			
8+00 - STRUCTURE	HILLCREST RD	30	100	---
STRUCTURE - 11+80	HILLCREST RD	25	85	---
DRIVEWAY	HILLCREST RD	---	---	15
TOTAL		55	185	15

CONCRETE PAVEMENT

		415.0410 CONCRETE PAVEMENT APPROACH SLAB SY
STATION TO STATION	LOCATION	
9+31.75 - 9+46.75	HILLCREST RD	35
10+53.25 - 10+48.25	HILLCREST RD	45
TOTAL		80

CONCRETE SURFACE DRAIN

			416.1010 CONCRETE SURFACE DRAIN CY
STATION	DIR	LOCATION	
9+30	LT	HILLCREST RD	4
9+30	RT	HILLCREST RD	4
TOTAL			8

CULVERT PIPES

		203.0100 REMOVING SMALL PIPE CULVERTS EA	520.1018 APRON ENDWALL FOR CULVERT PIPE 18-IN EA	521.3118 CULVERT PIPE CORRUGATED STEEL 18-IN LF			
STATION	LOCATION				STEEL THICKNESS	UP INVERT	DN INVERT
11+32, RT	HILLCREST RD	1	2	32	0.064	794.00	792.25
TOTAL		1	2	32			

SALVAGED GUARDRAIL

			614.0920 SALVAGED RAIL LF	614.0925 SALVAGED GUARDRAIL END TREATMENTS EACH
STATION	DIR	LOCATION		
8+00 TO STRUCTURE	LT	HILLCREST RD	150	1
8+00 TO STRUCTURE	RT	HILLCREST RD	80	1
STRUCTURE TO 11+80	LT	HILLCREST RD	115	1
STRUCTURE TO 11+80	RT	HILLCREST RD	65	1
TOTAL			410	4

STEEL PLATE BEAM GUARD

		614.0200 STEEL THRIE BEAM STRUCTURE APPROACH LF	614.0305 STEEL PLATE BEAM GUARD CLASS A LF	614.0345 STEEL PLATE BEAM GUARD SHORT RADIUS LF	614.0390 STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL EACH	614.2300 MGS GUARDRAIL 3 LF	614.2500 MGS THRIE BEAM TRANSITION LF	614.2610 MGS GUARDRAIL TERMINAL EAT EACH
STATION TO STATION	LOCATION							
8+44.3 - STRUCTURE, RT	HILLCREST	---	---	---	---	12.5	39.4	1
8+19.3 - STRUCTURE, LT	HILLCREST	---	---	---		37.5	39.4	1
STRUCTURE - 11+20, RT	HILLCREST	20.65	28.1	44	1	---	---	---
STRUCTURE - 11+55.8, LT	HILLCREST	---	---	---		12.5	39.4	1
TOTALS		20.65	28.1	44	1	62.5	118.2	3
ROUNDED TOTAL		21	28	44	1	63	118	3

LANDSCAPING

		625.0100 TOPSOIL SY	628.2008 EROSION MAT URBAN CLASS I TYPE B SY	630.0130 SEEDING NO 30 LB	630.0160 SEEDING NO 60 LB	630.0200 SEEDING TEMPORARY LB	629.0210 FERTILIZER TYPE B CWT
STATION TO STATION	LOCATION						
7+40 - 9+45, LT	HILLCREST	670	670	12	-	9	0.5
7+50 - 9+45, RT	HILLCREST	730	730	14	-	9	0.5
10+55 - 12+50, LT	HILLCREST	470	470	9	-	6	0.3
10+55 - 11+90, RT	HILLCREST	250	250	5	-	3	0.2
UNDISTRIBUTED		530	530	10	10	8	0.3
TOTAL		2,650	2,650	50	10	35	1.7

EROSION CONTROL ITEMS

		628.1504 SILT FENCE LF	628.1520 SILT FENCE MAINTENANCE LF	628.1905 MOBILIZATIONS EROSION CONTROL EACH	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL EACH	628.7570 ROCK BAGS EACH	628.7555 CULVERT PIPE CHECKS EACH
STATION TO STATION	LOCATION						
7+40 - 9+45, LT	HILLCREST RD	280	280	---	---	10	---
7+50 - 9+45, RT	HILLCREST RD	290	290	---	---	10	---
10+55 - 12+50, LT	HILLCREST RD	240	240	---	---	10	---
10+55 - 11+90, RT	HILLCREST RD	160	160	---	---	10	3
UNDISTRIBUTED	HILLCREST RD	240	240	4	2	10	1
TOTAL		1,210	1,210	4	2	50	4

ALL ITEMS ARE CATEGORY 0010 UNLESS OTHERWISE NOTED

SIGNS REFLECTIVE TYPE II & POSTS WOOD

STATION	DIR	LOCATION	CODE	SIGN SIZE HORIZ X VERT IN X IN	634.0614 POSTS WOOD 4X6-INCH X 14-FT EACH	637.2230 SIGNS TYPE II RELFECTIVE F SF
9+45	RT	HILLCREST	W5-52R	12 X 36	1	3
9+45	LT	HILLCREST	W5-52L	12 X 36	1	3
10+55	RT	HILLCREST	W5-52L	12 X 36	1	3
10+55	LT	HILLCREST	W5-52R	12 X 36	1	3
TOTAL					4	12

TRAFFIC CONTROL ROAD CLOSURE

LOCATION	APROX. SERVICE PERIOD	643.0420 BARRICADES TYPE III EACH		643.0705 WARNING LIGHTS TYPE A EACH		643.0900 SIGNS EACH	
		NO.	DAYS	NO.	DAYS	NO.	DAYS
WEST OF PROJECT	75	10	750	16	1200	7	525
EAST OF PROJECT	75	10	750	16	1200	7	525
TOTALS			1,500		2,400		1,050

MARKING LINE EPOXY 4-INCH

STATION	TO	STATION	LOCATION	646.1020	
				4-INCH DOUBLE YELLOW LF	4-INCH WHITE EDGELINE LF
8+00	-	11+80	HILLCREST	760	760
TOTAL				1,520	

CONSTRUCTION STAKING

STATION	TO	STATION	LOCATION	650.4500 SUBGRADE LF	650.5000 BASE LF	CATEGORY 0020 650.6500 STRUCTURE LAYOUT LS	650.9910 SUPPLEMENTAL CONTROL LS	650.9920 SLOPE STAKES LF
7+40	-	9+45	HILLCREST	205	205	---	---	205
10+55	-	12+50	HILLCREST	195	195	---	---	195
PROJECT			HILLCREST	---	---	1	---	---
TOTAL				400	400	1	1	400

REMOVING SIGNS TYPE II AND REMOVING SMALL SIGN SUPPORTS

STATION	DIR	LOCATION	DESCRIPTION	638.2602 REMOVING SIGNS TYPE II EACH	638.3000 REMOVING SMALL SIGN SUPPORTS EACH
9+60	RT	HILLCREST	OBJECT MARKER	1	1
9+60	LT	HILLCREST	OBJECT MARKER	1	1
10+40	RT	HILLCREST	OBJECT MARKER	1	1
10+40	LT	HILLCREST	OBJECT MARKER	1	1
TOTAL				4	4

MOVING SIGNS

FROM STATION	LOCATION	TO STATION	FACE DIR.	DESCRIPTION	638.2102 MOVING SIGNS TYPE II EACH	634.0616 POSTS WOOD 4X6-INCH X 16-FT EACH	REMARKS
11+23	HILLCREST RD	11+23	EAST	BRANCH RIVER WATERSHED	1	1	---
11+23	HILLCREST RD	11+23	EAST	REPORT SPILLS	1	---	PLACE ON POST WITH BRANCH RIVER WATERSHED
TOTAL					2	1	

RIPRAP

STATION	DIR	LOCATION	606.0200 MEDIUM RIPRAP CY	645.0120 GEOTEXTILE FABRIC TYPE HR SY
9+30	LT	HILLCREST RD	10	20
9+30	RT	HILLCREST RD	10	20
10+65/11+05	RT	HILLCREST RD	20	40
TOTAL			40	80

TURBIDITY BARRIER

STATION	LOCATION	628.6005 SY
9+90	HILLCREST RD	70
10+25	HILLCREST RD	100
TOTAL		170

SEISMOGRAPH

	999.1000.S
LOCATION	LS
HILLCREST RD	2
TOTAL	2

CRACK & DAMAGE SURVEY

	999.1500.S
LOCATION	LS
HILLCREST RD	2
TOTAL	2

SAWING ASPHALT

STATION	LOCATION	690.0150 SAWING ASPHALT LF
8+00	HILLCREST	22
11+80	HILLCREST	22
TOTAL		44

ALL ITEMS ARE CATEGORY 0010 UNLESS OTHERWISE NOTED

LEVELS ON = 01.02, 03.04, 05.06, 07.08, 09.10, 11.12, 13.14, 15.16, 17.18, 19.20, 21.22, 23.24, 25.26, 27.28, 29.30, 31.32, 33.34, 35.36, 37.38, 39.40, 41.42, 43.44, 45.46, 47.48, 49.50, 51.52, 53.54, 55.56, 57.58, 59.60, 61.62, 63.64

Conventional Signs and Abbreviations

SECTION LINE	AC	ACRES	R	RADIUS
QUARTER LINE	Δ	CENTRAL ANGLE	R/L	RANGE
TOWNSHIP AND RANGE LINE	C/L	CENTERLINE	R/W	REFERENCE LINE
PROPOSED OR NEW CENTERLINE	COR.	CORNER	1/4 LINE	RIGHT OF WAY
PROPOSED OR NEW R/W LINE	CTH	COUNTY TRUNK HIGHWAY	1/2 LINE	QUARTER LINE
EXISTING R/W LINE	D	DEGREE OF CURVE	3/4 LINE	SIXTEENTH LINE
LOT LINE	E	EAST	S	SOUTH
PROPERTY LINE	L	LENGTH OF CURVE	SEC	SECTION
COUNTY LIMITS LINE	LC	LONG CHORD	SEC LINE	SECTION LINE
SLOPE INTERCEPTS	LCB	LONG CHORD BEARING	STH	STATE TRUNK HIGHWAY
EXISTING MONUMENTATION	MI	MILE	SF	SQUARE FEET
FENCE	N	NORTH	STA	STATION
SECTION OR QUARTER CORNER	N.T.S.	NOT TO SCALE	T	TOWN
TELEPHONE	PC	POINT OF CURVATURE	T	TANGENT LENGTH OF CURVE
GAS	PI	POINT OF INTERSECTION	TLE	TEMPORARY LIMITED EASEMENT
WATER	PT	POINT OF TANGENCY	USH	UNITED STATES HIGHWAY
ELECTRIC	PLE	PERMANENT LIMITED EASEMENT	W	WEST
FIBER OPTIC	P/L	PROPERTY LINE		
SANITARY	PC LINE	PRIVATE CLAIM LINE		
STORM SEWER				

NO ACCESS (BY ACQUISITION)	NO ACCESS (BY STATUTORY AUTHORITY)	NO ACCESS (BY PREVIOUS PROJECT)	TEMPORARY LIMITED EASEMENT	PERMANENT LIMITED EASEMENT	FEE TITLE
RIGHT-OF-WAY MONUMENTS SET AT NEWLY ACQUIRED R/W ANGLE POINTS	PARCEL NUMBER	UTILITY PARCEL NUMBER	R/W POINT NUMBER	COMPENSABLE NON-COMPENSABLE	POWER POLE
TELEPHONE POLE	TELEPHONE PEDESTAL				

LINE	BEARING	DISTANCE
L1	S01°25'34"W	10.05'
L2	N76°03'36"E	89.30'
L3	S00°59'51"E	20.00'
L4	S01°25'34"W	80.07'
L5	S01°51'22"E	5.00'
L6	N89°00'09"E	128.88'
L7	S01°08'24"W	25.02'
L8	S89°00'09"W	63.21'
L9	N00°59'51"W	10.00'
L10	N75°08'25"W	73.20'
L11	S01°25'34"W	40.02'
L12	S89°01'00"W	11.28'

Notes:

POSITIONS SHOWN ON THIS PLAT ARE WISCONSIN COUNTY COORDINATES, MANITOWOC COUNTY, NAD 83 (2011) IN US SURVEY FEET. VALUES SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.


RIGHT OF WAY MONUMENTS ARE TYPE 2 MONUMENTS (TYPICALLY 3/4 X 24" REBAR) AND WILL BE PLACED PRIOR TO THE COMPLETION OF THE PROJECT.

RIGHT OF WAY BOUNDARIES ARE DEFINED WITH COURSES OF THE PERIMETER OF THE HIGHWAY LANDS REFERENCED TO THE U.S. PUBLIC LAND SURVEY OR OTHER SURVEYS OF PUBLIC RECORD.

PROPERTY LINES SHOWN ON THIS PLAT ARE DRAWN FROM DATA DERIVED OF MAPS AND DOCUMENTS OF PUBLIC RECORD AND/OR EXISTING OCCUPATION LINES. EXCLUDING RIGHT-OF-WAY BOUNDARIES, THIS PLAT MAY NOT BE A TRUE REPRESENTATION OF EXISTING PROPERTY LINES AND SHOULD NOT BE USED AS A SUBSTITUTE FOR AN ACCURATE FIELD SURVEY.

DIMENSIONS FOR THE NEW RIGHT-OF-WAY ARE MEASURED ALONG AND PERPENDICULAR TO THE NEW REFERENCE LINE.

HILLCREST ROAD IS DEFINED FROM R/W CONVEYANCES DOC NO'S VOL. 47L PG. 116, DOC. NO. 465899 AND VOL. 47L PG. 140 DOC. NO. 465920



NOT TO SCALE

TOWN

BEGIN RELOCATION ORDER
STA 7+00.00

50.25' SOUTH OF AND 12.52' WEST OF THE
SOUTHWEST CORNER OF SECTION 14, T20N,
R22E, TOWN OF FRANKLIN, MANITOWOC
COUNTY, WISCONSIN
Y: 339060.922
X: 185484.075

1 SW-SW
SECTION 14
PAMELA A. BRAUN, GAIL S. DENOR,
THOMAS R. WENZLAFF & JULIE GRIMM

END RELOCATION ORDER
STA 12+00.00

4167' SOUTH OF AND 487.40'
EAST OF SOUTHWEST CORNER,
SEC 14, T20N, R22E, TOWN OF
FRANKLIN, MANITOWOC COUNTY,
WISCONSIN
Y: 339069.504
X: 185984.001

FRONTIER COMMUNICATION
F/K/A/ GENERAL TELEPHONE CO.
5 ROD EASEMENT, VOL 44B,
PG. 26L, DOC. NO. 454214

FRONTIER COMMUNICATION
F/K/A/ GENERAL TELEPHONE CO.
2 ROD EASEMENT, VOL 52L,
PG. 140, DOC. NO. 491609

UTILITY INTEREST REQUIRED

PARCEL NUMBER	OWNER	INTEREST REQUIRED
90	FRONTIER COMMUNICATIONS	RELEASE OF RIGHTS

SCALE 0 60' 120'
TOTAL NET LENGTH OF CENTERLINE = 0.095 MI.

ACCEPTED FOR
TOWN OF FRANKLIN

11-28-16 (Date) *David L. Kucinek* (Signature & Title of Official)



ORIGINAL PLANS PREPARED BY

OMNI
ASSOCIATES
APPLETON, WISCONSIN

WISCONSIN
DAVID A. YURK
S-2648
OSHKOSH,
WI
PROFESSIONAL LAND SURVEYOR

11-17-2016 (Date) *David A. Yurk* (Signature)


BENCH MARKS			
NO.	STATION	DESCRIPTION	ELEV.
BM1	7+28, 36'RT	60 D SPIKE IN 10" ASPEN TREE	788.69
BM2	12+38, 46'RT	60D SPIKE IN PP*2022-23W7	804.77
BM3	15+20, 37' L	60D SPIKE IN PP*2022-14L10	813.95




PROJECT NO: 4316-09-71	HWY: HILLCREST RD	COUNTY: MANITOWOC	PLAN AND PROFILE: HILLCREST RD	SHEET 13
------------------------	-------------------	-------------------	--------------------------------	----------

Standard Detail Drawing List


08D02-06	CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
08F01-11	APRON ENDWALLS FOR CULVERT PIPE
12A03-10	NAME PLATE (STRUCTURES)
13B02-08A	CONCRETE PAVEMENT APPROACH SLAB
14B15-09A	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-09B	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-09C	STEEL PLATE BEAM GUARD, CLASS "A", INSTALLATION & ELEMENTS
14B20-11A	STEEL THRIE BEAM STRUCTURE APPROACH
14B20-11F	STEEL THRIE BEAM STRUCTURE APPROACH, CONNECTION TO BRIDGE RAILING TYPE "M"
14B27-01A	STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL
14B27-01B	STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL
14B27-01C	STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL
14B42-04A	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-04B	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-04C	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B44-02A	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-02B	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-02C	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B45-04A	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04B	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04C	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-04H	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
15C02-06A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-06B	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C06-08	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-17A	LONGITUDINAL MARKING (MAINLINE)
15D38-01A	TEMPORARY TRAFFIC CONTROL FIXED MESSAGE SIGNS
15D38-01B	ATTACHMENT OF SIGNS TO POSTS




SECTION F-F




SECTION C-C




SECTION D-D




SECTION H-H



SECTION E-E



LOCATION OF TIE BARS IN WINGWALL



* PARTIAL PLAN VIEW
SURFACE DRAIN WITHOUT PIPE
TYPE "B"

⑧ THIS DIMENSION MAY VARY DEPENDING ON THE SPACING OF POSTS FOR THE STEEL PLATE BEAM GUARD. THE TYPICAL LOCATION FOR THE SURFACE DRAIN IS WHERE THE POST SPACING WIDENS TO 3'-1½".

CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

94408

DATE

FHWA

/S/ Jerry H. Zogg

ROADWAY STANDARDS DEVELOPMENT


ROADWAY STANDARDS DEVELOPMENT ENGINEER



- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1½" X 1½" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.



SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED <u>4-29-05</u> DATE	<u>/S/ Beth Cannestra</u> CHIEF ROADWAY DEVELOPMENT ENGINEER




GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SANDBAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT, H, EXCEEDS 8 FT., POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE 02 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BED ROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.




TURBIDITY BARRIER DETAIL SHOWING TYPICAL PLACEMENT AT STRUCTURES

TURBIDITY BARRIER	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 6/04/02 DATE	/S/ Beth Canestra CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA	


METAL APRON ENDWALLS											
PIPE DIA. (IN.)	MIN. THICK. (Inches)		DIMENSIONS (Inches)							APPROX. SLOPE	BODY
	STEEL	ALUM.	A (±1")	B (MAX.)	H (±1")	L (±1 1/2")	L1 ①	L2 ①	W (±2")		
12	.064	.060	6	6	6	21	12	17 1/2	24	2 1/2 to 1	1 Pc.
15	.064	.060	7	8	6	26	14	21 3/4	30	2 1/2 to 1	1 Pc.
18	.064	.060	8	10	6	31	15	28 1/4	36	2 1/2 to 1	1 Pc.
21	.064	.060	9	12	6	36	18	29 5/8	42	2 1/2 to 1	1 Pc.
24	.064	.075	10	13	6	41	18	37 1/4	48	2 1/2 to 1	1 Pc.
30	.079	.075	12	16	8	51	18	52 1/4	60	2 1/2 to 1	1 Pc.
36	.079	.105	14	19	9	60	24	59 3/4	72	2 1/2 to 1	2 Pc.
42	.109	.105	16	22	11	69	24	75 5/8	84	2 1/2 to 1	2 Pc.
48	.109	.105	18	27	12	78	24	81	90	2 1/4 to 1	3 Pc.
54	.109	.105	18	30	12	84	30	85 1/2	102	2 1/4 to 1	3 Pc.
60	.109x	.105x	18	33	12	87	—	—	114	2 to 1	3 Pc.
66	.109x	.105x	18	36	12	87	—	—	120	2 to 1	3 Pc.
72	.109x	.105x	18	39	12	87	—	—	126	2 to 1	3 Pc.
78	.109x	.105x	18	42	12	87	—	—	132	1 1/2 to 1	3 Pc.
84	.109x	.105x	18	45	12	87	—	—	138	1 1/2 to 1	3 Pc.
90	.109x	.105x	18	37	12	87	—	—	144	1 1/2 to 1	3 Pc.
96	.109x	.105x	18	35	12	87	—	—	150	1 1/2 to 1	3 Pc.

* EXCEPT CENTER PANEL
SEE GENERAL NOTES




PLAN VIEW

REINFORCED
EDGE (SEE
SECTION A-A)




END VIEW




SIDE ELEVATION
METAL ENDWALLS

REINFORCED CONCRETE APRON ENDWALLS											
PIPE DIA. (IN.)	DIMENSIONS (Inches)							APPROX. SLOPE			
	T	A	B	C	D	E	G				
12	2	4	24	48 1/8	72 1/8	24	2	3 to 1			
15	2 1/4	6	27	46	73	30	2 1/4	3 to 1			
18	2 1/2	9	27	46	73	36	2 1/2	3 to 1			
21	2 3/4	9	36	37 1/2	73 1/2	42	2 3/4	3 to 1			
24	3	9 1/2	43 1/2	30	73 1/2	48	3	3 to 1			
27	3 1/4	10 1/2	49 1/2	24	73 1/2	54	3 1/4	3 to 1			
30	3 1/2	12	54	19 3/4	73 1/2	60	3 1/2	3 to 1			
36	4	15	63	34 3/4	97 3/4	72	4	3 to 1			
42	4 1/2	21	63	35	98	78	4 1/2	3 to 1			
48	5	24	72	26	98	84	5	3 to 1			
54	5 1/2	27	65	33 1/4-35	98 1/4-100	90	5 1/2	2 2/5 to 1			
60	6	30-35	60	39	99	96	5	2 to 1			
66	6 1/2	24-30	72-78	21-27	99	102	5 1/2	2 to 1			
72	7	24-36	78	21	99	108	6	2 to 1			
78	7 1/2	24-36	78	21	99	114	6 1/2	2 to 1			
84	8	36	90 1/2	21	111 1/2	120	6 1/2	1 1/2 to 1			
90	8 1/2	41	87 1/2	24	111 1/2	132	6 1/2	1 1/2 to 1			


* MINIMUM
** MAXIMUM



PLAN




END VIEW




LONGITUDINAL SECTION
CONCRETE ENDWALLS

1" WIDE, 12 GA. (0.109"
THICK) GALVANIZED STRAP
WITH STANDARD 6" X 1/2"
BAND BOLT AND NUT




ALTERNATE FOR TYPE 1 CONNECTION
END SECTION CONNECTOR STRAP




TYPE 1

FOR 12" THRU 24" CORR. PIPE




TYPE 2

FOR 30" THRU 96" CORR. PIPE



TYPE 3

FOR 42" THRU 96" CORR. PIPE



TYPE 5

ALTERNATE FOR:
ALL SIZES CORRUGATED CIRCULAR PIPE


NOTE: DIMPLED BAND FITS OVER OUTSIDE OF ENDWALL,
AND CORRUGATED BAND FITS INSIDE ENDWALL.
DIMPLED BAND MAY BE USED WITH HELICALLY
CORRUGATED PIPE.

FOR CIRCUMFERENTIALLY CORRUGATED PIPE USE
ENDWALL CONNECTION DETAILS 1, 2, 3 OR 5
AS APPLICABLE.

FOR HELICALLY CORRUGATED PIPE USE ENDWALL
CONNECTION DETAILS 1, 2 OR 5.

FOR HELICALLY CORRUGATED PIPES WITH TWO
CIRCUMFERENTIAL CORRUGATIONS AT EACH END
USE ENDWALL CONNECTION DETAILS 1, 2 OR 3.

CONNECTION DETAILS



SECTION A-A

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON
THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE
STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

CONCRETE CULVERT ENDWALLS MAY NOT BE USED WITH GALVANIZED STEEL
OR ALUMINUM CULVERT PIPE OR VISE VERSA. GALVANIZED STEEL OR
ALUMINUM ENDWALLS SHALL NORMALLY BE INSTALLED ON CULVERT PIPE
OF THE SAME METAL.

ALL THREE PIECE STEEL APRON ENDWALLS FOR 60" DIAMETER PIPE AND
LARGER SHALL HAVE 0.109" SIDES AND 0.138" CENTER PANELS. ALL
THREE PIECE ALUMINUM APRON ENDWALLS FOR 60" DIAMETER PIPE AND
LARGER SHALL HAVE 0.105" SIDES AND 0.134" CENTER PANELS. THE WIDTH
OF CENTER PANELS SHALL BE GREATER THAN 20 PERCENT OF THE PIPE
PERIMETER.

LAP SEAMS SHALL BE TIGHTLY JOINED BY GALVANIZED RIVETS OR BOLTS
FOR STEEL UNITS AND ALUMINUM RIVETS AND BOLTS FOR ALUMINUM UNITS.
FOR THE 60" THROUGH 96" DIAMETER APRON ENDWALL SIZES, THE REINFORCED
EDGES AND CENTER PANEL SEAMS SHALL BE FURTHER REINFORCED WITH
GALVANIZED STEEL OR ALUMINUM STIFFENER ANGLES. THE ANGLES SHALL BE
ATTACHED BY GALVANIZED NUTS AND BOLTS FOR STEEL UNITS AND ALUMINUM
NUTS AND BOLTS FOR ALUMINUM UNITS.


WHERE TWO OR MORE PIPES WITH APRON ENDWALLS ARE LAID ADJACENT
TO EACH OTHER, THEY SHALL BE SEPARATED BY A DISTANCE SUFFICIENT
TO PROVIDE A MINIMUM CLEARANCE OF 6 INCHES BETWEEN APRON ENDWALLS.

① FOR PIPE SIZES UP TO 60" DIAMETER, A 180° ROLLED EDGE MAY BE USED
INSTEAD OF STEEL ROD REINFORCEMENT. SEE SECTION A-A.


APRON ENDWALLS FOR CULVERT PIPE

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
11/30/94
DATE
/S/ Rory L. Rhinesmith
CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA



TYPICAL NAME PLATE
(BRIDGES, CULVERTS, AND RETAINING WALLS)




**NUMBERING DESIGNATION
MULTI-UNIT STRUCTURES**

GENERAL NOTES


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.




SECTION A-A



ALTERNATE LUG

- ① ADHERE ANCHOR LUG TO PRECAST RETAINING WALL WITH EPOXY RESIN.



ALTERNATE LUG
(FOR ATTACHMENT TO PRECAST STRUCTURES)

**NAME PLATE
(STRUCTURES)**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED


3/26/10
DATE

FHWA


/S/ Scot Becker
CHIEF STRUCTURAL DEVELOPMENT ENGINEER



**SKewed APPROACH
(PAVEMENT MORE THAN 2 LANES)**



**SKEDS > 20°
(PAVEMENT WIDTH ≤ 30')**




**SKEDS ≤ 20°
(PAVEMENT WIDTH ≤ 30')
APPROACH SLAB AND ADJACENT PAVEMENT**


* (RS) = REINFORCED CONCRETE SLAB
* (PS) = PAVED CONCRETE SHOULDER OR CONCRETE DRAINAGE SLAB
(SEE DETAILS ELSEWHERE IN THE PLAN)
* (NRS) = NON-REINFORCED CONCRETE SLAB

*** STANDARD DOWEL BAR DIAMETER
(SEE SDD 13C11, & SDD 13C13)


- (A) STANDARD CONTRACTION JOINT NORMAL TO ℓ OR ℓ_c
(B) STANDARD LONGITUDINAL JOINT WITH TIE BARS.
(C) 1½" EXPANSION JOINT WITH DOWEL BARS NORMAL TO ℓ OR ℓ_c



**SECTION A-A
REINFORCEMENT POSITIONING DETAIL**



**SECTION C-C
TRANSITION DETAIL
APPROACH SLAB TO ADJACENT PAVEMENT**




**SECTION D-D
CONTRACTION JOINT**

GENERAL NOTES


THE CONTRACTOR MAY SPLICE NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLICE PER BAR. THE LENGTH OF LAP IS 20 INCHES.

TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.

- THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2'-0" C-C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
- THE CONTRACTOR MAY OMIT TIE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
- DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
- USE A JOINT SEALANT MEETING THE REQUIREMENTS OF ASTM D6690.
- PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.



**SECTION B-B
BEND DETAIL
BOTTOM REINFORCEMENT**



EXPANSION JOINT DETAIL

**CONCRETE PAVEMENT
APPROACH SLAB**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June, 2015 /S/ Peter Kemp, P.E.
DATE PAVEMENT SUPERVISOR
FHWA

6


- S.D.D. 14 B 15-9a



TYPICAL INSTALLATION OF STEEL PLATE BEAM GUARD





STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




FRONT VIEW

POST SPACING STANDARD INSTALLATION

SECTION THRU W BEAM




FRONT VIEW
BEAM SPLICE AT WOOD POST
AND POST MOUNTING DETAIL




FRONT VIEW

POST SPACING FOR LONGER POST
AT HALF POST SPACING W BEAM (LHW)



FRONT VIEW
BEAM SPLICE AT STEEL POST

TYPICAL SPLICING DETAILS
OF STEEL PLATE BEAM GUARD





NESTED W BEAM (NW)

USE ALL OTHER STANDARD BEAM GUARD DETAILS FOR
CONSTRUCTING NESTED W BEAM (NW)

REFLECTOR SPACING^⑨

	BEAM GUARD LENGTH	REFLECTOR SPACING	NO. SURFACES REFLECTORIZED	MIN. NO. REFLECTORS
ONE WAY TRAFFIC	< 200'	50' C-C	1	3
	> 200'	100' C-C	1	
TWO WAY TRAFFIC	< 200'	25' C-C	1 ^⑩	6
	> 200'	50' C-C	1	
TWO WAY TRAFFIC	< 200'	50' C-C	2 ^⑪	3
	> 200'	100' C-C	2	




ONE SIDED REFLECTOR DETAIL AND TYPICAL INSTALLATION

GENERAL NOTES

- ⑧ PROVIDE SILVER REFLECTIVE SHEETING ON ALL REFLECTORS EXCEPT THOSE LOCATED ALONG THE LEFT EDGE OF ONE-WAY ROADWAYS, WHICH SHALL BE PROVIDED WITH YELLOW REFLECTIVE SHEETING. SHEETING IS TYPE H. SEE STANDARD SPECIFICATION 637.
- ⑨ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
- ⑩ REVERSE EVERY OTHER REFLECTOR FOR 2-WAY VISIBILITY. THE CONTRACTOR MAY FURNISH TWO-SIDED REFLECTORS IN LIEU OF ONE-SIDED REFLECTORS.
- ⑪ PROVIDE AN ANGLE OF BEND OF 90° ± 1° FOR TWO-SIDED REFLECTORS.
- ⑫ 8 - 5/8" ϕ X 2" BUTTON HEAD BOLTS WITH OVAL SHOULDERS & RECESS NUTS.
- ⑬ 5/8" DIA. BUTTON HEAD BOLT AND RECESS NUT WITH 5/8" DIA. F844 FLAT WASHER UNDER NUT.


STEEL PLATE BEAM GUARD,
CLASS "A",
INSTALLATION & ELEMENTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



DETAIL FOR DOUBLE BLOCKS

THE NUMBER OF DOUBLE BLOCK POSTS
WITHIN A BARRIER RUN IS UNLIMITED




DETAIL FOR TRIPLE BLOCKS


TRIPLE BLOCK DETAIL IS LIMITED TO ONE
LOCATION WITHIN A BEAM GUARD RUN.

NOTES: USE DOUBLE OR TRIPLE BLOCKS WHEN UNDERGROUND OBSTACLES
PREVENT THE POST FROM BEING INSTALLED.

DO NOT USE EXTRA BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND
SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION
DISTANCE OF THE BARRIER.



PLAN VIEW BEAM LAPPING DETAIL



POST DRIVING FOR CONTINUOUS UNDERGROUND OBSTRUCTION

STEEL PLATE BEAM GUARD,
CLASS "A",
INSTALLATION & ELEMENTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

June 2016
DATE

FHWA

/S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER





PLATE WASHER DETAIL


GENERAL NOTES

BOLT THE THRIE BEAM TO ALL POSTS AND BLOCKOUTS. DRILL OR PUNCH BOLT HOLES IN THE BEAM IF THE POST SPACING IS LESS THAN 6'-3".


DO NOT USE STEEL POSTS AND NOTCHED PLASTIC BLOCKOUTS IN THE STEEL THRIE BEAM STRUCTURAL APPROACH AND THE TRANSITION SECTION OF STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATIONS.

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2 1/2", AND 12" DIAMETER AROUND POST. SEE 14B15 FOR MORE DETAILS.


- ① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.
- ② MINIMUM EMBEDMENT SHALL BE 4'-0". WHERE EXISTING CONDITIONS DO NOT PERMIT THE APPROPRIATE EARTHWORK SHOWN ON THE PLAN TYPICAL SECTIONS OR DETAILS, THE ENGINEER MAY ALLOW THE REDUCTION OR ELIMINATION OF THE 2 FOOT DISTANCE TO THE HINGE POINT. OTHERWISE BUILD AS THE PLAN SHOWS OR AS THE ENGINEER DIRECTS. IF THE 2 FOOT DISTANCE TO THE HINGE POINT IS REDUCED OR ELIMINATED, INCREASE THE POST EMBEDMENT DEPTH TO 4'-6" OR MORE.
- ③ POST BOLTS ARE 5/8" DIAMETER ASTM A307 BUTTON HEAD BOLT. A POST BOLT REQUIRES A 5/8" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX AND A 5/8" DIAMETER F844 FLAT WASHER. LENGTH OF POST BOLT MAY VARY.
- ④ ALL WOOD POSTS MUST BE 6" X 8" AND AT LEAST 7'-0" LONG.




TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE




THRIE BEAM TERMINAL CONNECTOR



THRIE BEAM SPLICE



SECTION THRU THRIE BEAM RAIL ELEMENT



SECTION A-A

STEEL THRIE BEAM STRUCTURE APPROACH

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

8/31/2012

DATE

FHWA



/s/ Jerry H. Zogg

ROADWAY STANDARDS DEVELOPMENT


ENGINEER

GENERAL NOTES




① VARY THIS DIMENSION DEPENDING ON ABUTMENT TYPE, WINGWALL DETAILS, AND ANGLE OF SKEW. PLACE THE FIRST WOOD POST OFF THE BRIDGE SHALL BE AS CLOSE AS FEASIBLE TO THE STEEL END POST.





BACK-UP PLATE DETAIL, TYPE "M"



ANCHOR PLATE DETAIL, TYPE "M"



ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"




THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"


**STEEL THRIE BEAM STRUCTURE
APPROACH CONNECTION TO
BRIDGE RAILING TYPE "M"**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
8/31/2012 DATE /S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT
ENGINEER
FHWA



TYPICAL LAYOUT
(8' RADIUS SHOWN)



SECTION A-A
(CRT POST)

TYPICAL LAP SPLICES
(8' RADIUS SHOWN)

GENERAL NOTES

ALL ANGLES, CHANNELS, AND PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A36 AND THE STRUCTURAL TUBING SHALL CONFORM TO ASTM A 500. WELDING SHALL MEET THE CURRENT REQUIREMENTS OF THE AMERICAN WELDING SOCIETY STRUCTURAL WELDING CODE ANSI/AWS D1.1. ALL STRUCTURAL STEEL SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A 123. PUNCHING, DRILLING, CUTTING, OR WELDING WILL NOT BE PERMITTED AFTER GALVANIZING. FURNISH AND INSTALL HARDWARE PER STANDARD SPECIFICATION 614.2, UNLESS NOTED OTHERWISE.


SHOP BEND CURVED RAIL SECTIONS.

SEE STANDARD DETAIL DRAWING 14 B 15 FOR OTHER DETAIL.

- ① ON THE 8 FOOT RADIUS INSTALLATION, DO NOT INSTALL BUTTON HEAD BOLT AT CENTER CRT POST.
- ② RADIUS FROM 8' - 36'. SEE PLAN.
- ③ HEIGHT TRANSITION MAY BE REQUIRED. SEE PLAN OR PROJECT ENGINEER.
- ④ 5/8" Ø X 1'-6" BUTTON HEAD BOLT AND RECESS NUT WITH ROUND WASHER UNDER NUT.

RADIUS	NUMBER OF CRT POSTS	*NUMBER AND LENGTH OF CURVED RAILS	REQUIRED AREA FREE OF FIXED OBJECTS (LENGTH x WIDTH)
8'	5	1 at 12.5'	25' x 15'
16'	7	1 at 25'	30' x 15'
24'	9	1 at 25' and 1 at 12.5'	40' x 20'
32'	11	2 at 25'	50' x 20'


* THE NUMBER OF RAILS IS BASED ON A 90° INTERSECTION. SEE PLAN FOR NON 90° INSTALLATIONS.




SECTION B-B
(BEAM GUARD POST)

STEEL PLATE BEAM GUARD
SHORT RADIUS TERMINAL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



PLAN VIEW




ELEVATION VIEW


STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL

GENERAL NOTES

- ① ATTACH W BEAM RAIL TO THE STEEL PIPE WITH A $\frac{5}{8}$ " X 2" BUTTON HEAD BOLT WITH NO WASHER. CONNECTION TO THE POST IS NOT REQUIRED.
- INSTALL GALVANIZED $\frac{3}{4}$ " (6X19) PREFORMED WIRE OR INDEPENDENT WIRE ROPE CORE CONFORMING TO AASHTO M 30. MANUFACTURE WIRE ROPE OUT OF IMPROVED PLOW STEEL WITH A MINIMUM BREAKING STRENGTH OF 42,800 PSI.




DETAIL A




DETAIL B

(BEAM GUARD AND TERMINAL SECTION NOT SHOWN)


STEEL PLATE BEAM GUARD
SHORT RADIUS TERMINALSTATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




RECTANGULAR PLATE WASHER




DETAIL D




END PLATE




SECTION C-C
(END PLATE REMOVED)




ANCHOR BRACKET




DETAIL C




WOOD BREAKAWAY POST




BEARING PLATE



SOIL PLATE






CABLE ASSEMBLY



STEEL TUBE



<p>STEEL PLATE BEAM GUARD SHORT RADIUS TERMINAL</p>	
<p>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</p>	
<p>APPROVED 12/18/08 DATE</p>	<p>/S/ Jerry H. Zogg ROADWAY STANDARDS DEVELOPMENT ENGINEER</p>
<p>FHWA</p>	

- ① WOOD OR STEEL POSTS (W6X9 OR W6X8.5) MAY BE USED. DO NOT INTERMIX WOOD AND STEEL POSTS. INSTALL STEEL POSTS WITH HOLES ON APPROACHING TRAFFIC SIDE.
- ② USE WOOD OR APPROVED PLASTIC BLOCKOUTS. WOOD BLOCKOUTS MAY BE CONSTRUCTED OUT OF TWO OR MORE WOOD BLOCKOUTS. SEE ALTERNATE WOOD BLOCKOUT DETAIL. DIMENSIONS OF APPROVED PLASTIC BLOCKOUTS MAY VARY.
- ③ IF ROCK IS ENCOUNTERED DURING EXCAVATION, PROVIDE A HOLE 12 INCHES IN DIAMETER EXTENDING 20 INCHES DEEP INTO THE ROCK. PLACE APPROXIMATELY $2\frac{1}{2}$ INCHES OF GRANULAR MATERIAL IN THE BOTTOM OF THE HOLE. CUT THE POSTS TO THE LENGTH AND INSTALL. BACKFILL WITH EXCAVATED MATERIAL AND COMPACT. BACKFILL IS TO BE FREE OF LARGE ROCKS.
- ④ WHEN THE DISTANCE FROM BACK OF POST TO SHOULDER HINGE POINT IS LESS THAN 2 FEET INSTALL LONGER POST AT HALF POST SPACING (K).
- ⑤ FOR NEW MGS INSTALLATION TOP OF W-BEAM RAIL TOLERANCE IS $\pm 1"$. FOR EXISTING MGS INSTALLATION TOP OF W-BEAM IS BETWEEN $27\frac{3}{4}"$ TO 32".
- ⑥ WHEN USING STEEL POST AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.




END VIEW


LOCATED ALONG A ROADWAY SHOULDER
STANDARD INSTALLATION




**STEEL POST &
HOLE PUNCHING DETAIL
(w6X9)^①**




PLAN VIEW
WOOD POST,
BLOCKOUT & BEAM




PLAN VIEW
STEEL POST,
PLASTIC BLOCKOUT & BEAM



WOOD POST
(6" X 8") NOMINAL ^①




**WOOD OR
PLASTIC BLOCKOUT ⁽²⁾**




FRONT VIEW

POST SPACING STANDARD INSTALLATION




FRONT VIEW

HALF POST SPACING (HS) AND HALF POST SPACING WITH LONGER POSTS (K)




FRONT VIEW


QUARTER POST SPACING (QS)




FRONT VIEW AT WOOD POST




FRONT VIEW AT STEEL POST



FRONT VIEW
MID-SPAN BEAM SPLICE



SECTION THRU W-BEAM RAIL



ONE SIDED REFLECTOR DETAIL AND TYPICAL INSTALLATION


- ⑦ PROVIDE SILVER REFLECTIVE SHEETING ON ALL REFLECTORS EXCEPT THOSE LOCATED ALONG THE LEFT EDGE OF ONE-WAY ROADWAYS, WHICH SHALL BE PROVIDED WITH YELLOW REFLECTIVE SHEETING. SHEETING IS TYPE H. SEE STANDARD SPECIFICATION 637.
 - ⑧ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL. RAIL SPLICE LOCATIONS ARE THE ONLY ACCEPTABLE LOCATIONS FOR REFLECTORS.
 - ⑨ REVERSE EVERY OTHER REFLECTOR FOR 2-WAY VISIBILITY. THE CONTRACTOR MAY FURNISH TWO-SIDED REFLECTORS IN LIEU OF ONE-SIDED REFLECTORS.
 - ⑩ PROVIDE AN ANGLE OF BEND OF $90^\circ \pm 1^\circ$ FOR TWO-SIDED REFLECTORS.
 - ⑪ 25 FEET OF HALF POST SPACING IS REQUIRED ON APPROACH AND DEPARTURE ENDS OF QUARTER POST SPACING.
- POST BOLTS ARE A $\frac{5}{8}$ " DIAMETER ASTM A307 GUARDRAIL BOLT. A POST BOLT REQUIRES $\frac{5}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT AND $\frac{5}{8}$ " DIAMETER F844 FLAT WASHER. POST BOLTS MAY BE LONGER IF MULTIPLE BLOCKOUTS ARE BEING USED.
- GUARD RAIL SPLICE BOLTS ARE A $\frac{5}{8}$ " DIAMETER ASTM A307 GUARDRAIL HEAD BOLT. A GUARDRAIL SPLICE BOLT REQUIRES $\frac{5}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT.

REFLECTOR SPACING

	BEAM GUARD LENGTH	REFLECTOR SPACING	NO. SURFACES REFLECTORIZED	MIN. NO. REFLECTORS
ONE WAY TRAFFIC	< 200'	50' C-C	1	3
	> 200'	100' C-C	1	
TWO WAY TRAFFIC	< 200'	25' C-C	1 ⑨	6
	> 200'	50' C-C	1	
TWO WAY TRAFFIC	< 200'	50' C-C	2 ⑩	3
	> 200'	100' C-C	2	


MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



DETAIL FOR 16" BLOCKOUT DEPTH


IT IS ACCEPTABLE TO USE BLOCKOUTS UP TO 16" DEEP TO INCREASE THE POST OFFSET TO AVOID UNDERGROUND OBSTACLES. THERE IS NO LIMIT TO THE NUMBER OF POSTS THAT CAN HAVE ADDITIONAL BLOCKOUTS UP TO 16" DEEP.




DETAIL FOR 36" BLOCKOUT DEPTH

NOTES: UNDER SPECIAL CIRCUMSTANCES, SUCH AS AVOIDING OBSTACLES THAT ARE NOT RELOCATED, IT IS ACCEPTABLE TO INSTALL ADDITIONAL BLOCKOUTS TO OBTAIN UP TO 36" DEPTH FOR ONE OR TWO POSTS IN A SECTION OF GUARDRAIL.


DO NOT USE 16" OR 36" BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION DISTANCE OF THE BARRIER.




POST BOLT TABLE




ALTERNATE BOLT HEAD




POST BOLT, SPLICE BOLT AND RECESS NUT




PLAN VIEW
BEAM LAPPING DETAIL



POST DRIVING FOR CONTINUOUS UNDERGROUND OBSTRUCTION



SIDE VIEW



TOP VIEW

ALTERNATE WOOD BLOCKOUT DETAIL

MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2016 DATE /S/ Jerry H. Zogg
ROADWAY STANDARDS DEVELOPMENT ENGINEER
FHWA

GENERAL NOTES

- (A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL), AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.
- (B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED.
- (C) DIFFERENT MANUFACTURES REQUIRE DIFFERENT PERFORATED W-BEAM RAIL END PANELS. SEE MANUFACTURES INFORMATION.
- (D) THE TOP OF THE STEEL TUBE ON POST 1 AND POST 2 SHALL NOT BE MORE THAN 3" ABOVE THE FINISH GROUND ELEVATION.
- (E) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF-TAPPING SCREWS, ONE SCREW PER CORNER.
- (G) 1/2" DIAMETER X 3" LONG LAG BOLT AND WASHER.
- (H) HARDWARE VARIES BETWEEN DIFFERENT MANUFACTURES. SEE MANUFACTURE'S DRAWING FOR INFORMATION.
- (I) DIMENSIONS MAY VARY. SEE MANUFACTURE'S INFORMATION.


SEE SDD 14B42 FOR MORE INFORMATION.


* DO NOT ATTACH BLOCKOUTS TO POSTS 1 AND 2.

DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.




W-BEAM RAIL SPLICES ARE LOCATED AT POST NUMBER 3, AND BETWEEN POST 5 AND 6, BETWEEN POSTS 7 AND 8, AND MIDDLE OF THE SPAN AFTER POST 9.

THE CENTER OF THE UPPER 3/2" DIAMETER HOLE ON POST NUMBER 3 THROUGH POST 9 IS TO BE FLUSH WITH THE GROUND LINE UP TO A MAXIMUM OF 2" ABOVE GROUND LINE.






9 H
GENERIC GROUND STRUT






8 H
GENERIC ANCHOR CABLE BOX

BILL OF MATERIALS


PART NO.	DESCRIPTION
MATERIALS PROVIDED BY MGS EAT MANUFACTURER. SEE MANUFACTURER'S DETAILS FOR MORE INFORMATION.	
①	WOOD BREAKAWAY POST
②	6" X 8" X 0.188", 6'-0" LONG FOUNDATION TUBE AT POSTS 1 AND 2
③	WOOD CRT
④	WOOD BLOCKOUT
⑤	PIPE SLEEVE
⑥	BEARING PLATE
⑦	BCT CABLE ASSEMBLY
⑧	ANCHOR CABLE BOX
⑨	GROUND STRUT
⑩	PERFORATED W-BEAM RAIL END PANEL, 12'-6" LONG.
⑪	STANDARD W-BEAM RAIL. MULTIPLE SECTIONS REQUIRED. SECTIONS VARY IN LENGTH.
⑫	END SECTION EAT
⑬	0.040" ALUMINUM SHEET WITH REFLECTIVE SHEETING TYPE F PER SECTION 637 OF THE STANDARD SPECIFICATIONS
⑭	EAT MARKER POST - YELLOW (SEE APPROVED PRODUCTS LIST)



⑥
BEARING PLATE




<p>MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)</p>	
<p>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</p>	
<p>APPROVED June 2014</p>	<p>/S/ Jerry H. Zogg</p>
<p>DATE</p>	<p>ROADWAY STANDARDS DEVELOPMENT ENGINEER</p>
<p>FHWA</p>	



TWO WAY TRAFFIC

Ⓣ THRIE BEAM CONNECTION



ONE WAY TRAFFIC

Ⓦ W-BEAM CONNECTION WHEN REQUIRED

GENERAL NOTES

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2½", AND 12" DIAMETER AROUND POST. SEE 14B42 FOR MORE DETAILS.


TRANSITION USES STEEL POSTS ONLY.

SEE STANDARD DETAIL DRAWING 14 B 42 FOR MORE INFORMATION.


① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.

② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.

TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE



PLAN VIEW



ELEVATION VIEW


MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES


- 2 OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- 3 WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 10D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- 4 TOLERANCE FOR TOP OF W-BEAM RAIL IS $\pm 1"$.




SECTION A-A
POSTS 1-5



SECTION D-D
POSTS 12-17



SECTION B-B
POST 6



SECTION C-C
POSTS 7-11







PLATE WASHER DETAIL



SPlice DETAIL




THRIE BEAM
TERMINAL CONNECTOR




SECTION THRU THRIE
BEAM RAIL ELEMENT

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




W-BEAM TO THRIE BEAM TRANSITION SECTION




6'-3" THRIE BEAM SECTION




12'-6" THRIE BEAM SECTION




FRONT VIEW SIDE VIEW
STEEL POSTS 1-5




FRONT VIEW SIDE VIEW
STEEL POSTS 6-17




TOP VIEW



FRONT VIEW
BLOCKOUT
POSTS 1-5



TOP VIEW



FRONT VIEW
BLOCKOUT
POSTS 6-17


GENERAL NOTES

STEEL POSTS ARE W6X9 OR W6X8.5.


BOLT HOLES FOR POST ARE ON FRONT AND OF SIDE OF POST.

(3) WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.

(5) WOOD BLOCKS MAY BE CONSTRUCTED OUT OF 2 WOOD BLOCKS. SEE ALTERNATE WOOD BLOCK DETAIL.



SIDE VIEW



TOP VIEW


ALTERNATE WOOD BLOCKOUT DETAIL

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES

④ TOLERANCE FOR TOP OF W-BEAM RAIL IS $\pm 1"$.




FRONT VIEW




PLAN VIEW

BACK-UP PLATE DETAIL, TYPE "M"




FRONT VIEW


ANCHOR PLATE DETAIL, TYPE "M"



SECTION M-M




SECTION L-L




FRONT VIEW

ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"



FRONT VIEW



PLAN VIEW

THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"

MIDWEST GUARDRAIL SYSTEM
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

June, 2015


DATE

FHWA

/s/ Jerry H. Zogg

ROADWAY STANDARDS DEVELOPMENT


ENGINEER



DETAIL A


MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE GREATER THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)















DETAIL B
MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE LESS THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (F T)
25	200
30	200
35	350
40	350
45	500
50	550
55	750



- # LEGEND
-  SIGN ON PERMANENT SUPPORT
-  TYPE III BARRICADE
-  TYPE III BARRICADE WITH ATTACHED SIGN
-  TYPE "A" WARNING LIGHT (FLASHING)
-  WORK AREA
-  M4-8
-  M3-X
-  M1-4
-  M1-5A
-  M1-6
-  M05-1
-  M06-1
- FLAGS, 16" X 16" MIN., (ORANGE)

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦

BARRICADES AND SIGNS FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

Sept. 2015	/S/ Peter Amakobe Atepe
DATE	STATEWIDE WORK ZONE TRAFFIC
FHWA	SAFETY ENGINEER



SEE SDD 15C2-SHEET "a" FOR LEGEND

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION OR, FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL D FOR FULL ROAD CLOSURES.

TYPE "A" LOW-INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11-2, R11-3, M4-9, R11-4 AND R10-61 SIGNS PLACED ON BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11-2 SHALL BE 48" X 30".

R11-3, R11-4 AND R10-61 SHALL BE 60" X 30".

M4-9 SHALL BE 30" X 24".

M3-X SHALL BE 24" X 12". (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS.)

M4-8 SHALL BE 24" X 12". (30" X 15" IF NEEDED TO MATCH EXISTING SIGNS.)

M1-4, M1-5A, AND M1-6 SHALL BE 24" X 24". (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS.)


M05-1 AND M06-1 SHALL BE 21" X 21". (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS.)

D1-X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.

R1-1 SHALL BE 36" X 36".

- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8-FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL D.
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE LANE CLOSURE BARRICADE DETAIL E.
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11-2 AND R11-3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR MAINLINE CLOSURES	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
Sept. 2015 DATE	/S/ Peter Amokobe Atepe STATEWIDE WORK ZONE TRAFFIC SAFETY ENGINEER
FHWA	



SITUATION 1

WARRANTING CRITERIA:
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.


DISTANCE TABLE

POSTED OR 85th PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	750'

GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

- ① LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.
- ② OMIT ON ONE-WAY TRAVELLED WAYS.
- ③ EDGE OF W5-52 SIGN SHALL BE PLACED IN LINE WITH FACE OF CURB OR PARAPET.




SITUATION 2

WARRANTING CRITERIA:
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET.


SIGNING & MARKING FOR TWO LANE BRIDGES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
4-18-16 /S/ Matthew R. Rauch
DATE STATE SIGNING AND MARKING ENGINEER
FHWA




TWO WAY TRAFFIC




ONE WAY TRAFFIC

PERMANENT PAVEMENT MARKING



TWO WAY TRAFFIC



ONE WAY TRAFFIC

TEMPORARY PAVEMENT MARKING

GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

① NO PASSING ZONE W14-3 SIGN SHALL BE LOCATED WITHIN 50 FEET OF THE "T" MARKING.

NOTE

ARROW SYMBOL (→) SHOWS DIRECTION OF TRAVEL

LEGEND


—●— "T" MARKING

● POST MOUNTED SIGN

LONGITUDINAL MARKING
(MAINLINE)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Sept., 2016 /S/ Matthew R. Rauch
DATE STATE SIGNING AND MARKING ENGINEER
FHWA





DETAIL OF TUBULAR STEEL SIGN POST

TUBULAR STEEL POSTS

AREA OF SIGN INSTALLATION (SQ. FT.)	NUMBER OF REQUIRED TUBULAR STEEL POSTS
9 OR LESS	1
GREATER THAN 9 LESS THAN OR EQUAL TO 18	2
GREATER THAN 18 LESS THAN OR EQUAL TO 27	3

SIGNS WIDER THAN 3 FEET OR LARGER THAN 9 SQ. FT. SHALL BE MOUNTED ON MULTIPLE POSTS (SEE ABOVE TABLE).

SIGNS LARGER THAN 27 SQ. FT. SHALL NOT BE MOUNTED ON TUBULAR STEEL POSTS.




URBAN AREA


POST MOUNTING DETAIL FOR TEMPORARY TRAFFIC CONTROL FIXED MESSAGE SIGNS

WOOD POST EMBEDMENT DEPTH

AREA OF SIGN INSTALLATION (SQ. FT.)	D (MIN)
20 OR LESS	4'
GREATER THAN 20	5'



4"x6" WOOD POST MODIFICATION



RURAL AREA

4" X 6" WOOD POST

POST SPACING REQUIREMENTS		NUMBER OF WOOD POSTS REQUIRED
L	E	
48" OR LESS AND LESS THAN 20 SQ. FT.	-	1
LESS THAN 60"	12"	2
60" TO 120"	L/5	2
GREATER THAN 120" LESS THAN 168"	12"	3
168" AND GREATER	12"	4


SEE NOTE ③

GENERAL NOTES

- ① 6 FEET FROM THE EDGE OF PAVEMENT (EDGE LINE LOCATION) UNLESS OTHERWISE DIRECTED BY THE PROJECT ENGINEER. LATERAL OFFSET SHOULD BE ADJUSTED TO AVOID THE DITCH FLOWLINE.
- ② THE EXISTENCE OF CURB AND GUTTER DOES NOT IN ITSELF MANDATE THE VERTICAL CLEARANCE ILLUSTRATED. THAT HEIGHT IS TYPICALLY MEASURED WHERE THERE IS SIDEWALK ADJACENT TO THE ROADWAY OR PARKING IS PERMITTED. IN THE ABSENCE OF SIDEWALK, VERTICAL CLEARANCE IS MEASURED FROM THE TOP OF THE CURB. IF NO SIDEWALK AND NO PARKING, VERTICAL CLEARANCE MAY BE REDUCED TO 5 FOOT MINIMUM. OFFSET OF SIGNS IS MEASURED FROM THE CURB FLOWLINE.
- ③ FOR SIGNS REQUIRING 4 POSTS, SPACE INTERMEDIATE POSTS EVENLY.

TEMPORARY TRAFFIC CONTROL
FIXED MESSAGE SIGNS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



NUTS, BOLTS AND LAGS USED FOR MOUNTING SIGNS SHALL HAVE HEXAGONAL HEADS AND SHALL BE EITHER:

- A. HOT DIP GALVANIZED IN ACCORDANCE WITH ASTM DESIGNATION: A 153, CLASS D, OR SC 3
- B. ELECTRO-GALVANIZED IN ACCORDANCE WITH ASTM DESIGNATION: B 633, TYPE III, SC 3

THREADS ON BOLTS AND NUTS SHALL BE MANUFACTURED WITH SUFFICIENT ALLOWANCE FOR THE CADMIUM PLATE OR GALVANIZED COATING TO PERMIT THE NUTS TO RUN FREELY ON THE BOLTS.

- WOOD POSTS (4" x 4" or 4" x 6")
- LAG SCREWS - 3/8" x 3"
 - MACHINE BOLTS - 5/16" x 6-1/2" OR 7" LENGTH W/ NUTS


- SQUARE STEEL POSTS (2" x 2")
- MACHINE BOLTS - 3/8" x 3-1/4" LENGTH W/ NUTS
 - RIVETS - 9/32" (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

- WASHERS (ALL POSTS) -
- 1-1/4" O.D. x 3/8" I.D. x 1/16" STEEL
 - 1-1/4" O.D. x 3/8" I.D. x .080 NYLON FOR ALL TYPE H SIGNS




* TWO DIFFERENT FASTENING SYSTEMS ARE SHOWN FOR ILLUSTRATION PURPOSES. ON ANY INDIVIDUAL SIGN, EITHER ONE OR THE OTHER SYSTEM SHALL BE USED. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA. FOR A SINGLE POST INSTALLATION, ALL SIGNS GREATER THAN 9 SQ. FT. REQUIRE THE USE OF 3 FASTENERS.

ATTACHMENT OF SIGNS TO POSTS		
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION		
APPROVED Feb. 2015	/S/ Travis Feltes	
DATE	STATE TRAFFIC ENGINEER OF DESIGN	
FHWA		

URBAN AREA



RURAL AREA (See Note 2)



GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on barrier wall, see A4-10 sign plate.
3. For expressways and freeways, mounting height is 7'- 3" (±) or 6'-3" (±) depending upon existence of a sub-sign.
4. Minimum mounting height for J assemblies (A2-1S) is 7'-3" (±) or 6'-3" (±) per urban or rural detail respectively.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'- 3" (±).
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. The (±) tolerance for mounting height is 3 inches.
8. Folding signs shall be mounted at a height of 5'-3" (±) or as directed by the Engineer.
9. The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (±). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±).

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq.Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

* * The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.


* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION OF PERMANENT TYPE II SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
for State Traffic Engineer

DATE 7/23/15 PLATE NO. A4-3.20



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :



- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

- STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)
- MACHINE BOLTS - 5/16" X 1-3/4" Length w/ lock nuts
- WOOD POSTS (4" x 4" or 4" x 6")
- LAG SCREWS - 3/8" X 3" (NO STRINGERS ON BACK OF SIGN)
 - 3/8" X 4" (STRINGERS ON BACK OF SIGN)
- SQUARE STEEL POSTS (2" x 2")
- MACHINE BOLTS - 3/8" X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)
 - 3/8" X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)
- RIVETS - 9/32" (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL
- O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH
- WASHERS (ALL POSTS) -
- 1-1/4" O.D. X 3/8" I.D. X 1/16" STEEL
 - 1-1/4" O.D. X 3/8" I.D. X .080 NYLON

* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.

ATTACHMENT OF SIGNS TO POSTS	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R. Rauch</i> For State Traffic Engineer
DATE 8/11/16	PLATE NO. 15 A4-8.8



SIDE VIEW

GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two 1½" diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Chester J. Spang
for State Traffic Engineer

DATE 3/27/97

PLATE NO. A4-11.2

PROJECT NO:

HWY:


COUNTY:

SHEET NO:

E

NOTES

- 1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
- 2. Color:
 - Background - White
 - Message - Black
- 3. Message Series - D
- 4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.




R11-2B

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
2M	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
3	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
4	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
5	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0

STANDARD SIGN	
R11-2B	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R. Rauch</i> For State Traffic Engineer
DATE 4/1/11	PLATE NO. R11-2B.2

NOTES

1. Sign is Type II - Type H Reflective
2. Color:
 - Background - White
 - Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals to nearest quarter mile and optically adjust spacing to achieve proper balance.



** See Note 5

R11-3B

The diagram shows a 1/4 mile race track layout. The track is represented by a horizontal line with arrows at both ends. The layout is divided into segments by vertical lines. The segments are labeled as follows: P (the first segment), Q (the second segment), R (the third segment), X (the fourth segment), and Y (the fifth segment). The segments are labeled with letters P, Q, R, X, and Y. The segments are labeled with letters P, Q, R, X, and Y. The segments are labeled with letters P, Q, R, X, and Y.

[illegible]

STANDARD SIGN	
R11-3B	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<u>Matthew R Rauch</u> for State Traffic Engineer
DATE 3/21/17	PLATE NO. R11-3B.3


PROJECT NO:	HWY:	COUNTY:		SHEET NO:	18	E
-------------	------	---------	--	-----------	----	----------

NOTES

1. Sign is Type II - Type H Reflective
2. Color:


Background - White

Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals to nearest quarter mile and optically adjust spacing to achieve proper balance.



R11-3C

** See Note 5





SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	15	1 3⁄8	1⁄2	5⁄8	4	3	2 1⁄2	13 1⁄4	2 1⁄4	3	8	8	1 1⁄2	2	10 3⁄4		7 1⁄8									3.75
2S	60	24	1 3⁄8	1⁄2	5⁄8	6	5	4	20 1⁄8	3	5	12	13 1⁄4	1 3⁄4	3	17 3⁄8		11 7⁄8									10.0
2M	60	24	1 3⁄8	1⁄2	5⁄8	6	5	4	20 1⁄8	3	5	12	13 1⁄4	1 3⁄4	3	17 3⁄8		11 7⁄8									10.0
3																											
4																											
5																											

STANDARD SIGN
R11-3C

WISCONSIN DEPT OF TRANSPORTATION

APPROVED
Matthew R. Rauch
for State Traffic Engineer

DATE 7/28/16 PLATE NO. R11-3C.3



NOTES

- 1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
- 2. Color:
Background - Yellow
Message - Black
- 3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
- 4. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36				4 3⁄8	3 1⁄2	5 5⁄8	45°	4	4																3.0
2M	12	36				4 3⁄8	3 1⁄2	5 5⁄8	45°	4	4																3.0
3	18	54				6	5 1⁄2	8 1⁄2	45°	6	6 5⁄16																6.75
4																											
5																											


STANDARD SIGN

W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
for State Traffic Engineer

DATE 5/29/12 PLATE NO. W5-52.9



W20-3A

500 FT

W20-3D

1000 FT

W20-3C

1500 FT

W20-3B

1/2 MILE

W20-3G

1 MILE

W20-3F

NOTES

1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:
Background - Orange
Message - Black
3. Message Series - see note 5
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Lines 1 and 2 are Series D.
Line 3 is Series D for AHEAD and Series C for all other distances.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36		1 5/8	5/8	3/4	5	3 3/8	3 1/2	1 1/8	4	8 3/8	8 7/8	12 1/2	11	9	6	10 1/8	2 1/2	1 7/8	5 5/8	8	1 3/8	4 1/2	3 1/2	10 3/4	1 3/4	9.0
2S	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
2M	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
3	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
4	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
5	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0

STANDARD SIGN
W20-3A, B, C, D, F & G

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*
For State Traffic Engineer

DATE 3/18/11 PLATE NO. W20-3.7

PROJECT NO:


HWY:

COUNTY:

SHEET NO:

21

E



TRAFFIC DATA

ADT = 590 (2018)
650 (2038)
RDS = 40 M.P.H.

DESIGN DATA

STRUCTURE IS DESIGNED FOR FUTURE WEARING SURFACE OF 20\"/>

LIVE LOAD:

DESIGN LOADING HL-93
INVENTORY RATING FACTOR RF = 1.27
OPERATING RATING FACTOR RF = 1.65
WISCONSIN STANDARD
PERMIT VEHICLE (WIS-SPV) 250 KIPS

MATERIAL PROPERTIES:

CONCRETE MASONRY
SUPERSTRUCTURE f'c = 4,000 PSI
ALL OTHER f'c = 3,500 PSI
HIGH STRENGTH BAR STEEL REINFORCEMENT, GRADE 60 fy = 60,000 PSI
54W\"/>

HYDRAULIC DATA

Q100 2,300 C.F.S.
VELOCITY 5.18 F.P.S.
HIGH WATER EL. 780.88 (100 YEAR)
HIGH WATER EL. 777.78 (2 YEAR)
WATERWAY AREA 444 S.F.
DRAINAGE AREA 81.5 SQ. MILES
OVERTOPPING FREQUENCY = N/A
SCOUR CRITICAL CODE = 8

FOUNDATION DATA


ABUTMENTS TO BE SUPPORTED ON HP 10X42 STEEL PILING. PILING AT THE WEST ABUTMENT SHALL BE PREBORED A MINIMUM OF 3' INTO WEATHERED ROCK. AFTER PILES HAVE BEEN FIRMLY SEATED, FILL THE SHAFT WITH CEMENT GROUT. PILING AT THE EAST ABUTMENT SHALL BE DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 180 TONS** PER PILE.

ESTIMATED 15' LONG AT WEST ABUTMENT
ESTIMATED 15' LONG AT EAST ABUTMENT

** THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE DRIVEN PILE CAPACITY.

LIST OF DRAWINGS

1. GENERAL PLAN
2. CROSS SECTION & QUANTITIES
3. SUBSURFACE EXPLORATION
4. WEST ABUTMENT
5. WEST ABUTMENT DETAILS
6. EAST ABUTMENT
7. EAST ABUTMENT DETAILS
8. 54W\"/>



CONSULTANT CONTACT

KRISTOFER OLSON
OMNI ASSOCIATES, INC.
(920) 735-6900

BRIDGE OFFICE CONTACT

WILLIAM DREHER
(608) 266-8489

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY			
OMNI ASSOCIATES			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED	<i>William C. Dreher</i>	SOR	08/28/17
CHIEF STRUCTURES DESIGN ENGINEER DATE			
STRUCTURE B-36-220			
HILLCREST ROAD OVER BRANCH RIVER			
COUNTY	MANITOWOC	TOWN	FRANKLIN
DESIGN SPEC.	AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS		LOAD HL-93
DESIGNED BY	BRE	DESIGN CK'D. KRO	DRAWN BY BRE PLANS CK'D. KRO
GENERAL PLAN			SHEET 1 OF 12

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

THE SLOPE OF FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TO THE EXTENT SHOWN ON SHEET 1 AND IN THE ABUTMENT DETAILS.

THIS BRIDGE WILL REPLACE THE EXISTING SINGLE SPAN STEEL GIRDER BRIDGE SUPPORTED ON CONCRETE RETAINING ABUTMENTS. THE STRUCTURE WAS BUILT IN 1950.


ELASTOMERIC BEARING PADS NEED NOT BE INDIVIDUALLY MOLDED PROVIDED THE CUT EDGES ARE SMOOTH AND TRUE.

AT THE BACKFACE OF ABUTMENTS ALL EXCAVATED VOLUME NOT
OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH
STRUCTURE BACKFILL.

THE EXISTING GROUND LINE SHALL BE USED AS THE UPPER LIMITS OF EXCAVATION.

THE HAUNCH CONCRETE QUANTITY IS BASED ON THE AVERAGE HAUNCH SHOWN ON THE PRESTRESSED GIRDER DETAILS SHEET, WHICH IS THE MAXIMUM HAUNCH QUANTITY FOR WHICH THE CONTRACTOR WILL BE PAID.

☆ PROTECTIVE SURFACE TREATMENT SHALL BE APPLIED TO THE ENTIRE TOP, SIDES, EXTERIOR 1'-0" OF THE UNDERSIDE OF THE DECK, TOP AND EXTERIOR EXPOSED FACE OF WINGS, AND THE END 1'-0" OF THE FRONT FACE OF ABUTMENT.




CROSS SECTION THRU ROADWAY

BENCH MARKS (NAVD 88)

NO.	STATION	DESCRIPTION	ELEV.
BM1	7+28, 36' RT.	60D SPIKE IN 10" ASPEN TREE	788.69
BM2	12+38, 46' RT.	60D SPIKE IN PP#2022-23W7	804.77
BM3	15+20, 37' LT.	60D SPIKE IN PP#2022-14L10	813.95


TOTAL ESTIMATED QUANTITIES

ITEM NO.	BID ITEMS	UNIT	SUPER.	WEST ABUT.	EAST ABUT.	TOTALS
203.0600.S	REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS STA 10+00	LS	----	----	----	1
206.1000	EXCAVATION FOR STRUCTURES BRIDGES B-36-220	LS	----	----	----	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	----	310	310	620
502.0100	CONCRETE MASONRY BRIDGES	CY	138	35	35	208
502.3200	PROTECTIVE SURFACE TREATMENT	SY	450	----	----	450
503.0155	PRESTRESSED GIRDER TYPE 154W-INCH	LF	420	----	----	420
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	----	1,580	1,580	3,160
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	21,100	1,150	1,150	23,400
506.2605	BEARING PADS ELASTOMERIC NON-LAMINATED	EACH	8	----	----	8
506.4000	STEEL DIAPHRAGMS B-36-220	EACH	6	----	----	6
513.4061	RAILING TUBULAR TYPE M B-36-220	LF	218	----	----	218
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	----	11	11	22
550.0020	PRE-BORING ROCK OR CONSOLIDATED MATERIALS	LF	----	91	----	91
550.1100	PILING STEEL HP 10-INCH X 42 LB	LF	----	105	105	210
606.0200	RIPRAP MEDIUM	CY	----	20	20	40
606.0300	RIPRAP HEAVY	CY	----	130	150	280
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	----	53	53	106
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	----	45	45	90
645.0120	GEOTEXTILE TYPE HR	SY	----	225	250	475
	NON-BID ITEMS					
	FILLER	SIZE	—	—	—	1/2" & 3/4"




PROFILE GRADE LINE

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		BRE	PLANS CK'D. KRO
CROSS SECTION & QUANTITIES		SHEET 2 OF 12	



BORINGS TAKEN BY:
GEOTECHNICAL DRILLING CONTRACTOR, LLC.
WAUSAU, WI
MARCH 28, 2016

GEOTECHNICAL REPORT BY:
OMNI ASSOCIATES, LLC.
APPLETON, WI
MAY, 2016




STATE PROJECT NUMBER

4316-09-71

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



- (1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)
- (2) UNLESS OTHERWISE SPECIFIED THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

- ▽ AT TIME OF DRILLING
- ▽ END OF DRILLING
- ▽ AFTER DRILLING


ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		KRW	PLANS CK'D. KRO
SUBSURFACE EXPLORATION		SHEET 3 OF 12	




ELEVATION
(LOOKING WEST)



- (A05) CONSTRUCTION JOINT-FORMED BY BEVELED 2 x 6 BETWEEN BEAM SEATS.
- (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN (SEE SHEET 5 FOR DETAILS).
- (A17) 1/2" FILLER INCLUDED IN WING LENGTH, SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE.)
- (A19) 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- (A22) A505 BARS SPACED @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
- (X) DENOTES WING NUMBER

WEST ABUTMENT TO BE SUPPORTED ON HP 10 X 42 STEEL PILING. ESTIMATED 15'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 180 TONS PER PILE. PILES SHALL BE PREBORED A MINIMUM OF 3- FEET INTO BEDROCK. AFTER PILES HAVE BEEN FIRMLY SEATED, FILL THE AREA AROUND THE PILING WITH CEMENT GROUT.

SEE SHEET 5 FOR WINGWALL DETAILS, BILL OF BARS, AND BAR BENDING
DIAGRAMS.




HORIZ. BARS NOT OTHERWISE
IDENTIFIED ARE A604 BARS

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
		DRAWN BY	MRW PLANS CK'D. BRE
WEST ABUTMENT		SHEET 4 OF 12	


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	SERIES	LOCATION
A401		7	28'-0"	X		BODY - ONE PER PILE
A402		14	2'-3"			BODY - TWO PER PILE
A503		38	15'-6"	X		BODY - STIRRUPS
A604		17	30'-2"			BODY - HORIZONTAL
A505	X	15	2'-0"			BODY - VERTICAL, DOWEL
A406	X	8	12'-10"	X		WINGS - STIRRUPS
A407	X	44	11'-1"	X	△	WINGS - STIRRUPS
A508	X	10	13'-7"			WINGS - HORIZONTAL, F.F.
A709	X	14	14'-7"			WINGS - HORIZONTAL
A410	X	8	11'-8"			WINGS - HORIZONTAL
A411	X	16	7'-0"		△	WINGS - HORIZONTAL
A412	X	4	12'-2"	X		WINGS - HORIZONTAL, TOP
A613		8	3'-8"	X		BODY - END

BAR SERIES

BAR NO.	NO. REQ'D.	LENGTH
A407	4 SERIES OF 11	9'-5" TO 12'-9"
A411	4 SERIES OF 4	2'-8" TO 11'-4"




BAR BENDING DIAGRAMS




* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SCREEN, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".


THE RODENT SCREEN SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SCREEN TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SCREEN SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH SHEET METAL SCREWS.




WING 1




WING 2



SECTION A-A




SECTION B-B




(A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6.
(18" R.M.W. @ B.F. & 3/4" "V" GROOVE @ F.F. IF JOINT IS USED).

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
		DRAWN BY	MRW PLANS CK'D. BRE
WEST ABUTMENT DETAILS		SHEET 5 OF 12	



ELEVATION
(LOOKING EAST)



SECTION THRU BODY

HORIZ. BARS NOT OTHERWISE
IDENTIFIED ARE B604 BARS



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
		DRAWN BY	MRW PLANS CK'D. BRE
EAST ABUTMENT		SHEET 6 OF 12	


BILL OF BARS

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	SERIES	LOCATION
B401		7	28'-0"	X		BODY - ONE PER PILE
B402		14	2'-3"			BODY - TWO PER PILE
B503		38	15'-6"	X		BODY - STIRRUPS
B604		17	30'-2"			BODY - HORIZONTAL
B505	X	15	2'-0"			BODY - VERTICAL, DOWEL
B406	X	8	12'-10"	X		WINGS - STIRRUPS
B407	X	44	11'-1"	X	△	WINGS - STIRRUPS
B508	X	10	13'-7"			WINGS - HORIZONTAL, F.F.
B709	X	14	14'-7"			WINGS - HORIZONTAL
B410	X	8	11'-8"			WINGS - HORIZONTAL
B411	X	16	7'-0"		△	WINGS - HORIZONTAL
B412	X	4	12'-2"	X		WINGS - HORIZONTAL, TOP
B613		8	3'-8"	X		BODY - END


△ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE BAR SERIES TABLE FOR ACTUAL LENGTHS.

BAR SERIES


BAR NO.	NO. REQ'D.	LENGTH
B407	4 SERIES OF 11	9'-5" TO 12'-9"
B411	4 SERIES OF 4	2'-8" TO 11'-4"




BAR BENDING DIAGRAMS




WING 3



WING 4




SECTION A-A



SECTION B-B

LEGEND

- (A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6. (18" R.M.W. @ B.F. & 3/4" "V" GROOVE @ F.F. IF JOINT IS USED).
- (A15) PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO NORTH SLOPES. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.
- ▲ BACKFILL PAY LIMITS. BACKFILL BEYOND BACKFILL PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.



TYPICAL SECTION THRU ABUTMENT

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		MRW	PLANS CK'D. BRE
EAST ABUTMENT DETAILS		SHEET 7 OF 12	

TOP OF GIRDER TO BE ROUGH FLOATED AND BROOMED TRANSVERSELY, EXCEPT THE OUTSIDE 15" OF GIRDER, WHICH SHALL RECEIVE A SMOOTH FINISH. AN APPROVED CONCRETE SEALER SHALL BE APPLIED TO ALL SMOOTH SURFACES INCLUDING THE OUTSIDE 15" OF THE TOP FLANGE.

THE GIRDERS SHALL BE PROVIDED WITH A SUITABLE LIFTING DEVICE FOR HANDLING AND ERECTING THE GIRDERS. SEE SECT. 503.3-3 OF STANDARD SPECIFICATIONS FOR GUIDANCE.

STRANDS SHALL BE FLUSH WITH END OF GIRDER. FOR GIRDER ENDS EMBEDDED COMPLETELY IN CONCRETE, END OF STRANDS SHALL BE COATED WITH NON-BITUMINOUS JOINT SEALER. FOR GIRDER ENDS THAT ARE FINALLY EXPOSED, COAT THE GIRDER ENDS, EXPOSED STRAND ENDS AND ALL NON-BONDING SURFACES WITHIN 2 FEET OF THE GIRDER ENDS WITH A NON-PIGMENTED EPOXY CONFORMING TO AASHTO M-235 TYPE III, GRADE 2, CLASS B OR C. THE EPOXY SHALL BE APPLIED AT LEAST 3 DAYS AFTER MOIST CURING HAS CEASED AND PRIOR TO THE APPLICATION OF THE SEALER.

ALL GIRDERS SHALL BE CAST FULL LENGTH AS SHOWN.

SPACING SHOWN FOR #4 STIRRUPS IS FOR GRADE 60 REINFORCEMENT.

AN ALTERNATE EQUIVALENT OF WELDED WIRE FABRIC (WWF)
ASTM A1064 MAY BE SUBSTITUTED FOR THE STIRRUP
REINFORCEMENT SHOWN, UPON APPROVAL OF THE STRUCTURES
DEVELOPMENT SECTION.

PRESTRESSING STRANDS SHALL BE (0.6" DIA.)-7 WIRE
LOW-RELAXATION STRANDS WITH AN ULTIMATE STRENGTH OF
270,000 PSI.

FOR DIAPHRAGM INSERT & CONNECTION DETAILS SEE "STEEL
DIAPHRAGM" SHEET.




*THE THEORETICAL INITIAL CAMBER VALUE AT THE TIME OF STRAND RELEASE AT MIDSPAN MULTIPLIED BY A FACTOR OF 1.4 TO ACCOUNT FOR CAMBER GROWTH FROM THE TIME OF STRAND RELEASE TO JOBSITE PLACEMENT.

SPAN	CAMBER (IN.)
1	2.19

THESE VALUES ARE NOT TO BE USED IN DETERMINING 'T'.
USE ACTUAL GIRDER SHOTS.
THESE VALUES ARE FOR INFORMATIONAL PURPOSES ONLY.



- (A) DETAIL TYP. AT EACH END
- (B) 6 #4 BARS, FULL LENGTH, MIN. LAP = 1'-11"



* MINIMUM CYLINDER STRENGTH OF CONCRETE @ TIME OF TRANSFER OF PRESTRESS FORCE.

[illegible]

BOTTOM FLANGE

NOTES


ALL DIAPHRAGM MATERIAL NOT EMBEDDED IN THE CONCRETE GIRDER SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "STEEL DIAPHRAGMS B-36-220", EACH.

EACH DIAPHRAGM BETWEEN GIRDERS SHALL CONSTITUTE ONE UNIT.


ALL DIAPHRAGM STRUCTURAL STEEL SHALL BE ASTM A709 GRADE 36.

ALL DIAPHRAGM MATERIAL INCLUDING BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED AFTER FABRICATION.


STEEL DIAPHRAGM TO CONCRETE WEB CONNECTION SHALL BE SNUG-TIGHT PLUS 1/4 TURN, UNLESS NOTED OTHERWISE. HIGH STRENGTH BOLTS FOR WEB CONNECTION SHALL MEET THE REQUIREMENTS FOR ASTM A325 OR ASTM A449.




PART TRANSVERSE SECTION AT DIAPHRAGM



SECTION A-A
(FOR EXTERIOR ATTACHMENT)




TYP. STRAND PATTERN




DIAPHRAGM SUPPORT

* 2 1/2" FOR ALTERNATE PLATE DIAPHRAGM




SECTION THRU
ALTERNATE DIAPHRAGM




DETAIL B


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		BRE	PLANS CK'D. KRO
STEEL DIAPHRAGM		SHEET 9 OF 12	



SLAB PLAN




SECTION S-S



CROSS SECTION THRU ROADWAY
(LOOKING EAST)


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		BRE	PLANS CK'D. KRO
SUPERSTRUCTURE		SHEET 10 OF 12	



FRAMING PLAN

BILL OF BARS


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	LOCATION
S501	X	301	30'-2"		TRANS. TOP & BOT.
S402	X	174	40'-0"		LONG. TOP & BOTTOM
S403	X	87	29'-6"		LONG. TOP & BOTTOM
S604	X	72	12'-0"	X	AT RAIL POST
S605	X	128	6'-0"		AT INTERIOR RAIL POST
S606	X	16	4'-10"	X	AT END RAIL POST
S607	X	14	30'-2"		DIAPH. HORIZONTAL, B.F. & TOP
S608	X	60	4'-10"		DIAPH. HORIZONTAL, F.F.
S509	X	50	15'-0"	X	DIAPH. STIRRUPS VERTICAL
S510	X	32	11'-10"	X	DIAPH. STIRRUPS VERTICAL
S511	X	50	5'-7"	X	DIAPH. TOP
S612	X	16	6'-6"	X	DIAPH. HORIZONTAL, ENDS
S613	X	4	1'-2"		DIAPH. HORIZONTAL, ENDS




BAR BEND DIAGRAMS

TOP OF DECK ELEVATIONS


LOCATION	W.ABUT.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	E. ABUT.
N. EDGE	792.56	792.64	792.74	792.86	793.00	793.14	793.31	793.49	793.69	793.90	794.13
GIRDER 1	792.61	792.70	792.80	792.92	793.05	793.20	793.37	793.55	793.74	793.96	794.19
GIRDER 2	792.78	792.86	792.97	793.08	793.22	793.37	793.53	793.71	793.91	794.12	794.35
GIRDER 3	792.78	792.86	792.97	793.08	793.22	793.37	793.53	793.71	793.91	794.12	794.35
GIRDER 4	792.61	792.70	792.80	792.92	793.05	793.20	793.37	793.55	793.74	793.96	794.19
S. EDGE	792.56	792.64	792.74	792.86	793.00	793.14	793.31	793.49	793.69	793.90	794.13



PART LONGIT. SECTION



DEAD LOAD DEFLECTION DIAGRAM




DECK HAUNCH DETAIL

IF 1/4" MINIMUM HAUNCH HEIGHT AT EDGE OF GIRDER CANNOT BE MAINTAINED, THE GRADE LINE MAY BE REVISED BY THE ENGINEER AT THE OPTION OF THE CONTRACTOR, THE PLAN DECK THICKNESS SHALL BE HELD. NOTIFY THE STRUCTURES SECTION IF THE GRADE LINE IS RAISED FROM THE PLAN PROFILE BY MORE THAN 1/2" OR, ** IF 3" MINIMUM DECK EMBEDMENT OF TIE BAR CANNOT BE OBTAINED.

TO DETERMINE 'T', ELEV. OF TOP OF GIR'S. AT C/L OF SUBSTRUCTURE UNITS & AT 1/10 POINTS OF EACH SPAN SHALL BE TAKEN. THEN FOLLOW THIS PROCESS:

- TOP OF DECK ELEV. AT FINAL GRADE
- TOP OF GIRDER ELEVATION
- + DEAD LOAD DEFLECTION
- DECK THICKNESS
- = HAUNCH HEIGHT 'T'

NOTE: AN AVERAGE HAUNCH ('T') OF 3 3/8" WAS USED IN THE QUANTITY "CONCRETE MASONRY BRIDGES".



BEARING PAD DETAIL


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		BRE	PLANS CK'D. KRO
SUPERSTRUCTURE DETAILS		SHEET 11 OF 12	

LEGEND


- ① W6 x 25 WITH 1/8" x 1/2" HORIZONTAL SLOTS ON EACH SIDE OF POST FOR BOLT NO. 6. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1/4" x 11 3/4" x 1'-8" WITH 1 3/8" x 1 5/8" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN. SLOTS PARALLEL TO SHORT SIDE OF PLATE
- ③ ASTM A449 - 1/8" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED), 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1'-9" LONG IN ABUTMENT WINGS. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1'-3" LONG. USE 10 3/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTIBILITY.)
- ④ 5/8" x 11" x 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 3/8" DIA. HOLES FOR ANCHOR BOLTS NO. 3
- ⑤ TS 5 x 4 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑤A TS 5 x 5 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH NUT, 3/8" x 1 5/8" x 1 5/8" WASHER, AND LOCK WASHER (2 REQ'D. AT EACH RAIL TO POST LOCATION).
- ⑦ 1/2" THK. BACK-UP PLATE WITH 2 - 7/8" x 1/2" THREADED SHOP WELDED STUDS (ITEM 12). BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑧ 1" DIA. HOLES IN PLATE NO. 7 & TUBES NO. 5A FOR 7/8" DIA. A325 BOLTS WITH HEX NUTS AND WASHERS. 6 HOLES IN TUBES AND PLATE NO. 7.
- ⑨ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- ⑩ 3/8" x 3 5/8" x 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- ⑩A 3/8" x 2 5/8" x 2'-4" PLATE USED IN NO. 5, 3/8" x 3 5/8" x 2'-4" PLATE USED IN NO. 5A. 2 PER RAIL.
- ⑪ 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. USE 1 5/8" x 1/4" LONG. SLOTTED HOLES AT FIELD JOINTS AND 1 5/8" x 2 1/4" MIN. LONG. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 10A.
- ⑫ 7/8" DIA. x 1 1/2" LONG THREADED SHOP WELDED STUDS (2 REQ'D.).
- ⑬ 3/8" x 8" x 1'-6" PLATE. BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑭ 7/8" DIA. x 2" LONG A325 HEX BOLT WITH NUT AND WASHER. (5 REQ'D.)
- ⑮ 1" DIA. HOLES IN TUBES NO. 5A FOR 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. 4 HOLES IN TUBES.

GENERAL NOTES


1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M (B-36-220)" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8 TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE. RAILS SHALL BE SPLICED IN A PANEL OVER EXPANSION JOINTS.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY S.S.P.C. SPECIFICATIONS.
10. THIS RAILING MEETS NCHRP REPORT 350 EVALUATION CRITERIA FOR TEST LEVEL 4 (TL-4).



SECTION THRU RAILING ON DECK




FIELD ERECTION JOINT DETAIL




ANCHOR BOLTS




SHOP RAIL SPLICE DETAIL
(LOCATION MUST BE SHOWN ON SHOP DRAWINGS)




SECTION A-A




DETAIL AT END POST
(THRIE BEAM RAIL ATTACHMENT)




ANCHOR PLATE
AT BEAM GUARD ATTACHMENT



ANCHOR PLATE
AT RAIL TO DECK CONNECTION



BACK-UP PLATE DETAIL
AT BEAM GUARD ATTACHMENT





PART ELEVATION OF RAILING


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-220			
DRAWN BY		BRE	PLANS CK'D. KRO
TUBULAR STEEL RAILING TYPE 'M'		SHEET 12 OF 12	


EARTHWORK


STATION	AREA (SF)				Incremental Vol (CY) (Unadjusted)				Cumulative Vol (CY)		Mass Ordinate
	Cut	Salvaged/Unusable Pavement Material	Fill	EBS	Cut	Salvaged/Unusable Pavement Material	Fill	EBS	Cut 1.00	Expanded Fill 1.25	
07+25	0.00	0.00	0.00	0.00	0	0	0	0	0	0	0
07+40	5.50	0.00	0.50	0.00	2	0	0	0	2	0	1
07+50	9.16	0.00	46.80	6.00	3	0	9	1	4	11	-7
07+75	8.14	0.00	109.26	17.10	8	0	72	11	12	101	-89
08+00	30.57	4.58	137.43	23.20	18	0	114	19	30	244	-214
08+19.43	30.35	4.58	143.79	20.90	22	3	101	16	52	371	-322
08+44.43	29.57	4.58	148.29	18.50	28	4	135	18	80	540	-467
08+50	29.03	4.58	131.37	16.20	6	1	29	4	86	576	-498
08+69.43	26.88	4.58	128.13	16.90	20	3	93	12	106	693	-598
08+94.43	21.33	4.58	177.40	22.40	22	4	141	18	128	869	-757
09+00	19.62	4.58	198.18	24.20	4	1	39	5	133	918	-802
09+31.75	20.49	4.58	191.40	21.20	24	5	229	27	156	1,204	-1070
09+46.75	15.12	4.58	241.42	25.90	10	3	120	13	166	1,354	-1213
STRUCTURE											
10+53.25	0.00	4.58	278.27	28.20	0	0	0	0	166	1,354	-1213
10+68.25	13.49	4.58	177.09	18.30	4	3	126	13	170	1,512	-1370
11+00	7.13	4.58	126.88	11.60	12	5	179	18	182	1,736	-1587
11+05.57	6.99	4.58	123.78	25.50	1	1	26	4	183	1,768	-1619
11+25	34.75	4.58	112.86	11.90	15	3	85	13	198	1,875	-1713
11+30.57	35.52	17.08	137.59	17.20	7	2	26	3	206	1,907	-1741
11+50	21.95	4.58	46.54	17.40	21	8	66	12	226	1,990	-1810
11+55.57	25.74	4.58	32.40	0.00	5	1	8	2	231	2,000	-1817
11+80	32.00	4.58	13.18	0.00	26	4	21	0	257	2,026	-1820
12+00	4.39	0.00	8.36	0.00	13	0	8	0	271	2,036	-1817
12+50	5.41	0.00	0.11	0.00	9	0	8	0	280	2,045	-1818
12+75	0.00	0.00	0.00	0.00	3	0	0	0	282	2,045	-1815

















Notes



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>