


WKE
PROJECT ID: 1000-68-93
COUNTY: SE REGION WIDE

MAY 2018

ORDER OF SHEETS

Section No. 1	Title
Section No. 2	Typical Sections and Details
Section No. 3	Estimate of Quantities
Section No. 3	Miscellaneous Quantities
Section No. 4	Right of Way Plat
Section No. 5	Plan and Profile
Section No. 6	Standard Detail Drawings
Section No. 7	Sign Plates
Section No. 8	Structure Plans
Section No. 9	Computer Earthwork Data
Section No. 9	Cross Sections

TOTAL SHEETS = 36




DESIGN DESIGNATION

A.A.D.T.	=	N/A
A.A.D.T.	=	N/A
D.H.V.	=	N/A
D.D.	=	N/A
T.	=	N/A
DESIGN SPEED	=	N/A
ESALS	=	N/A

CONVENTIONAL SYMBOLS	
PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	OVERHEAD UTILITY
PROPOSED CULVERT (Box or Pipe)	FIBER OPTIC
COMBUSTIBLE FLUIDS	GAS
MARSH AREA	SANITARY SEWER
WOODED OR SHRUB AREA	STORM SEWER
	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
PLAN OF PROPOSED IMPROVEMENT
HIGHWAY LIGHTING MAINTENANCE 2018
VARIOUS HIGHWAYS
SE REGION - WIDE

STATE PROJECT NUMBER
1000-68-93



TOTAL NET LENGTH OF CENTERLINE = 0.000 MI.

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COUNTY COORDINATES, COUNTY COUNTY, NAD83 (YEAR), IN U.S. SURVEY FEET. VALUES ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
1000-68-93		

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY

Surveyor _____

Designer ERIC PEREA

Project Manager ERIC PEREA

Regional Examiner _____

Regional Supervisor MITZI DOBERSEK

APPROVED FOR THE DEPARTMENT

DATE: 12/4/17 [Signature]
(Signature)

E

UTILITY CONTACTS

TO OBTAIN LOCATION OF
PARTICIPANTS' UNDERGROUND
FACILITIES BEFORE YOU
DIG IN WISCONSIN

WIS. STATUTE 182.0175 (1974)
REQUIRES MIN. OF 3 WORK DAYS
NOTICE BEFORE YOU EXCAVATE



MILWAUKEE COUNTY - HIGHWAY MAINTENANCE

MR. GREG HEISEL
HIGHWAY MAINTENANCE MANAGER
10190 WATERTOWN PLK ROAD
WAUWATOSA, WI 53266
414-257-6566
GREG.HEISEL@MILWCNTY.COM

MILWAUKEE COUNTY - HIGHWAY MAINTENANCE

MILWAUKEE COUNTY - HIGHWAY MAINTENANCE
MR. STANLEY L. JACKSON
ELECTRICAL MECHANIC SUPERVISOR
10190 WATERTOWN PLK ROAD
WAUWATOSA, WI 53226
414-257-6593
STANLEY.JACKSON@MILWCNTY.COM

WISCONSIN DEPT. OF TRANSPORTATION

MS. RHONDA MOGILKA
SE REGION ELECTRICAL FIELD UNIT (EFU)
935 S 60TH STREET
WEST ALLIS, WI 53214
414-266-1167
RHONDA.MOGILKA@DOT.WI.GOV

STATE AGENCIES

WISCONSIN DEPARTMENT OF NATURAL RESOURCES

MR. CRAIG WEBSTER - DNR SOUTHEAST REGION
141 NW BARSTOW ST.
WAUKESHA, WI 53187
(262) 574-2141
CRAIG.WEBSTER@DOT.WI.GOV

WISCONSIN DEPARTMENT OF TRANPORTATION

MR. ERIC PEREA - PROJECT MANAGER
935 S. 60TH ST.
WEST ALLIS, WI 53214
(414) 750-0935
ERIC.PEREA@DOT.WI.GOV

WISCONSIN DEPARTMENT OF TRANSPORTATION

MR. STEVEN KUHLMAN PROJECT MANAGER
141 NW BARSTOW ST
WAUKESHA, WI 53187-0798
(414) 745.7569
STEVEN.KUHLMAN@DOT.WI.GOV



















WISCONSIN DEPARTMENT OF TRANSPORTATION

MS. RABI BISTA - SE REGION UTILITY COORDINATOR
141 NW BARSTOW ST
WAUKESHA, WI 53187-0798
(262) 548-5690
RABI.BISTA@DOT.WI.GOV

GENERAL NOTES

- 1. THE LOCATIONS ON EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN. SEE UTILITY OCCUPATION PLANS FOR ADDITIONAL INFORMATION.
- 2. THE CONTRACTOR SHALL NOTIFY DIGGERS HOTLINE AND AFFECTED UTILITIES PRIOR TO THE START OF WORK. ANY LOCAL MUNICIPAL UTILITY WHICH IS NOT A MEMBER OF THE DIGGERS HOTLINE MUST BE CONTACTED SEPARATELY.
- 3. TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.
- 4. TEMPORARY STORAGE OF ANY EXCAVATED MATERIAL WILL NOT BE PERMITTED IN WETLANDS

TRAFFIC CONTROL PLAN LEGEND

	TYPE III BARRICADE
	TYPE III BARRICADE WITH ATTACHED SIGN
	TRAFFIC CONTROL DRUM
	TRAFFIC CONTROL DRUM WITH TYPE C STEADY BURN LIGHT
	FLASHING ARROW BOARD
	SIGN ON PERMANENT SUPPORT
	SIGN ON TEMPORARY SUPPORT
	DELINEATOR FLEXIBLE/TUBULAR MARKER
	TYPE A WARNING LIGHT (FLASHING)
	TYPE B WARNING LIGHT (HIGH INTENSITY FLASHING)
	TYPE C WARNING LIGHT (STEADY BURN)
	CONCRETE BARRIER TEMPORARY PRECAST
	WORK AREA
	TEMPORARY RAISED PAVEMENT MARKER (ONE WAY REFLECTOR)
	TEMPORARY RAISED PAVEMENT MARKER (TWO WAY REFLECTOR)
	FLAGGER, EQUIPPED WITH STOP/SLOW PADDLE FASTENED ON SUPPORT STAFF
	DIRECTION OF TRAFFIC
	PORTABLE CHAGEABLE MESSAGE BOARD

HIGHWAY LIGHTING DISTRIBUTION CENTERS

Milwaukee County

40



LEGEND

XX

FREEWAY LIGHTING

XX

SPLITTER CABINETS

*

PROPOSED LIGHTING

XX

TUNNEL LIGHTING

○

LED LIGHTING

OZAUKEE CO. (45)
MILWAUKEE CO. (40)

FOND DU LAC
STH 145
FREEWAY

WAUKESHA (67)
MILWAUKEE (40)

ZOO FREEWAY
USH 45

STADIUM FREEWAY
USH 41

PARK
FREEWAY
STH 145

I-794

I-94


E-W

I-894 ZOO
USH 45

I-43, I-894
AIRPORT FREEWAY

AIRPORT
SPUR
STH 119

MILWAUKEE (40)
RACINE (51)



HIGHWAY LIGHTING DISTRIBUTION CENTERS



LEGEND





FREEMWAY LIGHTING

SPLITTER CABINETS

PROPOSED LIGHTING

TUNNEL LIGHTING

LED LIGHTING



GENERAL NOTES:

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE SPECIAL PROVISIONS.

LETTERS AND NUMBERS 2"
SERIES "D" SELF ADHESIVE
VINYL CUTOUTS

PLAQUE FACE BACKGROUND
SELF ADHESIVE SHEETING
WHITE (NON-RETROREFLECTIVE)

BASE MATERIAL TO BE
SHEET ALUMINUM, 0.060"
MIN. THICKNESS


SPACING BETWEEN LETTERS
AND NUMBERS TO BE 1/2"
(IF QUANTITY OF NUMERALS
OR LETTERS IS LESS THAN
SHOWN, LEAVE SPACE AT
RIGHT SIDE OF PLAQUE)

DISTRIBUTION CENTER
IDENTIFICATION PLAQUE

CHAMBERS


MNEMONIC
(SEE MISC. QTYS.)
(NO. OF CHARACTERS VARIES
THIRD PLAQUE MAY BE
NECESSARY)

FASTEN LEFT, CENTER AND RIGHT
OF PLAQUE WITH 3 STAINLESS
STEEL POP RIVETS



DISTRIBUTION CENTER IDENTIFICATION PLAQUE
REQUIREMENTS AND PLACEMENTS
(TYPICAL ALL CONTROL CABINETS)


TWO REQUIRED CABINET AND METER PEDESTALS
(PAID AS PLAQUES SEQUENCE IDENTIFICATIONS)



APROX. 10 1/2" x
7"


*SOME LOCATIONS WILL BE 240 VOLTS

TRAFFIC CONTROL FOR FREEWAY LIGHTING MAINTENANCE
SHORT TERM (1 TO 12 HOURS) AND INTERMEDIATE TERM (OVERNIGHT TO 7 DAYS OR LESS)
SHOULDER OR LANE CLOSURE



TYPICAL SHOULDER CLOSURE

(RIGHT SHOULDER CLOSURE SHOWN,
LEFT SHOULDER CLOSURE SIMILAR)



TYPICAL ONE-LANE CLOSURE


(RIGHT LANE CLOSURE SHOWN,
LEFT LANE CLOSURE SIMILAR)

GENERAL NOTES: TRAFFIC CONTROL

1. THE CONTRACTOR SHALL FURNISH, ERECT, MAINTAIN, MOVE AND REMOVE ALL TRAFFIC CONTROL SIGNS, SIGN SUPPORTS, CHANNELIZING DEVICES, ARROW BOARDS, WARNING LIGHTS, ETC. AS SPECIFIED IN THIS DETAIL, THE STANDARD SPECIFICATIONS, THE PLANS AND/OR THE SPECIAL PROVISIONS AND/OR AS DIRECTED BY THE ENGINEER.
2. THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS AND CHANNELIZING DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AND/OR AS DIRECTED BY THE ENGINEER.
3. IF THE HORIZONTAL ALIGNMENT IS SUCH THAT A CURVE MAY REQUIRE ADDITIONAL DELINEATION, THE CHANNELIZING DEVICE SPACING MAY BE DECREASED TO 50' IN THE WORK SPACE.
4. FOR DAYTIME ONLY OPERATION: WARNING LIGHTS ARE NOT REQUIRED. ALL LANE CLOSURE SIGNS SHALL BE COVERED OR TURNED FROM THE MOTORIST'S VIEW AND CHANNELIZING DEVICES SHALL BE REMOVED BEYOND THE SHOULDER AT THE END OF THE WORKDAY IF THE LANE IS RESTORED TO A SAFE OPERATING CONDITION.
5. FOR NIGHT TIME OPERATION: CHANNELIZING DEVICES IN THE TRANSITION SPACE SHALL HAVE TYPE "C" (STEADY BURN) WARNING LIGHTS, BARRICADES SHIELDING AN ISOLATED HAZARD, SHALL HAVE TYPE "A" (LOW INTENSITY FLASHING) WARNING LIGHTS.
6. ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.
7. "WO" SIGN DESIGNATIONS ARE THE SAME AS "W" SIGN DESIGNATIONS EXCEPT THAT BACKGROUND IS ORANGE.
8. IF LANE CLOSURE IS MORE THAN 1 MILE, PLACE TYPE III BARRICADES APPROXIMATELY EVERY 1000' ACROSS THE CLOSED LANE TO HELP ENFORCE THE DELINEATION.
9. CONSIDER GEOMETRICS WHEN LOCATING SIGNS AND ARROW BOARD SO THE DRIVER HAS A CLEAR VIEW OF THE ARROW BOARD AND LANE CLOSURE DRUMS FOR A MINIMUM 1500' IN FRONT OF DRUMS.

LEGEND:

- SIGN ON TEMPORARY SUPPORT
- CHANNELIZING DEVICE (CONE OR DRUM)
- ARROW BOARD







**MOBILE OPERATION ON SHOULDER
FOR 10' OR WIDER SHOULDERS ONLY**
(RIGHT SHOULDER CLOSURE SHOWN,
LEFT SHOULDER CLOSURE SIMILAR)

TRAFFIC CONTROL FOR FREEWAY LIGHTING MAINTENANCE
MOBILE OPERATIONS - SHOULDER CLOSURE
CONTINUOUS OR INTERMITTENT MOVEMENT (STOPS LESS THAN 15 MINUTES)

GENERAL NOTES: TRAFFIC CONTROL

1. THE CONTRACTOR SHALL FURNISH, ERECT, MAINTAIN, MOVE AND REMOVE ALL TRAFFIC CONTROL SIGNS, SIGN SUPPORTS, CHANNELIZING DEVICES, TMAs, ARROW BOARDS, WARNING LIGHTS, ETC. AS SPECIFIED IN THIS DETAIL, THE STANDARD SPECIFICATIONS, THE PLANS AND/OR THE SPECIAL PROVISIONS AND/OR AS DIRECTED BY THE ENGINEER.
2. THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS AND CHANNELIZING DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AND/OR AS DIRECTED BY THE ENGINEER.
3. IF THE HORIZONTAL ALIGNMENT IS SUCH THAT A CURVE REDUCES VISIBILITY, PROTECTION VEHICLE OPERATORS SHOULD INCREASE THE LENGTH OF THE BUFFER SPACE TO MAINTAIN VISIBILITY TO VEHICLES APPROACHING FROM THE REAR.
4. MOBILE OPERATIONS ARE PERMITTED FOR DAYTIME OPERATIONS ONLY.
5. THE ENGINEER IN THE FIELD MAY PROHIBIT MOBILE OPERATIONS DURING RAIN OR WHEN FOGGY.
6. ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.
7. "WO" SIGN DESIGNATIONS ARE THE SAME AS "W" SIGN DESIGNATIONS EXCEPT THAT BACKGROUND IS ORANGE.

LEGEND:

-  SIGN ON TEMPORARY SUPPORT
-  ARROW BOARD
-  TMA (TRUCK MOUNTED ATTENUATOR)
-  WORK VEHICLE

Estimate Of Quantities

1000-68-93

Line	Item	Item Description	Unit	Total	Qty
0002	204.9060.S	Removing (item description) 01. Luminaires	EACH	686.000	686.000
0004	619.1000	Mobilization	EACH	1.000	1.000
0006	643.0300	Traffic Control Drums	DAY	200.000	200.000
0008	643.0420	Traffic Control Barricades Type III	DAY	25.000	25.000
0010	643.0705	Traffic Control Warning Lights Type A	DAY	20.000	20.000
0012	643.0715	Traffic Control Warning Lights Type C	DAY	20.000	20.000
0014	643.0800	Traffic Control Arrow Boards	DAY	65.000	65.000
0016	643.0900	Traffic Control Signs	DAY	150.000	150.000
0018	643.1050	Traffic Control Signs PCMS	DAY	10.000	10.000
0020	643.1055.S	Truck or Trailer Mounted Attenuator	DAY	55.000	55.000
0022	643.5000	Traffic Control	EACH	1.000	1.000
0024	655.0610	Electrical Wire Lighting 12 AWG	LF	200.000	200.000
0026	SPV.0060	Special 01. Plaques Sequence Identification	EACH	5.000	5.000
0028	SPV.0060	Special 02 Light Tower Rat Screens	EACH	10.000	10.000
0030	SPV.0060	Special 03. Fuse Holders	EACH	50.000	50.000
0032	SPV.0060	Special 04. Fuses Type FNQ	EACH	100.000	100.000
0034	SPV.0060	Special 05. Plumbing Light Poles	EACH	5.000	5.000
0036	SPV.0060	Special 06. Trasport and Install State Furnished Luminaires LED	EACH	616.000	616.000
0038	SPV.0060	Special 07. Transport and Install State Furnished Highmast Luminaires LED	EACH	34.000	34.000
0040	SPV.0060	Special 08. Luminaires Probeam LED	EACH	36.000	36.000
0042	SPV.0060	Special 09. Distribution Center Preventative Maintenance	EACH	34.000	34.000
0044	SPV.0060	Special 10. Group Luminaire Maintenance Sign Light 250W MV	EACH	3.000	3.000
0046	SPV.0060	Special 11. Tunnel Luminaire Maintenance 150 Watt HPS	EACH	13.000	13.000
0048	SPV.0060	Special 12. Tunnel Luminaire Maintenance 200 Watt HPS	EACH	22.000	22.000
0050	SPV.0060	Special 13. Tunnel Luminaire Maintenance 250 Watt HPS	EACH	3.000	3.000
0052	SPV.0060	Special 14. Tunnel Luminaire Maintenance 400 Watt HPS	EACH	532.000	532.000
0054	SPV.0060	Special 15. Group Clean Tunnel Luminaires	EACH	570.000	570.000

WISCONSIN DEPARTMENT OF TRANSPORTATION - SOUTHEAST REGION - WAUKESHA
HIGHWAY LIGHTING DISTRIBUTION CENTERS

LABEL HL- OR AS SHOWN	FORMAT	MAINTENANCE \ FIRST RESPONSE	COUNTY	HIGHWAY	DISTRIBUTION CENTER LOCATION	BRANCH CIRCUIT VOLTAGE	FIELD WIRING METHOD
30-HH	SERVICE	STATE/ STATE	KENOSHA	STH 50	SE QUADRANT STH 50 & 104TH AVE	120/240	ISOLATED NEUTRAL
30-KC	SERVICE	STATE/ STATE	KENOSHA	I-94	NW QUADRANT I-94 & CTH C	240/480	ISOLATED NEUTRAL
30-KD	SERVICE	STATE/ STATE	KENOSHA	I-94	NE QUADRANT I-94 & CTH C	240/480	ISOLATED NEUTRAL
30-KK	SERVICE	STATE/ STATE	KENOSHA	I-94	SE QUADRANT I-94 & STH 158	240/480	ISOLATED NEUTRAL
30-LV	SERVICE	STATE/ STATE	KENOSHA	STH 165	NORTH SIDE WISCONSIN INFORMATION CENTER	240/480	ISOLATED NEUTRAL
30-NF	SERVICE WITH RAMP GATE	STATE/ STATE	KENOSHA	I-94	NW QUADRANT SB OFF RAMP	240/480	ISOLATED NEUTRAL
30-PS	SERVICE	STATE/ STATE	KENOSHA	I-94	KENOSHA SAFETY AND WEIGHT FACILITY	240/480	ISOLATED NEUTRAL
30-WS	SERVICE	STATE/ STATE	KENOSHA	STH 31	NW QUADRANT STH 31 & CTH S	120/240	ISOLATED NEUTRAL
40-HO	SERVICE WITH ITS DERIVED	MILW CO/ MILW CO	MILWAUKEE	STH 38	WEST SIDE STH 38 AT NORTH TUNNEL PORTAL	480Y/277	ISOLATED NEUTRAL
40-KI	SERVICE	MILW CO/ MILW CO	MILWAUKEE	I-43	CIVIC CENTER GARAGE	480 V	PHASE-PHASE
40-QA	SERVICE WITH ITS DERIVED	MILW CO/ MILW CO	MILWAUKEE	MARQUETTE	NORTHEAST QUADRANT I-43 AND WELLS	480Y/277	ISOLATED NEUTRAL
40-TX	SERVICE WITH DERIVED HUT	MILW CO/ MILW CO	MILWAUKEE	MITCHELL	20TH WEST SIDE NORTH OF FREEWAY	480Y/277	ISOLATED NEUTRAL
40-TY	SERVICE WITH DERIVED HUT	MILW CO/ MILW CO	MILWAUKEE	MITCHELL	15TH PLACE AT VAN NORMAN	480Y/277	ISOLATED NEUTRAL
40-TZ	SERVICE WITH DERIVED HUT	MILW CO/ MILW CO	MILWAUKEE	MITCHELL	16TH STREET AND CUDAHY AVENUE	480Y/277	ISOLATED NEUTRAL
51-YK	SERVICE	STATE/ STATE	RACINE	STH 20	NW QUADRANT STH 20 AND US 45	240/480	ISOLATED NEUTRAL
67-BG	SERVICE WITH ITS	STATE/ STATE	WAUKESHA	STH 164	BIG BEND PARK & RIDE	120/240	ISOLATED NEUTRAL
67-CE	SERVICE	STATE/ STATE	WAUKESHA	STH 16	SB JJ OFF RAMP	240/480	ISOLATED NEUTRAL
67-DE	SERVICE	STATE/ STATE	WAUKESHA	STH 83	SW QUADRANT STH 83 & STH 59	240/480	ISOLATED NEUTRAL
67-FM	SUBPANEL TO HL-67-QW	STATE/ STATE	WAUKESHA	I-94	NE QUADRANT CTH P	240/480	ISOLATED NEUTRAL
67-GF	SERVICE	STATE/ STATE	WAUKESHA	STH 83	NW QUADRANT STH 83 & GOLF RD	480Y/277	ISOLATED NEUTRAL
67-GC	SERVICE	MILW CO/ STATE	WAUKESHA	US 18	NORTH SIDE CTH JJ WEST OF US 18	240/480	ISOLATED NEUTRAL
67-GK	SERVICE	MILW CO/ STATE	WAUKESHA	US 18	BARKER RD	480Y/277	ISOLATED NEUTRAL
67-GS	SERVICE	MILW CO/ STATE	WAUKESHA	I-94	RAMP, EB US 18 TO EB I-94	240/480	ISOLATED NEUTRAL
67-GW	SERVICE	MILW CO/ STATE	WAUKESHA	I-94	800 LARY COURT @ I-94	240/480	ISOLATED NEUTRAL
67-HE	SERVICE	STATE/ STATE	WAUKESHA	STH 83	NE QUADRANT STH 83 & HERITAGE DRIVE	240/480	ISOLATED NEUTRAL
67-MD	SERVICE	STATE/ STATE	WAUKESHA	I-94	I-94 AT CTH G MEADOWBROOK PARK & RIDE	240/480	ISOLATED NEUTRAL
67-MK	SERVICE	STATE/ STATE	WAUKESHA	STH 83	STH 83 & I-43 NE QUADRANT	240/480	ISOLATED NEUTRAL
67-MU	SERVICE	STATE/ STATE	WAUKESHA	STH 83	NW QUADRANT STH 83 & CTH I	240/480	ISOLATED NEUTRAL
67-PC	SERVICE	STATE/ STATE	WAUKESHA	STH 164	N36W23996 CAPITOL DRIVE	120/240	ISOLATED NEUTRAL
67-PE	SERVICE	STATE/ STATE	WAUKESHA	STH 164	SW QUADRANT 164 & WATERTOWN RD	120/240	ISOLATED NEUTRAL
67-PJ	SERVICE	STATE/ STATE	WAUKESHA	I-94	NW QUADRANT I-94 & CTH J	240/480	ISOLATED NEUTRAL
67-PK	SERVICE WITH ITS	STATE/ STATE	WAUKESHA	I-94	STH 164 AT I-94	240/480	ISOLATED NEUTRAL
67-PT	SERVICE	STATE/ STATE	WAUKESHA	I-94	SW QUADRANT I-94 AT CTH SS	240/480	ISOLATED NEUTRAL
67-RD	SERVICE	STATE/ STATE	WAUKESHA	US 18	NW QUADRANT US 18 & MORELAND RD	240/480	ISOLATED NEUTRAL
67-SY	SERVICE	STATE/ STATE	WAUKESHA	STH 83	NW QUADRANT STH 83 & CTH X	240/480	ISOLATED NEUTRAL

GROUP CABINET AND LUMINAIRE MAINTENANCE

SPV.0060.09 DISTRIBUTION CENTER PREVENTIVE MAINTENANCE
SPV.0060.10 GROUP LUMINAIRE MAINENANCE SIGN LIGHT 250W MV

* ADDITIONAL QUANTITIES FOUND ELSEWHERE

LABEL HL-	HIGHWAY AND SEGMENT	COMMENTS	SPV.0060.09 DISTRIB CENTER MAINT EACH	SPV.0060.10 SIGN LIGHT 250W MV EACH
30-HH	STH 50	SEE RETROFIT TABLE	1	--
30-KC	I-94	SEE RETROFIT TABLE	1	--
30-KD	I-94	SEE RETROFIT TABLE	1	--
30-KK	I-94	SEE RETROFIT TABLE	1	--
30-LV	STH 165	SEE RETROFIT TABLE	1	--
30-NF	I-94	SEE RETROFIT TABLE	1	--
30-PS	I-94	SEE RETROFIT TABLE	1	--
30-WS	STH 31	SEE RETROFIT TABLE	1	--
40-HO	STH 38	SEE TUNNEL TABLE	1	--
40-KI	I-43	SEE TUNNEL TABLE	1	--
40-TX	MITCHELL	SEE TUNNEL TABLE	1	--
40-TY	MITCHELL	SEE TUNNEL TABLE	1	--
40-TZ	MITCHELL	SEE TUNNEL TABLE	1	--
51-YK	STH 20	SEE RETROFIT TABLE	1	--
67-BG	STH 164	SEE RETROFIT TABLE	1	--
67-CE	STH 16	SEE RETROFIT TABLE	1	--
67-DE	STH 83	SEE RETROFIT TABLE	1	--
67-FM	I-94	SEE RETROFIT TABLE	1	--
67-GF	STH 83	SEE RETROFIT TABLE	1	--
67-GC	US 18	SEE RETROFIT TABLE	1	--
67-GK	US 18	SEE RETROFIT TABLE	1	3
67-GS	I-94	SEE RETROFIT TABLE	1	--
67-GW	I-94	SEE RETROFIT TABLE	1	--
67-HE	STH 83	SEE RETROFIT TABLE	1	--
67-MD	I-94	SEE RETROFIT TABLE	1	--
67-MK	STH 83	SEE RETROFIT TABLE	1	--
67-MU	STH 83	SEE RETROFIT TABLE	1	--
67-PC	STH 164	SEE RETROFIT TABLE	1	--
67-PE	STH 164	SEE RETROFIT TABLE	1	--
67-PJ	I-94	SEE RETROFIT TABLE	1	--
67-PK	I-94	SEE RETROFIT TABLE	1	--
67-PT	I-94	SEE RETROFIT TABLE	1	--
67-RD	US 18	SEE RETROFIT TABLE	1	--
67-SY	STH 83	SEE RETROFIT TABLE	1	--
TOTAL			34	3

TUNNEL LUMINAIRE MAINTENANCE

SPV.0060.11 TO SPV.0060 .14 TUNNEL LUMINAIRE MAINTENANCE (VARIOUS)
SPV.0060.15 GROUP CLEAN TUNNEL LUMINAIRES

* ADDITIONAL QUANTITIES SHOWN ELSEWHERE

LABEL	TUNNEL	SPV.0060.11	SPV.0060.12	SPV.0060.13	SPV.0060.14	SPV.0060.15
		TUNNEL	TUNNEL	TUNNEL	TUNNEL	GROUP
		150 W	200 W	250 W	400 W	CLEAN
						TUNNEL LUMINAIRES
		EACH	EACH	EACH	EACH	EACH
HL-40-HO	HOWELL TUNNEL BOTH WAYS	18	--	--	94	112
HL-40-KI	KILBOURN NB ENTRANCE	13	--	3	5	21
HL-40-QA	KILBOURN EB EXIT	--	22	--	37	59
HL-40-TX	MITCHELL IC TUNNEL #1 W-N	--	--	--	161	161
HL-40-TY	MITCHELL IC TUNNEL #2 W-N	--	--	--	151	151
HL-40-TZ	MITCHELL IC TUNNEL #3 N-W	--	--	--	178	178
TOTAL		13	22	3	532	570

MOBILIZATION ITEMS

ITEM	ITEM	UNIT	QUANTITY
619.1000	MOBILIZATION	EACH	1

WORK ZONE TRAFFIC CONTROL

ITEM	ITEM	UNIT	QUANTITY
643.0300	TRAFFIC CONTROL DRUMS ***	DAY	200
643.0420	TRAFFIC CONTROL BARRICADES TYPE III	DAY	25
643.0705	TRAFFIC CONTROL WARNING LIGHTS TYPE A	DAY	20
643.0715	TRAFFIC CONTROL WARNING LIGHTS TYPE C	DAY	20
643.0800	TRAFFIC CONTROL ARROW BOARDS	DAY	65
643.0900	TRAFFIC CONTROL SIGNS	DAY	150
643.1050	TRAFFIC CONTROL SIGNS PCMS	DAY	10
643.5000	TRAFFIC CONTROL	EACH	1
643.1055.S	TRUCK OR TRAILER MOUNTED ATTENUATOR	DAY	55


*** APPROVED TRAFFIC CONES WILL BE ACCEPTED FOR THIS ITEM FOR SHORT-TERM DAYTIME WORK, BUT WILL NOT BE MEASURED FOR PAYMENT. SEE THE SPECIAL PROVISIONS.

UNDISTRIBUTED HIGHWAY LIGHTING MAINTENANCE


ITEM	QTY.	UNIT	DESCRIPTION
655.0610	200	L.F.	ELECTRICAL WIRE LIGHTING 12 AWG
SPV.0060.01	5	EACH	PLAQUES SEQUENCE IDENTIFICATION
SPV.0060.02	10	EACH	LIGHT TOWER RAT SCREENS
SPV.0060.03	50	EACH	FUSE HOLDERS
SPV.0060.04	100	EACH	FUSES TYPE FNQ
SPV.0060.06	5	EACH	PLUMBING LIGHT POLES

Standard Detail Drawing List


10A01-03	ELECTRICAL HANDHOLE WIRING
10A02-03	IDENTIFICATION PLAQUES LIGHT POLES
10A05-02	ELECTRICAL DETAILS GROUND MOUNT LIGHT POLES ISOLATED NEUTRAL SYSTEMS
10A06-02	ELECTRICAL DETAILS GROUND MOUNT LIGHT POLES GROUNDED NEUTRAL SYSTEMS
10A07-02	ELECTRICAL DETAILS GROUND MOUNT LIGHT POLES PHASE-TO-PHASE SYSTEMS
10A08-02	ELECTRICAL DETAILS STRUCTURE MOUNT LIGHT POLES ISOLATED NEUTRAL SYSTEMS
10A09-02	ELECTRICAL DETAILS STRUCTURE MOUNT LIGHT POLES GROUNDED NEUTRAL SYSTEMS
10A10-02	ELECTRICAL DETAILS STRUCTURE MOUNT LIGHT POLES PHASE-TO-PHASE SYSTEMS
10A11-02	ELECTRICAL DETAILS MEDIAN MOUNT LIGHT POLES ISOLATED NEUTRAL SYSTEMS
10A12-02	ELECTRICAL DETAILS MEDIAN MOUNT LIGHT POLES GROUNDED NEUTRAL SYSTEMS
10A14-02A	ELECTRICAL DETAILS HIGH MAST LIGHTING
10A14-02B	ELECTRICAL DETAILS HIGH MAST LIGHTING
15C02-06A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C04-03	TRAFFIC CONTROL, ADVANCE WARNING SIGNS 45 M. P. H. OR GREATER TWO-WAY UNDIVIDED ROAD OPEN TO TRAFFIC
15C05-03	TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40 M. P. H. OR LESS
15D05-04	TRAFFIC CONTROL, SINGLE LANE CROSSOVER ENTRANCE WITH BARRIER
15D14-03	TRAFFIC CONTROL, TWO LANE CLOSURE ON FREEWAY OR EXPRESSWAY, SHORT-TERM (LESS THAN 24 HOURS)
15D15-03B	TRAFFIC CONTROL, ENTRANCE RAMP WITHIN LANE CLOSURE
15D16-03	TRAFFIC CONTROL, EXIT RAMP CLOSURE
15D27-03	TRAFFIC CONTROL, SHOULDER CLOSURE ON DIVIDED ROADWAY, SPEEDS GREATER THAN 40 MPH



EQUIPMENT GROUNDING
CONDUCTOR SLACK



UNGROUND CONDUCTOR SLACK
(AND GROUNDED NEUTRAL SLACK
IN GROUNDED NEUTRAL SYSTEM)



HANDHOLE GROUNDING LUG

(NUT, BOLT, WASHERS, AND LOCK WASHERS
SHALL BE STAINLESS STEEL)

CONDUCTOR COLOR CODES

KEY	CONDUCTOR	COLOR
3	UNGROUND LINE WIRE	*
4	GROUNDED LINE WIRE	WHITE
5	SYSTEM GROUNDING LINE WIRE	GREEN
6	GROUNDING ELECTRODE CONDUCTOR	BARE
11	UNGROUND POLE WIRE	*
12	GROUNDED POLE WIRE	WHITE
13	EQUIPMENT GROUNDING POLE WIRE	GREEN

* FOLLOW COLOR CODING SHOWN IN THE PLANS.
WHERE THE PLANS DO NOT SHOW COLOR CODING,
USE BLACK FOR SINGLE LUMINAIRE POLES; BLACK
AND RED FOR TWIN LUMINAIRE POLES.



1 POLE (1P)



2 POLE (2P)

FUSE ASSEMBLIES

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING
SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE ELECTRICAL DETAILS FOR THE
APPLICATION, WHICH MAY BE A LIGHT POLE, SIGN BRIDGE, ETC.


THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT
SPICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING
LUG TO THE CONNECTOR.

THREE POLE WIRES ARE SHOWN FOR A SINGLE LUMINAIRE LIGHT POLE.
THREE ADDITIONAL POLE WIRES REQUIRED FOR TWIN LUMINAIRE LIGHT POLES
ARE OMITTED FROM THE DRAWING FOR CLARITY. IN THE TWIN POLE CASE,
BUNDLE EACH SET OF THREE WIRES WITH A NYLON CABLE TIE.


IN 3-PHASE SYSTEMS, THERE WILL BE ONE MORE UNGROUNDED LINE WIRE,
WHICH IS OMITTED FROM THE DRAWING FOR CLARITY.

CIRCUIT TAGS SHALL BE INSTALLED ONLY WHERE REQUIRED IN THE SPECIAL
PROVISIONS.


TYPICAL CONDUCTOR SLACK AT HANDHOLES



CUTAWAY HANDHOLE DETAIL
GROUNDED NEUTRAL SYSTEMS
1-φ



CUTAWAY HANDHOLE DETAIL
ISOLATED NEUTRAL SYSTEMS
1-φ SHOWN; 3-φ WYE SIMILAR
(SEE GENERAL NOTE)



CUTAWAY HANDHOLE DETAIL
PHASE-TO-PHASE SYSTEMS
1-φ SHOWN; 3-φ DELTA SIMILAR
(SEE GENERAL NOTE)


- HANDHOLE AND COVER
- INSULATED SPLICE
- UNGROUND LINE WIRE
- GROUNDED LINE WIRE
- SYSTEM GROUNDING LINE WIRE
- GROUNDING ELECTRODE CONDUCTOR
- HANDHOLE GROUNDING LUG
- FUSE ASSEMBLY, 1P OR 2P AS REQUIRED
- CIRCUIT TAG (SEE GENERAL NOTE)
- REVERSIBLE PRESSURE OR COMPRESSION
GROUNDING CONNECTOR (NOT INSULATED)
- UNGROUND POLE WIRE
- GROUNDED POLE WIRE
- EQUIPMENT GROUNDING POLE WIRE

ELECTRICAL HANDHOLE WIRING

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Sept. 2014 /S/ Ahmet Demirelek
DATE STATE ELECTRICAL ENGINEER
FHWA

NOTE: REQUIRED CONDUCTOR SLACK NOT SHOWN ON "CUTAWAY HAND HOLE" DETAILS FOR
DRAWING CLARITY, SEE "TYPICAL CONDUCTOR SLACK AT HANDHOLES" ON THIS SHEET.



MEDIAN POLE SINGLE ARM POLE

LOCATION OF LIGHT POLE
CIRCUIT/SEQUENCE PLAQUE

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PLAQUES SHALL BE INCIDENTAL TO ALL NEW INSTALLATIONS.

WHERE SHOWN IN THE PLANS, REPLACEMENT PLAQUES WILL BE MEASURED AND PAID SEPARATELY.

FASTEN TOP, CENTER AND BOTTOM OF PLAQUE TO POLE OR OTHER LOCATION AS FOLLOWS:

- GALVANIZED STEEL SHAFT - STAINLESS STEEL POP RIVETS
- A588 STEEL SHAFT - SHIM FOR DRAINAGE WITH STAINLESS WASHERS; FASTEN WITH STAINLESS SELF-TAPPING SCREWS
- ALUMINUM SHAFTS - ALUMINUM POP RIVETS

MOUNTING HEIGHT SHALL BE APPROXIMATELY 5.0' ABOVE CURB OR SHOULDER. ADJUST IF IT IS KNOWN THAT REQUIRED TRAFFIC SIGNS WILL OBSTRUCT.

PLAQUE MATERIALS:


- BASE - SHEET ALUMINUM, 0.060" THICK.
- FACE - WHITE, SELF-ADHESIVE VINYL SHEETING, NON-RETROREFLECTIVE
- LINES - BLACK, 1/2" WIDE, SELF-ADHESIVE
- CHARACTERS - BLACK, SELF-ADHESIVE, SERIES "D", SIZE AS SHOWN
- COLOR PATCHES - VARIOUS COLORS, SELF-ADHESIVE VINYL SHEETING

WITH THE APPROVAL OF THE ENGINEER, THE BASE MATERIAL MAY BE OMITTED AND THE FACE ADHERED DIRECTLY TO THE SURFACE, IN CASES SUCH AS SMOOTH, CLEAN ALUMINUM POLES.

ALTERNATIVE COMPUTER-GENERATED SIGN LETTERING MAY BE ACCEPTED IF THE ENGINEER FINDS IT TO BE EQUIVALENT.

COLOR PATCH CODE FOR HPS AND LED LUMINAIRES

HPS	LED	COLOR PATCH CODE
1000 WATT		NO PATCH
400 WATT	CATEGORY D	ORANGE
310 WATT		BLUE
250 WATT	CATEGORY C	ORANGE WITH WHITE STRIPE
200 WATT		RED
150 WATT	CATEGORY B	GREEN
100 WATT	CATEGORY A	BROWN
70 WATT	CATEGORY UDL	BROWN WITH WHITE STRIPE



LIGHT POLE CIRCUIT/SEQUENCE
PLAQUE

IDENTIFICATION PLAQUES
LIGHT POLES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Feb. 2015
DATE

/S/ Ahmet Demirelek
STATE ELECTRICAL ENGINEER

FHWA

GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.

THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT SPLICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING LUG TO THE CONNECTOR.

WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES. WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
3- ϕ 208Y/120VAC OR 480Y/277VAC 4 WIRE

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ -GROUND	BALLAST WATTAGE	
	70-200 W	250-400 W
120 VAC	5 A	10 A
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
1- ϕ 120/240VAC OR 240/480VAC 3 WIRE

LEGEND

- A, B, X, Y, Z UNGROUNDED CIRCUIT CONDUCTORS
- N GROUNDED CIRCUIT CONDUCTORS
- GND EQUIPMENT GROUNDING CONDUCTOR
- P POLE (ELECTRICAL CIRCUIT)
- ϕ PHASE (ELECTRICAL CURRENT)
- [Symbol] HANDHOLE GROUND LUG
- [Symbol] SINGLE-POLE (1P) FUSE ASSEMBLY
- [Symbol] TWO-POLE (2P) FUSE ASSEMBLY
- [Symbol] UNFUSED LUMINAIRE
- [Symbol] EQUIPMENT GROUNDING ELECTRODE
- [Symbol] TERMINAL
- [Symbol] SPLICE
- [Symbol] CONDUCTOR
- [Symbol] EXOTHERMIC WELD

ELECTRICAL DETAILS
GROUND MOUNT LIGHT POLES
ISOLATED NEUTRAL SYSTEM

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.

THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT SPLICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING LUG TO THE CONNECTOR.

WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES. WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.

THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.



TYPICAL WIRING DIAGRAM
GROUNDED NEUTRAL SYSTEM
1- ϕ 240/480VAC 3 WIRE OR 480VAC 2 WIRE

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ -GROUND	BALLAST WATTAGE	
	70-200 W	250-400 W
120 VAC	5 A	10 A
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A

LEGEND

- A, B, X, Y, Z UNGROUNDED CIRCUIT CONDUCTORS
- N GROUNDED CIRCUIT CONDUCTORS
- GND EQUIPMENT GROUNDING CONDUCTOR
- P POLE (ELECTRICAL CIRCUIT)
- ϕ PHASE (ELECTRICAL CURRENT)
- [Symbol] HANDHOLE GROUND LUG
- [Symbol] SINGLE-POLE (1P) FUSE ASSEMBLY
- [Symbol] TWO-POLE (2P) FUSE ASSEMBLY
- [Symbol] UNFUSED LUMINAIRE
- [Symbol] EQUIPMENT GROUNDING ELECTRODE
- o TERMINAL
- SPLICE
- CONDUCTOR
- EXOTHERMIC WELD

ELECTRICAL DETAILS
GROUND MOUNT LIGHT POLES
GROUNDED NEUTRAL SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.

THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT SPLICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING LUG TO THE CONNECTOR.

WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES.
WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.



TYPICAL WIRING DIAGRAM
PHASE-TO-PHASE DELTA SYSTEM
3-φ 480VAC 3 WIRE

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE φ - φ	BALLAST WATTAGE	
	70-200 W	250-400 W
240 VAC	2P-5 A	2P-5 A
480 VAC	2P-5 A	2P-5 A



TYPICAL WIRING DIAGRAM
UNGROUND SYSTEM
1-φ 120-120VAC 2 WIRE

LEGEND

- A, B, X, Y, Z UNGROUNDED CIRCUIT CONDUCTORS
- N GROUNDED CIRCUIT CONDUCTORS
- GND EQUIPMENT GROUNDING CONDUCTOR
- P POLE (ELECTRICAL CIRCUIT)
- φ PHASE (ELECTRICAL CURRENT)
- [Symbol] HANDHOLE GROUND LUG
- [Symbol] SINGLE-POLE (1P) FUSE ASSEMBLY
- [Symbol] TWO-POLE (2P) FUSE ASSEMBLY
- [Symbol] UNFUSED LUMINAIRE
- [Symbol] EQUIPMENT GROUNDING ELECTRODE
- o TERMINAL
- SPLICE
- CONDUCTOR
- EXOTHERMIC WELD

ELECTRICAL DETAILS
GROUND MOUNT LIGHT POLES
PHASE-TO-PHASE SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ-GROUND	BALLAST WATTAGE	
	70-200 W	250-400 W
120 VAC	5 A	10 A
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.










WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES. WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

WIRE SIZE FROM THE JUNCTION BOX TO THE POLE HANDHOLE SHALL EQUAL THE SIZE OF THE POLE WIRE.


THE INTENT OF JUNCTION BOX SPLICES AS SHOWN IN THIS DETAIL IS FOR LIGHTING SYSTEMS WITH HEAVY LINE WIRE TOO LARGE TO PULL THROUGH THE CONDUIT INTO THE POLE HANDHOLE, DUE TO CONDUIT FILL REQUIREMENTS OF N.E.C., AND/OR THE STIFFNESS OF THE WIRE COMPARED TO THE NUMBER OF BENDS IN THE CONDUIT. IN CASES WHERE LINE WIRE IS LIGHTER, SUCH AS SMALLER SYSTEMS OR TOWARD THE FURTHEST END OF A LARGER SYSTEM, PULL THE LINE WIRE INTO THE POLE HANDHOLE FOR SPLICING.

LEGEND

- A . B . X . Y . Z
- N
- GND
- P
- ϕ
- 
- 
- 
- 
- 
- 
- 
- 
- 
- UNGROUNDING CIRCUIT CONDUCTORS
- GROUNDING CIRCUIT CONDUCTORS
- EQUIPMENT GROUNDING CONDUCTOR
- POLE (ELECTRICAL CIRCUIT)
- PHASE (ELECTRICAL CURRENT)
- HANDHOLE GROUND LUG
- SINGLE-POLE (1P) FUSE ASSEMBLY
- TWO-POLE (2P) FUSE ASSEMBLY
- UNFUSED LUMINAIRE
- EQUIPMENT GROUNDING ELECTRODE
- TERMINAL
- SPLICE
- CONDUCTOR
- EXOTHERMIC WELD



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
3-ϕ 208Y/120VAC OR 480Y/277VAC 4 WIRE



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
1-ϕ 120/240VAC OR 240/480VAC 3 WIRE

ELECTRICAL DETAILS
STRUCTURE MOUNT LIGHT POLES
ISOLATED NEUTRAL SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 DATE /S/ John Corbin
STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ-GROUND	BALLAST WATTAGE	
	70-200 W	250-400 W
120 VAC	5 A	10 A
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.






WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES.
WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

WIRE SIZE FROM THE JUNCTION BOX TO THE POLE HANDHOLE SHALL EQUAL THE SIZE OF THE POLE WIRE.

THE INTENT OF JUNCTION BOX SPLICES AS SHOWN IN THIS DETAIL IS FOR LIGHTING SYSTEMS WITH HEAVY LINE WIRE TOO LARGE TO PULL THROUGH THE CONDUIT INTO THE POLE HANDHOLE, DUE TO CONDUIT FILL REQUIREMENTS OF N.E.C., AND/OR THE STIFFNESS OF THE WIRE COMPARED TO THE NUMBER OF BENDS IN THE CONDUIT. IN CASES WHERE LINE WIRE IS LIGHTER, SUCH AS SMALLER SYSTEMS OR TOWARD THE FURTHEST END OF A LARGER SYSTEM, PULL THE LINE WIRE INTO THE POLE HANDHOLE FOR SPLICING.

LEGEND

- A, B, X, Y, Z
- UNGROUND
- CIRCUIT
- CONDUCTORS
- N
- GROUND
- CIRCUIT
- CONDUCTORS
- GND
- EQUIPMENT
- GROUNDING
- CONDUCTOR
- P
- POLE
- (ELECTRICAL
- CIRCUIT)
- ϕ
- PHASE
- (ELECTRICAL
- CURRENT)
- 
- HANDHOLE
- GROUND
- LUG
- 
- SINGLE-POLE (1P)
- FUSE
- ASSEMBLY
- 
- TWO-POLE (2P)
- FUSE
- ASSEMBLY
- 
- UNFUSED
- LUMINAIRE
- 
- EQUIPMENT
- GROUNDING
- ELECTRODE
- o
- TERMINAL
- .
- SPLICE
-
- CONDUCTOR
-
- EXOTHERMIC
- WELD



TYPICAL WIRING DIAGRAM
GROUNDED NEUTRAL SYSTEM
1-ϕ 240/480VAC OR 3 WIRE OR 480VAC 2 WIRE

ELECTRICAL DETAILS
STRUCTURE MOUNT LIGHT POLES
GROUNDED NEUTRAL SYSTEM

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 DATE /S/ John Corbin
STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ - ϕ	BALLAST WATTAGE	
	70-200 W	250-400 W
240 VAC	2P-5 A	2P-5 A
480 VAC	2P-5 A	2P-5 A

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.






WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES.
WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

WIRE SIZE FROM THE JUNCTION BOX TO THE POLE HANDHOLE SHALL EQUAL THE SIZE OF THE POLE WIRE.


THE INTENT OF JUNCTION BOX SPLICES AS SHOWN IN THIS DETAIL IS FOR LIGHTING SYSTEMS WITH HEAVY LINE WIRE TOO LARGE TO PULL THROUGH THE CONDUIT INTO THE POLE HANDHOLE, DUE TO CONDUIT FILL REQUIREMENTS OF N.E.C., AND/OR THE STIFFNESS OF THE WIRE COMPARED TO THE NUMBER OF BENDS IN THE CONDUIT. IN CASES WHERE LINE WIRE IS LIGHTER, SUCH AS SMALLER SYSTEMS OR TOWARD THE FURTHEST END OF A LARGER SYSTEM, PULL THE LINE WIRE INTO THE POLE HANDHOLE FOR SPLICING.

LEGEND

A, B, X, Y, Z	UNGROUNDING CIRCUIT CONDUCTORS
N	GROUNDING CIRCUIT CONDUCTORS
GND	EQUIPMENT GROUNDING CONDUCTOR
P	POLE (ELECTRICAL CIRCUIT)
ϕ	PHASE (ELECTRICAL CURRENT)
	HANDHOLE GROUND LUG
	SINGLE-POLE (1P) FUSE ASSEMBLY
	TWO-POLE (2P) FUSE ASSEMBLY
	UNFUSED LUMINAIRE
	EQUIPMENT GROUNDING ELECTRODE
○	TERMINAL
•	SPLICE
—	CONDUCTOR
■	EXOTHERMIC WELD



TYPICAL WIRING DIAGRAM
PHASE - TO - PHASE DELTA SYSTEM
3-ϕ 480VAC 3 WIRE



TYPICAL WIRING DIAGRAM
UNGROUNDING SYSTEM
1-ϕ 120 - 120VAC 2 WIRE

ELECTRICAL DETAILS
STRUCTURE MOUNT LIGHT POLES
PHASE-TO-PHASE SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 DATE /S/ John Corbin
STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

LEGEND

- A, B, X, Y, Z

UNGROUND

CIRCUIT

CONDUCTORS
- N

GROUND

CIRCUIT

CONDUCTORS
- GND

EQUIPMENT

GROUNDING

CONDUCTOR
- P


POLE

(ELECTRICAL

CIRCUIT)
- ϕ


PHASE

(ELECTRICAL


CURRENT)
- 

HANDHOLE

GROUND

LUG
- 


UNFUSED

LUMINAIRE
- 

SINGLE

POLE (1P)

FUSE

ASSEMBLY
- 

EQUIPMENT


GROUNDING

ELECTRODE
- o

TERMINAL
- .

SPLICE
- CONDUCTOR
- EXOTHERMIC

WELD



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
1-ϕ 240/480VAC 3 WIRE

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.

THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT SPLICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING LUG TO THE CONNECTOR.

WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES. WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.


THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

WIRE SIZE FROM THE JUNCTION BOX TO THE POLE HANDHOLE SHALL EQUAL THE SIZE OF THE POLE WIRE.

THE INTENT OF JUNCTION BOX SPLICES AS SHOWN IN THIS DETAIL IS FOR LIGHTING SYSTEMS WITH HEAVY LINE WIRE TOO LARGE TO PULL THROUGH THE CONDUIT INTO THE POLE HANDHOLE, DUE TO CONDUIT FILL REQUIREMENTS OF N.E.C., AND/OR THE STIFFNESS OF THE WIRE COMPARED TO THE NUMBER OF BENDS IN THE CONDUIT. IN CASES WHERE LINE WIRE IS LIGHTER, SUCH AS SMALLER SYSTEMS OR TOWARD THE FURTHEST END OF A LARGER SYSTEM, PULL THE LINE WIRE INTO THE POLE HANDHOLE FOR SPLICING.

HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ-GROUND	BALLAST WATTAGE	
	150-200 W	250-400 W
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A



TYPICAL WIRING DIAGRAM
ISOLATED NEUTRAL SYSTEM
3-ϕ 480Y/277VAC 4 WIRE

ELECTRICAL DETAILS
MEDIAN MOUNT LIGHT POLES
ISOLATED NEUTRAL SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA

LEGEND

- A, B, X, Y, Z

UNGROUND

CIRCUIT

CONDUCTORS
- N

GROUND

CIRCUIT

CONDUCTORS
- GND

EQUIPMENT

GROUNDING

CONDUCTOR
- P


POLE

(ELECTRICAL

CIRCUIT)
- ϕ


PHASE

(ELECTRICAL


CURRENT)
- 

HANDHOLE

GROUND

LUG
- 


UNFUSED

LUMINAIRE
- 

SINGLE

POLE (1P)

FUSE


ASSEMBLY
- 

EQUIPMENT

GROUNDING

ELECTRODE
- TERMINAL
- SPLICE
- CONDUCTOR
- EXOTHERMIC

WELD



TYPICAL WIRING DIAGRAM
GROUNDED NEUTRAL SYSTEM
1-ϕ 240/480VAC OR 3 WIRE OR 480VAC 2 WIRE

GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

USE THIS DETAIL IN CONJUNCTION WITH THE DETAIL FOR ELECTRICAL HANDHOLE WIRING.

THE GROUNDING ELECTRODE CONDUCTOR SHALL BE CONTINUOUS WITHOUT SPLICES FROM THE GROUNDING ELECTRODE THROUGH THE HANDHOLE GROUNDING LUG TO THE CONNECTOR.

WIRING FOR SINGLE LUMINAIRE POLES IS SHOWN WITH SOLID LINES. WIRING FOR THE SECOND LUMINAIRE OF TWIN LUMINAIRE POLES IS SHOWN WITH DOTTED LINES.

THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

WIRE SIZE FROM THE JUNCTION BOX TO THE POLE HANDHOLE SHALL EQUAL THE SIZE OF THE POLE WIRE.

THE INTENT OF JUNCTION BOX SPLICES AS SHOWN IN THIS DETAIL IS FOR LIGHTING SYSTEMS WITH HEAVY LINE WIRE TOO LARGE TO PULL THROUGH THE CONDUIT INTO THE POLE HANDHOLE, DUE TO CONDUIT FILL REQUIREMENTS OF N.E.C., AND/OR THE STIFFNESS OF THE WIRE COMPARED TO THE NUMBER OF BENDS IN THE CONDUIT. IN CASES WHERE LINE WIRE IS LIGHTER, SUCH AS SMALLER SYSTEMS OR TOWARD THE FURTHEST END OF A LARGER SYSTEM, PULL THE LINE WIRE INTO THE POLE HANDHOLE FOR SPLICING.


HANDHOLE FUSE SCHEDULES

LINE VOLTAGE ϕ-GROUND	BALLAST WATTAGE	
	150-200 W	250-400 W
240 VAC	5 A	5 A
277 VAC	5 A	5 A
480 VAC	3 A	5 A


ELECTRICAL DETAILS
MEDIAN MOUNT LIGHT POLES
GROUNDED NEUTRAL SYSTEMS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
10/25/2010 /S/ John Corbin
DATE STATE ELECTRICAL ENGINEER FOR HWYS
FHWA



EQUIPMENT GROUNDING GRID AND FOUNDATION ELECTRICAL DETAILS




LOWER RING OPTICS PLAN
1- ϕ CASE SHOWN; 3- ϕ CASE SIMILAR

OVER CURRENT AND POWER CORD SCHEDULE

LINE VOLTAGE	HAND HOLE BREAKERS	INDIVIDUAL LUMINAIRE FUSES	POWER CORD	PRONGS ON LOAD BREAK DISCONNECT
1- ϕ 120/240VAC: 3 WIRE	2-30A, 1P, 277VAC	20A	10-3 + GND "SO"	A,B,N,GND
1- ϕ 240/480VAC: 3 WIRE	2-30A, 1P, 277VAC	10A	10-3 + GND "SO"	A,B,N,GND
3- ϕ 480Y/277VAC: 4 WIRE	3-30A, 1P, 277VAC	10A	10-4 + GND "SO"	X,Y,Z,N,GND
3- ϕ 208Y/120VAC: 4 WIRE	3-30A, 1P, 277VAC	20A	10-4 + GND "SO"	X,Y,Z,N,GND
1- ϕ 480VAC: 2 WIRE	1-20A, 2P, 600VAC	5A	10-3 + GND "SO"	A,B,N,GND

LEGEND



GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

IN CASES WHERE THE PLANS SHOW LINE IN/LINE OUT DISTRIBUTION SYSTEMS, FURNISH FEED-THROUGH LUGS IN THE CIRCUIT BREAKER ENCLOSURE.

THE PLANS WILL SHOW WHICH CIRCUIT LEG(S) ARE CONNECTED TO EACH INSTALLATION.

FIELD RECODING OF UNGROUNDED CONDUCTORS IN TYPE "SO" CABLE MAY BE REQUIRED TO CONFORM TO SYSTEM COLOR CODING AS SHOWN IN THE PLANS.


CIRCUIT BREAKERS SHALL BE MINIMUM 14 kAIC AT THE VOLTAGE SHOWN.

LOADBREAK DISCONNECTS SHALL BE MELTRIC TYPE "DR", 30 AMP, 600 VOLT, DO NOT SUBSTITUTE. FURNISH "FDP" FINGER/PALM DRAW PLATES (APPLIES TO THE PLUG AND RECEPTACLE ONLY, NOT TO THE APPLIANCE INLET). FURNISH "LP" MOISTURE PROTECTION (APPLIES TO THE PLUG ONLY, NOT TO THE RECEPTACLE OR THE APPLIANCE INLET).

SURGE ARRESTORS SHALL BE 650 VAC, 2P OR 3P AS REQUIRED.

CIRCUIT BREAKER ENCLOSURES SHALL BE NEMA 1, 100 AMP, 600 VOLT, 2P OR 3P AS REQUIRED, SURFACE MOUNT. IN ALL SYSTEMS, FURNISH A MINIMUM 4-TERMINAL GROUND BUS. IN ISOLATED NEUTRAL SYSTEMS, ADDITIONALLY FURNISH A MINIMUM 1-TERMINAL NEUTRAL BUS. BUSSES SHALL BE RATED FOR NO. 10 AWG THROUGH NO. 2 AWG CU.


- 1 LOADBREAK DISCONNECT - MALE PLUG
- 2 LOADBREAK DISCONNECT - FEMALE RECEPTACLE
- 3 LOADBREAK DISCONNECT - MALE APPLIANCE INLET
- 4 SURGE ARRESTOR - 2P OR 3P AS REQUIRED
- 5 CIRCUIT BREAKER ENCLOSURE
- 6 CIRCUIT BREAKER
- 7 CIRCUIT BREAKER ENCLOSURE NEUTRAL BUS
- 8 CIRCUIT BREAKER ENCLOSURE EQUIPMENT GROUNDING BUS
- 9 LOWERING RING JUNCTION BOX (WEEP HOLE REQUIRED)
- 10 TERMINAL STRIP




ONE LINE DIAGRAM
ANY LINE VOLTAGE PER OVER CURRENT AND POWER CORD SCHEDULE

ELECTRICAL DETAILS
HIGH MAST LIGHTING


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




TYPICAL WIRING DIAGRAM-HANDHOLE
ISOLATED NEUTRAL SYSTEM
1- ϕ 120/240VAC OR 240/480VAC 3 WIRE



LOWERING RING JUNCTION BOX WIRING DIAGRAM
TYPICAL 1- ϕ CASE SHOWN; 3- ϕ CASE SIMILAR



TYPICAL WIRING DIAGRAM-HANDHOLE
ISOLATED NEUTRAL SYSTEM
3- ϕ 480Y/277VAC 4 WIRE
OR 3- ϕ 208Y/120VAC 4 WIRE



TYPICAL WIRING DIAGRAM-HANDHOLE
GROUNDED NEUTRAL SYSTEM
1- ϕ 240/480VAC 3 WIRE OR 480VAC 2 WIRE

ELECTRICAL DETAILS
HIGH MAST LIGHTING


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED

10/25/2010
DATE


FHWA

/S/ John Corbin
STATE ELECTRICAL ENGINEER FOR HWYS



DETAIL A
MAINLINE CLOSURE WITH POSTED DETOUR


WORK ZONE GREATER THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL B













MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE LESS THAN 1/2 MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (F T)
25	200
30	200
35	350
40	350
45	500
50	550
55	750


- # LEGEND
-  SIGN ON PERMANENT SUPPORT
-  TYPE III BARRICADE
-  TYPE III BARRICADE WITH ATTACHED SIGN
-  TYPE "A" WARNING LIGHT (FLASHING)
-  WORK AREA
-  M4-8
-  M3-X
-  M1-4
- OR
-  M1-5A
- OR
-  M1-6
-  M05-1
- OR
-  M06-1
- FLAGS, 16" X 16" MIN., (ORANGE)

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦

BARRICADES AND SIGNS FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

Sept. 2015	/S/ Peter Amakobe Atepe
DATE	STATEWIDE WORK ZONE TRAFFIC
FHWA	SAFETY ENGINEER



TYPICAL SIDEROAD APPROACH WARNING SIGN DETAIL

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.


ALL SIGNS ARE 48"x48" UNLESS OTHERWISE NOTED.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS RE-ESTABLISHED.

* OMIT G20-1 SIGNS IF LENGTH OF WORK AREA IS 2 MILES OR LESS.

** PLACE ADDITIONAL W20-1A "ROAD WORK AHEAD" SIGN IF WORK AREA WITHIN THE PROJECT IS SEPARATED BY MORE THAN 2 MILES FROM PREVIOUS WORK AREA.




LEGEND

- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC
- WORK AREA

TRAFFIC CONTROL, ADVANCE
WARNING SIGNS 45 M.P.H.
OR GREATER TWO-WAY
UNDIVIDED ROAD OPEN TO TRAFFIC

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Sept. 2015 /S/ Peter Amokobe Atepe
DATE STATEWIDE WORK ZONE TRAFFIC
FHWA SAFETY ENGINEER



TYPICAL SIDEROAD APPROACH WARNING SIGN DETAIL

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.


THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48"x48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS, 36"x36" SIGNS MAY BE USED INSTEAD OF 48"x48" SIGNS.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS RE-ESTABLISHED.

* THE THIRD W20-1 SIGN IS REQUIRED ONLY IF THERE IS AN INTERSECTION BETWEEN THE "ROAD WORK 500 FT" SIGN AND THE WORK ZONE. ADJUST THE PLACEMENT OF THIS SIGN BASED ON INTERSECTION LOCATION AND OTHER FIELD CONDITIONS.



LEGEND

- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC
- WORK AREA

TRAFFIC CONTROL, ADVANCE
WARNING SIGNS 40 M.P.H.
OR LESS TWO-WAY UNDIVIDED
ROAD OPEN TO TRAFFIC

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Sept. 2015 /S/ Peter Amakobe Atepe
DATE STATEWIDE WORK ZONE TRAFFIC
FHWA SAFETY ENGINEER

*** NOTE: SEE SDD 15 D 12 FOR LANE CLOSURE DETAILS.

GENERAL NOTES

ALL SIGNS ARE 48"x48" UNLESS OTHERWISE NOTED.

"W0" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH THE TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER. NO WARNING LIGHTS SHALL BE WORKING ON "COVERED" OR "DOWNED" SIGNS.


THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET, (500 FEET DESIRABLE) DISTANCE TO EXISTING SIGNS.

TEMPORARY PAVEMENT MARKING REMOVABLE TAPE SHALL BE USED WHEN CROSSING PERMANENT ROADWAY SURFACES THAT WILL REMAIN AFTER USE OF CROSSOVER.

6

6




TRAFFIC CONTROL,
SINGLE LANE CROSSOVER
ENTRANCE WITH BARRIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
July 14, 2015 /S/ Peter Amakobe Atepe
DATE STATEWIDE WORK ZONE TRAFFIC
FHWA SAFETY ENGINEER

S.D.D. 15 D 5-4

S.D.D. 15 D 5-4



LEGEND

- TYPE III BARRICADE
- TYPE III BARRICADE WITH ATTACHED SIGN
- SIGN ON TEMPORARY SUPPORT
- TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT
- TRAFFIC CONTROL DRUM
- FLASHING ARROW BOARD
- DIRECTION OF TRAFFIC
- WORK AREA

GENERAL NOTES

THIS DETAIL IS TYPICAL FOR CLOSING THE RIGHT TWO LANES. FOR CLOSING THE LEFT TWO LANES, REVERSE THE TRAFFIC CONTROL.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.

"WO" SIGNS ARE THE SAME AS "W" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

W20-1E AND G20-2A SIGNS ARE NOT REQUIRED IF THE LANE CLOSURE IS WITHIN A LARGER WORK ZONE WHERE THESE SIGNS ARE ALREADY PRESENT.

CONSIDER GEOMETRICS WHEN LOCATING SIGNS AND ARROWBOARDS SO THE APPROACHING DRIVER HAS A CLEAR VIEW OF THE ARROWBOARDS AND LANE CLOSURE DRUMS FOR A MINIMUM 1500 FEET IN FRONT OF DRUMS.

WHEN A RAMP OR SIDE ROAD INTERSECTS THE FACILITY ON WHICH THE WORK IS BEING PERFORMED, ADDITIONAL TRAFFIC CONTROLS SHALL BE PROVIDED AS SPECIFIED IN THE PLANS AND/OR SPECIAL PROVISIONS OR AS APPROVED BY THE ENGINEER.


BARRICADES IN A CLOSED LANE THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION OR, FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

CHANNELIZING DEVICES PLACED ADJACENT TO WORK AREA SHALL BE PULLED BACK FROM THE TRAVEL LANE WHEN WORK IS NOT IN PROGRESS.

WARNING LIGHTS ARE NOT REQUIRED IF THE LANE CLOSURE IS A DAYTIME ONLY OPERATION.

TRAFFIC CONTROL. TWO LANE CLOSURE ON FREEWAY OR EXPRESSWAY. SHORT TERM (LESS THAN 24 HOURS)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED July 14, 2015 DATE	/S/ Peter Amakobe Atepe STATEWIDE WORK ZONE TRAFFIC SAFETY ENGINEER
FHWA	

TRAFFIC CONTROL, ENTRANCE RAMP WITHIN LEFT LANE CLOSURE



- ① EXTEND THE LENGTH OF MERGE AREA IF THE ENTERING (DESIGN) SPEED OF THE RAMP IS LESS THAN 50 MPH OR IF THE MAINLINE GRADE EXCEEDS +2.2%.
- ② END TEMPORARY MARKING AT 1/2 THE LENGTH OF FULL WIDTH OF THE ACCELERATION LANE.

TEMPORARY PAVEMENT DETAIL

(EXISTING RAMP DIMENSIONS MAY VARY. ADJUST TEMPORARY PAVEMENT ACCORDINGLY)

LEGEND

- ⊙ SIGN ON PERMANENT SUPPORT
- ⌄ SIGN ON TEMPORARY SUPPORT
- TRAFFIC CONTROL DRUM
- TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT
- ⌄ TYPE III BARRICADE WITH ATTACHED SIGN
- XXXXX REMOVING PAVEMENT MARKING
- ➡ DIRECTION OF TRAFFIC

GENERAL NOTES

THE INSTALLATIONS SHOWN ON THIS SHEET ARE TYPICAL EXAMPLES AND ARE NOT INTENDED TO REPRESENT ANY PARTICULAR RAMP. AT SPECIFIC FIELD LOCATIONS, SIMILAR INSTALLATIONS SHALL BE USED AND ADJUSTED TO THE GEOMETRICS OF THE RAMP AS COORDINATED WITH THE ENGINEER.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET, (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48"x48" UNLESS OTHERWISE NOTED.

"W0" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

SEE SEPARATE LANE CLOSURE DETAIL FOR TYPICAL SPACING OF TYPE III BARRICADES AND R11-2L "LANE CLOSED" SIGNS.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS, OR THAT WILL BE PLACED IN A CLOSED LANE, MAY BE MOUNTED ON PORTABLE SUPPORTS. USE SUPPORTS THAT PROVIDE A MINIMUM OF 5 FEET FROM THE BOTTOM OF THE SIGN TO THE PAVEMENT.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

REMOVE PAVEMENT MARKINGS AND PLACE TEMPORARY PAVEMENT MARKING REMOVABLE TAPE IF LANE CLOSURE IS TO BE IN PLACE FOR 7 OR MORE CONTINUOUS DAYS AND NIGHTS.

WARNING LIGHTS ARE NOT REQUIRED IF THE LANE CLOSURE IS A DAYTIME ONLY OPERATION.

TRAFFIC CONTROL, ENTRANCE RAMP WITHIN LANE CLOSURE


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
March, 2017 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER
FHWA



G20-60
108"x24"

OR



G20-60
108"x24"

PLACE SIGN G20-60 OVER MILEAGE
ON EXISTING E1-1A SIGN



COVER ARROW ON
EXISTING E4-1A
SIGN (COVERING
SIGNS TYPE I)

G20-61
120"x30"

GENERAL NOTES

THIS RAMP CLOSURE DETAIL IS TYPICAL FOR CLOSING A RIGHT SIDE EXIT RAMP. FOR A LEFT SIDE EXIT RAMP, REVERSE THE TRAFFIC CONTROL.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

PLACE TEMPORARY PAVEMENT MARKING, REMOVABLE TAPE IF RAMP CLOSURE IS TO BE IN PLACE FOR 4 OR MORE CONTINUOUS DAYS AND NIGHTS.

WORK AREAS WITH A DROPOFF ALONG THE EDGE OF AN OPEN TRAVEL LANE SHALL BE LEVELED WITH TEMPORARY FILL WHEN THE CONTRACTOR IS NOT WORKING ADJACENT TO THE TRAVEL LANE. DRUMS SHALL BE PLACED ENTIRELY OUTSIDE THE TRAVEL LANE, ALLOWING THE FULL UNOBSTRUCTED LANE WIDTH, WHEN THE WORK IS NOT IN PROGRESS.


WHERE MEDIAN BARRIER IS IN PLACE, SIGNS SHOWN ON LEFT SIDE OF ROADWAY MAY BE OMITTED FOR RIGHT SIDE RAMP CLOSURES OF LESS THAN 12-HOUR DURATION.

* W20-1 AND G20-2A SIGNS ARE NOT REQUIRED IF THE RAMP CLOSURE IS WITHIN A LARGER WORK ZONE WHERE THESE SIGNS ARE ALREADY PRESENT.

** PLACE "RAMP WILL BE CLOSED" SIGN 7 CALENDAR DAYS PRIOR TO CLOSURE OR AS DIRECTED BY THE ENGINEER. SEE WISCONSIN STANDARD SIGN PLATES FOR SIGN LAYOUT.

6

6



LEGEND

- TYPE III BARRICADE
- TYPE III BARRICADE WITH ATTACHED SIGN
- TRAFFIC CONTROL DRUM
- SIGN ON PERMANENT SUPPORT
- TYPE "A" WARNING LIGHT (FLASHING)
- DIRECTION OF TRAFFIC

TRAFFIC CONTROL, EXIT RAMP CLOSURE

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
Sept. 2015 /S/ Peter Amakobe Atepe
DATE STATEWIDE WORK ZONE TRAFFIC
FHWA SAFETY ENGINEER

S.D.D. 15 D 16-3

S.D.D. 15 D 16-3

LEGEND

- TRAFFIC CONTROL DRUM
- ⦿ SIGN ON PERMANENT SUPPORT
- ➡ DIRECTION OF TRAFFIC
- ⚡➡ FLASHING ARROW BOARD
- ▨ WORK AREA

GENERAL NOTES

THIS DETAIL IS TYPICAL FOR CLOSING THE RIGHT SHOULDER. FOR CLOSING THE LEFT SHOULDER, REVERSE THE TRAFFIC CONTROL.

THIS DETAIL MAY BE USED FOR DIVIDED ROADWAYS WITH ANY NUMBER OF TRAVEL LANES.

THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.

SIGN LAYOUTS SHALL BE IN ACCORDANCE WITH THE FHWA'S MANUAL OF STANDARD HIGHWAY SIGNS OR THE WISCONSIN STANDARD SIGN PLATES.


SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

CHANNELIZING DEVICES PLACED ADJACENT TO THE WORK AREA SHALL BE PULLED BACK FROM THE TRAVEL LANE WHEN WORK IS NOT IN PROGRESS.

WHEN A RAMP INTERSECTS THE FACILITY ON WHICH THE WORK IS BEING PERFORMED, ADDITIONAL TRAFFIC CONTROLS SHALL BE PROVIDED AS SPECIFIED IN THE PLANS AND/OR THE SPECIAL PROVISIONS OR AS APPROVED BY THE ENGINEER.

*FOR SHORT DURATION SHOULDER WORK OF LESS THAN ONE HOUR, THE W21-5a SIGN MAY BE OMITTED.



TRAFFIC CONTROL
SHOULDER CLOSURE ON DIVIDED
ROADWAY, SPEEDS GREATER
THAN 40 MPH

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2016 /S/ Peter Amakobe Atepe
DATE STATEWIDE WORK ZONE TRAFFIC
FHWA SAFETY ENGINEER



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>