Substructure Construction Inspection Session 3

Learning Outcomes

Upon completion of this course participants will be able to:

- Identify the critical elements of substructure construction.
- Perform basic plan and layout checks on critical bridge substructure elements.
- Identify the equipment used for substructure construction
- Perform pile driving inspection
- Perform bar steel reinforcement inspection
- Perform concrete placement inspection



WisDOT Bridge Construction Inspection Training - 202

3 - 2

Substructure Elements Abutments Piers • Piles • Piles FootingBody or Barrel Seal Footing Backwall Columns • Sidewalls Pier Cap Wing walls Seats • Riprap/Slope Paving/Backfill • Riprap

Primary	Subs	truct	ture l	Eval	luati	on l	tems

What to expect and inspect during substructure construction • Erosion Control

- Excavation
- Piling
- Forms
- Reinforcing Steel
- Concrete
- Backfill
- Slope Protection




Erosion Control

Review the Erosion Control sheets within the plan set and review the ECIP.

- Silt Fence
- Erosion Bales / Ditch Checks
- Turbidity Barrier or Steel Sheeting
- Filter Bag / Settling Basin
- Riprap and Erosion Mat






















Site Prepara	tion	
• Clearing and G	rubbing	
 Removal of Str 	ructures	
 Excavation for 	the Proposed Bridge	
A SECONDARY		
**OFTRING	WisDOT Bridge Construction Inspection Training - 2020	3 - 15




























Piling Plan Information Pile Function Types (Cast-in-Place, H-Piles, Steel Sheeting) Equipment and Methods for Installation (Driving Systems) Documentation Layout Test Pile Driving Specifications Filling Cast-in-Place Piling Cutting & Splicing




















Common Pile Driving Hammers • Air or Steam (Impact) • Diesel (Impact) • Vibratory WildOff Bridge Construction Transing - 2009

























Piling Specifications Section 550 in Standard Specs • Capacity determined by the Modified Gates formula • P=(0.875 x E1/2 x log(10/s)) - 50 • P = Nominal Resistance • E = Energy produced by hammer (ft-lbs) • s = Average penetration in inches/blow • (computed over max. distance of 1 inch) • For some structures, may use Wave Equation to determine pile capacity • Both methods result in an ultimate capacity • Contractor must submit required drive train information and receive approval before starting driving • Any change in drive train requires a new submittal and approval




























Achieving Plan Elevations for Piles • Driving to Plan Elevation • Ideally, All Piles are Driven to Same Elevation (Rare) • Splicing • Welding • Cutting











Welding General Overview A joining process producing coalescence of materials by heating them to the welding temperature, with or without the application of pressure or by the application of pressure alone, and with or without the use of filler material. Piling welding in the field is done without pressure Follows AWS D1.5 Bridge Welding Code Typical processes in field Shielded Metal Arc Welding (SMAW) A.K.A. Stick Welding Gas Metal Arc Welding (GMAW) A.K.A. MIG welding

Welding Symbol


FRESHING DESIGNATION
CONCINE REPORTS

FRESHING DESIGNATION
CONCINE REPORTS

FOR CHISTON WILL SECT

FOR CHISTON WILL SECTI

Figure 3—Standard Location of the Elements of a Welding Symbol

















What to Check When Welding

Refer to Table 2 of Section 5-20 in the CMM


- Is it raining?
- Has a bevel been ground in?
- Are the surfaces free of dirt, slag or other contaminants?
- Is there an electrode oven?
 - Is the oven on?
- When did the contractor open the hermetically sealed container?
- What is the ambient temperature?
















Recommendations After Pile Driving Cover tops of CIP piling Drop a rock Drop a tape RECORD ALL MEASUREMENTS





Forming & Reinforcement of Substructure Abutments Body or Barrel Backwall Wingwall Piers Footing Pier Shaft and/or Columns Beam Seats



Rebar Testing Requirements

- Test bars provided by mill
 - These bars are not to be taken to lab for testing
 - Splice into structure, with proper lap length
- Test samples dependent on weight (CMM 8-50)
 - No test bars needed per size for total weight <50,000#

 2 5' test bars per size per 50,000-100,000#

 3 5' test bars per size per 100,000-150,000#
- Test bars should be taken randomly preferably from differing heats



Timber Forms Constructed at Back Face























Concrete Curing

- Ideally concrete is given enough time to cure before form removal
 - This is rarely the case
- The Contractor should immediately begin finishing concrete upon form removal
- If there is an anticipated delay in surface rubbing
 Dissipating curing compound should be placed immediately upon all surfaces that will not be incorporated in further pours.
 Typically compound remains on surface for 30 days, if rubbing prior to this, contractor should water blast the surface.































Common Concrete Temperature Protection Methods Blankets Preheating Formwork Heating Mix in Cold Weather Icing Mix in Hot Weather Burlap / Plastic Covering



























































Inspector Vigilance Things to keep an eye on in the field • Water added to concrete trucks • Note the amount and where the load is placed • If load being tested, must be tested AFTER water added • Inspector may request concrete tested when deemed necessary • Improper concrete vibrating technique • Always inserted and removed vertically • Slow and controlled • Vibrator must penetrate the previously placed layer • Queued concrete trucks • Note when trucks arrive and start and end discharge • Without WR – 60 minutes from batch • With WR – 90 minutes from batch • Reinforcement spacing and clearances

Substructure Construction	
EXERCISES	
8 6	
WidDOT Bridge Construction Impection Training - 2020 3 - 145	
Exercise Questions	
Where do you find the required bearing resistance values of the piling?	
Foundation data sheets and with each footing unit in the plan.	
2.) What happens when piling tightens up quickly and you cannot count a whole foot	
as it is being driven?	
Have the contractor mark the piling every 10 blows. Equate measurement to table to find bearing. Continue until acceptable bearing is achieved.	
3.) Do different piling types require different pile driving caps?	
Yes, each shape requires a different cap. The pile cap must fit the	
configuration of the pile.	
WidDOT Bridge Construction Impection Training - 2020 3 - 145	
O TO	
Exercise Questions	
4.) A pile reaches bearing after driving it down 6 feet, and the pile next to it reaches	
bearing when driven down 40 feet. What action might you take in this instance?	
Contact BOS. Pull up the pile driven to 6 ft and move it over 2 feet toward the closest pile	
driven to the proper depth. Check soil borings and removal plans for obstruction. If it is only 6ft you may want to dig down to find the obstruction. Document all changes	
5.) Steel piling starts to bend. What do you do?	
STOP! Most likely reached refusal and required bearing.	
Mecono.	
WisDOT Bridge Construction Inspection Training - 2020 3 - 147	

Exercise Questi	<u>ons</u>	
	riving piling with a diesel hammer in a sensi nt you suggest to the contractor?	itive urban area.
encloses the ham • Restrict pile drivit • Notify the public	ng hours.	curtain that
7.) Exercise – Find you	r bearing chart	
	Gates bearing chart driving record, and bearing report	
TO THE PARTY OF TH	WisOOT Bridge Construction Inspection Training - 2020	3 - 148