Bridge Rehabilitation Inspection Session 5



Session 5 – Learning Outcomes

Upon completion of this session participants will be able to:

- Identify the critical elements of bridge rehabilitation construction.
- Perform basic checks on critical bridge rehabilitation elements.
- Perform joint replacement inspection.
- Perform concrete surface repair inspection.
- Perform concrete overlay inspection.
- Perform polymer overlay inspection.
- Perform deck replacement inspection.




Session 5 - Topics not covered

- Less commonly used overlay types
- Widenings
- Bearing replacement
- FRP (fiber reinforced polymer)
- Painting
 - SSPC Bridge Coating Inspection Course
- Cathodic protection








Bridge Rehabilitation – Key Resources	
AASHTOWare Project Construction Advantage of the construction of the construc	
CMM – Section 5-28 Concrete Deck Overlays and Structure Repairs https://wisconsindot.gov/irdwv/cmm/cm-05-28.pdffcm5-28	
Bridge Manual – Chapter 40 https://www.consinded.gov/chsdManuals/stret/manuals/bridge/ch40.pdf	
Bridge Standard Detail Drawings https://wisconsinded.gov/dtsdManuals/strct/manuals/bridge/std-ch40.pdf	
Annual Region Construction Conferences Attend in February/March	
Contact BOS/Consultant Designer Structure Design Contact on Plan Set Region Liaison Aaron Bonk, P.E.—Structures Design Chief (608) 261-0261	
WisDOT Bridge Construction Inspection Training - 2000 5 - 4	
Joint Replacement Overview	
Overview	-
Common Types of Expansion DevicesDemolition	-
Epoxy Anchors Setting Joint	
Reinforcement Installation	
Gland Installation Special Considerations	
and the second s	
WidOT firster Construction Impaction Faming - 2020 5 - 5	
	-
Common Joint Types	
 Called "Expansion Devices" in Bridge Manual Chapter 28 https://wisconsindot.gov/dtsdManuals/strct/manuals/bridge/ch28.p 	



































Adhesive Anchors – Key Inspection Items (Epoxy Anchors) Bid Items 502.41xx or 502.42xx Before the contractor starts drilling make sure they have the correct bit size! Read the adhesive manufacturer's installation instructions Example for Rd Head A7+ = 1716 or 18° targer than diameter of roolfrebar roolfrebar roolfrebar.





Adhesive Anchors – Key Inspection Items 1. The anchors must be installed by or under the direct supervision of an ACI/CRSI certified installer. 2. If the contractor doesn't have a certified installer then a non-destructive pullout test must be performed. 3. https://www.concrete.org/certification/enifyacertification/enifyacertification/ 4. https://www.concrete.org/certification/enifyacertification/enifyacertification/ 5. https://www.concrete.org/certification/enifyacertification/enifyacertification/ 6. https://www.concrete.org/certification/enifyacertification/enifyacertification/ 6. https://www.concrete.org/certification/enifyacertification/enifyacertification/ 6. https://www.concrete.org/certification/ 6.

Inspect the delivered joint

- When reviewing the shop drawings check for the number of field welds, most plan sets say only one field weld is permitted.
- Make sure that the person who field welds the joint steel is certified (need form DT2320)
 https://wisconsign.org/pubm.person/firmdocs/dt2320.docx
- Check that what is delivered matches the shop drawings

NOTES

OFFICE SPECE FRANTICE & STEEL EXTREMEND LASSS MORE ARE REQUEST FOR

OFFICE SPECE FRANTICE & STEEL EXTREMEND AND ASSESS MORE ARE REQUEST FOR

OFFICE SPECE FRANCIS AND ASSESS OF AN ASSESS OF A STEEL EXTREMENDS SEED FOR

EXCEPTION OF A STEEL ASSESS OF A STEEL ASSESS OF A STEEL ASSESS

OFFI SHARE OF A STEEL ASSESS OF A STEEL ASSESS



SCON STATE OF THE PROPERTY OF




































Concrete Surface Repair - Overview

Overview

- Determine Locations
- Correct/record Materials
- Saw cut
- Chipping Concrete
- Incorporate existing reinforcement
- Install nails and wire
- Measure areas
- Form/Pour



WisDOT Bridge Construction Inspection Training - 2020

5 - 43

Concrete Surface Repair - Determine Locations















Overlay - Overview Overview Common Types Milling Determine Locations of Deck Preparation and Full Depth Removal Deck Preparation Type 1 & Deck Preparation Type 2, Full Depth Repair Calibration of Mobile Mixer Dry Run Concrete Placement










Overlay – Milling – Warning don't mill too much! Bump concerns ... No approach work, in other words approaches are not being overlaid 1" of concrete is removed by milling Minimum concrete overlay thickness is 1.5" Do the math = extra 0.5" of concrete at the bridge ends DO NOT MILL 1.5" ACROSS ENTIRE BRIDGE LENGTH TO AVOID BUMP OK TO REMOVE ADDITIONAL DEPTH AT THE BRIDGE ENDS FOR A SHORT DISTANCE (TAPERED UP TO 1" REMOVAL)





Overlay – Milling – Warning don't mill too much! Amount of Preparation Decks Type 1 concerns ... DO NOT MILL DEEPER THAN 1" TO DECREASE AMOUNT OF HANDWORK Milling produces micro-cracking damage in bridge decks. Milling deeper than 1" results in increased levels of damage to the deck in addition to increasing the quantity of overlay concrete.





















































































Polymer Overlay – Overview Bid item: 509.5100.8 • Deck Preparation • Equipment • Application Wildoo' Bright Construction Training - 2020 5-181


























Polymer Overlay - Application • Do not allow application if ... • < 50 degrees • Rain predicted during cure • Concrete age is less than 28 days • Polymer gel time is less than 10 minutes • Moisture > 4.5%



Deck Replacement – Overview Girder Survey – bottom elevation Demolition Girder Survey – top elevation Girder damage reporting/fixing

Deck Replacement – Girder Survey – bottom elevation Prestressed & Steel girders do not always behave as expected after being in service for many years Survey the bottom of the girder at mid-span this will help get a better ride out of the new deck













