

BITUMINOUS MATERIAL FOR TACK COAT

STATION TO STATION	LOCATION	GALLON
0 + 00 TO 16 + 90	S.T.H. 96	340

REMOVING CONCRETE PAVEMENT, BUTT JOINTS

STATION TO STATION	LOCATION	SQ. YD.
16 + 90 - 19 + 48.55	FERRY ST. LT.	173
16 + 90 - 19 + 48.55	FERRY ST. RT.	167
TOTAL		340

BITUMINOUS QUANTITIES

STATION TO STATION	LOCATION	SALVAGED BITUMINOUS PAVEMENT TON	RECYCLED BITUMINOUS SURFACE TON	BITUMINOUS MATERIAL FOR PLANT MIX TON
0 + 00 TO 16 + 90	STH 96	2,742	2,698	89

PAVEMENT MARKING, EPOXY

STATION TO STATION	LOCATION	CENTERLINE LIN. FT.
0 + 00 TO 16 + 90	S.T.H. 96	620

DEPTH OF EXISTING PAVEMENT

STATION	LOCATION	THICKNESS INCH
2 + 64	7' RT.	4.25
5 + 28	7' LT.	4.38
7 + 92	14' RT.	4.0
11 + 09	15' LT.	4.25
14 + 26	4' RT.	4.25
18 + 48	8' LT.	4.25
21 + 12	13' RT.	4.13
22 + 70	5' RT.	5.0
23 + 76	13' LT.	5.25
23 + 81	9' LT.	4.75

SAWING EXISTING PAVEMENT

LOCATION	LIN. FT.
S.T.H. 96	80
SECOND STREET	24
FIRST STREET	24
OAK STREET	17
POPLAR STREET	26
GREEN STREET	26
BROADWAY STREET	86
TOTAL	283