



# APPLICATION/PERMIT TO CONSTRUCT, OPERATE AND MAINTAIN UTILITY FACILITIES ON HIGHWAY RIGHT-OF-WAY

Wisconsin Department of Transportation  
DT1553 7/2017 s. 66.0831, 84.08, 85.15, 86.07(2)(a), 86.16, 182.017 and other applicable Wis. Stats.

1. Applicant (Utility facility owner) Name and Address <b>WE ENERGIES</b> P.O. BOX 1699 APPLETON, WI 54912-1699		2. Work Start Date <b>5/4/2020</b>	3. Work Finish Date★ <b>10/29/2021</b>	6. Location Description (¼ section, section, town, range; provide plat and/or location maps) <b>SW1/4 Sec.04 T22N R16E</b>	
9. Facility Type (Check all that apply) and Description (Size, material, voltage, pressure, # fibers, etc.) <input type="checkbox"/> Comm: _____ <input type="checkbox"/> Electric: _____ <input checked="" type="checkbox"/> Gas/Oil: <b>50psig/60psig</b> <input type="checkbox"/> Water: _____ <input type="checkbox"/> Sewer: _____ <input type="checkbox"/> Casing: _____ <input type="checkbox"/> Conduit: _____ <input type="checkbox"/> : _____ <input type="checkbox"/> Transmission <input type="checkbox"/> Service <input checked="" type="checkbox"/> Distribution <input checked="" type="checkbox"/> Service ( <b>ESCP</b> )		4. Is the work due to a WisDOT highway project? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		7. Work Location (List all that apply) Town: <b>Ellington/Greenville</b> Village: _____ City: _____ County: <b>Outagamie</b>	
10. Facility Orientation (Check all that apply) <input checked="" type="checkbox"/> Underground <input type="checkbox"/> Overhead <input checked="" type="checkbox"/> Crossing <input checked="" type="checkbox"/> Parallel <input type="checkbox"/> OSOW high clearance route <input type="checkbox"/> Structure attachment <input type="checkbox"/> Scenic easement (Off right-of-way)		12. Proposed Work Methods (Check all that apply) <input checked="" type="checkbox"/> Trench <input type="checkbox"/> Plow <input type="checkbox"/> Place fill <input type="checkbox"/> Rock blasting <input type="checkbox"/> Place cable <input type="checkbox"/> Open cut in conduit pavement <input type="checkbox"/> Hand/mechanical excavation Bore: <input type="checkbox"/> Hydraulic (Auger/Jack/Tunnel) <input type="checkbox"/> Pneumatic (Mole) <input checked="" type="checkbox"/> Directional 1 (Manually tracked) <input type="checkbox"/> Directional 2 (Computer tracked) <input type="checkbox"/> Unknown (At this time) Install or attach to poles/towers: <input type="checkbox"/> New <input type="checkbox"/> Existing <input type="checkbox"/> Guys (~Diameter) (Name of existing owner) (Provide details for all guy-wires on plan sheets) Pothole (Subsurface excavation): <input type="checkbox"/> Air <input checked="" type="checkbox"/> Water Tree/vegetation control: <input type="checkbox"/> Trim (Prune) <input type="checkbox"/> Plant <input type="checkbox"/> Remove (Cut) <input type="checkbox"/> Mow <input type="checkbox"/> Chemically treat		13. Work Zone Description (Check all that apply). (Provide relevant diagram(s) with application.) <input type="checkbox"/> Not applicable <input type="checkbox"/> Full road closure: detour <input type="checkbox"/> Full road closure: temporary <input type="checkbox"/> Lane closure: without flagging <input type="checkbox"/> Lane closure: with flagging <input checked="" type="checkbox"/> Lane encroachment (2 feet or less) <input type="checkbox"/> Intersection/roundabout <input checked="" type="checkbox"/> Shoulder/parking lane closure <input type="checkbox"/> Railroad crossing Freeway/expressway location <input type="checkbox"/> Off shoulder: < 30' off white line <input type="checkbox"/> Off shoulder: ≥ 30' off white line <input type="checkbox"/> Near right-of-way line or fence Non-freeway/expressway location <input type="checkbox"/> Off shoulder: < 15' off white line <input type="checkbox"/> Off shoulder: ≥ 15' off white line <input type="checkbox"/> Back of curb: < 2' behind <input type="checkbox"/> Back of curb: ≥ 2' behind	
11. Work Types (Check all that apply) <input type="checkbox"/> New facility <input type="checkbox"/> Remove <input type="checkbox"/> Joint install <input type="checkbox"/> Maintenance <input checked="" type="checkbox"/> Improve or repair existing <input checked="" type="checkbox"/> Discontinue, left in place		14. Is the facility near a survey monument? <b>HMM 09-15-35</b> If yes, call (866) 568-2852 or email <a href="mailto:geodetic@dot.wi.gov">geodetic@dot.wi.gov</a> . <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		15. Will appurtenances be installed with the facility? If yes, provide a description and/or specification for each item. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
		16. Trans 401 project designation? If Major, provide a formal erosion control plan. <b>HMM 09-15-55</b> <input type="checkbox"/> Major <input checked="" type="checkbox"/> Minor		17. Are any environmental approvals, certifications or permits required from other regulatory agencies, including tribal governments? If yes, provide a copy of each item. If no, provide proof of other agency coordination as needed. <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

★ Includes permanent restoration. If the permitted work has not started by the "Work Finish Date", this permit is null and void. If the permitted work has started, but has not been completed by the "Work Finish Date", the work shall not be completed unless authorized through an approved written time extension or a subsequent permit. **ANY PERMIT ISSUED IS REVOCABLE.**

18. Utility Person Responsible for Construction <b>Greg Smedema- Operation Supervisor</b>	Telephone Number <b>920-380-3569</b>	<b>It is understood and agreed that WisDOT approval is subject to the applicant's full compliance with all pertinent statutes, as well as any regulations and rules of other jurisdictional agencies (which may be more restrictive), any supplemental permit provisions, and WisDOT's <u>Utility Accommodation Policy</u>, current edition.</b>
19. Utility or Project 24/7 Emergency Contact <b>We energies Emergency Hotline</b>	Telephone Number <b>800-261-5325</b>	
20. Provide company name and address of utility authorized representative if not employed by the applicant. <b>Cody Beckman</b>		<b>3/6/2020</b> (Utility Authorized Representative Signature – If filled via computer, brush script font) (Date) <b>cody.beckman@we-energies.com</b> Designer (Telephone Number) (Email Address)
21. Provide additional work details, if needed (use back page or include separate pages) <b>It is We energies intent to perform all of the gas facility relocations in the year 2020. There are four total work requests three under one permit one under a separate permit. See back page for work request list and areas.</b>		<b>This permit does not transfer any land, or give, grant or convey any land right, right in land, or easement in WisDOT right-of-way. It is not assignable or transferrable. If a utility facility changes ownership, this permit terminates. The new owner must obtain a permit in order to operate and maintain the facility in WisDOT right-of-way.</b>

## For Wisconsin Department of Transportation Use Only

<input checked="" type="checkbox"/> <b>UTILITY SHALL NOTIFY WisDOT REPRESENTATIVE LISTED BELOW 3 DAYS BEFORE STARTING ANY WORK:</b> Region contact, office address, telephone number and email address <b>Linda Skaleski</b> WisDOT, Northeast Region 944 Vanderperren Way Green Bay, WI 54304 920-492-4166 <a href="mailto:dotdtsdneutilitycoordination@dot.wi.gov">dotdtsdneutilitycoordination@dot.wi.gov</a>	<input checked="" type="checkbox"/> <b>Review All Supplemental Permit Provisions</b> <input checked="" type="checkbox"/> <b>Revisions Made to Drawings or Other Pages</b> <input checked="" type="checkbox"/> Lane Closure System notification required <b>HMM 09-15-60</b> <input type="checkbox"/> Insurance or performance bond required <input type="checkbox"/> Joint installation: See permit(s) # _____ <input type="checkbox"/> Private utility (Non-public ownership and/or use) <input type="checkbox"/> Expedited Service Connection Permit <input type="checkbox"/> This permit voids & supersedes # _____ issued: _____ <input type="checkbox"/>	Application Received <b>3/26/2020</b> Application Completed  Permit Issued  Permit Extended  Permit Amended  Permit Number <b>2020132</b>
<b>1146-75-72</b>		

# APPLICATION/PERMIT TO CONSTRUCT, OPERATE AND MAINTAIN UTILITY FACILITIES ON HIGHWAY RIGHT-OF-WAY *(continued)*

Wisconsin Department of Transportation DT1553

(WisDOT Improvement Project ID Numbers, if applicable)

(WisDOT Authorized Representative Signature – If filled via computer, Brush Script font)

Use this section to provide information that does not fit on front page

This work for State ID 1146-75-72 is to be performed under work requests:

4459694 for STH 15 from Greendale Road to Manley Road

4459680 for the intersection of North Road and STH 15

4459720 for STH 15 from Julius Drive to Lily of the Valley Road

## INDEMNIFICATION

This Applicant shall save and hold the State, its officers, employees, agents, and all private and governmental contractors and subcontractors with the State under Chapter 84 Wisconsin Statutes harmless, as allowed by Wisconsin law, from actions of any nature whatsoever (including any by Applicant itself) which arise out of, or are connected with, or are claimed to arise out of or be connected with any of the work done by the Applicant, or the construction or maintenance of facilities by the Applicant, pursuant to this permit or any other permit issued by the State for location of property, lines or facilities on highway right-of-way, (1) while the Applicant is performing its work, or (2) while any of the Applicant's property, equipment, or personnel, are in or about such place or the vicinity thereof, or (3) while any property constructed, placed or operated by or on behalf of Applicant remains on the State's property or right-of-way pursuant to this permit or any other permit issued by the State for location of property, lines or facilities on highway right-of-way; including without limiting the generality of the foregoing, all liability, damages, loss expense, claims, demands and actions on account of personal injury, death or property loss to the State, its officers, employees, agents, contractors, subcontractors or frequenters; to the Applicant, its employees, agents, contractors, subcontractors, or frequenters; or to any other persons, whether based upon, or claimed to be based upon, statutory (including, without limiting the generality of the foregoing, worker's compensation), contractual, tort, or whether or not caused or claimed to have been caused by active or inactive negligence or other breach of duty by the State, its officers, employees, agents, contractors, subcontractors or frequenters; Applicant, its employees, agents, contractors, subcontractors or frequenters; or any other person.

Without limiting the generality of the foregoing, the liability, damage, loss, expense, claims, demands and actions indemnified against shall include all liability, damage, loss, expense, claims, demands and actions for damage to any property, lines or facilities placed by or on behalf of the Applicant pursuant to this permit or any other permit issued by the State for location of property, lines or facilities on highway right-of-way in the past or present, or that are located on any highway or State property or right-of-way with or without a permit issued by the State, for any loss of data, information, or material; for trademark, copyright or patent infringement; for unfair competition or infringement of personal or property rights of any kind whatever. The Applicant shall at its own expense investigate all such claims and demands, attend to their settlement or other disposition, defend all actions based thereon and pay all charges of attorneys and all other costs and expenses of any kind arising from any such liability, damage, loss, claims, demands and actions.

Any transfer, whether voluntary or involuntary, of ownership or control of any property constructed, placed or operated by or on behalf of the Applicant that remains on the State's property or right-of-way pursuant to this permit shall not release Applicant from any of the indemnification requirements of this permit, unless the State is notified of such transfer in writing. Any acceptance by any other person or entity, whether voluntary or involuntary, of ownership or control of any property constructed, placed or operated by or on behalf of the Applicant that remains on the State's property or right-of-way pursuant to this permit, shall include acceptance of all of the indemnification requirements of this permit by the other person or entity receiving ownership or control.



## STANDARD SUPPLEMENTAL PERMIT PROVISIONS

For Wisconsin Department of Transportation Utility Facility Permits

### Acronyms used in this document:

- BMPs: Best Management Practices
- R/W: Right-of-Way
- UAP: Utility Accommodation Policy
- HMM: Highway Maintenance Manual
- WisDOT: Wisconsin Department of Transportation

### 1. GENERAL WORK REQUIREMENTS

- As required by Wisconsin Statute 182.0175, when filing your Diggers Hotline request ensure that this WisDOT Permit Number is in the Remarks Section of the Diggers Hotline Ticket.
- The Permittee shall bore under all driveways, private entrances, wetlands, culverts, and all roadways.
- The Permittee is responsible for obtaining any permits from the Department of Natural Resources, or any other agency that may have an interest in the area impacted by the construction of the utility facility.

2. **WORK DUE TO A WISDOT HIGHWAY PROJECT.** This approved permit constitutes acceptance that the work in this permit is compatible with permit requirements. This approved permit is NOT a Work Plan Approval/Start Work Notice as required by Trans 200.05(07). This approved permit is NOT a Work Plan Approval/Start Work Notice for a non-Trans 220 project. This approved permit does NOT approve or authorize an agreement between WisDOT and the Permittee for compensable work due to a WisDOT highway project.

3. **PERMIT TERM.** For as long as the Permittee continues to own, operate and maintain this utility facility within WisDOT R/W in accordance with the terms of its permit and WisDOT's UAP, this permit shall be valid.

4. **REVOCATION BY WISDOT.** WisDOT may revoke this permit if its own use of the R/W would be facilitated by the full or partial relocation of the Permittee utility facility, and shall provide the Permittee with written notice prior to revocation. At which time WisDOT shall work with the Permittee to find a suitable replacement area on R/W near the terminated location if possible. WisDOT shall not compensate the Permittee to move its utility facility in keeping with WisDOT's policy on compensable / non-compensable utility facility moves.

5. **TERMINATION BY PERMITTEE.** The Permittee may terminate this permit upon 60 days written notice to WisDOT. Upon such termination, the Permittee shall either remove its communication cable facility from the R/W, or abandon it in-place provided it does not constitute an environmental hazard.

6. **HOLIDAY WORK RESTRICTIONS for 2020.** The Permittee shall not work on January 1, May 25, July 3 & 4, September 7, and November 26, and December 25.

7. **WORK-TIME RESTRICTIONS.** Weekday work is from sunrise to sunset. Weekend work may be allowed upon prior approval from WisDOT. No work shall take place during nighttime hours unless authorized by WisDOT.

8. **TRAFFIC CONTROL.** All work zone traffic control will be in accordance with the Wisconsin Manual on Uniform Traffic Control Devices. Additional guidance is available from WisDOT through a booklet entitled, *Work Zone Safety, Guidelines for Construction, Maintenance, and Utility Operations* or from HMM 09-15-60.

9. **WORK AREA PROTECTION DURING NON-WORK TIMES.** The Permittee may store vehicles, equipment, or materials on the non-freeway R/W provided they are placed as close to the non-freeway R/W line as possible, but no less than 30 feet from the edge of the nearest travel lane. If vehicles, equipment, or materials must be parked or stored within an area that is less than 30 feet from the edge of the nearest travel lanes, appropriate temporary concrete or water-filled barriers, signing, and devices shall be utilized. The Permittee shall ensure that any excavations left open during non-work times are well marked and secured from public intrusion.

The primary objective will be maintenance of a safe traffic and working environment. No operation shall to any extent pose any hazard neither to, nor in any manner influence traffic at any time.

All vehicles used to conduct the work operations will be equipped with conspicuously visible roof-mounted revolving or strobe lights. These lights shall be in operation just prior to and during the time the work operations are being conducted. Hazard warning lights on the vehicles must also be operating.

10. **WORK RESTRICTIONS.** For the purposes of placement of these facilities, as stated with this permit request, the State security fence shall not be opened or damaged.

11. **CLEAR ZONE / DRAINAGE INTERFERENCE.** No topsoil or other excavated piles of soil shall be deposited in any manner that interferes with the clear zone or regular drainage patterns within the highway.

As much as possible, all equipment, operations, and spoil material should be situated or accomplished off of the highway.

12. **EROSION CONTROL.** The Permittee shall use the appropriate erosion control BMPs to contain soil directly at the site to prevent disturbed soil from getting into nearby waterways and wetlands. All appropriate erosion control devices shall be in place **prior to starting construction activities**. Temporary seeding shall be used as necessary after rough grading and before completion of the project. The Permittee shall ensure that erosion control BMPs used to protect restored areas remain in place until replacement vegetation achieves sustained growth.

The Permittee shall take all precautions necessary to prevent mud, dirt, or other debris from being deposited onto the shoulder or pavement of all access roads or highways. Any materials deposited on the shoulder or pavement shall be removed immediately. Ruts may remain as is if the Permittee is accessing the R/W from private property, but appropriate erosion control BMPs shall be used to contain disturbed soil at the site.

13. **R/W RESTORATION.** Upon completion of the project a variation of erosion control measures will be required to restore the area that has been disturbed allowing it to return to the manner it was in previous to the construction. All disturbed sites will require a seed mixture that includes a quick sprouting variety with fertilizer and mulch. Other possibilities that may have to be considered are Geotextile fabric, e-mat, and stone ditch checks.

The Permittee is responsible to assure that erosion control measures used to protect restored areas remain in place until replacement vegetation achieves sustained growth.

The basic drainage pattern of the highway shall remain undisturbed by the permitted work. Upon project completion, all spoils, debris, refuse, and waste resulting from the permitted work shall be removed from the work site. Should future maintenance work on the Permittee's utility facility result in the disturbance of the existing R/W, the Permittee shall restore the R/W to its original condition as soon as possible.

Any works or operations not in full compliance herewith shall justify an order by any inspecting officer of WisDOT to cease all further progress on the work, and to accomplish all restorations of disturbed areas, including full restorations of the pavement

Upon completion of the work, all disturbed areas shall be restored according to requirements stated in the Utility Accommodation Policy, HMM 09-15-65, and in a manner satisfactory to WisDOT

14. **NOTIFICATIONS / CONTACTS.** Notify Northeast Region permit coordinator/field inspector, by phone or email, three days prior to the start of construction. Notify Diggers' Hotline 800/242-8511 at least three working days prior to the start of any excavation. It is the obligation of the permittee to determine the location of, and avoid any damage to, the pre-existing lines and facilities of others.

15. **TREES.** Prevent the spread of oak wilt by treating all cut surfaces and abrasions sustained **between April 1 and September 30** by healthy oak trees and saplings with a thorough application of tree paint immediately upon discovering a wound. Between these dates, also paint the cut surfaces of the stumps of all healthy oak trees and saplings immediately after cutting, whether remaining in place or grubbed.

This permit approves the installation of facilities as shown on the diagram provided. If the above assigned position is not feasible, an alternate location of facilities shall be approved prior to installing the facilities by contacting the permit coordinator approving the permit. If the facility is later discovered to be at a location other than that designated by the permit you may be required to relocate the facility at your expense.

*This permit is subject to the attached drawings, these supplemental provisions, and WisDOT's Utility Accommodation Policy. New supplemental provisions may be added, or the existing ones deleted or amended in the future as different issues arise during the installation, operation and maintenance of the permittee's facilities.*



### 3.3 Subsurface Utility Excavation (SUE)

WisDOT allows SUE as a necessary tool for accurate vertical location of utilities. Two methods are available: air (vacuum) and water (jetting). Within the pavement structure (lanes, shoulders, curb & gutter), use **air** SUE rather than water. Water may be allowed if the air method cannot penetrate frozen and/or densely compacted soil. Air or water SUE may be used in other R/W areas beyond the pavement structure. Table 1 below outlines the basic steps for SUE work.

Consult WisDOT prior to using water SUE. If WisDOT agrees to its use, check the SUE water jetting box on the permit application and show hole locations on a drawing. Submit **before** pavement condition pictures at each SUE hole with the permit application, and provide pictures of the fully restored holes **after** the job is completed. This provides WisDOT and the utility with documentation that the restoration was finished. Monitor the holes over the next few years, or until WisDOT is satisfied that no additional settling is occurring or until a new resurfacing or pavement replacement project is done. A utility must repair any SUE hole settlement (Figure 2).

Numerous pictures are not needed. But pictures should be taken from the same angle and distance for the before and after conditions, and be far enough away to provide some sort of perspective for the location (i.e., not right next to the hole). Take pictures with a digital camera so they can be sent electronically, or if taken with a conventional camera, scan and send to WisDOT in a .jpg or .pdf format. No pictures are required for air SUE.

Use round cores for SUE holes within the pavement structure. Round cores are preferred since they prevent stress cracks due to elimination of corners. The maximum size of a SUE hole is 12" in diameter in the wheel paths and a maximum of 16" in diameter outside the wheel paths. Beyond the pavement structure, the hole size may be larger (18"-24") and square upon WisDOT approval.

**Table 1: Basic SUE Steps**

- |  |
|--|
| <ol style="list-style-type: none"> <li>1) Pavement is saw cut full depth, with a bit ranging from 12" to 16" in diameter; resulting in a "core".</li> <li>2) The core is removed and saved for reuse (if structurally sound).</li> <li>3) A protective steel ring is placed to protect the edge of the opening from damage.</li> <li>4) Vacuum equipment is used to excavate compacted material from bottom of base course down to beneath utility facility.</li> <li>5) Utility work is performed (e.g., leak repair, service connection).</li> <li>6) Utility facility is protected with fine material.</li> <li>7) Self-mixing flowable fill material is placed from top of fine material to bottom of base course (fill is designed to be traffic-bearing in 90 minutes).</li> <li>8) Non-shrink grout is placed (grout is designed to be traffic-bearing in about 90 minutes).</li> <li>9) The removed core (or a generic equivalent replacement core) is placed in the remaining opening (original alignment and orientation is maintained if removed core is used) forcing the grout to the surface to fill the annular space and core extraction hole.</li> <li>10) The restored opening is sealed.</li> </ol> |
|--|




**Figure 2: Improper SUE Restoration**

### 3.4 Non-Metallic Lines


Any non metallic pipe, cable or other kind of utility line which lacks a continuous and integral metallic component capable of detection by locating instruments shall be accompanied in its location by a continuous detectable metallic tracer wire or metallic tape.

### 3.5 Casing


Where crossings by underground lines are encased in protective conduit or duct, the encasement shall extend at least two feet beyond the toe of slope or three feet beyond the ditch line. On curbed sections, it shall extend at least outside the outer curbs.



Map data ©2020 1000 ft



Map data ©2020 500 ft







GAS WORK REQUEST

4459694

N2598 - SHOP

BANKER, MARK L

BECKMAN  
PLAT OF SURVEY

PIN 080077600  
ARNOLD J. WEYERS & MARY S. WEYERS  
DOC. 972975

LATENT AMBIGUITY  
IN DEED



TEM NO.	DESCRIPTION
1	TEE, PE MED VOLUME 3" X 2"
2	CLAMP, 3" IPS SUPPORT
3	REDUCER, 4IPS BUTT X 3IPS BUTT
4	ELL, 4" IPS 90 DEG. BUTT FUSE
5	CAP, 3" IPS BUTT FUSION END
6	TEE, PE MED VOLUME 3" X 2"
7	ELL, 4" IPS 90 DEG. BUTT FUSE
8	POST, TYPE #3 CONTROL PT #204815
9	ANODE, 1LB. MAGNESIUM (2)
10	SQUEEZE POINT

12" WATTLES MUST BE PLACED  
BETWEEN THE EXCAVATION  
AND THE WATERWAY

SEE DETAIL  
THIS PAGE

PROPOSED 4" PE 8'

2" BYPASS

RETIRE TP 129797  
REMOVE TEST BOX  
AND ALL WIRES.

CAUTION

WETLAND BOUNDARY


PROPOSED 4" PE 46'

PROPOSED 4" PE BORE 441'

WETLAND BOUNDARY

NOTE: LABEL THE CONTROL POST AT POINT 8 #204815  
\*BRING NEW AND EXISTING PE TRACER WIRES INTO  
THE TEST POST ALONG WITH 2X1# ANODE WIRES.  
\*ATTACH THE ANODE WIRE TO THE EXISTING PE TRACER WIRE,  
ATTACH AN ANODE WIRE TO THE NEW PE TRACER WIRE.  
\*KEEP THE NEW PE TRACER WIRE SEPARATED FROM THE  
EXISTING PE TRACER WIRE.  
\*LABEL EACH WIRE WITH MATERIAL AND DIRECTION.

DETAIL



PIN 080077800  
PATRICK & DAWN MCNICHOLS  
DOC. 1981571  
ZEMPLE, DENNIS H & LOIS

PIN 080077802  
WAYNE V. GERDTS & ZELLA J. GERDTS  
DOC. 1583255  
LC DOC. 1850354  
GERDTS, WAYNE V & ZELLA J

FRAC.  
SW-SW  
SEC. 31, T22N, R16E

N2587 - SHOP  
T&R  
5/8" PE  
878722

SCALE 1" = 50'

SHEET 2 OF 13

SHEET 3






GAS WORK REQUEST  
**4459694**

LEMKE, ALVIN H JR



ITEM NO.	DESCRIPTION
1	ELL, 4" IPS 45 DEG. BUTT FUSE
2	ELL, 4" IPS 45 DEG. BUTT FUSE



PIN 080077900  
DON E. PARKER & MARGARET A. PARKER  
DOC. 946939

**SHEET 4**

**N2569  
T&R  
1" PE  
3473740**  
  
PIN 080078500  
DOUGLAS J. SCHWOBE & BRENDA K. SCHWOBE  
DOC. 1368952

**N2561  
T&R  
5/8" PE  
902844**

PIN 080078600  
KENNETH R. WYNBOOM & THOMAS L. WYNBOOM  
DOC. 1978380






GAS WORK REQUEST

4459694

↑ SHEET 3 ↑



PIN 080078500  
DOUGLAS J. SCHWOBE & BRENDA K. SCHWOBE  
DOC. 1368952

PARKER, DON E  
LATENT  
AMBIGUITY  
IN DEED

PIN 080077900  
DON E. PARKER & MARGARET A. PARKER  
DOC. 946939

PARKER, DON E & MARGARET

YOUNG, RUTH M

ZEMPLE, DENNIS H & LOIS

YOUNG, RUTH M

TOWN



GAS WORK REQUEST

4459694

PROPOSED MAIN FROM STATION 22+43  
EAST TO 134' PAST STATION 29+00 IS TO  
BE INSTALLED AT A DEPTH OF 5' FROM  
EXISTING GRADE.


PIN 080078200  
JOAN M. JOSSART SURVIVOR'S TRUST U/A/D MAY 5, 1988  
DOC. 1749135

STATE OF WISCONSIN

DEPARTMENT OF

TRANSPORTATION

PIN 080079000  
RUTH M. YOUNG  
DOC. 1784603



ITEM NO.	DESCRIPTION
1	ANODE, 1LB. MAGNESIUM
2	POST, 78" TYPE #3 LOCATE POINT
3	ELL, 4" IPS 90 DEG. BUTT FUSE
4	POST, ROUND GAS PIPE MARKER 78"
5	ELL, 4" IPS 45 DEG. BUTT FUSE

YOUNG, RUTH M

PIN 080078400  
RUTH M. YOUNG  
DOC. 1784603

LATENT AMBIGUITY  
IN DEED

BLINK, JENNIFER L

WALSVIK, PENNY A

PULS, GAIL M

N2535  
N2535-X  
RPL  
5/8" PE  
897638

PIN 080079300  
GAIL M. PULS, PENNY A. WALSVIK & JENNIFER L. BLINK  
DOC. 1697622

STILES, GARY & JANE

HOIER  
PLAT OF SURV

PIN 080079200  
GARY STILES & JAN  
DOC. 719261



GAS WORK REQUEST

4459694

PROPOSED MAIN FROM STATION 22+43  
EAST TO 134' PAST STATION 29+00 IS TO  
BE INSTALLED AT A DEPTH OF 5' FROM  
EXISTING GRADE



SHEET 5

SHEET 7

N2531  
RPL  
5/8" PE  
896880

N2527

PIN 080079400  
REGINA HOIER,  
DOC. 1903245

HOIER, REGINA

PIN 080079100  
RJR VENTURES, LLC  
DOC. 1928357  
RJR VENTURES LLC

N2519  
RPL  
5/8" PE  
896920

N2519- TAV  
RPL  
3/4" PE  
896926

PIN 080079500  
RJR VENTURES, LLC  
DOC. 1928357

RJR VENTURES LLC

WATTERS, DAVID  
PIN 080078900  
DAVID WATTERS  
DOC. 1748718

ELLINGTON

STH 15

BILLBOARD






GAS WORK REQUEST

4459694

ITEM NO.	DESCRIPTION
1	POST, ROUND GAS PIPE MARKER 78"



SHEET 6

ALL WORLD FORD  
(STP PROPERTIES LLC)

N2484  
T&R  
2" PE  
4276456

W8171

SHEET 8

SCALE 1" = 50' SHEET 7 OF 13



TEM NO.	DESCRIPTION
1	ELL, 4" IPS 90 DEG. BUTT FUSION
2	POST, ROUND GAS PIPE MARKER 78"
3	ELL, 4" IPS 45 DEG. BUTT FUSION
4	POST, 78" TYPE #3 LOCATE POINT
5	ELL, 4" IPS 90 DEG. BUTT FUSION
6	POST, ROUND GAS PIPE MARKER 78"
7	ELL, 4" IPS 45 DEG. BUTT FUSION
8	ANODE, 1LB. MAGNESIUM

PIN 110019606  
PATRICIA H. JACK  
DOC. 1966221

CAUTION

12" SEDIMENT LOGS

EROSION MAT IN SWALE

SCALE 1" = 50'

SHEET 8 OF 13





GAS WORK REQUEST

4459694

SHEET 10



SHEET 8

ITEM NO.	DESCRIPTION
1	ELL, 4" IPS 90 DEG. BUTT FUSION
2	POST, ROUND GAS PIPE MARKER 78"
3	ELL, 4" IPS 90 DEG. BUTT FUSION
4	POST, ROUND GAS PIPE MARKER 78"
5	TEE, 4" IPS BUTT FUSION
6	POST, 78" TYPE #3 LOCATE POINT
7	VALVE, 4" IPS PE V84585 CONVENIENT
8	VALVE, 4" IPS PE V84586 CONVENIENT
9	ELL, 4" IPS 45 DEG. BUTT FUSION
10	POST, ROUND GAS PIPE MARKER 78"
11	POST, ROUND GAS PIPE MARKER 78"
12	ELL, 4" IPS 90 DEG. BUTT FUSION
13	ELL, 4" IPS 45 DEG. BUTT FUSION


**\*ABANDON AND REMOVE THE FACILITIES FOR CHECK POINTS 123392 AND 145699.**  
**\*FOR THE NEW TYPE #3 LOCATE POINT - LABEL AND BRING UP A WIRE FROM THE NORTH, SOUTH, WEST AND ANODE.**  
**\*BOND ALL WIRES.**

14	ANODE, 1LB. MAGNESIUM


SHEET 11

SCALE 1" = 50'

SHEET 9 OF 13








**NOTE:**  
\*INSTALL A TYPE 3 LOCATE POST.  
\*BRING THE NEW AND EXISTING PE TRACER WIRE ALONG WITH  
A 1# ANODE WIRE INTO THE LOCATE POST.  
\*ATTACH THE NEW PE TRACER WIRE TO THE EXISTING PE TRACER  
WIRE AND THE ANODE WIRE INTO THE LOCATE POST.  
\*LABEL EACH WIRE WITH MATERIAL AND DIRECTION.

ITEM NO.	DESCRIPTION
1	ELL, 4" IPS 90 DEG. BUTT FUSION
2	ELL, 4" IPS 45 DEG. BUTT FUSION
3	CLAMP, 4" IPS SUPPORT
4	COUPLING, 4" IPS ELECTROFUSION
5	CLAMP, 4" IPS SUPPORT
6	POST, 78" TYPE #3 LOCATE POINT
7	CAP, 4" IPS BUTT FUSION END
8	ANODE, 1LB. MAGNESIUM
9	TEE, PE HIGH VOLUME 4" X 2"
10	TEE, PE HIGH VOLUME 4" X 2"
11	SQUEEZE POINT

**NOTE: ALL 4" PE MAIN FORM STATION 14MAN+00  
NORTH TO STATION 14MAN+93 TO BE 7' DEEP.  
MAIN IS TO RISR IN ELEVATION TO TIE IN POINT.**





GAS WORK REQUEST

4459694

↑ SHEET 9 ↑



15' DRIVEWAY EASEMENT DOC. 1967329

N2407  
RPL  
3/4" PE  
918862

PIN 110019603  
DEBORAH J. JACK  
DOC. 1329583

JACK, DEBORAH J  
LOT 3  
CSM 3444  
V18/P3444  
DOC. 1318485

SEPV  
SEPTIC  
SEPV



ENV  
8, 27

PIN 110017100  
JAMES D. DEMPSEY & JEANNE E. DEMPSEY  
DOC. 1033444

DEMPSEY, JAMES D & JEANNE E

PLACE 2 12" SEDIMENT LOGS  
WITH 75' SPACING IN DITCH LINE

TEM NO.	DESCRIPTION
1	ELL, 4" IPS 90 DEG. BUTT FUSION
2	ELL, 4" IPS 90 DEG. BUTT FUSION
3	CLAMP, 4" IPS SUPPORT
4	REDUCER, 4IPS BUTT X 3IPS BUTT
5	CLAMP, 3" IPS SUPPORT
6	CAP, 3" IPS BUTT FUSION END
7	ANODE, 1LB. MAGNESIUM
8	TEE, PE MED VOLUME 3" X 2"
9	TEE, PE MED VOLUME 3" X 2"
10	SQUEEZE POINT

PIN 110019901  
GWEN A. BERGSBAKEN  
DOC. 1792586

LOEWENHAGEN, GWEN A

N2395

LOT 3  
CSM 5781  
V33/P5781  
DOC. 1787532

KAVANAUGH, DENNIS

THORPE, CYNTHIA

PIN 110017301  
DENNIS KAVANAUGH & CYNTHIA THORPE  
DOC. 1493997

2" BYPASS REQUIRED

PROPOSED 4" PE 25'  
PROPOSED 4" PE 26'  
12" SEDIMENT LOGS

NOTE: ATTACH THE NEW PE TRACER WIRE TO  
THE EXISTING TRACER WIRE WITH A 1# ANODE

RETIRE CIA 514203 AND  
ADD TO CIA 5666347

SCALE 1" = NA'

SHEET 11 OF 13

LOT 2

CSM 5781

V33/P5781

DOC. 1787532

PIN 110019902  
GARY T. HART & MARY L. HART  
DOC. 1792585



4459694

N2592 STH 15 SERVICE CROSSING APPROX. STATION 253MNE+50 SHEET 2

STATION	253+50	253+50	253+50	253+50	253+50	253+50	253+50	253+50	253+50	253+50
OFFSET	RT 115'	RT 90'	RT 80'	RT 77'	RT 71'	RT 67'	RT 58'	0	LT 78'	LT 95'
TOP OF MAIN ELEVATION	813	811	808	807	807	807	807	807	809	812
APPROX DEPTH FROM EXISTING	3'	3'	5'	5.5'	5.5'	5.5'	3'	8.5'	3'	3'
LOCATION	TEE									
NOTES	SOUTH	SLOPE	E-COMM	P-DITCH	E-GAS	P-DITCH	E-DITCH	E-RL	E-FIBER	NORTH
	ROW	INTERCEPT		S-EDGE		S-EDGE		MNE		ROW

N2588 STH 15 SERVICE CROSSING APPROX. STATION 254MNE+50 SHEET 2

STATION	254+50	254+50	254+50	254+50	254+50	254+50	254+50	254+50	254+50	
OFFSET	RT 115'	RT 92'	RT 77'	RT 73'	RT 65'	RT 56'	0	LT 33'	LT 50'	
TOP OF MAIN ELEVATION	815	814	809	809	810	810	810	812	814	
APPROX DEPTH FROM EXISTING	3'	3'	7'	7'	4'	2.5'	8'	3'	3'	
LOCATION	TEE									
NOTES	SOUTH	SLOPE	P-DITCH	E-GAS	P-DITCH	E-DITCH	E-RL	E-DITCH	E-ROW	
	ROW	INTERCEPT	S-EDGE		N-EDGE	SOUTH	MNE	NORTH	NORTH	

N2576 STH 15 SERVICE CROSSING APPROX STATION 258MNE+30 SHEET 3

STATION	258+30	258+30	258+30	258+30	258+30	258+30	258+30	258+30	258+30
OFFSET	RT 115'	RT 84'	RT 75'	RT 71'	RT 69'	RT 47'	0	LT 34'	LT 60'
TOP OF MAIN ELEVATION	829	819	819	819	819	818	820	822	832
APPROX DEPTH FROM EXISTING	3'	10'	9'	9'	8.5'	4'	8'	3.5'	3'
LOCATION	TEE								
NOTES	SOUTH	P-DITCH	E-COMM	P-DITCH		E-DITCH	E-RL	E-DITCH	E-ROW
	ROW	S-EDGE		N-EDGE		SOUTH	MNE	NORTH	NORTH

OLDE STH 15 (NEW ROAD) BORE 302' CROSSING APPROX. STATION 272MNE+00 SHEET 5

STATION	272+00	272+00	272+00	272+00	272+00	272+00	272+00	
OFFSET	RT 90'	RT 78'	RT 68'	RT46'	0	LT 56'	LT 212'	
TOP OF MAIN ELEVATION	850	850	850	843	844	844	847	
APPROX DEPTH FROM EXISTING	4'	3'	3'	9'	9'	7'	3'	
LOCATION	ELL		RL		RL		ELL	
NOTES	P-SOUTH	S-EDGE	N-EDGE	P-DITCH	P-CL	P-NORTH	P-NORTH	
	ROW	TRAIL	TRAIL		MNE	DITCH	ROW	

OLDE STH 15 (NEW ROAD) 326' CROSSING AT STATION 295MNE+50 SHEET 8

STATION	295+50	295+50	295+50	295+50	295+50	295+50	295+50	295+50	295+50	295+50
OFFSET	LT 110'	LT 62'	LT 22'	0	RT 47'	RT 81'	RT 105'	RT 118'	RT 159'	RT 216'
TOP OF MAIN ELEVATION	888	889	900	904	904	904	904	904	904	918
APPROX DEPTH FROM EXISTING	4'	4'	4.5'	3.5'	7.5'	4'	15'	16'	4'	4
LOCATION	ELL									ELL
NOTES	P-WEST	P-DITCH	CL	P-RL	P-RL	P-DITCH	P-RL	P-RL	TEMP DITCH	P-ROW
	ROW	WEST	MNW	MNE	MUT	EAST	TA	TB	EAST	EAST

MANLEY ROAD 171' CROSSING - APPROXIMATE STATIOIN 36+70 SHEET 9

STATION	36+70	36+70	36+70	36+70	36+70	36+70	36+70	36+70	36+70	36+70
OFFSET	LT 71'	LT 30'	LT 26'	LT 15'	0	RT 30'	RT 46'	RT 83'	RT 88'	RT 100'
TOP OF MAIN ELEVATION	921	913	912	912	911.5	911	911	917	918	919
APPROX DEPTH FROM EXISTING	3'	7'	6'	6'	7'	8.5'	9.5'	4'	4'	4'
LOCATION	ELL									TEE
NOTES	P-WEST	P-DITCH	E-COMM	E-ELEC	P-RL	P-DITCH	E-DITCH	E-GAS	E-COMM	P-EAST
	ROW	WEST	WEST		MANLEY	EAST	EAST		EAST	ROW

STH 15 AT MANLEY ROAD 279' CROSSING - APPROX STATION 494WB+04 SHEET 9

STATION	494+04	494+04	494+04	494+04	494+04	494+04	494+04	494+04	494+04	494+04	494+04	494+04
OFFSET	RT 114'	RT 110'	RT 106'	RT 92'	RT 80'	RT 62'	RT 41'	0	LT 31'	LT 60'	LT 137'	LT 165'
TOP OF MAIN ELEVATION	916	916	916	912	912	910	910	910	910	910	909	910
APPROX DEPTH FROM EXISTING	4'	4'	4'	7'	7'	7'	4'	7'	4'	5'	4'	4'
LOCATION	ELL											
NOTES	SOUTH	MATCH	SLOPE	TRAIL EDGE	P-RL	P-DITCH	E-DITCH	P-RL	P-DITCH	P-RL	P-DITCH	NORTH
	START	ROW - EAST	INTERCEPT	SOUTH	MUT	N-TRAIL	N-TRAIL	EB	EB-WB	WB	N-WB	END

N2407 MANLEY ROAD SERVICE REPLACEMENT APPROX STATION 34MAN+68 SHEET 11

STATION	34+68	34+68	34+68	34+68	34+68	34+68	34+68	34+68	34+68	34+68	34+68
OFFSET	RT 70.5'	RT 69.5'	RT 58.5'	RT 38.5'	0	LT 3.5'	LT 10'	LT 24.5'	LT 30'	LT 52'	
TOP OF MAIN ELEVATION	920	920	918	914	911	910	910	913	916	920	
APPROX DEPTH FROM EXISTING	3'	3'	5'	9'	7'	7'	7'	9'	7'	3'	
LOCATION	E-ROW					RL					
NOTES	SERV	E - TELE	E-GAS	P-DITCH	NEW	E-ELE	E - FIBER	P-DITCH	E ROW	P-ROW	
	TEE			EAST				WEST	WEST	WEST	





LOCAL ROAD - FROM INTERSECTION WEST TO DRIVEWAY (OLD STH 15)  
4" PE MAIN RUNNING LINE APPROX STATION 22LCL+50 TO 29LCL+00 - 12' FROM ROW BORE 638' SHEETS 5 & 6








STATION	22+62	23+00	23+50	26+60	24+00	25+00	25+50	26+00	26+25	26+50	27+00	27+50	28+00	28+50	29+00	
OFFSET	RT 42'	RT 46'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	RT 48'	
TOP OF MAIN ELEVATION	844	846	849	851	851	853	859	860	861	863	866	863	868	871	871	
APPROX DEPTH FROM EXISTING	4'	4'	7'	5.5'	4'	4'	4'	6'	5.5'	4'	4'	7.5'	4'	4'	4'	
LOCATION	ELL														END	
NOTES	START														DRIVEWAY	
	WEST END														EAST END	



















MANLEY ROAD NORTH - 4" PE MAIN RUNNING LINE APPROXIMATE  
STATION 10MAN+66 TO 12MAN+00 TRENCH 134' SHEETS 9 & 10

STATION	10+66	11+00	11+50	12+00				
OFFSET	RT 22'	RT 22'	RT 22'	RT 22'				
TOP OF MAIN ELEVATION	911	911	912	913				
APPROX DEPTH FROM EXISTING	4.5'	6'	5'	4'				
LOCATION	ELL							
NOTES	SOUTH			END				
	START							






<div><div>WE ENERGIES - GAS OPERATIONS</div><div>Unless otherwise noted in this document, the following notes apply: Existing facilities should be field verified prior to excavation. Utility information shown are from plans and have not been field verified. Maintain 12" min vertical clearance at crossing of existing electrical facilities. Maintain 6" min vertical clearance at crossing of other existing facilities. Maintain 18" min vertical clearance at crossing of existing storm sewer pipes. Maintain 5' clearance from storm sewer inlets. Staking of route or ROW by surveyor required prior to construction. Clearances shown are min distances - reference permit for specific clearance requirements. Additional information on excavation, backfilling &amp; clearances can be found in the Gas CRS 201. Restore all pavement, ROW, sidewalks, and customer's private property.</div></div>	<div>CONVENTIONAL SYMBOLS</div> <div><div><div></div><div>END OF MAIN CAPPED WITH AN ANODE ATTACHED TO THE TRACER WIRE - 2' x 4' EXCAVATION.</div></div><div><div></div><div>VALVE IN AN 8" DIAMETER METALLIC BOX SET TO GRADE</div></div><div><div></div><div>17# ANODE ATTACHED TO THE MAIN IN THE SAME TRENCH</div></div><div><div></div><div>GAS MAIN CUT OFF AND CAPPED 4' x 5' EXCAVATION</div></div><div><div></div><div>METER CHANGE</div></div><div><div></div><div>TEST &amp; RECONNECT SERVICE</div></div><div><div></div><div>REPLACE SERVICE</div></div></div>
---	--

<div><div>EROSION CONTROL LEGEND</div><div><div><div></div><div>APPROXIMATE LOCATION FOR UNDERGROUND FACILITY EXCAVATION</div></div><div><div></div><div>INLET PROTECTION, TYPE A/B/C/D</div></div><div><div></div><div>12" WATTLE or 12"/20" SEDIMENT LOG or 9.5"/20" EROSION EEL</div></div><div><div></div><div>STONE DITCH CHECK</div></div><div><div></div><div>ROCK BAG</div></div><div><div></div><div>MULCH</div></div><div><div></div><div>SOIL STABILIZER, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A URBAN</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B URBAN</div></div><div><div></div><div>EROSION MAT CLASS II</div></div><div><div></div><div>EROSION MAT CLASS III</div></div><div><div></div><div>VEGETATIVE BUFFER</div></div><div><div></div><div>TRACKING PAD</div></div><div><div></div><div>TIMBER MAT</div></div><div><div></div><div>SILT FENCE</div></div><div><div><div>TSB</div></div><div>TEMPORARY SEDIMENT BASIN</div></div><div><div></div><div>SURFACE WATER FLOW</div></div></div></div>	<div><div>WE ENERGIES WORK REQUEST ENVIRONMENTAL NOTES (Notes 1 through 7 apply to ALL work requests)</div><div><div><div>General</div><div><div>1. If WDNR and/or USACE permits were obtained for the project, all permit conditions shall be met during construction of the project.</div><div>Erosion Control</div><div><div>2. If soil disturbance occurs on slopes or channels/ditches leading to wetlands or waterways, or within wetlands, the disturbed areas shall be stabilized and appropriate erosion control Best Management Practices (BMP's) shall be implemented.</div><div>3. Erosion Control BMP's shall meet or exceed the approved WDNR Storm Water Management Technical Standards (<a href="http://dnr.wi.gov/topic/stormwater/standards/const_standards.html">http://dnr.wi.gov/topic/stormwater/standards/const_standards.html</a>). Refer to We Energies Construction Site Sediment and Erosion Control Standards.</div><div>4. Inspect installed erosion control BMP's at least one time per week and after ½" rain events: repair as necessary.</div><div>5. When temporary stabilization is required (e.g. for winter or short-term construction) prior to final restoration, soil stabilizer shall be installed wherever possible. Erosion mat shall be used temporarily only where appropriate, in accordance with state standards, and when approved by the Operations Supervisor.</div></div></div><div><div>Contaminated Soils</div><div><div>6. Whenever soil exhibiting obvious signs of contamination (e.g., discoloration, petroleum or solvent odor, free liquids other than water, buried containers or tanks, or other obvious signs of environmental impacts) is encountered during excavation or installation, cease work immediately, take appropriate immediate precautions to ensure worker health and safety, and contact the Operations Supervisor or Inspector.</div></div></div><div><div>Spills</div><div><div>7. If an oil spill occurs during construction, call the Environmental Incident Response Team (EIRT) at 414-430-3478:<div><div>a. Any quantity of oil is spilled into surface water;</div><div>b. Any oil spill greater than 50 ppm PCB into a sewer, vegetable garden, or grazing land;</div><div>c. Any oil spill containing greater than 500 ppm PCB;</div><div>d. Five gallons or more of oil spilled to the ground;</div><div>e. Any oil spill involving a police department, fire department, DNR, or concerned property owner.</div></div></div></div></div><div><div>Notes 8 through 27 apply as noted at specific points within each work request:</div><div><div>Dewatering</div><div><div>8. Dewatering of pits or trenches shall be done in accordance with state standards. Use an approved sediment bag, a straw bale dewatering basin, a combination of both, or equivalent.</div></div><div><div>Wetlands</div><div><div>9. As much as practicable, the majority of the work shall be staged from the public roadways and road shoulders, keeping equipment out of adjacent wetlands.</div><div>10. All work shall be conducted to minimize soil disturbance. No rutting will be allowed within the wetlands.</div><div>11. If soils are not frozen or stable to a point that avoids rutting, timber mats, mud tracks, or equivalent shall be utilized to access pole locations.</div><div>12. Excavated soils cannot be stockpiled in wetlands.</div></div></div></div><div><div>13. All excess spoils shall be removed from wetlands and placed in a suitable upland location.</div><div>14. Trenching and pit excavations within wetlands shall include soil segregation to facilitate restoration of pre-construction soil stratification, and restoration to pre-construction elevations.</div><div>15. Poles scheduled to be removed, and that occur within wetland, shall be cut at the ground surface.</div><div><div>Waterways</div><div><div>16. No work can be performed within the banks or below the ordinary high watermark of any navigable waterways/streams.</div><div>17. No crossing of navigable waterways with equipment can occur. Foot traffic is allowed.</div><div>18. Any disturbed soil within 75-feet of the ordinary high water mark of any navigable waterways/streams shall be stabilized within 24 hours of construction completion.</div></div></div><div><div>Threatened and Endangered Species</div><div><div>19. Threatened or endangered species are known to occur in the work area. It is illegal to harass, harm, or kill a protected species under state and federal regulations. Proper precautions shall be taken to ensure harm to individuals is avoided.</div><div>20. In order to protect the threatened or endangered species, work must be conducted between November 5 and March 15.</div><div>21. Exclusion fencing must be installed at the work area prior to March 15.</div><div>22. A qualified biologist must be present when conducting work at this location.</div></div><div><div>Invasive Species</div><div><div>23. State regulated invasive species are known to occur in the work area. Reasonable precautions are legally required to prevent the spread of these species. The Wisconsin Council on Forestry Transportation and Utility Right-of Way Best Management Practices should be followed: (<a href="http://council.wisconsinforestry.org/invasives/transportation/">http://council.wisconsinforestry.org/invasives/transportation/</a>).</div></div></div><div><div>Cultural and Historical Resources, cont.</div><div><div>24. The project is within or adjacent to an area that is identified by the State of Wisconsin as potentially having Native American artifacts, burial mounds or burial sites, which could be encountered during construction.</div><div>25. If human bone or any artifacts are discovered during construction, work must cease immediately. Contact the Environmental Department who will contact the State Burial Sites Preservation Office and determine the next steps that must be taken in order to comply with state law. Work at that site MAY NOT PROCEED until the Environmental Department authorizes it.</div><div>26. A "qualified archaeologist," as specified under Wis. Stats 157.70 (1) (i) and Wis. Admin. Code HS 2.04 (6), must be present to monitor all ground disturbing activities.</div></div></div><div><div>Frac-out Contingency Plan</div><div><div>27. A frac-out contingency plan shall be on-site and implemented accordingly. The contingency plan shall incorporate the following components.<div><div>a. Continuously inspect the bore paths for frac-outs in order to respond quickly and appropriately.</div><div>b. Containment materials (e.g. silt fence, straw bales, sand bags, etc.) shall be on site and available should a frac-out occur.</div></div></div></div></div></div></div></div></div></div></div>
---	---












**Note:**  
LCS entry will be required a minimum of 3 business days prior to work commencing.

## TRAFFIC CONTROL LEGEND

TRAFFIC CONTROL LEGEND	
	WORK AREA
	TEMP. SIGN SUPPORT
	TRAFFIC CONTROL DRUM WITHOUT LIGHT
	42" GRABBER CONE
	FLAGGER

## NOTES

- SHOULDER CLOSURE ALONG STH 15.
- FLAGGING SETUP ALONG MANLEY RD.

**Note:**  
Flaggers will move & setup signs according to crew location.

REFERENCE DOT S.D.D. 15 C 12-4

REFERENCE DOT S.D.D. 15 D 27-3



Q3 Contracting: 262-522-8015

**Q3 JOB NO:** 2531002

<b>PROJECT/P.O.#:</b> 4459694	<b>IO#</b> MRO22501629
-------------------------------	------------------------

**PREPARED BY:** ASHLEY OLSON

DATE PREPARED: 02/25/2020

**STAGING TIME: 1 HOUR**

**CUSTOMER NAME:** WE ENERGIES (WISC)

**ORDERED BY:** GREG SMEDEMA

**PROJECT LOCATION: STH 15**

CITY: ELLINGTON

**WORK DESCRIPTION: PAVING RELOCATION**








GAS WORK REQUEST

4459680

SHEET 2  
SHEET 3



NORTH ROAD MAIN CROSSING APPROXIMATE STATION 14+65 - 180'

STATION	14+06	14+41.5	14+54.5	14+58.3	14+64.5	14+69.3	14+76.9	
OFFSET	RT 123'	RT 67'	RT 36'	RT 24'	0	LT 18.5'	LT 48'	
TOP OF MAIN ELEVATION	880	880	880	880	880	880	880	
APPROX DEPTH FROM EXISTING	3'	8'	8'	6.5'	5'	7'	7.5'	
LOCATION	ELL	SHOULDER	SHOULDER	SHOULDER	RL	SHOULDER	DITCH	
NOTES	EAST	EXISTING	EXISTING	PROPOSED	REFERENCE	PROPOSED	WEST	
	START	EAST SIDE	WEST SIDE	EAST SIDE	LINE	WEST SIDE	END	

ITEM NO.	DESCRIPTION
1	TEE, PE SERVICE 4" X 1"
2	CLAMP, 4" IPS SUPPORT
3	ELL, 4" IPS 45 DEG. BUTT FUSION
4	POST, ROUND GAS PIPE MARKER 78"
5	ANODE, 1 LB. MAGNESIUM
6	CAP, 4" IPS BUTT FUSION END
7	TEE, PE SERVICE 4" X 1"
8	SQUEEZE POINT

PIN 110019401  
BEYER EAST, LLC  
DOC. 1767359  
BEYER EAST LLC

NOTE: 1" BYPASS IS REQUIRED

NOTE: RETIRE CP 108218 AND REMOVE BOX/ POST AND WIRES

PIN 110014206  
EQUITY TRUST CO., CUSTODIAN, FBO SUSAN M. KORTH IRA  
DOC. 1698195





GAS WORK REQUEST

4459680

NE-SE  
SEC. 5, T21N, R16E

OF

SERVICE CROSSING TO ADDRESS N2210 GREENVILLE DRIVE APPROX. STATION 546EB+76


STATION	546+76	546+76	546+76	546+76	546+76	546+76	546+76	546+76	546+76	
OFFSET	RT 120'	RT 84'	RT 65'	0	LT 40'	LT 60'	LT 115'	LT 126'	LT 160'	
TOP OF MAIN ELEVATION	881	880	883	884	883	885	883	883	886	
APPROX DEPTH FROM EXISTING	4'	4'	3'	3'	3'	4'	4'	6'	3'	
LOCATION	TEE									
NOTES	SOUTH ROW	P-DITCH SOUTH	P-RL MUT	P-RL EB	P-DITCH P-MEDIAN	P-RL WB	E-GAS	P-DITCH NORTH	P-ROW NORTH	



HAST, RAYMOND P & MARGIE J

PIN 110018801  
RAYMOND P. HAST & MARGIE J. HAST  
DOC. 659289

ITEM NO.	DESCRIPTION
1	CAP, 4" BUTT WITH 1/2" CTS PURGE
2	CAP, 1/2" CTS SOCKET FUSION END
3	ANODE, 1 LB. MAGNESIUM
4	FLUSH MOUNT, GAS PIPE MARKER



END OF MAIN TO BE  
UNDER HARD SURFACE.








BORE PIT  
8, 27



















WETLAND

PROPOSED 4" PE 552'

DEPTH AT CULVERT/DITCH 4'  
MINIMUM @ WATERWAY PER  
STANDARDS


SHEET 2  
SHEET 3


<div><div>WE ENERGIES - GAS OPERATIONS</div><div>Unless otherwise noted in this document, the following notes apply: Existing facilities should be field verified prior to excavation. Utility information shown are from plans and have not been field verified. Maintain 12" min vertical clearance at crossing of existing electrical facilities. Maintain 6" min vertical clearance at crossing of other existing facilities. Maintain 18" min vertical clearance at crossing of existing storm sewer pipes. Maintain 5' clearance from storm sewer inlets. Staking of route or ROW by surveyor required prior to construction. Clearances shown are min distances - reference permit for specific clearance requirements. Additional information on excavation, backfilling &amp; clearances can be found in the Gas CRS 201. Restore all pavement, ROW, sidewalks, and customer's private property.</div></div>	<div>CONVENTIONAL SYMBOLS</div> <div><div><div></div><div>END OF MAIN CAPPED WITH AN ANODE ATTACHED TO THE TRACER WIRE - 2' x 4' EXCAVATION.</div></div><div><div></div><div>VALVE IN AN 8" DIAMETER METALLIC BOX SET TO GRADE</div></div><div><div></div><div>17# ANODE ATTACHED TO THE MAIN IN THE SAME TRENCH</div></div><div><div></div><div>GAS MAIN CUT OFF AND CAPPED 4' x 5' EXCAVATION</div></div><div><div></div><div>METER CHANGE</div></div><div><div></div><div>TEST &amp; RECONNECT SERVICE</div></div><div><div></div><div>REPLACE SERVICE</div></div></div>
---	--


<div><div>EROSION CONTROL LEGEND</div><div><div><div></div><div>APPROXIMATE LOCATION FOR UNDERGROUND FACILITY EXCAVATION</div></div><div><div></div><div>INLET PROTECTION, TYPE A/B/C/D</div></div><div><div></div><div>12" WATTLE or 12"/20" SEDIMENT LOG or 9.5"/20" EROSION EEL</div></div><div><div></div><div>STONE DITCH CHECK</div></div><div><div></div><div>ROCK BAG</div></div><div><div></div><div>MULCH</div></div><div><div></div><div>SOIL STABILIZER, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A URBAN</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B URBAN</div></div><div><div></div><div>EROSION MAT CLASS II</div></div><div><div></div><div>EROSION MAT CLASS III</div></div><div><div></div><div>VEGETATIVE BUFFER</div></div><div><div></div><div>TRACKING PAD</div></div><div><div></div><div>TIMBER MAT</div></div><div><div></div><div>SILT FENCE</div></div><div><div><div>TSB</div></div><div>TEMPORARY SEDIMENT BASIN</div></div><div><div></div><div>SURFACE WATER FLOW</div></div></div></div> <td><div><div>WE ENERGIES WORK REQUEST ENVIRONMENTAL NOTES (Notes 1 through 7 apply to ALL work requests)</div><div><div><div>General</div><div><div>1. If WDNR and/or USACE permits were obtained for the project, all permit conditions shall be met during construction of the project.</div></div></div><div><div>Erosion Control</div><div><div>2. If soil disturbance occurs on slopes or channels/ditches leading to wetlands or waterways, or within wetlands, the disturbed areas shall be stabilized and appropriate erosion control Best Management Practices (BMP's) shall be implemented.</div><div>3. Erosion Control BMP's shall meet or exceed the approved WDNR Storm Water Management Technical Standards (<a href="http://dnr.wi.gov/topic/stormwater/standards/const_standards.html">http://dnr.wi.gov/topic/stormwater/standards/const_standards.html</a>). Refer to We Energies Construction Site Sediment and Erosion Control Standards.</div><div>4. Inspect installed erosion control BMP's at least one time per week and after ½" rain events: repair as necessary.</div><div>5. When temporary stabilization is required (e.g. for winter or short-term construction) prior to final restoration, soil stabilizer shall be installed wherever possible. Erosion mat shall be used temporarily only where appropriate, in accordance with state standards, and when approved by the Operations Supervisor.</div></div></div><div><div>Contaminated Soils</div><div><div>6. Whenever soil exhibiting obvious signs of contamination (e.g., discoloration, petroleum or solvent odor, free liquids other than water, buried containers or tanks, or other obvious signs of environmental impacts) is encountered during excavation or installation, cease work immediately, take appropriate immediate precautions to ensure worker health and safety, and contact the Operations Supervisor or Inspector.</div></div></div><div><div>Spills</div><div><div>7. If an oil spill occurs during construction, call the Environmental Incident Response Team (EIRT) at 414-430-3478:<div><div>a. Any quantity of oil is spilled into surface water;</div><div>b. Any oil spill greater than 50 ppm PCB into a sewer, vegetable garden, or grazing land;</div><div>c. Any oil spill containing greater than 500 ppm PCB;</div><div>d. Five gallons or more of oil spilled to the ground;</div><div>e. Any oil spill involving a police department, fire department, DNR, or concerned property owner.</div></div></div></div></div><div><div>Notes 8 through 27 apply as noted at specific points within each work request:</div><div><div>Dewatering</div><div><div>8. Dewatering of pits or trenches shall be done in accordance with state standards. Use an approved sediment bag, a straw bale dewatering basin, a combination of both, or equivalent.</div></div></div><div><div>Wetlands</div><div><div>9. As much as practicable, the majority of the work shall be staged from the public roadways and road shoulders, keeping equipment out of adjacent wetlands.</div><div>10. All work shall be conducted to minimize soil disturbance. No rutting will be allowed within the wetlands.</div><div>11. If soils are not frozen or stable to a point that avoids rutting, timber mats, mud tracks, or equivalent shall be utilized to access pole locations.</div><div>12. Excavated soils cannot be stockpiled in wetlands.</div></div></div><div><div>13. All excess spoils shall be removed from wetlands and placed in a suitable upland location.</div><div>14. Trenching and pit excavations within wetlands shall include soil segregation to facilitate restoration of pre-construction soil stratification, and restoration to pre-construction elevations.</div><div>15. Poles scheduled to be removed, and that occur within wetland, shall be cut at the ground surface.</div><div><div>Waterways</div><div><div>16. No work can be performed within the banks or below the ordinary high watermark of any navigable waterways/streams.</div><div>17. No crossing of navigable waterways with equipment can occur. Foot traffic is allowed.</div><div>18. Any disturbed soil within 75-feet of the ordinary high water mark of any navigable waterways/streams shall be stabilized within 24 hours of construction completion.</div></div></div><div><div>Threatened and Endangered Species</div><div><div>19. Threatened or endangered species are known to occur in the work area. It is illegal to harass, harm, or kill a protected species under state and federal regulations. Proper precautions shall be taken to ensure harm to individuals is avoided.</div><div>20. In order to protect the threatened or endangered species, work must be conducted between November 5 and March 15.</div><div>21. Exclusion fencing must be installed at the work area prior to March 15.</div><div>22. A qualified biologist must be present when conducting work at this location.</div></div><div><div>Invasive Species</div><div><div>23. State regulated invasive species are known to occur in the work area. Reasonable precautions are legally required to prevent the spread of these species. The Wisconsin Council on Forestry Transportation and Utility Right-of Way Best Management Practices should be followed: (<a href="http://council.wisconsinforestry.org/invasives/transportation/">http://council.wisconsinforestry.org/invasives/transportation/</a>).</div></div></div><div><div>Cultural and Historical Resources, cont.</div><div><div>24. The project is within or adjacent to an area that is identified by the State of Wisconsin as potentially having Native American artifacts, burial mounds or burial sites, which could be encountered during construction.</div><div>25. If human bone or any artifacts are discovered during construction, work must cease immediately. Contact the Environmental Department who will contact the State Burial Sites Preservation Office and determine the next steps that must be taken in order to comply with state law. Work at that site MAY NOT PROCEED until the Environmental Department authorizes it.</div><div>26. A "qualified archaeologist," as specified under Wis. Stats 157.70 (1) (i) and Wis. Admin. Code HS 2.04 (6), must be present to monitor all ground disturbing activities.</div></div></div><div><div>Frac-out Contingency Plan</div><div><div>27. A frac-out contingency plan shall be on-site and implemented accordingly. The contingency plan shall incorporate the following components.<div><div>a. Continuously inspect the bore paths for frac-outs in order to respond quickly and appropriately.</div><div>b. Containment materials (e.g. silt fence, straw bales, sand bags, etc.) shall be on site and available should a frac-out occur.</div></div></div></div></div></div></div></div></div></div></td>	<div><div>WE ENERGIES WORK REQUEST ENVIRONMENTAL NOTES (Notes 1 through 7 apply to ALL work requests)</div><div><div><div>General</div><div><div>1. If WDNR and/or USACE permits were obtained for the project, all permit conditions shall be met during construction of the project.</div></div></div><div><div>Erosion Control</div><div><div>2. If soil disturbance occurs on slopes or channels/ditches leading to wetlands or waterways, or within wetlands, the disturbed areas shall be stabilized and appropriate erosion control Best Management Practices (BMP's) shall be implemented.</div><div>3. Erosion Control BMP's shall meet or exceed the approved WDNR Storm Water Management Technical Standards (<a href="http://dnr.wi.gov/topic/stormwater/standards/const_standards.html">http://dnr.wi.gov/topic/stormwater/standards/const_standards.html</a>). Refer to We Energies Construction Site Sediment and Erosion Control Standards.</div><div>4. Inspect installed erosion control BMP's at least one time per week and after ½" rain events: repair as necessary.</div><div>5. When temporary stabilization is required (e.g. for winter or short-term construction) prior to final restoration, soil stabilizer shall be installed wherever possible. Erosion mat shall be used temporarily only where appropriate, in accordance with state standards, and when approved by the Operations Supervisor.</div></div></div><div><div>Contaminated Soils</div><div><div>6. Whenever soil exhibiting obvious signs of contamination (e.g., discoloration, petroleum or solvent odor, free liquids other than water, buried containers or tanks, or other obvious signs of environmental impacts) is encountered during excavation or installation, cease work immediately, take appropriate immediate precautions to ensure worker health and safety, and contact the Operations Supervisor or Inspector.</div></div></div><div><div>Spills</div><div><div>7. If an oil spill occurs during construction, call the Environmental Incident Response Team (EIRT) at 414-430-3478:<div><div>a. Any quantity of oil is spilled into surface water;</div><div>b. Any oil spill greater than 50 ppm PCB into a sewer, vegetable garden, or grazing land;</div><div>c. Any oil spill containing greater than 500 ppm PCB;</div><div>d. Five gallons or more of oil spilled to the ground;</div><div>e. Any oil spill involving a police department, fire department, DNR, or concerned property owner.</div></div></div></div></div><div><div>Notes 8 through 27 apply as noted at specific points within each work request:</div><div><div>Dewatering</div><div><div>8. Dewatering of pits or trenches shall be done in accordance with state standards. Use an approved sediment bag, a straw bale dewatering basin, a combination of both, or equivalent.</div></div></div><div><div>Wetlands</div><div><div>9. As much as practicable, the majority of the work shall be staged from the public roadways and road shoulders, keeping equipment out of adjacent wetlands.</div><div>10. All work shall be conducted to minimize soil disturbance. No rutting will be allowed within the wetlands.</div><div>11. If soils are not frozen or stable to a point that avoids rutting, timber mats, mud tracks, or equivalent shall be utilized to access pole locations.</div><div>12. Excavated soils cannot be stockpiled in wetlands.</div></div></div><div><div>13. All excess spoils shall be removed from wetlands and placed in a suitable upland location.</div><div>14. Trenching and pit excavations within wetlands shall include soil segregation to facilitate restoration of pre-construction soil stratification, and restoration to pre-construction elevations.</div><div>15. Poles scheduled to be removed, and that occur within wetland, shall be cut at the ground surface.</div><div><div>Waterways</div><div><div>16. No work can be performed within the banks or below the ordinary high watermark of any navigable waterways/streams.</div><div>17. No crossing of navigable waterways with equipment can occur. Foot traffic is allowed.</div><div>18. Any disturbed soil within 75-feet of the ordinary high water mark of any navigable waterways/streams shall be stabilized within 24 hours of construction completion.</div></div></div><div><div>Threatened and Endangered Species</div><div><div>19. Threatened or endangered species are known to occur in the work area. It is illegal to harass, harm, or kill a protected species under state and federal regulations. Proper precautions shall be taken to ensure harm to individuals is avoided.</div><div>20. In order to protect the threatened or endangered species, work must be conducted between November 5 and March 15.</div><div>21. Exclusion fencing must be installed at the work area prior to March 15.</div><div>22. A qualified biologist must be present when conducting work at this location.</div></div><div><div>Invasive Species</div><div><div>23. State regulated invasive species are known to occur in the work area. Reasonable precautions are legally required to prevent the spread of these species. The Wisconsin Council on Forestry Transportation and Utility Right-of Way Best Management Practices should be followed: (<a href="http://council.wisconsinforestry.org/invasives/transportation/">http://council.wisconsinforestry.org/invasives/transportation/</a>).</div></div></div><div><div>Cultural and Historical Resources, cont.</div><div><div>24. The project is within or adjacent to an area that is identified by the State of Wisconsin as potentially having Native American artifacts, burial mounds or burial sites, which could be encountered during construction.</div><div>25. If human bone or any artifacts are discovered during construction, work must cease immediately. Contact the Environmental Department who will contact the State Burial Sites Preservation Office and determine the next steps that must be taken in order to comply with state law. Work at that site MAY NOT PROCEED until the Environmental Department authorizes it.</div><div>26. A "qualified archaeologist," as specified under Wis. Stats 157.70 (1) (i) and Wis. Admin. Code HS 2.04 (6), must be present to monitor all ground disturbing activities.</div></div></div><div><div>Frac-out Contingency Plan</div><div><div>27. A frac-out contingency plan shall be on-site and implemented accordingly. The contingency plan shall incorporate the following components.<div><div>a. Continuously inspect the bore paths for frac-outs in order to respond quickly and appropriately.</div><div>b. Containment materials (e.g. silt fence, straw bales, sand bags, etc.) shall be on site and available should a frac-out occur.</div></div></div></div></div></div></div></div></div></div>
---	--












 = WORK AREA

 = TEMP. SIGN SUPPORT


 = 

 = 

REFERENCE DOT S.D.D. 15 D 28-3

<div> Primoris Service Corporation Q3 Contracting: 262-522-8015</div>		Q3 JOB NO:	2530798
		PREPARED BY:	RICHARD RYSKOSKI
		DATE PREPARED:	2/21/2020
		STAGING TIME:	1 Hour
CUSTOMER NAME:		ORDERED BY:	
WE ENERGIES WIGO GAS		CODY BECKMAN	
PROJECT / P.O. # :		CITY/TOWN/VILLAGE:	
4459680		ELLINGTON	
PROJECT LOCATION:		WORK DESCRIPTION:	
STH 15 AND NORTH RD		PAVING RELOCATION	



GAS WORK REQUEST	
	<b>4459720</b>
<input type="checkbox"/> C <input checked="" type="checkbox"/> T <input type="checkbox"/> V: <u>GREENVILLE</u>	
CUST/PROJ NAME: <u>STH 15 BYPASS 1146-75-72 PART 2</u>	
PROJECT LOCATION: <u>STH 15 FROM LILY OF THE VALLEY RD</u> <u>WEST TO JULIUS DRIVE</u>	
PREPARED BY: <u>CODY BECKMAN</u>	
E-MAIL: <u>cody.beckman@we-energies.com</u>	
OFFICE #: <u>920-380-3422</u>	CELL #: <u>920-428-1038</u>
PROJECT ID: <u>WI4459720</u>	IO #: <u>MRL21501630</u>
CGS #: _____	

TYPE OF WORK:	
<input type="checkbox"/> GDAM MAIN REPLACEMENT	<input type="checkbox"/> MAIN EXTENSION
<input checked="" type="checkbox"/> PAVING RELOCATION	<input type="checkbox"/> SERVICE
<input type="checkbox"/> OTHER _____	

<b>STAKING REQUIREMENTS:</b> <input checked="checked" type="checkbox"/> SURVEYOR <input type="checkbox"/> STAKED <input type="checkbox"/> DESIGNER <input type="checkbox"/> NOT NEEDED	<b>MAIN / SERVICE IN EASEMENT:</b> <input type="checkbox"/> YES      ROW WR# _____
--	---

CORROSION CONTACT: JIM DAVIS  
PHONE #: 414-221-3646

RESTORE PRIVATE PROPERTY: ☒ WE ENERGIES ☐ CUSTOMER

RAILROAD PERMITTING/FLAGGING REQUIRED ☐ YES ☒ NO

RR NAME NA	
MAIN SIZE, MAT'L, FT	INSTALL METHOD & FOOTAGE
6" PE 6340'	TRENCH 5466' BORE 874'
4" PE 1492'	TRENCH 369' BORE 1123'
2" PE 3065'	TRENCH 203' BORE 2862'
1" PE 11'	TRENCH 11'

**RELATED WR'S**

MAIN RETIREMENT WR 4459726 FOOTAGE 7700'

SERVICE REPLACEMENT WR 4459725 NO. 3

SERVICE RECONNECT WR 4459724 NO. 14

THREE SERVICES ARE INACTIVE AND ARE TO  
BE REMOVED.

### EROSION CONTROL NOTES

☒ IF DISTURBANCE OCCURS IN SUMMER, FINAL STABILIZATION SHALL BE PERMANENT SEED AND PROPERLY ANCHORED MULCH, UNLESS NOTED. IF DISTURBANCE OCCURS IN WINTER, TEMPORARY STABILIZATION SHALL BE SOIL STABILIZER, TYPE A, UNLESS NOTED. FINAL STABILIZATION IS REQUIRED IN SPRING.

☐ IF DISTURBANCE OCCURS WITHIN THE SLOPE INTERCEPT, FINAL STABILIZATION SHALL BE SOIL STABILIZER, TYPE A, UNLESS NOTED. IF DISTURBANCE OCCURS OUTSIDE THE SLOPE INTERCEPT, FINAL STABILIZATION SHALL BE PERMANENT SEED AND PROPERLY ANCHORED MULCH, UNLESS NOTED.

☒ IF DISTURBANCE OCCURS IN AGRICULTURAL FIELDS, SOIL SEGREGATION WILL NEED TO TAKE PLACE TO RETURN FIELDS TO PRE-CONSTRUCTION SOIL STRATIFICATION AND TO PRE-CONSTRUCTION ELEVATIONS.

☒ DEPENDING ON THE TIME OF YEAR AND WEATHER CONDITIONS, CONSIDER USING PLATES/MATS IN WETLANDS OR CROSSING DITCHES.

☒ STOCKPILE MATERIALS SHALL BE PLACED UPSLOPE FROM EXCAVATION. IF STOCKPILE MATERIALS MUST BE PLACED DOWNSLOPE OF EXCAVATION, PROTECT STOCKPILES WITH 12" WATTLES.

☐ PROJECT SPECIFIC EROSION CONTROL NOTES:

**JOB INFO:**


SECTION / TOWN / RANGE: NW1/4 SEC10, T21N, R16E

SITE VISIT COMPLETED BY: CODY BECKMAN

JOB OWNER: CODY BECKMAN

**CRITICAL SAFETY RULES - GO:**

1. Confined space procedures
2. Excavation and shoring
3. Live gas emergency procedures
4. Lock out - Tag out
5. Seat belts
6. Securing parked vehicles



CONTINGENCIES & COMMENTS:

DIGGERS HOTLINE REQUIRED.  
WE ENERGIES WILL RESTORE  
WE ENERGIES WILL NOT HAUL SPOIL

CUSTOMER IS REQUIRED TO LOCATE ALL  
PRIVATE UNDERGROUND FACILITIES PRIOR  
TO INSTALLATION.

WE ENERGIES IS NOT RESPONSIBLE FOR  
ROOT DAMAGE

**SHEET**

CONSTRUCTION REMARKS:

\* NEW MAIN TO BE INSTALLED AT 4" UNLESS NOTED ON THE

\* NEW MAIN TO BE INSTALLED AT 4' UNLESS NOTED ON THE

\* ALL NEW MAIN TO BE ADDED TO CIA 5666349

\* A PORTION OF THIS SECTION IS TO BE DUAL MAIN DUE TO  
TO BE CONSTRUCTED.

\* THERE ARE THREE ADDITIONAL MAIN SEGMENTS THAT ARE PRIVATE PROPERTY. EACH OF THE MAIN SEGMENTS ON EACH A 1" PE BYPASS.

\* NOTE - EXTRA DEPTH REQUIRED FOR THE 2" PE MAIN IN TH OF STH 15 FROM STATION 631EB+00 TO 636EB+00. MAIN DE FROM EXISTING GRADE.


\* NOTE - EXTRA DEPTH REQUIRED FOR THE 2" PE MAIN IN THE UNDER SHARED DRIVEWAY FOR N1873 AND 1875 STH 15. 1' DEEP FROM EXISTING GRADE.

\* NOTE - EXTRA DEPTH REQUIRED FOR THE 2" PE MAIN IN THE UNDER DRIVEWAY FOR N1817 STH 15. MAIN DEPTH TO BE EXISTING GRADE.

\* THE WIDOT HAS PURCHASED LARGE PORTIONS OF PROPERTY OF WAY. SEVERAL CUSTOMERS HAD PRIVATE FACILITIES OF WAY AND THESE PRIVATE FACILITIES ARE TO BE REMOVED BEFORE THE PROPOSED GAS MAIN CAN BE CONSTRUCTED.

\* TEMPERATURE MUST BE ABOVE 0 DEGREES FAHRENHEIT ( IF THE TEMPERATURE IS BELOW 0 DEGREES FAHRENHEIT, ENGINEERING FOR RE- REVIEW. 1" PE BYPASSES ARE SUF ONE WAY FEEDS.

\* ADDITIONAL SERVICE WORK REQUESTS ARE TO BE RELEASED  
 WR 4484797 - ADDRESS N1866 GREENVILLE DRIVE (STH 15)  
 WR 4484800 - ADDRESS N1868 GREENVILLE DRIVE (STH 15)  
 WR 4487778 - ADDRESS N2038 JULIUS DRIVE



WR 4459720	REV.	DESCRIPTION	BY	DATE
	0	DESIGN APPROVED FOR CONSTRUCTION	CB	2/27/20
Printed 3/12/2020 8:07:09 AM SHEET 1 OF 16				





GAS WORK REQUEST

4459720

- INSTALL A TYPE 3 LOCATE POST AT LOCATION 9
- BRING THE NEW AND EXISTING TRACER WIRE INTO THE LOCATE POST ALONG WITH A 1" ANODE WIRE.
- ATTACH THE NEW TRACER WIRE TO THE 1" ANODE WIRE IN THE LOCATE POST ALONG WITH THE EXISTING PE TRACER WIRE.
- LABEL EACH WIRE WITH MATERIAL AND DIRECTION.

LOT 1  
CSM 1634  
V9/P1634  
DOC. 1082065

N2034

1" BYPASS  
REQUIRED

2" PE 50D 02 800726  
MAIN ON EASEMENT  
1" WAY FEED

PROPOSED  
2" PE 16'


PROPOSED  
6" PE 101' 6" PE 73'

PROPOSED  
6" PE 42' BORE

PROPOSED  
6" PE 179'

PROPOSED  
6" PE 65'

PROPOSED  
6" PE 1534'



ITEM NO.	DESCRIPTION
1	POST, ROUND GAS PIPE MARKER 78"
2	CAP, 6" IPS BUTT WITH 1" CTS PURGE
3	CAP, 1" CTS SOCKET FUSION END
4	ANODE, 1 LB. MAGNESIUM
5	TEE, PE HIGH VOLUME 6" X 2"
6	TEE, PE SERVICE 2" X 1"
7	TEE, PE SERVICE 6" X 1"
8	CLAMP, 2" IPS SUPPORT
9	POST, 78" TYPE #3 LOCATE POST

10	CLAMP, 2" IPS SUPPORT
11	ANODE, 1 LB. MAGNESIUM

WITTHUHN  
PLAT OF SURVEY

PIN 110027100  
GLBB PROPERTIES, LLC  
DOC. 1770990

SHEET 3



**4459720**



SEPTIC



INL

SEPC

INL

INL

N2011  
RPL  
1/2" PE  
749685

PIN 110027401  
ROBERT R. STE  
DOC-959436



SMITH,  
DAVID G.

NER

T



IMMEL GROUP, LLC  
PIN 110027500  
IMMEL GROUP, LLC  
DOC. 1745850



ITEM NO.	DESCRIPTION
1	POST, 78" TYPE 3 LOCATE POINT
2	ANODE, 1 LB. MAGNESIUM



ITEM NO.	DESCRIPTION
1	ANODE, 1 LB. MAGNESIUM
2	POST, ROUND GAS PIPE MARKER 78"
3	ELL, 6" IPS 45 DEG. BUTT FUSION
4	VALVE, 6" IPS PE #84920 CONVENIENT
5	POST, ROUND GAS PIPE MARKER 78"
6	TEE, 6" IPS BUTT FUSION
7	REDUCER 6" IPS X 4" IPS BUTT FUSION
8	VALVE, 4" IPS PE #84922 CONVENIENT
9	ELL, 6" IPS 45 DEG. BUTT FUSION

10	TEE, 6" IPS BUTT FUSION
11	POST, ROUND GAS PIPE MARKER 78"
12	VALVE, 6" IPS PE #86262 CONVENIENT
13	REDUCER 6" IPS X 4" IPS BUTT FUSION
14	VALVE, 4" IPS PE #84921 CONVENIENT
15	ELL, 4" IPS 45 DEG. BUTT FUSION
16	POST, ROUND GAS PIPE MARKER 78"

TWO PRIVATE DRAIN TILE PIPES ARE IN THE AREA FROM THE FIELD TO THE DITCH. THE CUSTOMER PLACED STAKES AT THE RIGHT OF WAY TO MARK THEIR LOCATION IN OCTOBER OF 2017. VERIFY LOCATION PRIOR TO CONSTRUCTION.

IMMEL GROUP, LLC  
PIN 110027500  
IMMEL GROUP, LLC  
DOC. 1745850

PIN 110027501  
TRAVIS L. UHLF  
DOC. 1931207

JULIUS  
POS  
WISDO

POST  
ENV  
8, 2  
3

33


**CAUTION**

LOT 1  
CSM 5797  
V33/P5797  
DOC. 1795400



PIN 110030300  
FAITH COMMUNITY UNIT  
DOC. 868538 & 663676

N1966



**PROPOSED 6" PE 561'**

BERM AND GRADE TO BE CUT FOR DITCH DRAINAGE  
FROM STATION 613WB+45 TO 614WB+97. INSTALL  
MAIN AT 7' DEEP FROM GRADE WITHOUT BERM  
ELEVATION 880 - ELBOW TO BE 9' DEEP.

STH 15

STH 15

**NOTE: RETIRE AND  
REMOVE CP 118977**

PROPOSED 4  
NOTE: NEW MAIN FROM  
ELBOW SOUTH TO  
STATION 40+50 TO  
BE 4' DEEP

2 WAY FEED  
PROPOSED 4 PE 315  
NEW MAIN FROM  
WITH TO 150 TO

**SHEET 9**

**SHEET 8**

SCALE 1" = 50'

SHEET 5 OF 16




GAS WORK REQUEST

4459720

SHEET 7



ITEM NO.	DESCRIPTION
1	ELL, 4" IPS 45 DEG. BUTT FUSE
2	ELL, 4" IPS 45 DEG. BUTT FUSE




IMMEL GROUP LLC  
PIN 110027500  
IMMEL GROUP, LLC  
DOC. 1745850

IMMEL GROUP LLC  
PIN 110027500  
IMMEL GROUP, LLC  
DOC. 1745850

N1998  
T&R  
1/2" PE  
2043776  
CUSTOMER VALVE  
NEEDED AT ROW



ITEM NO.	DESCRIPTION
1	CAP 4" IPS BUTT WITH 1/2" CTS PURGE
2	CAP, 1/2" CTS SOCKET FUSION END
3	ANODE, 1 LB. MAGNESIUM
4	POST, ROUND GAS PIPE MARKER 78"








GAS WORK REQUEST

4459720

SHEET 5

TIE IN DETAIL - THIS SHEET



NOTE: AT LOCATION 5 CONNECT THE NEW PE TRACER WIRE TO THE EXISTING TRACER WIRE ALONG WITH A 1" ANODE WIRE.

ITEM NO.	DESCRIPTION
1	SQUEEZE POINT
2	CLAMP, 4" IPS SUPPORT
3	LOCATE POINT, TYPE 3 FLUSH MOUNT
4	CAP, 4" IPS BUTT FUSE END
5	ANODE, 1 LB. MAGNESIUM
6	ELL, 4" IPS 90 DEG. BUTT FUSE
7	ELL, 4" IPS 90 DEG. BUTT FUSE
8	CLAMP, 4" IPS SUPPORT

N1915  
T&R  
1" PE  
2043772

SCALE 1" = 50'

SHEET 8 OF 16



GAS WORK REQUEST

4459720

N1916  
T&R  
1" PE  
777938

PIN 110030204  
BASMAR, LLC  
DOC. 1564439

LOT 1  
CSM 3109  
V16/P3109  
DOC. 1262776

BASMAR LLC

PROPOSED STORMSEWER  
TO BE 2.5' TO 4' DEEP  
INSTALL GAS MAIN AT 5'  
AT STATION 622WB+21 RT 103'

THE SOUTH CULVERT END IS NOT  
VISIBLE. LOCATE IN FIELD PRIOR  
TO INSTALLING MAIN. MAINTAIN  
EXISTING DRAINAGE.

DEPTH OF 418' BORE IS TO  
BE AT 4' TO TOP OF MAIN.

CAUTION - WATER HYDRANT IN  
AREA FIND WATER MAIN PRIOR  
TO INSTALLING THE GAS MAIN IN  
THIS AREA.

MAINTAIN  
EXISTING  
DRAINAGE

PROPOSED 6" PE 561'

PROPOSED 6" PE BORE  
DRIVEWAY 48'

PROPOSED 6" PE 108'

PROPOSED 6" PE BORE 418'

PIN 110030202  
STATE OF WISCONSIN, DEPARTMENT  
OF TRANSPORTATION  
DOC. 885560

ENV  
8, 27

ENV  
8, 27

ENV  
8, 27

16.5' UTILITY EASEMENT J7000/19

4" PE 50D 86 8618

STH 15

STH 15

SHEET 5

Printed 3/12/2020

TOWN GREENVILLE SANITARY DST 1  
8:07:16 AM

SCALE 1" = 50'

SHEET 9 OF 16



**4459720**

ITEM NO.	DESCRIPTION
1	ELL, 6" IPS 45 DEG. BUTT FUSE
2	ELL, 6" IPS 45 DEG. BUTT FUSE
3	ELL, 6" IPS 45 DEG. BUTT FUSE
4	ELL, 6" IPS 45 DEG. BUTT FUSE
5	CAP, 2" IPS SOCKET X 1/2" CTS PURGE
6	ANODE, 1 LB. MAGNESIUM
7	POST, ROUND GAS PIPE MARKER 78"
8	ANODE, 1LB MAGNESIUM
9	CAP, 1/2" CTS SOCKET FUSION END

N1868   
**INA**  
**1/2" PE**  
**2043476**

BYTOF

FAMILY LTD

PARTNERSHIP

PIN 110030801  
THE BYT OF FAMILY  
1732839

LOT 2  
CSM 5720  
V33/P5720  
DOC. 1775497

**CAUTION - STORM SEWER  
IN AREA. LOCATE IN FIELD  
PRIOR TO INSTALLING GAS MAIN.**

**12" SEDIMENT  
LOGS 50' APART**

**SHEET 11**

**CAUTION**

**PROPOSED 2' PE BOFE 472'**

NOTE - EXTRA DEPTH REQUIRED  
FROM STATION 631EB+00 TO 636EB+00.  
MAIN DEPTH TO BE 5' DEEP

N1867  
T&R  
1/2" PE  
2043477

N1875  
T&R  
1" PE  
767265

N1873  
HOUSE  
T&R  
1/2" PE  
2043479

**T&R**  
**1" PE**  
**4041919**

N1881  
T&R  
1/2" PE  
746762

DOUGHTY  
AT OF SURVEY  
PIN 110031508  
JOHN B. HAYES &  
LOC. 1920382

SCALE 1" = 50

SHEET 10 OF 16



GAS WORK REQUEST

4459720


N1824  
RPL  
1 1/4" ST  
2043472

TEM NO.	DESCRIPTION
1	ELL, 6" IPS 90 DEG. BUTT FUSE
2	ELL, 6" IPS 90 DEG. BUTT FUSE
3	ELL, 6" IPS 90 DEG. BUTT FUSE
4	ELL, 6" IPS 90 DEG. BUTT FUSE
5	ANODE, 1LB MAGNESIUM
6	ELL, 6" IPS 90 DEG. BUTT FUSE
7	ELL, 6" IPS 90 DEG. BUTT FUSE
8	ELL, 6" IPS 90 DEG. BUTT FUSE
9	ELL, 6" IPS 90 DEG. BUTT FUSE

10	ANODE, 1LB MAGNESIUM

SHEET 13

SHEET 10





SHEET 12

SCALE 1" = 50'

SHEET 11 OF 16







GAS WORK REQUEST

4459720

SHEET 11

ITEM NO.	DESCRIPTION
1	ANODE, 1 LB MAGNESIUM
2	ELL, 6" IPS 90 DEG. BUTT FUSE
3	ELL, 6" IPS 90 DEG. BUTT FUSE
4	TEE, PE SERVICE 2" X 1"
5	TEE, PE SERVICE 2" X 1"
6	TEE, PE MED VOLUME 2" X 2"
7	CLAMP, 2" IPS SUPPORT
8	CLAMP, 2" IPS SUPPORT
9	CAP, 2" IPS SOCKET FUSION END

10	SQUEEZE POINT
11	CAP, 2" IPS SOCKET FUSION END
12	TEE, PE MED VOLUME 2" X 2"
13	SQUEEZE POINT
14	SQUEEZE POINT

PIN 110030700  
LYN REALESTATE, LLC  
DOC. 1697768

LOT 1  
CSM 3263  
V17/P3263  
DOC. 1286416


PIN 110246700  
SK EVERGREEN PARK, LLC ETAL  
DOC. 1878237, 1878238, 1878239

PIN 110247000  
DIN DEVELOPMENTS, LLC  
LOT 56  
1ST ADDITION TO  
DOC. 1738023

DEVELOPMENTS  
DIN  
LLC

12 SEDIMENT LOGS  
50' SPACING

SHEET 14









4459720

N2011 SERVICE CROSSING APPROX. STATION 596WB+52 SHEET 2

STATION	596+52	596+52	596+52	596+52	596+52	596+52	596+52	596+52	596+52	596+52
OFFSET	LT 80'	LT 60'	LT 55'	0	RT 26'	RT 60'	RT 115'	RT 132'	RT 150'	RT 170'
TOP OF MAIN ELEVATION	897	892	891	891	891	891	891	893	895	896
APPROX DEPTH FROM EXISTING	3'	9'	9'	9'	7'	8'	7'	6'	3'	3'
LOCATION	ELL									
NOTES	P-NORTH	E-COMM	P-DITCH	P-RL	P-DITCH	P-RL	P-DITCH	P-RL	P-DITCH	P-ROW
	ROW		NORTH-WB	WB	MEDIAN	EB	EAST	MUT	S-MUT	SOUTH

JULIUS DRIVE CROSSING APPROX. STATION 44JUL+10 SHEET 5

STATION	44+10	44+10	44+10	44+10	44+10	44+10	44+10	44+10
OFFSET	LT 43'	0	RT 8'	RT 27'	RT 41'	RT 44'	RT 47'	RT 70'
TOP OF MAIN ELEVATION	880	880	880	880	879	879	879	880
APPROX DEPTH FROM EXISTING	9'	7'	7'	4.5'	7'	7'	7'	7'
LOCATION	ELL							TEE
NOTES	WEST	P-DITCH	E-TELE	E-GAS	E-DITCH	P-RL	P-DITCH	E-SAN
	ROW	NORTH-WB			NORTH	WB	MEDIAN	

STH 15 CROSSING APPROX. STATION 616WB+79 SHEET 5

STATION	616+79	616+79	616+79	616+79	616+79	616+79	616+79	616+79
OFFSET	LT 106'	LT 78'	LT 55'	LT 50'	LT 36'	0	RT 38'	RT 53'
TOP OF MAIN ELEVATION	877	874	874	874	874	874	874	874
APPROX DEPTH FROM EXISTING	4'	7'	7'	7'	4'	9'	7'	5'
LOCATION	TEE							
NOTES	NORTH	P-DITCH	E-TELE	E-GAS	E-DITCH	P-RL	P-DITCH	E-SAN
	ROW	NORTH-WB			NORTH	WB	MEDIAN	

STH 15 CROSSING APPROX. STATION 616WB+79 SHEET 5 CONTINUED

STATION	616+79	616+79	616+79	616+79				
OFFSET	RT 60'	RT 74'	RT 92'	RT 103'				
TOP OF MAIN ELEVATION	874	874	874	874				
APPROX DEPTH FROM EXISTING	5'	5'	4'	5'				
LOCATION				ELL				
NOTES	P-RL	E-WATER	E-WATER	SOUTH				
	EB			ROW				

LILY OF THE VALLEY DRIVE CROSSING (NORTH) APPROX. STATION 16LOTV+14 SHEET 14

STATION	16+30	16+30	16+30	16+30	16+30	16+30	16+30	16+30	16+30	
OFFSET	LT 38'	LT 27'	LT 18'	0	RT 9'	RT 15'	RT 22'	RT 35'	RT 50'	
TOP OF MAIN ELEVATION	817	817	817	817	817	817	817	817	817	
APPROX DEPTH FROM EXISTING	3'	3'	4'	4'	4'	4'	4'	4'	4'	
LOCATION	ELL							TEE	ELL	
NOTES	WEST	E-FIBER	E-SAN	P-RL	E-STORM	E-WATER	ABDN	P-GAS	EAST	
	ROW			JUL			GAS		ROW	

STH 15 CROSSING APPROX. STATION 654WB+12 SHEET 14

STATION	654+12	654+12	654+12	654+12	654+12	654+12	654+12	654+12
OFFSET	LT 114'	LT 78'	LT 71'	LT 44'	LT 38'	0	RT 43'	RT 75'
TOP OF MAIN ELEVATION	817	817	817	821	821	821	817	816
APPROX DEPTH FROM EXISTING	4'	5'	5'	4'	4'	4'	7	6'
LOCATION	TEE							
NOTES	NORTH	E-ELEC	E-FIBER	E-COMM	ABDN	P-RL	P-STO	E-WATER
	ROW				GAS	WB	CAUTION	


STH 15 CROSSING APPROX. STATION 654WB+12 SHEET 14

STATION	654+12	654+12	654+12					
OFFSET	RT 84'	RT 108'	RT 141'					
TOP OF MAIN ELEVATION	818.5	819	822					
APPROX DEPTH FROM EXISTING	6.5'	6'	4'					
LOCATION			TEE					
NOTES	E-SAN	E-STO	SOUTH					
			END					

LILY OF THE VALLEY DRIVE CROSSING (SOUTH) APPROX. STATION 13LOTV+71 SHEET 12

STATION	13+71	13+71	13+71	13+71	13+71	13+71	13+71	13+71
OFFSET	RT 47'	RT 30'	RT 25'	RT 17'	0	LT 21'	LT 27'	LT 35'
TOP OF MAIN ELEVATION	821	821	821	821	821	820	818	819
APPROX DEPTH FROM EXISTING	4'	4.5'	4'	4'	4'	4'	4'	4'
LOCATION	TEE							
NOTES	EAST	E-ELEC	E-STO	E-WATER	P-RL	E-SAN	E-DITCH	WEST
	ROW				LOTV			END





**TRAFFIC CONTROL LEGEND**

WORK AREA	ARROWBOARD
TEMP. SIGN SUPPORT	
TRAFFIC CONTROL DRUM WITH LIGHT	
TRAFFIC CONTROL DRUM WITHOUT LIGHT	
42" GRABBER CONE	
FLAGGER	
TYPE III BARRICADE WITH ATTACHED SIGN	






**NOTES**

- RIGHT LANE CLOSURES ALONG GREENVILLE DR/STH 15, EASTBOUND & WESTBOUND.
  - FLAGGING SETUP ALONG LILY OF THE VALLEY DR.
- Note:**  
Flaggers will move & setup signs according to crew location.
- REFERENCE DOT S.D.D. 15 C 12-4  
REFERENCE DOT S.D.D. 15 D 20-4


Primoris Services Corporation Q3 Contracting: 262-522-8015	Q3 JOB NO: 2531000
	PROJECT/P.O.#: 4459720   IO#MRL21501630
	PREPARED BY: ASHLEY OLSON
DATE PREPARED: 02/24/2020	STAGING TIME: 1 HOUR
CUSTOMER NAME: WE ENERGIES (WISC)	ORDERED BY: GREG SMEDEMA
PROJECT LOCATION: STH 15 & NORTH RD	
CITY: ELLINGTON	
WORK DESCRIPTION: PAVING RELOCATION	







TRAFFIC CONTROL LEGEND		NOTES		PSC Primoris Services Corporation Q3 Contracting: 262-522-8015		Q3 JOB NO: 2531000	
	WORK AREA	<ul style="list-style-type: none"><li>• SHOULDER CLOSURE ALONG GREENVILLE DR/STH 15.</li><li>• FLAGGING SETUP ALONG JULIUS DR.</li></ul> <div><b>Note:</b> Flaggers will move &amp; setup signs according to crew location.</div> <div>REFERENCE DOT S.D.D. 15 C 12-4</div> <div>REFERENCE DOT S.D.D. 15 D 27-3</div>		PROJECT/P.O.#: 4459720   IO#MRL21501630		PREPARED BY: ASHLEY OLSON	
	TEMP. SIGN SUPPORT			DATE PREPARED: 02/24/2020		STAGING TIME: 1 HOUR	
	TRAFFIC CONTROL DRUM WITHOUT LIGHT			CUSTOMER NAME: WE ENERGIES (WISC)		ORDERED BY: GREG SMEDEMA	
	42" GRABBER CONE			PROJECT LOCATION: STH 15 & NORTH RD			
	FLAGGER			CITY: ELLINGTON			
				WORK DESCRIPTION: PAVING RELOCATION			




































<div>WE ENERGIES - GAS OPERATIONS</div> <div>Unless otherwise noted in this document, the following notes apply: Existing facilities should be field verified prior to excavation. Utility information shown are from plans and have not been field verified. Maintain 12" min vertical clearance at crossing of existing electrical facilities. Maintain 6" min vertical clearance at crossing of other existing facilities. Maintain 18" min vertical clearance at crossing of existing storm sewer pipes. Maintain 5' clearance from storm sewer inlets. Staking of route or ROW by surveyor required prior to construction. Clearances shown are min distances - reference permit for specific clearance requirements. Additional information on excavation, backfilling &amp; clearances can be found in the Gas CRS 201. Restore all pavement, ROW, sidewalks, and customer's private property.</div>		<div>CONVENTIONAL SYMBOLS</div> <div><div><div></div><div>END OF MAIN CAPPED WITH AN ANODE ATTACHED TO THE TRACER WIRE - 2' x 4' EXCAVATION.</div></div><div><div></div><div>VALVE IN AN 8" DIAMETER METALLIC BOX SET TO GRADE</div></div><div><div></div><div>17# ANODE ATTACHED TO THE MAIN IN THE SAME TRENCH</div></div><div><div></div><div>GAS MAIN CUT OFF AND CAPPED 4' x 5' EXCAVATION</div></div><div><div></div><div>METER CHANGE</div></div><div><div></div><div>TEST &amp; RECONNECT SERVICE</div></div><div><div></div><div>REPLACE SERVICE</div></div></div>	
<div>EROSION CONTROL LEGEND</div> <div><div><div></div><div>APPROXIMATE LOCATION FOR UNDERGROUND FACILITY EXCAVATION</div></div><div><div></div><div>INLET PROTECTION, TYPE A/B/C/D</div></div><div><div></div><div>12" WATTLE or 12"/20" SEDIMENT LOG or 9.5"/20" EROSION EEL</div></div><div><div></div><div>STONE DITCH CHECK</div></div><div><div></div><div>ROCK BAG</div></div><div><div></div><div>MULCH</div></div><div><div></div><div>SOIL STABILIZER, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE A URBAN</div></div><div><div></div><div>EROSION MAT CLASS I, TYPE B URBAN</div></div><div><div></div><div>EROSION MAT CLASS II</div></div><div><div></div><div>EROSION MAT CLASS III</div></div><div><div></div><div>VEGETATIVE BUFFER</div></div><div><div></div><div>TRACKING PAD</div></div><div><div></div><div>TIMBER MAT</div></div><div><div></div><div>SILT FENCE</div></div><div><div><div><div>TSB</div></div></div><div>TEMPORARY SEDIMENT BASIN</div></div><div><div></div><div>SURFACE WATER FLOW</div></div></div>		<div>WE ENERGIES WORK REQUEST ENVIRONMENTAL NOTES (Notes 1 through 7 apply to ALL work requests)</div> <div><div><div>General</div><div><div>1. If WDNR and/or USACE permits were obtained for the project, all permit conditions shall be met during construction of the project.</div><div>Erosion Control</div><div><div>2. If soil disturbance occurs on slopes or channels/ditches leading to wetlands or waterways, or within wetlands, the disturbed areas shall be stabilized and appropriate erosion control Best Management Practices (BMP's) shall be implemented.</div><div>3. Erosion Control BMP's shall meet or exceed the approved WDNR Storm Water Management Technical Standards (<a href="http://dnr.wi.gov/topic/stormwater/standards/const_standards.html">http://dnr.wi.gov/topic/stormwater/standards/const_standards.html</a>). Refer to We Energies Construction Site Sediment and Erosion Control Standards.</div><div>4. Inspect installed erosion control BMP's at least one time per week and after ½" rain events: repair as necessary.</div><div>5. When temporary stabilization is required (e.g. for winter or short-term construction) prior to final restoration, soil stabilizer shall be installed wherever possible. Erosion mat shall be used temporarily only where appropriate, in accordance with state standards, and when approved by the Operations Supervisor.</div></div></div><div><div>Contaminated Soils</div><div><div>6. Whenever soil exhibiting obvious signs of contamination (e.g., discoloration, petroleum or solvent odor, free liquids other than water, buried containers or tanks, or other obvious signs of environmental impacts) is encountered during excavation or installation, cease work immediately, take appropriate immediate precautions to ensure worker health and safety, and contact the Operations Supervisor or Inspector.</div></div></div><div><div>Spills</div><div><div>7. If an oil spill occurs during construction, call the Environmental Incident Response Team (EIRT) at 414-430-3478:<div><div>a. Any quantity of oil is spilled into surface water;</div><div>b. Any oil spill greater than 50 ppm PCB into a sewer, vegetable garden, or grazing land;</div><div>c. Any oil spill containing greater than 500 ppm PCB;</div><div>d. Five gallons or more of oil spilled to the ground;</div><div>e. Any oil spill involving a police department, fire department, DNR, or concerned property owner.</div></div></div></div></div><div><div>Notes 8 through 27 apply as noted at specific points within each work request:</div></div><div><div>Dewatering</div><div><div>8. Dewatering of pits or trenches shall be done in accordance with state standards. Use an approved sediment bag, a straw bale dewatering basin, a combination of both, or equivalent.</div></div></div><div><div>Wetlands</div><div><div>9. As much as practicable, the majority of the work shall be staged from the public roadways and road shoulders, keeping equipment out of adjacent wetlands.</div><div>10. All work shall be conducted to minimize soil disturbance. No rutting will be allowed within the wetlands.</div><div>11. If soils are not frozen or stable to a point that avoids rutting, timber mats, mud tracks, or equivalent shall be utilized to access pole locations.</div><div>12. Excavated soils cannot be stockpiled in wetlands.</div></div></div><div><div>13. All excess spoils shall be removed from wetlands and placed in a suitable upland location.</div><div>14. Trenching and pit excavations within wetlands shall include soil segregation to facilitate restoration of pre-construction soil stratification, and restoration to pre-construction elevations.</div><div>15. Poles scheduled to be removed, and that occur within wetland, shall be cut at the ground surface.</div><div><div>Waterways</div><div><div>16. No work can be performed within the banks or below the ordinary high watermark of any navigable waterways/streams.</div><div>17. No crossing of navigable waterways with equipment can occur. Foot traffic is allowed.</div><div>18. Any disturbed soil within 75-feet of the ordinary high water mark of any navigable waterways/streams shall be stabilized within 24 hours of construction completion.</div></div></div><div><div>Threatened and Endangered Species</div><div><div>19. Threatened or endangered species are known to occur in the work area. It is illegal to harass, harm, or kill a protected species under state and federal regulations. Proper precautions shall be taken to ensure harm to individuals is avoided.</div><div>20. In order to protect the threatened or endangered species, work must be conducted between November 5 and March 15.</div><div>21. Exclusion fencing must be installed at the work area prior to March 15.</div><div>22. A qualified biologist must be present when conducting work at this location.</div></div></div><div><div>Invasive Species</div><div><div>23. State regulated invasive species are known to occur in the work area. Reasonable precautions are legally required to prevent the spread of these species. The Wisconsin Council on Forestry Transportation and Utility Right-of Way Best Management Practices should be followed: (<a href="http://council.wisconsinforestry.org/invasives/transportation/">http://council.wisconsinforestry.org/invasives/transportation/</a>).</div></div></div><div><div>Cultural and Historical Resources, cont.</div><div><div>24. The project is within or adjacent to an area that is identified by the State of Wisconsin as potentially having Native American artifacts, burial mounds or burial sites, which could be encountered during construction.</div><div>25. If human bone or any artifacts are discovered during construction, work must cease immediately. Contact the Environmental Department who will contact the State Burial Sites Preservation Office and determine the next steps that must be taken in order to comply with state law. Work at that site MAY NOT PROCEED until the Environmental Department authorizes it.</div><div>26. A "qualified archaeologist," as specified under Wis. Stats 157.70 (1) (i) and Wis. Admin. Code HS 2.04 (6), must be present to monitor all ground disturbing activities.</div></div></div><div><div>Frac-out Contingency Plan</div><div><div>27. A frac-out contingency plan shall be on-site and implemented accordingly. The contingency plan shall incorporate the following components.<div><div>a. Continuously inspect the bore paths for frac-outs in order to respond quickly and appropriately.</div><div>b. Containment materials (e.g. silt fence, straw bales, sand bags, etc.) shall be on site and available should a frac-out occur.</div></div></div></div></div></div></div></div>	





# SDD 15D28 Traffic Control, Work on Shoulder or Parking Lane, Undivided Roadway

## LEGEND

- SIGN ON PERMANENT SUPPORT
- TRAFFIC CONTROL DRUM
- DIRECTION OF TRAFFIC
- WORK ZONE

If shoulder closure encroaches onto or over the travel way edgeline, a lane closure with flagging should be utilized instead.

TABLE A

SHOULDER TAPER LENGTH (FEET)					BUFFER SPACE (FEET)
S \ W	4	6	8	10	
30	20	30	40	50	200
35	30	45	55	70	250
40	40	55	75	90	305
45	60	90	120	150	360
50	70	100	135	170	425
55	75	110	150	185	495

W = SHOULDER WIDTH (FEET)  
S = NON-CONSTRUCTION SPEED LIMIT (MPH)

TAPER LENGTH

L = WS AT 45 MPH OR GREATER  
L = WS<sup>2</sup> / 60 AT 40 MPH OR LESS

SHOULDER TAPER LENGTH = 1/3L

## GENERAL NOTES

ALL SIGNS ARE 48"X48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS IN URBAN AREAS, 36" X 36" SIGNS MAY BE USED IF APPROVED BY THE REGIONAL TRAFFIC UNIT.

"WO" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH THE TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

CHANNELIZING DEVICES PLACED ADJACENT TO WORK AREA SHALL BE PULLED BACK FROM THE TRAVEL LANE WHEN WORK IS NOT IN PROGRESS.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.


W20-1A AND G20-2A SIGNS ARE NOT REQUIRED IF THE WORK AREA IS WITHIN A LARGER WORK ZONE WHERE THESE SIGNS ARE ALREADY RESENT. G20-2A SIGNS MAY ALSO BE OMITTED IF DURATION OF WORK IS LESS THAN 7 CONTINUOUS DAYS AND NIGHTS.

6

SDD 15D28 - 03

6

SDD 15D28 - 03



### TRAFFIC CONTROL, WORK ON SHOULDER OR PARKING LANE, UNDIVIDED ROADWAY

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
August 2019  
DATE  
/S/ Andrew Heidtke  
STATEWIDE WORK ZONE TRAFFIC  
SAFETY ENGINEER

FHWA