


PROJECT ID: 8949-05-72

COUNTY: DUNN

ORDER OF SHEETS

Section No. 1	Title
Section No. 2	Typical Sections and Details
Section No. 3	Estimate of Quantities
Section No. 3	Miscellaneous Quantities
Section No. 4	Right of Way Plat
Section No. 5	Plan and Profile
Section No. 6	Standard Detail Drawings
Section No. 7	Sign Plates
Section No. 8	Structure Plans
Section No. 9	Computer Earthwork Data
Section No. 9	Cross Sections

TOTAL SHEETS =



DESIGN DESIGNATION


A.A.D.T.	2018	=	1900
A.A.D.T.	2038	=	2400
D.H.V.		=	72
D.D.		=	60/40
T.		=	3.6%
DESIGN SPEED		=	60 MPH
ESALS		=	150,000

CONVENTIONAL SYMBOLS


PLAN	
CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE	
GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	


	ROCK
	LABEL
	95.36
	310TH ST
	315TH ST
	320TH ST
	45TH AVE
	ST
	6TH ST
	80TH ST
	106TH ST
	155TH ST
	171ST ST
	130TH ST
	140TH ST
	150TH ST
	160TH ST
	170TH ST
	180TH ST
	190TH ST
	200TH ST
	210TH ST
	220TH ST
	230TH ST
	240TH ST
	250TH ST
	260TH ST
	270TH ST
	280TH ST
	290TH ST
	300TH ST
	310TH ST
	320TH ST
	330TH ST
	340TH ST
	350TH ST
	360TH ST
	370TH ST
	380TH ST
	390TH ST
	400TH ST
	410TH ST
	420TH ST
	430TH ST
	440TH ST
	450TH ST
	460TH ST
	470TH ST
	480TH ST
	490TH ST
	500TH ST
	510TH ST
	520TH ST
	530TH ST
	540TH ST
	550TH ST
	560TH ST
	570TH ST
	580TH ST
	590TH ST
	600TH ST
	610TH ST
	620TH ST
	630TH ST
	640TH ST
	650TH ST
	660TH ST
	670TH ST
	680TH ST
	690TH ST
	700TH ST
	710TH ST
	720TH ST
	730TH ST
	740TH ST
	750TH ST
	760TH ST
	770TH ST
	780TH ST
	790TH ST
	800TH ST
	810TH ST
	820TH ST
	830TH ST
	840TH ST
	850TH ST
	860TH ST
	870TH ST
	880TH ST
	890TH ST
	900TH ST
	910TH ST
	920TH ST
	930TH ST
	940TH ST
	950TH ST
	960TH ST
	970TH ST
	980TH ST
	990TH ST
	1000TH ST
	1010TH ST
	1020TH ST
	1030TH ST
	1040TH ST
	1050TH ST
	1060TH ST
	1070TH ST
	1080TH ST
	1090TH ST
	1100TH ST
	1110TH ST
	1120TH ST
	1130TH ST
	1140TH ST
	1150TH ST
	1160TH ST
	1170TH ST
	1180TH ST
	1190TH ST
	1200TH ST
	1210TH ST
	1220TH ST
	1230TH ST
	1240TH ST
	1250TH ST
	1260TH ST
	1270TH ST
	1280TH ST
	1290TH ST
	1300TH ST
	1310TH ST
	1320TH ST
	1330TH ST
	1340TH ST
	1350TH ST
	1360TH ST
	1370TH ST
	1380TH ST
	1390TH ST
	1400TH ST
	1410TH ST
	1420TH ST
	1430TH ST
	1440TH ST
	1450TH ST
	1460TH ST
	1470TH ST
	1480TH ST
	1490TH ST
	1500TH ST
	1510TH ST
	1520TH ST
	1530TH ST
	1540TH ST
	1550TH ST
	1560TH ST
	1570TH ST
	1580TH ST
	1590TH ST
	1600TH ST
	1610TH ST
	1620TH ST
	1630TH ST
	1640TH ST
	1650TH ST
	1660TH ST
	1670TH ST
	1680TH ST
	1690TH ST
	1700TH ST
	1710TH ST
	1720TH ST
	1730TH ST
	1740TH ST
	1750TH ST
	1760TH ST
	1770TH ST
	1780TH ST
	1790TH ST
	1800TH ST
	1810TH ST
	1820TH ST
	1830TH ST
	1840TH ST
	1850TH ST
	1860TH ST
	1870TH ST
	1880TH ST
	1890TH ST
	1900TH ST
	1910TH ST
	1920TH ST
	1930TH ST
	1940TH ST
	1950TH ST
	1960TH ST
	1970TH ST
	1980TH ST
	1990TH ST
	2000TH ST
	2010TH ST
	2020TH ST
	2030TH ST
	2040TH ST
	2050TH ST
	2060TH ST
	2070TH ST
	2080TH ST
	2090TH ST
	2100TH ST
	2110TH ST
	2120TH ST
	2130TH ST
	2140TH ST
	2150TH ST
	2160TH ST
	2170TH ST
	2180TH ST
	2190TH ST
	2200TH ST
	2210TH ST
	2220TH ST
	2230TH ST
	2240TH ST
	2250TH ST
	2260TH ST
	2270TH ST
	2280TH ST
	2290TH ST
	2300TH ST
	2310TH ST
	2320TH ST
	2330TH ST
	2340TH ST
	2350TH ST
	2360TH ST
	2370TH ST
	2380TH ST
	2390TH ST
	2400TH ST
	2410TH ST
	2420TH ST
	2430TH ST
	2440TH ST
	2450TH ST
	2460TH ST
	2470TH ST
	2480TH ST
	2490TH ST
	2500TH ST
	2510TH ST
	2520TH ST
	2530TH ST
	2540TH ST
	2550TH ST
	2560TH ST
	2570TH ST
	2580TH ST
	2590TH ST
	2600TH ST
	2610TH ST
	2620TH ST
	2630TH ST
	2640TH ST
	2650TH ST
	2660TH ST
	2670TH ST
	2680TH ST
	2690TH ST
	2700TH ST
	2710TH ST
	2720TH ST
	2730TH ST
	2740TH ST
	2750TH ST
	2760TH ST
	2770TH ST
	2780TH ST
	2790TH ST
	2800TH ST
	2810TH ST
	2820TH ST
	2830TH ST
	2840TH ST
	2850TH ST
	2860TH ST
	2870TH ST
	2880TH ST
	2890TH ST
	2900TH ST
	2910TH ST
	2920TH ST
	2930TH ST
	2940TH ST
	2950TH ST
	2960TH ST
	2970TH ST
	2980TH ST
	2990TH ST
	3000TH ST
	3010TH ST
	3020TH ST
	3030TH ST
	3040TH ST
	3050TH ST
	3060TH ST
	3070TH ST
	3080TH ST
	3090TH ST
	3100TH ST
	3110TH ST
	3120TH ST
	3130TH ST
	3140TH ST
	3150TH ST
	3160TH ST
	3170TH ST
	3180TH ST
	3190TH ST
	3200TH ST
	3210TH ST
	3220TH ST
	3230TH ST
	3240TH ST
	3250TH ST
	3260TH ST
	3270TH ST
	3280TH ST
	3290TH ST
	3300TH ST
	3310TH ST
	3320TH ST
	3330TH ST
	3340TH ST
	3350TH ST
	3360TH ST
	3370TH ST
	3380TH ST
	3390TH ST
	3400TH ST
	3410TH ST
	3420TH ST
	3430TH ST
	3440TH ST
	3450TH ST
	3460TH ST
	3470TH ST
	3480TH ST
	3490TH ST
	3500TH ST
	3510TH ST
	3520TH ST
	3530TH ST
	3540TH ST
	3550TH ST
	3560TH ST
	3570TH ST
	3580TH ST
	3590TH ST
	3600TH ST
	3610TH ST
	3620TH ST
	3630TH ST
	3640TH ST
	3650TH ST
	3660TH ST
	3670TH ST
	3680TH ST
	3690TH ST
	3700TH ST
	3710TH ST</




EXISTING TYPICAL SECTION  
 STA. 71+00 - STA. 74+11.95  
 STA. 75+07.05 - STA. 78+53




EXISTING TYPICAL SECTION  
 STA. 74+11.95 - STA. 75+07.05  
 STA. 76+10.91 - STA. 77+29.66




FINISHED TYPICAL SECTION  
 STA. 71+00 - STA. 75+03.42 LT.  
 STA. 71+00 - STA. 72+90.40 RT.  
 STA. 77+29.66 - STA. 78+52.75 RT.  
 STA. 78+23.79 - STA. 79+59.96 LT.




FINISHED TYPICAL SECTION  
 STA. 72+90.40 - STA. 75+03.72 RT.  
 STA. 76+15.33 - STA. 77+29.66 RT.  
 STA. 76+15.33 - STA. 78+23.79 LT.




106TH STREET EXISTING TYPICAL SECTION




106TH STREET FINISHED TYPICAL SECTION  
STA. 11+74 - STA. 12+97.38







106TH STREET FINISHED TYPICAL SECTION  
STA. 10+67 - STA. 11+74





106TH STREET FINISHED TYPICAL SECTION  
STA. 10+18 - STA. 10+67











PROJECT NO: 8949-05-72	HWY: USH 12	COUNTY: DUNN	PLAN AND PROFILE: WILSON CREEK BRIDGE	SHEET	E
------------------------	-------------	--------------	---------------------------------------	-------	---



5



5



DESIGN DATA

**LIVE LOAD:**  
DESIGN LOADING: HL-93  
INVENTORY RATING FACTOR: RF =  
OPERATING RATING FACTOR: RF =  
WISCONSIN STANDARD PERMIT VEHICLE (WIS.-SPV): (KIPS)

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

**MATERIAL PROPERTIES:**  
CONCRETE MASONRY:  
SUPERSTRUCTURE & STRUCTURAL APPROACH SLAB —  $f'_c$  = 4,000 P.S.I.  
ALL OTHER —  $f'_c$  = 3,500 P.S.I.

BAR STEEL REINFORCEMENT:  
GRADE 60 —  $f_y$  = 60,000 P.S.I.  
STAINLESS, GRADE 60 —  $f_y$  = 60,000 P.S.I.

45W" PRESTRESSED GIRDERS:  
CONCRETE MASONRY —  $f'_c$  = P.S.I.  
STRANDS: 0.6" DIA. WITH ULTIMATE TENSILE STRENGTH OF 270,000 P.S.I.

FOUNDATION DATA

ABUTMENTS TO BE SUPPORTED ON PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF TONS \*\* PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA, ESTIMATED LONG.

\*\* THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE DRIVEN PILE CAPACITY.

HYDRAULIC DATA

**100 YEAR FREQUENCY**  
 $Q_{100}$  = 2,893 C.F.S.  
VEL. = 7.60 F.P.S.  
HW.<sub>100</sub> = EL. 944.92  
WATERWAY AREA = 380 SQ. FT.  
DRAINAGE AREA = 10.10 SQ. MI.  
ROADWAY OVERTOPPING = N/A  
SCOUR CRITICAL CODE = 8

TRAFFIC VOLUME

**USH 12**  
ADT = 2,400 (2038)  
R.D.S. = 60 M.P.H.

CURVE DATA

**USH 12**  
P.I. = STA. 75+72.62  
 $\Delta$  = 28°57'09"  
D = 3°01'53"  
T = 487.95'  
L = 955.05'  
R = 1890.00'  
P.C. = STA. 70+84.67  
P.T. = STA. 80+39.72

2 YEAR FREQUENCY

$Q_2$  = 625 C.F.S.  
VEL. = 3.8 F.P.S.  
HW.<sub>2</sub> = EL. 941.82

LOCATION	DIM. A
W. ABUT.	0'-10 $\frac{3}{4}$ "
E. ABUT.	0'-8 $\frac{3}{4}$ "


TANGENT OFFSET  
DETAIL & TABLE

PRELIMINARY PLAN

**STRUCTURE DESIGN CONTACTS:**  
JONATHON RESHESKE (608) 266-8491  
LAURA SHADEWALD (608) 267-9592


LIST OF DRAWINGS

1. GENERAL PLAN
2. CROSS SECTION & QUANTITIES
3. CONSTRUCTION STAGING

NO.	DATE	REVISION	BY
 <b>BUREAU OF STRUCTURES</b>			
ACCEPTED CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
<b>STRUCTURE B-17-206</b>			
USH 12 OVER WILSON CREEK			
COUNTY	DUNN	TOWN	STANTON
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS			
DESIGNED BY	DESIGNED CK'D.	DRAWN BY	PLANS CK'D.
JLR	JDM	JLR	JDM
<b>GENERAL PLAN</b>			SHEET 1 OF 2


\* PROVIDE FOR THREE BEAM GUARD RAIL ATTACHMENT AT UNUSED ANCHOR ASSEMBLIES CAULK HOLES SHUT WITH "100% SILICONE CAULK".

⊙ INDICATES WING NUMBER



GENERAL NOTES


- DRAWINGS SHALL NOT BE SCALED.
- BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.
- THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.
- BEVEL EXPOSED EDGES OF CONCRETE  $\frac{3}{4}$ " UNLESS OTHERWISE NOTED.
- AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL.
- EXCAVATION BELOW THE ABUTMENT AND USE OF ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.
- THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS.
- ELASTOMERIC BEARING PADS NEED NOT BE INDIVIDUALLY MOLDED PROVIDED THE CUT EDGES ARE SMOOTH AND TRUE.
- PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE ENTIRE EXPOSED TOP OF DECK AND TO THE VERTICAL AND HORIZONTAL SURFACES OF THE PAVING NOTCHES AT ABUTMENT DIAPHRAGMS.
- PIGMENTED PROTECTIVE SURFACE SEALER TO BE APPLIED TO THE FRONT FACE AND THE TOP OF THE PARAPETS.
- THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TYPE "HR" TO THE EXTENT SHOWN ON SHEET 1 AND THE ABUTMENT DETAILS.
- THE HAUNCH CONCRETE QUANTITY IS BASED ON THE AVERAGE HAUNCH SHOWN ON THE "45W PRESTRESSED GIRDER DETAILS 2" SHEET.



SECTION THRU ROADWAY  
(LOOKING UPSTATION)

TOTAL ESTIMATED QUANTITIES


BID ITEM NUMBER	BID ITEMS	UNIT	SUPER.	WEST ABUT.	EAST ABUT.	TOTALS
203.0600.S	REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS STA. 75+60.00±	LS	—	—	—	1
206.1000	EXCAVATION FOR STRUCTURES BRIDGES B-17-206	LS	—	—	—	1
210.1500	BACKFILL STRUCTURE TYPE A	TON				
502.0100	CONCRETE MASONRY BRIDGES	CY				
502.3200	PROTECTIVE SURFACE TREATMENT	SY				
502.3210	PIGMENTED SURFACE SEALER	SY				
503.0146	PRESTRESSED GIRDER TYPE I 45W-INCH	LF				
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB				
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB				
506.2605	BEARING PADS ELASTOMERIC NON-LAMINATED	EACH				
506.4000	STEEL DIAPHRAGMS B-17-206	EACH				
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY				
550.11XX	PILING STEEL HP 1X-INCH X XX LB	LF				
606.0300	RIPRAP HEAVY	CY				
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF				
614.0150	ANCHOR ASSEMBLIES FOR STEEL PLATE BEAM GUARD	EACH				
645.0120	GEOTEXTILE TYPE HR	SY				
	NON-BID ITEMS					
	BRIDGE SEAT PROTECTION	L.S.	—	—	—	1
	FILLER	SIZE	—	—	—	1/2", 3/4"



TYPICAL SECTION  
THRU ABUTMENT

(A1 ABUTMENT WITHOUT STRUCTURAL APPROACH)

- ▲ BACKFILL PAY LIMITS. BACKFILL BEYOND BACKFILL PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.
- PIPE UNDERDRAIN WRAPPED (6 INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.



PROFILE GRADE LINE - USH 12

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-17-206			
		DRAWN BY JLR	PLANS CK'D. JDM
CROSS SECTION & QUANTITIES		SHEET 2	