ENGLISH - STREAM CROSSING STRUCTURE SURVEY REPORT Wisconsin Department of Transportation DT1698 1/2002 (Replaces EB53) ☐ Other Right ☐ Box Culvert Culvert Extension ☐ Left Preliminary Plan Due Date Final Plan Due Date Town of (N/A for Culverts) Village of Milwaukee 9/6/2002 Design Project ID County New Structure Number Highway 1060-05-03 Milwaukee B-40-1412-004 **IH 794** Construction Project ID Aesthetics Level (For Levels 2, 3 & 4, Explain on Page 4) **⊠** 3 TBD □ 2 Section Town Range Station 22E 730+00 29

Identify Stream (If Applicable)

Traffic Forecast Data

55

Roadway

Design

Speed

mph

Functional Class

Urban Principal

Arterial-Freeway

Average Daily

Traffic (ADT)

42.800

Milwaukee River

Design Year

Instructions for Structure Survey

In addition to this report, the following information shall be submitted.

1. Small County Map on which the location of proposed structure is shown in red and highway relocation, if any, in green.

2025

- Plan and Profile Sheet on proposed reference line of highway showing the following: (a) Ground line; (b) Finished grade line;
 (c) Profile grade line elevations at least every 100 feet for 1,000 feet each side of the structure; (d) Vertical curve control points; (e) Horizontal curve control points; (f) Curve data, including full SE and runoff distance.
- 3. Contour Map of the site drawn to a scale of not less than 1" = 20 feet with one-foot contours and showing the following (a) Existing highway and structure; (b) Proposed highway alignment and R/W; (c) Station numbers; (d) North point; (e) Buildings; (f) Underground facilities; (g) Other features which influence the design; (h) Recommended channel change; (i) Direction of stream flow; (j) Stations at end of existing structure; (k) Proposed structure and extent of riprap for consultant designed structures.
- 4. Typical Roadway Cross Section of proposed approaches showing the following: (a) Dimensions; (b) Slopes; (c) Type and width of surfacing or pavement; (d) Sidewalk, curb and gutter; (e) Subgrade and pavement thickness; (f) Clear zone width.
- 5. **Stream Cross Section** at upstream and downstream face of existing bridge and at one bridge length upstream and downstream. Surface water elevations at 1500 feet upstream and downstream of existing bridge.
- Original Photographs of: (a) Existing structure; (b) Upstream and downstream structures; (c) Buildings within 100 feet of the proposed structure; (d) Unobstructed panoramic view looking upstream and downstream from proposed structure. *Air photo mosaics if available.*
- 7. **Proposed Location Map** showing structure location and number, one per structure when there are multiple structures on the project.
- 8. Attach a copy of the regulatory flood plain map (FEMA map) depicting the site.

Indicate Purpose

David Nguyen

262/548-6725

Mark Maday

414/212-4400 x241

Waterway

Other (Describe) Overpass

District Contact Person/Area Code with Telephone Number

Consultant Contact Person/Area Code with Telephone Number

9. For consultant designed structures - Hydraulic Report which may contain the following: (a) USGS quadrangle sheet showing proposed location, highway alignment and reach of river; (b) All available flood history, high water marks with date of occurrence, nature of flooding, damages and scour information; (c) Factors affecting water stages; (d) Navigation Clearance, for guidance in making report, see Chapter 8 of Bridge Design Manual; (e) Discussion of alternatives considered, factors influencing selection.

1		oposed Structure				
Preference for Structure Type at the 48" Steel Plate Girder with C.I.		Check here if to be de	etermined by Central	Office		
Roadway Width Between Curbs		Cross Slope on De N.C. (0.02) Ft./F	ck or N.C. (Normal Crown)		
68 Ft. Sidewalks - Number		Sidewalk Clear Wi				
None	Durant Attach mont	N/A Ft.	on Roam Guard not I lead	on Culvert		
Specify Wing Location for Beam (N/A	Suard Attachment	Specify Clear Zone Width when Beam Guard not Used on Culvert N/A				
Specify Wing Location for Surface See Page 4	Drain Anchors	Specify Wing Location where N/A	Bridge Barrier/Rail Contine	ues on Roadway Approach		
YES NO		YES NO				
☐ Is Project in Flood Hazard Area		Structur	re Backfill Required			
(If not, Plea	Have Soil Borings been Requested (If not, Please Explain on Page 4)		Lighting Required on Bridge			
☐ ☐ Staged Construction ☐ Temporary Structure Required			t Circle Diameter mm mber for Barrel Recommended			
ы гетрогату эпистите Required		(Culver	t only)			
Proposed Disposition of Ex	isting Structure		oroject on the Madorial i	igilway Cystoni.		
YES NO						
	re will be Removed n will be included in Struc	ture Plan Quantities				
Structu	re will remain in Service	Structure Number B-40				
·		s Unit "Site Investigation Rep	ort"			
If utilities will be carried on the Type Size	e structure, complete the t Opening S	following data. Size at Abutments	Weight	Pressure		
1,7,5						
	For St	ructure Designers Us	e ''			
		oposed Box Culvert				
Aprons	Type 🛪		Elevations			
Inlet	The second secon	A Company of the Comp				
Outlet	Section 1997 Annual Sectio					
Openings - Number	Clear Span at F	Right Angles to Axis of Box	Inside Height of E	Box		
Slope of Channel at Culvert						
Spans - Number	Spans Lengths 93' -122' - 89'	Proposed Structures (G.L. to C.L. of Substructure)	Skew None	KH.E. 🔲 LH.E.		
Drainage Area 682	97 - 1-10 H35-93 L76-E270 F76-93	14.800 cfs				
		cfs		in in the second of the second		
	Ft/Sec. Q (Rdwy.)	<u> </u>				
	Sq. Ft. Q (Suple. Str		기가 되고 밝혔다면서 이번 시간			
Waterway Area 4910 Scour Code	cq. i kcq. (Sapie. Su					
Temporary Structure	Overtopping	Frequency (If>100Yrs.÷NA	Regulatory Hi	gh Water		
Q Yr.	cfs. Q Yr.	cfs				
High Water	Ft. High Water	Ft.		Ft.		
Min. A (BR)	Sq. Ft.					
and the second s		·				

Existing Structures At or Near Proposed Site

STRUCTURE DATA	UPSTREAM	AT SITE	DOWNSTREAM
Structure Number (B / P / C)	N/A	B-40-285 (36A)	B-40-285 (36B)
Railroad or Highway Structure	Highway	Highway	Highway
Distance from Proposed Site in Miles	0.05		0.01
Type: Superstructure	Steel Girder & Deck	Steel Girder CIP Deck	Steel Girder CIP Deck
Substructure: Abutments	Reinforced Concrete	N/A	N/A
Piers	Reinforced Concrete	Reinforced Concrete	Reinforced Concrete
Is Structure Supported on Bearing Piles?		Yes	
Condition: Superstructure		Fair	
Substructure		Fair	
Year Built	Unknown	1966	1966
Number of Spans	3	3	3
Clear Span (Between Inside Faces of Substructure Units) Lengths Along CL Roadway/Track	50'	116'	116'
Roadway Width Between Curbs		Varies 63' to 69'	57'-6"
Sidewalk: Number		0	
Clear Width		N/A	;
Location		N/A	
Skew: Stream	Unknown	6 degrees	3 degrees
Structure	Unknown	None	None
* Elevation Finished Grade	Unknown	613.47	611.45
+ + Low Chord	Unknown	608.26	606.24
Does Drift Pass Satisfactorily	Unknown	Yes	Yes
Does Ice Pass Satisfactorily	Unknown	Yes	Yes
Character of Material in Stream Bed	Silts	Silts	Silts
** Character of Drainage Basin	50%Urban, 50%Flat	50%Urban, 50%Flat	50%Urban, 50%Flat
Stream-Bed Scour: Visable (Y/N)	N	N	N
Due to Restricted Waterway			
Due to Poor Location			
Due to Improper Skew			
Extreme High Water Elevation - Date	584.30	584.30	584.30
Cause of High Water and Source of Information	Lake Mich High Water	Lake Mich High Water	Lake Mich High Water
Low Water Elevation	578.10	578.10	578.10
Normal Water Elevation	579.60	579.60	579.60
Streambed Elevation	Varies	Varies	Varies
Water Surface Date	1500' Upstream	At Site	1500' Downstream
Elevation ***			

Existing Culvert Information

				
Attach Sketcl Slope of Cha Elevation:	nnel at Structure (ft./100 ft.) Finished Grade Inlet - Invert - Top of Opening Discharge - Invert - Top of Opening		Spans: Width Norma Allowable Hig Floor: Concre Condition:	

- Use same datum for all structures within one-half mile of proposed structure.

 Mountains, Hilly, Rolling, Flat, Swampy, Wooded, Cultivated, Pasture, etc. Give percentage of each.

 Measured along thread of channel.

 Take these elevations at the same station.

Additional Information

Elaborate on other concerns such as: DNR, Local, Aesthetics and Stage Construction

Aesthetics Level

Aesthetics issues are currently being investigated by the Community Sensitive Design committees. Some aesthetic improvements are possible for this structure, but the exact nature and extent are not known at this time.

Deck Drainage

Drainage requirements have not been determined yet. Specific information may not be available until the final design phase.

Soil Borings and Foundation Information

Existing soil borings have been included with the subsurface exploration sheets. However, new soil borings will be taken for this structure during final design. The soils reports and recommendations are not available at this time and foundation types and data are yet to be determined.

Lighting

On-deck lighting requirements have not been yet determined. However, since the Milwaukee area freeways are typically lit, it is likely that lighting will be required on the bridge.

Disposition of Existing Structure

Within the "Core" (the project area south of the Courthouse Annex), 88 bridge units with a combined deck area of approximately 46,000 square yards, will be removed and replaced with a new set of structures in a revised configuration. Bid Items for the structure removals will be included with the appropriate contracts.

Vertical Clearance

The existing navigational opening will be unchanged to maintain both horizontal and vertical clearances.

Utility Information

Freeway Traffic Management System (FTMS) facilities will be carried by the structure. The type, size and location of the FTMS conduits, junction boxes, poles and other appurtenances will be determined during final design. At this time it is known that at least eight 1 ½" diameter conduits (or equivalent) are required. WisDOT and FHWA are currently studying the effects of placing conduits (non-structural voids) with parapets and may place a limit on the number or total volume of conduits that may be allowed. Final conduit and equipment locations will be affected by these limits and conduits in excess of these limits may need to be located within the deck slab or elsewhere on the structure.

On-deck lighting will require some conduits and other equipment to be carried by the structure (in the parapets or elsewhere – see discussion above). Number and sizes to be determined.

It is proposed that the WE Energies high pressure 30" diameter steam line currently carried by the existing IH 794 westbound structure be re-routed to the new eastbound structure to facilitate demolition of the westbound structure. Other non-freeway system utilities (water, gas, etc.) will not be carried by this structure.

	FOR BRIDGE OFFICE USE	
Plans Checked By	Date	