



Soils & Engineering Services, Inc.

April 10, 2019

Project 12939.3 R07

Mr. Jeff Hanson, Project Manager
Dane Partners, LLC
901 Deming Way, Suite 203
Madison, Wisconsin 53717

Subject: Geotechnical Exploration and Analyses Report
Structure B-13-731
(IH-39/90 Northbound Bridge over Northbound Exit Ramp to USH-12/18 Westbound)
Project ID 1007-10-02/05
Illinois State Line - Madison
USH-12/18 Interchange
IH-39
Dane County, Wisconsin

Dear Mr. Hanson

We have completed the requested exploration consisting of the performance of two standard soil borings at the subject site, and the associated laboratory testing and geotechnical engineering analyses. The purpose of these soil borings was to obtain information about the soil, bedrock, and groundwater conditions at the soil boring locations. We present our findings, comments, recommendations, and analyses results in the enclosed *Geotechnical Exploration and Analyses Report* for the subject bridge.

Respectfully submitted,

SOILS & ENGINEERING SERVICES, INC.

Craig M. Bower, P.E.

CMB:DER:cmb

Enclosure


GEOTECHNICAL EXPLORATION AND ANALYSES REPORT

STRUCTURE B-13-731
(IH-39/90 NORTHBOUND BRIDGE OVER NORTHBOUND EXIT RAMP TO
USH-12/18 WESTBOUND)
PROJECT ID 1007-10-02/05
ILLINOIS STATE LINE - MADISON
USH-12/18 INTERCHANGE
IH-39
DANE COUNTY, WISCONSIN
SES Project Number 12939.3

Prepared By

Soils & Engineering Services, Inc.
1102 Stewart Street
Madison, Wisconsin 53713-4648
phone: (608) 274-7600
facsimile: (608) 274-7511
e-mail: soils@soils.ws

Craig M. Bower, P.E.



Submitted To

Dane Partners, LLC
901 Deming Way, Suite 203
Madison, Wisconsin 53717
Phone: (608) 827-8810

Mr. Jeff Hanson, Project Manager

April 10, 2019



TABLE OF CONTENTS

I.	INTRODUCTION	Page 1
II.	PROJECT INFORMATION	Page 1
III.	FIELD EXPLORATION	Page 2
IV.	SOIL AND BEDROCK STRATIGRAPHY	Page 3
V.	GROUNDWATER	Page 4
VI.	LABORATORY AND FIELD TESTS	Page 4
VII.	ANALYSES PROCEDURES, ASSUMPTIONS, & GIVEN INFORMATION	Page 6
	A. Shallow Spread Footing Foundations	Page 6
	B. Deep Driven Pile Foundations	Page 6
	1. Existing IH-39/90 Southbound Structure B-13-461	Page 6
	2. Groundwater Elevations	Page 8
	3. Pile-Supported Footing Base Information	Page 8
	4. Pre-boring	Page 9
	5. Allowable Driving Resistances	Page 9
	6. Design 'Required Driving Resistance' (Rn_{dyn}) and 'Factored Axial Compression Resistance' (P_r)	Page 15
	7. Drivability Evaluation	Page 16
	8. Downdrag Load	Page 17
	C. Lateral Deflection Analyses	Page 18
VIII.	ANALYSES RESULTS	Page 18
	A. Shallow Spread Footing Foundation Analyses	Page 18
	B. Deep Driven Pile Foundation Analyses	Page 18
	C. Lateral Deflection Analyses	Page 21
IX.	BRIDGE CONSTRUCTION	Page 21
	A. Shallow Foundations	Page 21
	B. Deep Foundations	Page 21
	C. General Comments and Recommendations	Page 22



TABLE OF CONTENTS

X. CLOSING COMMENTS	Page 22
----------------------------------	----------------

LIST OF TABLES

Table A: Recommended Soil Design Parameters and Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10¾-inch- outside-diameter, Steel CIP-Pipe-Piles	Page 10
Table B: Recommended Driven Steel CIP-Pipe-Pile Information for Structure B-13-731	Page 20

LIST OF APPENDICES

Appendix A

- B-13-731 Preliminary Plan Sheet 1 of 4, Exhibit A
- 60% Plan Cross-Section Sheet PRE-93, Exhibit B
- 60% Plan Cross-Section Sheet PRE-94, Exhibit C
- R-13-352 General Plan Sheet, Exhibit D
- R-13-353 General Plan Sheet, Exhibit E

Appendix B

- Boring Location Sketches, Drawing 12939.3-7A and 12939.3-7B
- WisDOT Boring Logs for Borings SB-7 and SB-8
- Laboratory Test Result Records, Figures 1 through 4

Appendix C

- Table 7-1: Recommended Soil Design Parameters
- Table 7-2: Deep Driven Pile Foundation Analyses' Results; *APILE* Static Analyses' Average Unfactored Soil Design Parameters
- Table 7-3: Deep Driven Pile Foundation Analyses' Results; *APILE* Static and *GRLWEAP* Drivability Analyses' Results



I. INTRODUCTION

This *Geotechnical Exploration and Analyses Report* for Structure B-13-731 summarizes the findings of the geotechnical exploration, laboratory tests, and geotechnical engineering analyses performed for the design and construction of a new two-span bridge IH-39/90 Northbound Bridge over Northbound Exit Ramp to USH-12/18 Westbound for the northern section of the IH-39/90 reconstruction project in the Town of Blooming Grove, Dane County, Wisconsin. We completed this work under the general direction of Dane Partners, LLC who established the general scope of the work.

The intent of this report is to convey the information obtained from the soil borings, to present the results of laboratory and field tests, to provide the results of our engineering analyses, and to present our comments and recommendations for the design and construction of the proposed structure. Variations in soil conditions should be expected between or beyond the borings, or between sample intervals, the nature and extent of which might not become evident until construction is undertaken. The project geotechnical engineer, or their designated representative, should make observations at the time of construction of the structure to determine if the subsurface conditions are as indicated by the exploration performed, and to validate our comments, analyses, and recommendations presented in this report for the subject structure.

II. PROJECT INFORMATION

The subject bridge described herein is a part of the planned widening and reconstruction of Interstate Highway 39 (IH-39) in Dane County. The planned IH-39 improvement consists of the design and construction of bridges, bridge widening, retaining walls, sign structures, sound barrier walls, roadway widening, and roadway reconstruction. The portion of the IH-39 improvement in Dane County is considered the North Segment for the proposed work. Separate reports address each of the improvements involved with this project.

The subject of this report is a new IH-39/90 Northbound Bridge over Northbound Exit Ramp to USH-12/18 Westbound bridge with Structure ID B-13-731. Ayres Associates, Inc. (AAI) provided preliminary drawings dated February 13, March 12, and April 1, 2019, for use in preparing this report. Please refer to enclosed Exhibits A through E in Appendix A which present the drawings provided by AAI that we utilized in our analyses.

Based on the drawings provided, the proposed two-span bridge bridge will have a total length of approximately 192 feet and a total width of approximately 63 feet. Two abutments and one pier will provide foundation support for the two-span bridge bridge structure. The pier will be offset from the center of the length of the bridge. The southern bridge span is approximately 129 feet long and the northern bridge span is approximately 58 feet long. New north and south approach embankments will be constructed along the eastern side



of the existing Southbound IH-39/90 roadway embankment. A mechanically stabilized earth (MSE) retaining wall will be constructed in front of each of the abutments to retain the new approach embankments.

III. FIELD EXPLORATION

We performed two standard soil borings, designated Borings SB-7 and SB-8 at or near the staked locations found in the field and as presented on the Location Sketches, Drawings 12939.3-7A and 12939.3-7B, enclosed in Appendix B. We adjusted the location of Boring SB-7 approximately 11 feet southwest of the staked location due to access restrictions.

We drilled and sampled borings for Structure B-13-731 to the following depths below ground surface and corresponding elevation:

Soil Boring	Substructure Unit	Ground Surface Elevation (feet)	Bottom of Boring	
			Depth (feet-inch)	Elevation (feet)
SB-7	South Abutment	870.2	99'-1"	771.1
SB-8	North Abutment	870.9	89'-6"	781.4

We used 2¼-inch-inside-diameter hollow-stem augers to maintain an open borehole as we advanced the boreholes of these borings to the last sample depth. We added water to the inside of the HSA to counteract the water pressure present during the drilling of these borings.

As we advanced the boreholes of these borings, we obtained soil samples at 2½-foot intervals starting at a depth of 1-foot below the ground surface and continued to a depth of 10 feet. We increased the sampling interval to 5 feet from a depth of 10 feet to the boring termination depth. We performed this sampling using a 2-inch-outside-diameter split-barrel sampler according to AASHTO Designation T206. We visually identified the recovered soils in general compliance with the Unified Soil Classification System (USCS).

We depict the subsoil stratification at the locations of the borings on the WisDOT Boring Logs enclosed in Appendix B. The WisDOT Boring Logs are drafted with a depth scale and the depth and respective elevation of each stratum change is denoted.

AAI staked the requested boring locations in the field. Due to drilling rig access restrictions and existing roadway embankments, and/or the presence of utility lines, we drilled Boring SB-7 at an offset from the requested location. AAI determined the coordinates and ground



surface elevation of each of the soil borings after completion of the drilling and sampling and provided this information to us. The “northing” and “easting” grid coordinates, stationing, and ground surface elevations at the locations of the borings are provided on the WisDOT Boring Logs.

IV. SOIL AND BEDROCK STRATIGRAPHY

The soil stratigraphy encountered at Borings SB-7 and SB-8 can generally be characterized as topsoil and fill material overlying native soil strata. Neither of the borings encountered bedrock within the depths drilled.

We found the surficial soils at Boring SB-7 to be frozen on the day of the sampling as follows:

Boring	Ground Surface Elevation (feet)	Estimated Frost Top		Estimated Frost Bottom	
		Depth (feet-inch)	Elevation (feet)	Depth (feet-inch)	Elevation (feet)
SB-7	870.2	0'-0"	870.2	3'-0"	867.2

The borings encountered variable fill material and topsoil strata. We describe the fill material and topsoil strata encountered at the borings as follows:

- Boring SB-7 encountered 3 inches of very dark brown LEAN CLAY (CL) FILL TOPSOIL over 33 inches of brown fine to coarse SILTY SAND WITH GRAVEL (SM) FILL over 12 inches of brown SANDY LEAN CLAY (CL) FILL over 6 inches of brown fine to coarse SILTY SAND WITH GRAVEL (SM) FILL.
- Boring SB-8 encountered 7 inches of dark brown LEAN CLAY (CL) TOPSOIL.

Below the topsoil and fill material, the borings encountered a variable native soil strata. We describe the native soil strata encountered at the borings as follows:

- Boring SB-7 encountered brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL over reddish-brown to light brown fine CLAYEY SAND WITH GRAVEL (SC) GLACIAL TILL over brown to reddish-brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL over grayish-brown fine POORLY-GRADED SAND WITH GRAVEL (SP) over grayish-brown SANDY LEAN CLAY (CL) over brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL with few irregular gray CLAYEY SAND (SC) lenses.



- Boring SB-8 encountered brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL over brown fine SILTY CLAYEY SAND (SC-SM) GLACIAL TILL over brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL over brown fine to coarse POORLY-GRADED GRAVEL WITH SILT AND SAND (GP-GM).

We note that the gravel content varied from trace to some in the GLACIAL TILL strata.

Please refer to the enclosed WisDOT Boring Logs for a further description of the topsoil, fill material, and native soil strata encountered at the locations of Borings SB-7 and SB-8.

V. GROUNDWATER

Our drilling crew found the boreholes of the borings to have a water level and were caved at or after the completion of the drilling and sampling at the borings.

We summarize the water and caved level depths and respective elevations for the borings as follows:

Boring	Ground Surface Elevation (feet)	Water Level			Caved Level		
		Depth (feet-inch)	Elevation (feet)	Comments	Depth (feet-inch)	Elevation (feet)	Comments
SB-7	870.2	3'-2"	867.0	At completion	12'-4"	857.9	At completion
SB-8	870.9	22'-4"	848.6	At completion	34'-10"	836.1	At completion
		3'-0"	867.9	Estimated based on soil samples	—	—	—

We expect the groundwater level to fluctuate as influenced by precipitation, snowmelt, surface water runoff, and other hydrological and hydrogeological factors. The groundwater level at the time of construction of the subject bridge may be higher or lower than the groundwater levels encountered on the days that we performed the borings.

VI. LABORATORY AND FIELD TESTS

We performed laboratory tests on selected split-barrel soil samples obtained from the borings to determine the physical properties of the fill material and native soil encountered at the boring locations. The laboratory tests consisted of moisture content (MC), Atterberg limits (liquid limit and plasticity index), dry densities (Dry Wt), unconfined compressive strength (q_u), percentage of soil particles passing the No. 200-mesh sieve (Fines), and



particle size distribution analysis. In addition to the above tests, we tested some of the cohesive soils for approximate unconfined compressive strength (q_p) using a spring penetrometer.

The field test consisted of the standard penetration test (SPT). We performed the SPT during the sampling procedure at the boring locations. The SPT is the number of blows per foot ("N" value) needed to drive the split-barrel sampler using a 140-pound hammer free-falling for 30 inches. We determined the corrected standard penetration resistance $\{(N_1)_{60}\text{-value}\}$ which is the N-value corrected for hammer efficiency and normalized to an effective overburden pressure at 1-atmosphere based on estimated densities for the soils encountered by the borings.

We include the laboratory and field test results obtained for this report on the WisDOT Boring Logs and/or Laboratory Test Result Records, Figures 1 through 4, enclosed in Appendix B. We used the results from the Atterberg limits, Fines, and particle size distribution tests to confirm or modify the USCS soil identifications in general compliance with USCS classification procedures as defined in ASTM Designation D2487.

The laboratory and field test results for the borings suggest the following:

- The granular fill material is in a moist relative moisture condition and in a very loose to loose state of relative density.
- The cohesive fill material is in a moist relative moisture condition and of medium consistency.
- The granular native soil strata are in a moist relative moisture condition to approximately elevation 868 feet below which they are in a wet relative moisture condition
- At Boring SB-7, the granular native soil strata are in a very loose to loose state of relative density to approximately elevation 823, medium dense state of relative density to approximately elevation 801 feet below which they are in a dense to very dense state of relative density. The SANDY LEAN CLAY (CL) stratum encountered at this boring within the granular soil strata below elevation 801 feet is of very stiff to hard consistency.
- At Boring SB-8, the granular native soil strata are in a very loose to loose state of relative density to approximately elevation 859, loose to medium dense state of relative density to approximately elevation 804 feet below which they are in a dense to very dense state of relative density.



We used the laboratory and field test results in our evaluation of the topsoil and native soil strata encountered at the boring locations to determine soil parameters to use in the design of the foundation system for the subject IH-39/90 Northbound Bridge over Northbound Exit Ramp to USH-12/18 Westbound.

VII. ANALYSES PROCEDURES, ASSUMPTIONS, & GIVEN INFORMATION

Using the information obtained from Borings SB-7 and SB-8 performed in the vicinity of the abutments of the proposed bridge structure, we performed geotechnical analyses for shallow foundations and deep driven pile foundations for the substructure units of the proposed bridge using Load and Resistance Factor Design (LRFD) procedures presented in Chapter 11 of the WisDOT *Bridge Manual* (WBM) dated January 2019, and related chapters in the AASHTO *LRFD Bridge Design Specifications for Highway Bridges*, 8th Edition.

A. Shallow Spread Footing Foundations

Per Chapter 12 of the IH-39 Project Manual, the use of a driven pile foundation for the corridor structures is preferred unless shallow spread footing foundations are placed on bedrock or other high bearing capacity material. Therefore, shallow spread footing foundations for the abutments are not being considered since bedrock was not encountered by the borings performed.

B. Deep Driven Pile Foundations

1. Existing IH-39/90 Southbound Structure B-13-461

We reviewed the WisDOT *Site Investigation Report* dated November 8, 1995, and the pile driving data for the 1997 construction of the existing IH-39/90 Southbound Bridge (Structure B-13-461) over Northbound Exit Ramp to USH-12/18 Westbound. Our review of this information is as follows:

- The WisDOT *Site Investigation Report* contained the following information:
 - The 1995 borings encountered low to moderate strength granular soil strata over moderate to high strength granular soil strata. Bedrock was not encountered within the depth explored by these borings. This is similar to the soil stratification encountered by Borings SB-7 and SB-8 for the current work.
 - Recommended 10x42 H-piles with a design bearing capacity of 55 tons or 110 kips. The report recommends a factor of safety of 2, which equates to a Rn_{dyn} of 110 tons or 220 kips for these piles.



- The recommended H-pile tip elevations for the substructure units were as follows:
 - North Abutment – 790 feet
 - Pier 1 (north) – 790 feet
 - Pier 2 (south) – 790 feet
 - South Abutment – 786 feet

- The pile driving records for existing Southbound IH-39/90 Bridge (Structure B-13-461) over Northbound Exit Ramp to USH-12/18 shows that 10x42 H-piles were driven to support the substructure units. These records indicated the following:
 - The 10x42 H-piles were designed for a bearing capacity of 55 tons or 110 kips, which equates to a Rn_{dyn} of 110 tons or 220 kips using the recommended factor of safety of 2.
 - For the North Abutment:
 - The plan length was 100 feet.
 - The cut-off lengths ranged from 83.0 to 195.6 feet with an average of 110.0 feet.
 - The estimated tip elevations ranged from 802.7 to 690.1 feet with an average of 775.7 feet. This indicates the piles drove approximately 13 feet shallower to 100 feet deeper than anticipated.
 - The Rn_{dyn} ranged from 234 to 265 kips with an average of 253 kips.
 - For the Pier 1 (north):
 - The plan length was 80 feet.
 - The cut-off lengths ranged from 44.4 to 77.7 feet with an average of 71.1 feet.
 - The estimated tip elevations ranged from 822.6 to 789.3 feet with an average of 795.9 feet. This indicates the piles drove approximately 12 feet shallower to 0 feet deeper than anticipated.
 - The Rn_{dyn} ranged from 229 to 298 kips with an average of 249 kips.
 - For the Pier 2 (south):
 - The plan length was 75 feet.
 - The cut-off lengths ranged from 68.2 to 80.0 feet with an average of 73.0 feet.
 - The estimated tip elevations ranged from 795.8 to 784.0 feet with an average of 791.0 feet. This indicates the piles drove approximately 6 feet shallower to 6 feet deeper than anticipated.
 - The Rn_{dyn} ranged from 229 to 296 kips with an average of 255 kips.



- For the South Abutment:
 - The plan length was 100 feet.
 - The cut-off lengths ranged from 86.9 to 99.4 feet with an average of 91.5 feet.
 - The estimated tip elevations ranged from 798.2 to 785.7 feet with an average of 793.6 feet. This indicates the piles drove approximately 35 feet shallower to 1-foot deeper than anticipated.
 - The $R_{n_{dyn}}$ ranged from 229 to 279 kips with an average of 253 kips.

2. Groundwater Elevations

Based on the results of the borings completed for the subject bridge structure for the North Segment of the IH-39 Reconstruction project, we recommend a design groundwater elevation of 867.0 feet be used for our pile driving and ultimate capacity computations.

3. Pile-Supported Footing Base Information

AAI provided the following pile-supported footing (pile cap) base and lowest ground surface elevations at the substructure units for the subject bridge structure. Where MSE retaining walls are constructed to retain the approach embankments at substructure units, the berm elevation used in our computations is the proposed ground surface elevation in front of the MSE retaining wall.

We note that the approach embankments for this structure will be constructed on the east side of the existing southbound roadway embankment. For our computations, we used the elevations for the proposed structure at the northbound reference line.

Substructure Unit	Nearest Boring(s)	Berm Elevation (feet)	Pile Cap Base Elevation (feet)
South Abutment	SB-7	869.9	887.7
Pier	SB-8	873.6	862.0
North Abutment	SB-8	871.5	887.7



We anticipate the piles for the North and South Abutments will be driven after the embankment areas have been prepared and fill placed to reach the bottom elevation of the proposed MSE-retained approach embankments. Additionally, the piles will be driven prior to construction of the proposed MSE retaining walls located in front of the approach embankments.

We anticipate the piles for the Pier will be driven after the area in the vicinity of the substructure unit has been graded.

4. Pre-boring

As presented in WBM Chapter 11.3.1.6, pre-boring is required for displacement (i.e., cast-in-place or CIP) piles driven into new embankments over 10 feet in height. Based on the plans provided, pre-boring is not required for the North and South Abutments.

5. Allowable Driving Resistances

We used the computer program *APILE* to compute the ultimate skin friction and end bearing parameters and the ultimate and factored capacities of the soils encountered by the borings using static analyses.¹ We present the angle of internal friction (ϕ), unit weight (γ), and cohesion (c) values used in *APILE* in enclosed Table 7-1 in Appendix C and in Table A pages 10 through 14. The cohesion values are based on the approximate unconfined compressive strength readings obtained using a spring penetrometer and the laboratory unconfined compression strength test results. We estimated the density values based on: (1) wet density (γ_w) test results of selected representative samples of the various strata encountered by the borings performed; (2) the standard penetration results obtained by the borings performed; and, (3) our experience with similar material. We computed the angle of internal friction values using empirical formulas based on the N_{160} -values for each soil stratum. As recommended in a 2013 WisDOT Research Program (WHRP) report written by Dr. James Long, we limited the computed maximum friction angle to 36 or 40 degrees depending upon the N_{160} -values for computing skin friction and end bearing capacities for driven piles.² We used the percentage loss of soil strength during driving from Table 11.3-4 of the WBM based on the type of soil for each stratum for cast-in-place (CIP) pipe piles. Due to the reported over-driving of H-piles on other WisDOT bridge projects, we increase the percentage

¹APILE. Vers. 2014. Austin, TX: Ensoft, Inc., 2014. Computer software.

²James H. Long, PhD, PE, Improving Agreement Between Static Method and Dynamic Formula for Driven Cast-In-Place Piles in Wisconsin. (Madison, WI: Wisconsin Department of Transportation, 2013).



Table A: Recommended Soil Design Parameters And Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10 3/4-inch-outside-diameter, Steel CIP-Pipe Pile

Elevation (feet)	Material Type	Estimated Soil Parameters			Driven Pile Parameters			
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***	Skin Friction† (psf)	End Bearing† (psf)
889.0 to 887.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
887.7 to 879.2	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
879.2 to 870.2	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
870.2 to 870.0	Replace existing dark brown LEAN CLAY WITH SAND (CL) FILL TOPSOIL with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
870.0 to 868.9	Replace existing brown fine to coarse SILTY SAND WITH GRAVEL (SM) FILL with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
868.9 to 867.4		120.0	31	0	---	---	1,170	0
867.4 to 867.2		120.0	31	0	33	0.45	70	4,100
867.2 to 867.0	SANDY LEAN CLAY (CL) — medium plasticity, brown, moist, medium consistency, FILL	125.0	0	800	50	0.35	70	5,900
867.0 to 866.2		125.0	0	800	50	0.35	70	5,700
866.2 to 865.7	SILTY SAND WITH GRAVEL (SM) — fine to coarse grained, non-plastic to low plasticity fines, brown, moist, very loose to loose relative density, FILL	120.0	31	0	33	0.45	90	6,700
865.7 to 859.2	SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, wet, loose to very loose relative density, GLACIAL TILL, trace to some gravel	152.0	29	0	33	0.45	140	10,300

Table Notes

- The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the $N_{1,60}$ value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- ** The Driving SSL values presented in Table 11.3.4 of the WisDOT Bridge Manual were used for the recommended driven cast-in-place, steel pipe piles.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.
- † The Skin Friction and End Bearing values presented above are the computed unfactored average capacities for the indicated stratum/substratum.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
SSL = soil strength loss.

psf = pounds per square foot.
NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Bot = Cohesion @ bottom of stratum/sub-stratum.

Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.



Table A: Recommended Soil Design Parameters And Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10 3/4-inch-outside-diameter, Steel CIP-Pipe Pile

Elevation (feet)	Material Type	Estimated Soil Parameters				Driven Pile Parameters			
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***	Skin Friction [†] (psf)	End Bearing [†] (psf)	
859.2 to 853.2		152.0	29	0	33	0.45	240	13,600	
853.2 to 848.2		152.0	31	0	33	0.45	390	19,600	
848.2 to 838.2		152.0	29	0	33	0.45	460	13,600	
838.2 to 830.7		152.0	29	0	33	0.45	620	13,300	
830.7 to 823.2		152.0	29	0	33	0.45	760	13,500	
823.2 to 813.2	CLAYEY SAND WITH GRAVEL (SC) — fine grained, medium plasticity fines, reddish-brown to light brown, wet, medium dense relative density, GLACIAL TILL, trace to some gravel	146.0	31	0	33	0.45	1,080	20,500	
813.2 to 803.2	SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist to wet, medium dense relative density, GLACIAL TILL, trace to some gravel	152.0	32	0	33	0.45	1,410	32,100	
803.2 to 800.7	POORLY-GRADED SAND WITH GRAVEL (SP) — fine grained, light grayish-brown and brown, wet, medium dense relative density	125.0	31	0	17	0.45	1,420	24,800	
800.7 to 798.2	SANDY LEAN CLAY (CL) — medium plasticity, grayish-brown, moist, hard to very stiff consistency	132.0	0	3,800	50	0.35	3,680	36,400	
798.2 to 788.2	SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist, dense to very dense relative density, GLACIAL TILL, trace to some gravel, with few irregular gray CLAYEY SAND (SC) lenses	152.0	34	0	33	0.45	2,050	72,800	

Table Notes

- The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N_{160} value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- ** The Driving SSL values presented in Table 11.3-4 of the WisDOT Bridge Manual were used for the recommended driven cast-in-place, steel pipe piles.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downward, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.
- † The Skin Friction and End Bearing values presented above are the computed unfactored average capacities for the indicated stratum/substratum.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
SSL = soil strength loss.

psf = pounds per square foot.
NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.

Bot = Cohesion @ bottom of stratum/sub-stratum.



Table A: Recommended Soil Design Parameters And Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10 3/4-inch-outside-diameter, Steel CIP-Pipe Pile

Elevation (feet)	Material Type	Estimated Soil Parameters			Driven Pile Parameters			
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***	Skin Friction† (psf)	End Bearing† (psf)
788.2 to 783.2		152.0	38 [36]	0	33	0.45	2,770	144,000
783.2 to 774.2		152.0	45 [36]	0	17	0.45	3,010	157,000
774.2 to 771.1		152.0	45 [40]	0	17	0.45	4,730	371,000
----- End of Boring SB-7 @ Elevation 771.1 feet -----								

Table Notes

- The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N_{60} value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- ** The Driving SSL values presented in Table 11.3-4 of the WisDOT Bridge Manual were used for the recommended driven cast-in-place, steel pipe piles.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.
- † The Skin Friction and End Bearing values presented above are the computed unfactored average capacities for the indicated stratum/substratum.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
psf = pounds per square foot.
NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.
Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.
Bot = Cohesion @ bottom of stratum/sub-stratum.



Table A: Recommended Soil Design Parameters And Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10%-inch-outside-diameter, Steel CIP-Pipe Pile

Elevation (feet)	Material Type	Estimated Soil Parameters			Driven Pile Parameters			
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***	Skin Friction† (psf)	End Bearing† (psf)
889.0 to 887.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
887.7 to 879.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
879.7 to 871.5	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	---	---
871.5 to 870.9	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---	510	0
870.9 to 870.3	Replace existing dark brown LEAN CLAY WITH SAND (CL) FILL TOPSOIL with MSE Retaining Wall Backfill	120.0	30	0	---	---	530	0
870.3 to 868.0	Replace existing brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL trace to some gravel with MSE Retaining Wall Backfill	120.0	30	0	---	---	600	0
868.0 to 867.0		152.0	30	0	33	0.45	10	1,000
867.0 to 858.9		152.0	30	0	33	0.45	80	6,600
858.9 to 848.9	SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, wet, loose to medium dense relative density; GLACIAL TILL, trace to some gravel	152.0	29	0	33	0.45	250	13,400
848.9 to 843.9		152.0	31	0	33	0.45	460	19,700
843.9 to 836.4		152.0	29	0	33	0.45	500	13,600

Table Notes

- The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N_{60} -value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- ** The Driving SSL values presented in Table 11.3-4 of the WisDOT Bridge Manual were used for the recommended driven cast-in-place, steel pipe piles.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.
- † The Skin Friction and End Bearing values presented above are the computed unfactored average capacities for the indicated stratum/substratum.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
SSL = soil strength loss.

psf = pounds per square foot.
NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.
Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.

Bot = Cohesion @ bottom of stratum/sub-stratum.



Table A: Recommended Soil Design Parameters And Foundation Capacities for WisDOT Structure B-13-731 for Recommended 10 3/4-inch-outside-diameter, Steel CIP-Pipe Pile

Elevation (feet)	Material Type	Estimated Soil Parameters				Driven Pile Parameters			
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***	Skin Friction† (psf)	End Bearing† (psf)	
836.4 to 828.9		152.0	29	0	33	0.45	640	13,600	
828.9 to 818.9		152.0	31	0	33	0.45	940	20,100	
818.9 to 808.9		152.0	29	0	33	0.45	980	13,700	
808.9 to 803.9		152.0	31	0	33	0.45	1,320	23,400	
803.9 to 798.9	SILTY CLAYEY SAND (SC-SM) — fine grained, low plasticity fines, brown, moist, dense relative density, GLACIAL TILL, trace to some gravel	146.0	35	0	33	0.45	1,990	103,000	
798.9 to 788.9	SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist, very dense relative density, GLACIAL TILL, trace to some gravel	152.0	42 [36]	0	33	0.45	2,510	156,000	
788.9 to 781.4	POORLY-GRADED GRAVEL WITH SILT AND SAND (GP-GM) — fine to coarse grained, non-plastic to low plasticity fines, brown, wet, very dense relative density	120.0	45 [40]	0	0	0.45	4,070	404,000	

Table Notes

The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
 * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N_{60} value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (J). Please refer to geotechnical report for further explanation.

** The Driving SSL values presented in Table 11.3-4 of the WisDOT Bridge Manual were used for the recommended driven cast-in-place, steel pipe piles.

*** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.

† The Skin Friction and End Bearing values presented above are the computed unfactored average capacities for the indicated stratum/substratum.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
 psf = pounds per square foot.
 NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.
 Bot = Cohesion @ bottom of stratum/sub-stratum.



loss of soil strength during driving values from the WBM values for H-piles. We used the Static Nominal Axial Compression Resistance Factors (ϕ_{stat}) from Table 11.3-1 of the WBM based on the type of soil for each stratum. The percentage loss of soil strength and ϕ_{stat} factors used are included in enclosed Table 7-2 in Appendix C and in Tables A on pages 10 through 14.

6. Design 'Required Driving Resistance' (Rn_{dyn}) and 'Factored Axial Compression Resistance' (P_r)

Based on the types of soils encountered by Borings SB-7 and SB-8, we evaluated driven 10¾-inch-outside-diameter, steel CIP-pipe-piles and driven 10x42 steel H-piles in our analyses of the deep foundations for the proposed substructure units for North and South Abutments. AAI requested that the minimum Rn_{dyn} for the CIP-pipe-piles be 130 tons or 260 kips.

The Design Rn_{dyn} for a selected pile type is determined by using the Design P_r for the selected pile and a dynamic resistance factor (ϕ_{dyn}) of 0.5 for driven piles where the modified Gates dynamic formula is planned to be used for construction driving criteria. The Design P_r and Rn_{dyn} values for the evaluated pile types, as presented in Table 11.3-5 of the WBM, are summarized as follows:

H-Pile Sizes	Maximum P_r (kips)	Maximum Rn_{dyn} (kips)
10x42	180	360

CIP Pipe Pile Sizes		Maximum P_r (kips)	Maximum Rn_{dyn} (kips)
Outside Diameter (inches)	Wall Thickness (inches)		
10¾	0.250	130	260
	0.365 or 0.500	150	300

Per Mr. Jeff Horsfall with WisDOT, all piles are driven to the Design Rn_{dyn} at the time of installation. For the subject bridge structure, the Design Rn_{dyn} equals the Maximum Rn_{dyn} for the selected CIP-pipe-piles or H-piles. Thus, we computed the Design Pile Tip Elevation for the selected CIP-pipe-pile or H-pile type based on the Design Rn_{dyn} , the static resistance factor, and the percentage loss of soil strength during driving for the soil strata encountered at each boring performed for the subject bridge structure.



7. Drivability Evaluation

We used the computer program *GRLWEAP* to perform the drivability evaluation for the selected H-piles and CIP-pipe-piles driven into the soils encountered by the borings.³ We check drivability using the *APILE*-computed ultimate skin friction and ultimate end bearing parameters and the assigned percentage loss of soil strength for each soil stratum. We used *APILE* to create the preliminary data file for use in *GRLWEAP*.

We perform our drivability evaluation using the Delmag D16-32 and Delmag D30-32 diesel pile driving hammers. We initially determine the drivability of piles using the Delmag D16-32 pile driving hammer. If the specified pile is refused using the Delmag D16-32 above the design pile tip elevation, then we determine drivability of the specified pile using the Delmag D30-32 pile driving hammer. We define driven pile refusal as occurring when the estimated number of blows for a pile driving hammer as computed by *GRLWEAP* is equal to or greater than 120 blows per foot. The allowable steel stress is defined as 90 percent of the yield steel stress for a pile type. Per Mr. Jeff Horsfall with WisDOT, the steel stress at any time during driving should not exceed the allowable steel stress for a pile type. If the 'Driving Stress' (σ_{dr}) as computed by *GRLWEAP* for the specified piles exceeds 90 percent of the steel yield stress (35 ksi) of the shell of CIP-pipe-piles or of the steel yield stress (50 ksi) of H-piles, then the pile is overstressed and we make the following adjustments:

- For CIP-pipe-piles
 - Increase steel yield stress to 45 ksi.⁴
 - Increase shell thickness and restart the analyses process.
 - Decrease the Design Rn_{dyn} and restart the analyses process, OR switch to using H-piles.
- For H-Piles
 - Decrease the Design Rn_{dyn} and restart the analyses process.

We use the following default pile hammer cushion parameters included in *GRLWEAP* for the Delmag D16-32 and Delmag D30-32 diesel pile driving hammers equipped with a 21-inch lead size in our drivability evaluation.

³GRLWEAP. Vers. 2010. Cleveland, OH: GRL Engineers, Inc. *GRLWEAP*. 2010. Computer software.

⁴Per Mr. Jeff Horsfall with WisDOT, the use of 45 ksi steel for CIP pipe piles is acceptable to WisDOT.



GRLWEAP Default Pile Hammer Cushion Parameter	CIP Pipe Pile	H-Pile
Cushion Material	50% Aluminum and 50% Conbest	50% Aluminum and 50% Conbest
Area (inches ²)	227	227
Elastic Modulus (ksi)	530	530
Coefficient of Restitution	0.8	0.8
Helmet Weight (kips)	1.7	1.9
Thickness (inches)	2.0	2.0

8. Downdrag Load

Per WBM Chapter 11.3.1.17.1, downdrag load, or negative shaft resistance, occurs due to settlement of the embankment caused by the additional loading imposed on the existing soils from the raising of the grade at a proposed substructure unit. WisDOT states that factored downdrag loads of 126, 168, and 294 kips are allowed in addition to the Design P_r for 10x42, 12x53, and 14x73 H-piles, respectively, driven to refusal on relatively-sound bedrock using modified Gates driving criteria to determine the Driving $R_{n_{dyn}}$. Downdrag loads on displacement piles (e.g., CIP piles) or non-end bearing H-piles reduce the Design P_r of the pile unless countermeasures are undertaken to minimize the downdrag condition.

WisDOT specifies that the provisions specified by AASHTO for downdrag should be used to compute downdrag loads. AASHTO specifies that downdrag loads should be applied if the settlement between the soil and the installed pile is 0.4 inches or greater. Soil settlement below the installed pile is ignored in these computations. We used the preliminary cross-section drawings provided by AAI to determine the maximum height of fill to be placed at each substructure unit. We use the procedures and equations presented in AASHTO Section 10.6.2.4 to estimate settlement between the soil and the installed pile to the computed maximum depth of each pile type/size analyzed.

After determining which soil strata could cause downdrag, we apply the AASHTO specified downdrag (DD) load factor to the computed unfactored skin friction load for the affected soil strata. For the driven portion of a pile, we apply a 1.4 DD load factor to the *APILE*-computed unfactored skin friction load. For the prebored portion of a pile or where embankments are constructed after piles



are driven, we apply a 1.25 DD load factor to the unfactored skin friction load computed using AASHTO specified drilled shaft analyses procedures.

C. Lateral Deflection Analyses

We understand that the proposed abutments will be Type A1 (sill) abutments. We understand no lateral force analyses are required for the abutments.

VIII. ANALYSES RESULTS

A. Shallow Spread Footing Foundation Analyses

We did not perform shallow spread footing foundation analyses for the abutments or piers for the subject bridge structure for the reasons presented above in Section VII.A.

B. Deep Driven Pile Foundation Analyses

We performed the static and drivability analyses using the AASHTO and WisDOT procedures and the given and estimated information as outlined above in Section VII.B. We used *APILE* to complete the static analyses and *GRLWEAP* to complete the drivability analyses for the deep driven pile foundation for the abutments and pier for the subject bridge structure. Enclosed Table 7-2 in Appendix C and Table A on pages 10 through 14 present the average unfactored end bearing and average unfactored skin friction without soil driving loss values derived from the *APILE* static computations for the soil strata for each of the borings. Enclosed Table 7-3 in Appendix C presents the static and drivability results including the Design Pile Tip Elevations; Design, Driving, and Ultimate $R_{n_{dyn}}$; Design and Factored P_r ; and estimated Maximum σ_{dr} from the *APILE* and *GRLWEAP* computations for each of the borings. Using static analyses, we used the Design $R_{n_{dyn}}$ for steel CIP-pipe-piles or steel H-piles and the estimated soil driving loss for each stratum to determine the design pile tip elevation as presented in Table 7-3 in Appendix C. We used a dynamic resistance factor of 0.5 to compute the Design P_r presented in Table 7-3. Using static analyses, we computed the Factored P_r presented in Table 7-3 using the static resistance factors presented in Table 7-1 in Appendix B. Where the computed Factored P_r is higher than the Design P_r , we recommend the Design P_r be used in designing the pile foundation layout.

The analyses' results indicate that the use of driven steel CIP-pipe-piles or steel H-piles would be acceptable to support the substructure units for the South Abutment, Pier, and North Abutment for the proposed bridge structure. Our analyses indicate that thicker wall CIP-pipe-piles with an increased steel yield stress should be used



due to the presence of the very dense GLACIAL TILL soil strata. If used, the steel H-piles for this bridge structure would be functioning as a friction pile terminating in very dense GLACIAL TILL instead of an end-bearing pile due to the lack of bedrock within the depth explored by the borings. Based on the reported over-driving of H-piles functioning as friction piles for bridge structures for the South IH-39 Segment and as shown for the H-piles driven for the adjacent B-13-461 structure, we do not recommend that H-piles be considered for supporting the substructure units for the subject bridge structure due to the potential for the H-piles to over-drive to reach the design required driving capacity.

Therefore, we recommend 10¾-inch-outside-diameter, 0.500-inch-thick, 45 ksi steel, CIP-pipe-piles provide foundation support for the South Abutment, Pier, and North Abutment substructure units. Please refer to Table B on page 20 for our recommended Design $R_{n_{dyn}}$, Design P_r , Design Pile Tip Elevation, Driving $R_{n_{dyn}}$, and other pertinent design values for each substructure unit. Our drivability analyses indicate a Delmag D16-32 or similar pile driving hammer should be able to drive the recommended steel CIP-pipe-piles.

We computed a settlement of approximately 1¼ inches between the existing soil strata and the total length of an installed pile due to the construction of the south and north approach embankments. Per AASHTO, downdrag load should be considered when computed settlements between existing soil strata and the total length of an installed pile are greater than or equal to 0.4 inches. We compute elevations 838.2 feet and 836.4 feet, respectively for the south and north approach embankment, to be the elevation below which the estimated settlement between the soil and the installed pile will be less than 0.4 inches. The soil strata above these elevations contribute to downdrag loading of the installed pile.

Due to the minor changes in the ground surface elevation at the Pier substructure unit, downdrag load due to settlement between the existing soil strata and the total length of installed pile is estimated to less than 0.4 inches.

Based on the computed settlement between the soil and the total length of installed pile due to the south and north approach embankments and per AASHTO and the WBM, we computed the Factored Downdrag Load presented in Table B due to soils above elevation 838.2 feet at Boring SB-7 and above elevation 836.4 feet at Boring SB-8. We recommend the reduction of the Design P_r by the Factored Downdrag Load presented in Table B for the recommended 10¾-inch-outside-diameter, 0.500-inch-thick, 45 ksi steel, CIP-pipe-piles. Alternatively, the downdrag load could be countered by: (1) pre-boring through the existing soil strata to the specified elevations [or lower] and leaving a permanent pipe sleeve, (2) coating the pile with bitumen to the specified elevations [or lower], or (3) removing the existing soil strata



Table B: Recommended Driven Steel CIP-pipe-pile Information for Structure B-13-731‡

Substructure Unit	South Abutment	Pier	North Abutment
Nearest Boring	SB-7	SB-8	SB-8
Pile Cap Base Elevation (feet)	887.7	862.0	887.7
CIP Diameter (inches)	10¾	10¾	10¾
CIP Shell Thickness (inches)	0.500	0.500	0.500
CIP Steel Yield Stress (ksi)	45	45	45
Design $R_{n_{dyn}}$ (kips)	300	300	300
Design P_r (kips)	150	150	150
Factored Downdrag Load (kips)*	54	0	60
Design Pile Tip Elevation (feet)	784.9	772.9	772.9
Computed Pile Length (feet)	102.8	89.1	114.8
Recommended Plan Pile Length (feet)†	87	76	98
Driving $R_{n_{dyn}}$ (kips)	300	300	300
Hammer Type	Delmag D16-32	Delmag D16-32	Delmag D16-32

‡ See attached Table 7-3 in Appendix B for additional driven pile drivability results.

† Please refer to page 21 for an explanation of the recommended plan pile lengths.

* Per WBM 11.3.1.17.1, the recommended Design P_r should be reduced by the recommended Factored Downdrag Load for the recommended CIP-pipe-piles unless countermeasures are taken.

to the specified elevations [or lower] within the footprint of the substructure unit and replacing with WisDOT structural fill material.

Some of the newer bridges along the I-39 Corridor were constructed with either H-piles or CIP piles. We were informed that the H-piles are typically driving deeper than the computed depths in soils and the CIP piles are typically reaching capacity at shallower than computed depths, although some piles are driving deeper and shallower within the same substructure. For bridge Structure B-53-323 (Avalon



Road), H-piles for the abutments drove significantly deeper than computed and CIP were driven in the median to depths 3 to 6 feet shallower than computed.

Based on the reported shallower pile tip depth of driven CIP-pipe-piles for the I-39 Corridor and as indicated by Borings SB-7 and SB-8 that the thickness and type of soil overburden is variable, we recommend an average of approximately 15 percent be subtracted from the computed pile lengths as presented in Table B on page 20 for the recommended 10¾-inch-outside-diameter, 0.500-inch-thick, 45 ksi steel, CIP-pipe-piles installed at the substructure units for the South and North Abutments for the subject bridge structure to allow for the anticipated soil overburden variability.

Although Borings SB-7 and SB-8 did not encounter any cobbles or boulders in the GLACIAL TILL strata, it is known that GLACIAL TILL soils can contain a variable quantity of these large particles and that these large particles can be erratically located within the GLACIAL TILL soil matrix. Therefore, we recommend conical pile points be used for the CIP-pipe-piles due to the potential to encounter cobbles and/or boulders within the very dense GLACIAL TILL soils. The conical pile points help to evenly distribute the driving stresses to the steel shell of these piles which will help to reduce the potential of damage to the piles during driving.

C. Lateral Deflection Analyses

We did not perform lateral deflection analyses for any of the substructure units for the subject bridge structure.

IX. BRIDGE CONSTRUCTION

We offer the following comments and recommendations regarding the construction of the two-span bridge for the North Segment of the IH-39 Reconstruction Project.

A. Shallow Foundations

Shallow spread footing foundations are not being considered for the abutments and piers for the subject bridge structure for the reasons presented above in Section VII.A.

B. Deep Foundations

We recommend a deep foundation system consisting of 10¾-inch-outside-diameter, 0.500-inch-thick, 45 ksi steel, CIP-pipe-piles driven in accordance with the WisDOT *Standard Specifications for Highway and Structure Construction* and relevant



special provisions to support the proposed substructure units for the South and North Abutments and the Pier for the subject bridge reconstruction.

Using the proposed pile cap base elevations as presented on Exhibit A and the recommended plan pile lengths as presented in Table B on page 20, we estimate the recommended steel CIP-pipe-piles will achieve the Design $R_{n_{dyn}}$ of 300 kips in very dense GLACIAL TILL in the vicinity of the following estimated pile tip elevations:

Substructure Unit	Nearest Boring(s)	Estimated Pile Tip Elevation (feet)
South Abutment	SB-7	800
Pier	SB-8	786
North Abutment	SB-8	789

Please refer to Table B on page 20 for a summary of the analyses results for the recommended steel H-piles. Additional static and drivability analyses' results information is presented in Tables 7-2 and 7-3 in Appendix C.

The final driven length of the steel CIP-pipe-piles will depend on: (1) the variability of the soil overburden thickness, (2) the variability of the soil overburden density, and (3) the selected pile hammer type. Therefore, variations in the installed length of steel CIP-pipe-piles should be anticipated.

C. General Comments and Recommendations

We recommend that all work associated with the selected foundation system at the project site be performed in accordance with the WisDOT *Standard Specifications for Highway and Structure Construction* and relevant special provisions.

Slope protection should be provided in the vicinity of and around all substructure foundation units as required by WisDOT standards to reduce the potential for erosion.

X. CLOSING COMMENTS

Soils & Engineering Services, Inc. prepared this report for the exclusive use of Dane Partners, LLC and the Wisconsin Department of Transportation to aid in the design of the



proposed Illinois State Line - Madison for the North Segment of the IH-39 Reconstruction Project in the Town of Blooming Grove, in Dane County, Wisconsin. The recommendations in this report are based on the project information provided to our office. Soils & Engineering Services, Inc. should review any changes in the nature, design, or location of the proposed bridge after submittal of this *Geotechnical Exploration and Analyses Report* for Structure B-13-731 to revise the recommendations in the report, if necessary. The nature and extent of soil or groundwater variations between the boring locations may not become evident until the time of excavation or construction of the subject bridge. If soil or groundwater variations are evident at the time of excavation or construction, it will be necessary for Soils & Engineering Services, Inc. to re-evaluate the soil and groundwater, and other site conditions, which may result in the revision of our recommendations in this report.

Soils & Engineering Services, Inc. should review the final design and specification documents for this project to verify that our recommendations regarding the foundation system are interpreted correctly and implemented in the design of the subject bridge as they are intended. It is further recommended that the project geotechnical engineer be present at the time of pile installation for the proposed bridge structure to observe compliance with the design concept and specifications, and to provide recommendations to modify the design if subsurface conditions differ from those anticipated prior to construction. It is important that the pile load capacity, soil strength, bedrock integrity, degree of compaction, and other soil properties required be confirmed and/or determined at the time of excavation and construction activities for the subject bridge.

The recommendations provided in this report are based on our identification/classification and interpretation of the soils and information given on the WisDOT Boring Logs, and may not be based solely on the contents of the driller's field logs.

Soils & Engineering Services, Inc. prepared this report for the subject bridge in accordance with generally accepted geotechnical engineering practices at this time. Soils & Engineering Services, Inc. offers no other expressed or implied warranty.

Soils & Engineering Services, Inc. will store the soil samples obtained from the soil borings performed for this project for a period of 60 calendar days after the date of this report. Please advise us if we should extend this period.

We recommend that this *Geotechnical Exploration and Analyses Report*, in its entirety, for Proposed Structure B-13-731 be made available to bidding contractors or subcontractors for information purposes. The Appendices, WisDOT Boring Logs, and other attachments referenced in this report should not be separated from the text of this report. This report should be considered invalid if used for purposes other than those described herein.



Safety precautions, such as those required by OSHA and the Wisconsin Department of Safety and Professional Services, should be followed throughout the entire construction of the proposed project. They include, but are not limited to, the proper sloping and/or support of excavation sidewalls and adjacent embankments, roadways, sidewalks, railroad lines, utility lines, and/or buildings.

Soils & Engineering Services, Inc. respectfully submits this *Geotechnical Exploration and Analyses Report*, dated April 10, 2019, for Proposed Structure B-13-731 to **Dane Partners, LLC** and the **Wisconsin Department of Transportation**.



Appendix A



B-13-731 Preliminary Plan Sheet 1 of 4, Exhibit A
60% Plan Cross-Section Sheet PRE-93, Exhibit B
60% Plan Cross-Section Sheet PRE-94, Exhibit C
R-13-352 General Plan Sheet, Exhibit D
R-13-353 General Plan Sheet, Exhibit E



DATE: DATE: DATE: CHECKED BY: BACK CHECKED BY: CORRECTED BY:

8

\$PRNAME\$ U:\41-0660.0X - IH-39 Dane Partners General Bridge Information\BIC Struct 139.NB over 139.NB Off



- LIST OF DRAWINGS
1. PRELIMINARY PLAN
 2. TYPICAL SECTIONS
 3. DESIGN DATA AND QUANTITIES
 4. GENERAL NOTES AND PROFILES
 5. SUBSURFACE EXPLORATION

FOR TYPICAL SECTIONS,
SEE SHEET 2
FOR DESIGN DATA,
SEE SHEET 3

BRIDGE OFFICE CONTACT:
WILLIAM DREHER
(608)-266-8489
CONSULTANT CONTACT:
CHRIS MCMAHON
(715)-834-3161



STATE PROJECT NUMBER


1007-12-78

EXHIBIT A

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY AYRES ASSOCIATES 3433 Oakwood Hills Parkway Eau Claire, WI 54701 www.AyresAssociates.com			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED _____ CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
STRUCTURE B-13-731			
I-39/90 NB OVER RAMP TO USH-12/18 WB			
COUNTY	DANE	TOWN/CITY/VILLAGE	BLOOMING GROVE
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS			
DESIGNED BY	CBM	DESIGN CK'D.	DRAWN BY JLB PLANS CK'D.
PRELIMINARY PLAN			SHEET 1 OF 5

8





9



9

PROJECT NO: 1007-12-78	HWY: IH 39	COUNTY: DANE	CROSS SECTIONS: IH 39 NB	SHEET	E
------------------------	------------	--------------	--------------------------	-------	---

\$PRNAME\$
U:\41-0660.0X - IH-39 Dane Partners General Bridge Information\RETAINING WALLS\B-13-731\B-13-352

CHECKED BY:
DATE:
BACK CHECKED BY:
DATE:
CORRECTED BY:

8



4/2/2019

PENTABLE:BReau.shd.utl.tbl

STATE PROJECT NUMBER

1007-12-78

ALLOWABLE WALL SYSTEMS

WALL CONCRETE PANEL MSE

MATERIAL PROPERTIES

CONCRETE MASONRY (COPING) $f'_c = 3,500$ P.S.I.

BAR STEEL REINFORCEMENT (GRADE 60) $f_y = 60,000$ p.s.i.

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.
BEVEL ALL EXPOSED EDGES OF CONCRETE $\frac{3}{4}$ " UNLESS NOTED OTHERWISE.
BAR STEEL REINFORCEMENT SHALL HAVE 2" CLEAR COVER UNLESS OTHERWISE SHOWN OR NOTED.

ALL WALL STATIONING AND OFFSETS ARE GIVEN AT THE FRONT FACE OF THE WALL R-13-352.

THE EXISTING GROUND LINE IS THE UPPER LIMIT OF EXCAVATION FOR STRUCTURES.

COORDINATE THE CONSTRUCTION OF RETAINING WALL R-13-352 WITH THE SOUTH ABUTMENT OF BRIDGE B-13-731.

ALL BAR STEEL REINFORCEMENT IN CAST-IN-PLACE CONCRETE IS TO BE EPOXY COATED.

THE PLAN QUANTITY FOR THE ITEM "WALL CONCRETE PANEL MECHANICALLY STABILIZED EARTH" IS BASED ON A WALL HEIGHT MEASURED FROM THE TOP OF WALL TO A CONSTANT DEPTH OF 1'-6" BELOW FINISHED GRADE.

THE QUANTITY OF CONCRETE MASONRY, COATED REINFORCING STEEL, AND RUBBERIZED MEMBRANE WATERPROOFING FOR THE CAST-IN-PLACE COPING IS INCIDENTAL TO BID ITEM "WALL CONCRETE PANEL MECHANICALLY STABILIZED EARTH".

LIST OF DRAWINGS

1. GENERAL PLAN
2. QUANTITIES & WALL DATA
3. WALL DETAILS
4. WALL DETAILS
5. TUBULAR STEEL RAILING SCREENING
6. SUBSURFACE EXPLORATION

EXHIBIT D

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY AYRES ASSOCIATES 3433 Oakwood Hills Parkway Eau Claire, WI 54701 www.AyresAssociates.com			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED		CHIEF STRUCTURES DESIGN ENGINEER	DATE
STRUCTURE R-13-352			
MSE WALL ALONG B-13-731 S. ABUT.			
COUNTY	DANE	TOWN/CITY/VILLAGE	BLOOMING GROVE
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS			
DESIGNED BY	DESIGN CK'D.	DRAWN BY	PLANS CK'D.
GENERAL PLAN			SHEET 1 OF 6

BRIDGE OFFICE CONTACT:
WILLIAM DREHER
(608)-266-8489

CONSULTANT CONTACT:
CHRIS MCMAHON
(715)-834-3161


I.D.

DATE:

\$PRNAME\$
U:\41-0660.0X - IH-39 Dane Partners General Bridge Information\RETAINING WALLS\B-13-731\B-13-353 NO


CHECKED BY:
BACK CHECKED BY:
CORRECTED BY:

8



- F.F. DENOTES FRONT FACE.
- INDICATES WING NUMBER ON BRIDGE B-13-731
- ▣ PIPE UNDERDRAIN WRAPPED, 6-INCH, SLOPE 0.5% MIN. TO SUITABLE DRAINAGE, ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN. SEE SHEET 3.

PLAN
MSE RETAINING WALL



BRIDGE OFFICE CONTACT:
WILLIAM DREHER
(608)-266-8489

CONSULTANT CONTACT:
CHRIS MCMAHON
(715)-834-3161

STATE PROJECT NUMBER

1007-12-78

ALLOWABLE WALL SYSTEMS

WALL CONCRETE PANEL MSE

MATERIAL PROPERTIES

CONCRETE MASONRY (COPING) $f'_c = 3,500$ P.S.I.

BAR STEEL REINFORCEMENT (GRADE 60) $f_y = 60,000$ p.s.i.

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BEVEL ALL EXPOSED EDGES OF CONCRETE $\frac{3}{4}$ " UNLESS NOTED OTHERWISE.

BAR STEEL REINFORCEMENT SHALL HAVE 2" CLEAR COVER UNLESS OTHERWISE SHOWN OR NOTED.

ALL WALL STATIONING AND OFFSETS ARE GIVEN AT THE FRONT FACE OF THE WALL R-13-353.

THE EXISTING GROUND LINE IS THE UPPER LIMIT OF EXCAVATION FOR STRUCTURES.

COORDINATE THE CONSTRUCTION OF RETAINING WALL R-13-353 WITH THE NORTH ABUTMENT OF BRIDGE B-13-731.

ALL BAR STEEL REINFORCEMENT IN CAST-IN-PLACE CONCRETE IS TO BE EPOXY COATED.

THE PLAN QUANTITY FOR THE ITEM "WALL CONCRETE PANEL MECHANICALLY STABILIZED EARTH" IS BASED ON A WALL HEIGHT MEASURED FROM THE TOP OF WALL A CONSTANT DEPTH OF 1'-6" BELOW FINISHED GRADE.

THE QUANTITY OF CONCRETE MASONRY, COATED REINFORCING STEEL, AND RUBBERIZED MEMBRANE WATERPROOFING FOR THE CAST-IN-PLACE COPING IS INCIDENTAL TO BID ITEM "WALL CONCRETE PANEL MECHANICALLY STABILIZED EARTH".

LIST OF DRAWINGS

1. GENERAL PLAN
2. QUANTITIES & WALL DATA
3. WALL DETAILS
4. WALL DETAILS
5. TUBULAR STEEL RAILING SCREENING
6. SUBSURFACE EXPLORATION



EXHIBIT E

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY AYRES ASSOCIATES 3433 Oakwood Hills Parkway Eau Claire, WI 54701 www.AyresAssociates.com			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED _____ CHIEF STRUCTURES DESIGN ENGINEER DATE			
STRUCTURE R-13-353			
MSE WALL ALONG B-13-731 N. ABUT.			
COUNTY	DANE	TOWN/CITY/VILLAGE	BLOOMING GROVE
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS			
DESIGNED BY	DESIGN CK'D.	DRAWN BY	PLANS CK'D.
GENERAL PLAN			SHEET 1 OF 6

Appendix B


Boring Location Sketch, Drawing 12939.3-7A and 12939.3-7B
WisDOT Boring Logs for Borings SB-7 and SB-8
Laboratory Test Result Records, Figures 1 through 4





NOT-TO-SCALE

 Soils & Engineering Services, Inc. 1102 STEWART STREET • MADISON, WISCONSIN 53713 Phone: 608-274-7600 • 888-866-SOIL (7645) Fax: 608-274-7511 • Email: soils@soils.ws CONSULTING CIVIL ENGINEERS SINCE 1966	LOCATION SKETCH IH-39 North Segment IH-39/90 NB Bridge Over NB Exit to USH-12/18 WB Illinois State Line - Madison USH-12/18 Interchange Town of Blooming Grove, Dane County, Wisconsin WisDOT State ID 1007-10-02/05	DRAWING 12939.3-7A
---	---	------------------------------



Soils & Engineering Services, Inc.
 1102 STEWART STREET • MADISON, WISCONSIN 53713
 Phone: 608-274-7600 • 888-866-SOIL (7645)
 Fax: 608-274-7511 • Email: soils@soils.ws
 CONSULTING CIVIL ENGINEERS SINCE 1966

LOCATION SKETCH
 IH-39 North Segment
 IH-39/90 NB Bridge Over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

DRAWING
 12939.3-7B

N:\PROJECTS\12600 PROJECTS\12939-1-39 SEGMENTS\12939-1-39 NORTH\12939-3 BRSV\31.NB BR.NB.XRAMP\DRAWINGS\12939-3.139N.NB.BR.NB.XRAMP.TN.BLOOMGROVE.DANE.CO.1007-10-02.R07.WISDOT.LOGS.B-13-731.GPJ

End of Boring at 99.1 ft.

Segment 04/10/19

10 NB

Segment 04/10/19

WI Dept. of Transportation
3502 Kinsman Blvd.
Madison, WI 53704

WISDOT PROJECT ID:
1007-10-02/05

WISDOT STRUCTURE ID:
B-13-731

BORING ID:
SB-8

PAGE NO:
1 of 3

WISDOT PROJECT NAME:
IH-39 North Segment

CONSULTANT:
Dane Partners, LLC

CONSULTANT PROJECT NO:
12939.3

LATITUDE:
473700.32

LONGITUDE:
849743.38

ROADWAY NAME:
Bridge over NB Exit to USH-12/18 WB

DRAWING CONTRACTOR:
Soils & Engineering Services, Inc.

DRILLING CONTRACTOR PROJECT NO:
12939.3

NORTHING:
473700.32

EASTING:
849743.38

DATE STARTED:
1/09/19

CREW CHIEF:
S. Hunger

DRILL RIG:
CME 550X

COORDINATE SYSTEM:
WCCS

DATE COMPLETED:
1/09/19

LOGGED BY:
G. Prior

HOLE SIZE:
5.6 in

HORIZONTAL DATUM:
WCCS Dane

VERTICAL DATUM:
MSL

COUNTY:
Dane

LOG QC BY:
C. Bower

HAMMER TYPE:
Automatic

STREAMBED ELEVATION:
NA

STATION:
2574+10 'NB (OES)'

OFFSET:
10' L

TOWNSHIP:
7N

RANGE:
10E

SECTION:
23

1/4 SECTION:
SW

1/4 SECTION:
SE

SURFACE ELEVATION:
870.9 ft

SAMPLE TYPE NUMBER	RECOVERY (in) (RQD)	Moisture	BLOW COUNTS (N VALUE)	Depth (ft)	Graphic	Soil / Rock Description and Geological Origin for Each Major Unit / Comments	USCS / AASHTO	Strength Qp (tsf)	Liquid Limit (%)	Plasticity Index (%)	Boulders	Drilling Method	Notes
GS		M		0.6		LEAN CLAY, dark brown, moist, medium plasticity, topsoil	CL	870.3				HSA	2 1/4"-inside-diameter continuous flight hollow-stem augers
SPT 1 AU	0	M	4-5-5 (10)			SILTY SAND WITH GRAVEL, brown, fine to medium grained, moist to wet, loose to very loose, non-plastic to low plasticity, trace to some gravel, glacial till							N1 ₆₀ =22
SPT 2	16	W	2-3-2 (5)	5									N1 ₆₀ =10
SPT 3	14	W 13	3-3-3 (6)				SM						Dry Wt = 141 pcf MC = 12.7% N1 ₆₀ =10
SPT 4	18	W	2-2-2 (4)	10									N1 ₆₀ =8
SPT 5	18	W	2-3-4 (7)	15		SILTY SAND WITH GRAVEL, brown, fine to medium grained, wet, loose to medium dense, non-plastic to low plasticity, trace to some gravel, glacial till		858.9					N1 ₆₀ =9
SPT 6	18	W	2-3-3 (6)	20									N1 ₆₀ =8
SPT 7	14	W	3-3-9 (12)	25			SM						N1 ₆₀ =15
SPT 8	18	W	2-2-3 (5)	30									N1 ₆₀ =7
SPT 9	18	W	3-4-5 (9)										N1 ₆₀ =10

WATER LEVEL & CAVE-IN OBSERVATION DATA

WATER ENCOUNTERED DURING DRILLING:	NMR	CAVE - IN DEPTH AT COMPLETION:	34.83ft.	WET ☐
WATER LEVEL AT COMPLETION:	22.33ft.	CAVE - IN DEPTH AFTER 0 HOURS:	NMR	WET ☐
				DRY ☐

NOTES: 1) Stratification lines between soil types represent the approximate boundary; gradual transition between in-situ soil layers should be expected.
2) NE = Not Encountered; NMR = No Measurement Recorded


Dry Wt = 134 pcf
Fines = 47%
2¼"-inside-diameter
continuous flight
hollow-stem augers
and water
MC = 8.9%
 $q_u = 2.04$ tsf
 $N_{160} = 27$
 $N_{100} = 57$

N:\PROJECTS\12900 PROJECTS\12939.1-39 SEGMENTS\12939.1-39 NORTH\12939.3.BRS\731.NB BR.NB XRAMP\DRAWINGS\12939.3.139N.NB BR.NB XRAMP.TN BLOOMG GROVE.DANE CO.1007-10-02.R07.WISDOT LOGS.B-13-731.GPJ IH-39 North Segment 04/10/19

				WI Dept. of Transportation 3502 Kinsman Blvd. Madison, WI 53704				WISDOT PROJECT ID: 1007-10-02/05		BORING ID: SB-8			
				WISDOT STRUCTURE ID: B-13-731		PAGE NO: 3 of 3							
SAMPLE TYPE NUMBER	RECOVERY (in) (RQD)	Moisture	BLOW COUNTS (N VALUE)	Depth (ft)	Graphic	Soil / Rock Description and Geological Origin for Each Major Unit / Comments	USCS / AASHTO	Strength Qp (tsf)	Liquid Limit (%)	Plasticity Index (%)	Boulders	Drilling Method	Notes
 SPT 19	6	W 9	64-36/3"	85		82.0 POORLY GRADED GRAVEL WITH SILT AND SAND, brown, poorly graded, fine to coarse grained, wet, very dense, non-plastic to low plasticity 788.9	SM						Fines = 7% MC = 9.0% N ₆₀ =47-27/3"
 SPT 20	12	W	28-72			89.5 781.4	GP-GM						N ₆₀ =20-53
End of Boring at 89.5 ft.													

ATTERBERG LIMITS TEST REPORT

ASTM Test Designation D4318/AASHTO Test Designations T89 & T90



Specimen Identification	LL	PL	PI	Sample Classification
● Boring SB-7, 14'-9" Depth	NP	NP	NP	SILTY SAND (SM) — 7% gravel, 64% sand, 29.1% fines, fine to medium grained, non-plastic fines, light brown, wet, loose relative density, GLACIAL TILL , few gravel
☒ Boring SB-8, 69'-7" Depth	17	10	7	SILTY CLAYEY SAND (SC-SM) — 6% gravel, 47% sand, 47.4% fines, fine grained, low plasticity fines, grayish-brown, moist, GLACIAL TILL , few gravel



Soils & Engineering Services, Inc.

1102 STEWART STREET • MADISON, WISCONSIN 53713

Phone: 608-274-7600 • 888-866-SOIL (7645)

Fax: 608-274-7511 • Email: soils@soils.ws

CONSULTING CIVIL ENGINEERS SINCE 1966

LABORATORY TEST RESULT RECORD

IH-39 North Segment

IH-39/90 NB Bridge over NB Exit to USH-12/18 WB

Illinois State Line - Madison

USH-12/18 Interchange

Town of Blooming Grove, Dane County, Wisconsin


WisDOT State ID 1007-10-02/05

12939.3

FIGURE 1

UNCONFINED COMPRESSION TEST REPORT

ASTM Test Designation D2166



Unconfined Compression Test Results for **Boring SB-8**

Sample			Diameter (inches)	Height (inches)	H:D Ratio	Wet Density (^{lb} / _{ft} ³)	Dry Density (^{lb} / _{ft} ³)	MC (%)	Failure	
Identification	Classification	Type							Stress (^{ton} / _{ft} ²)	Strain (%)
● 69'-7" Depth	SILTY CLAYEY SAND (SC-SM) GLACIAL TILL	SS2	1.534	1.976	1.3	146.4	134.4	8.9	2.04	12.0

SS2=2-inch-outside-diameter, split-barrel sampler



Soils & Engineering Services, Inc.

1102 STEWART STREET • MADISON, WISCONSIN 53713

Phone: 608-274-7600 • 888-866-SOIL (7645)

Fax: 608-274-7511 • Email: soils@soils.ws

CONSULTING CIVIL ENGINEERS SINCE 1966

LABORATORY TEST RESULT RECORD

IH-39 North Segment

IH-39/90 NB Bridge over NB Exit to USH-12/18 WB

Illinois State Line - Madison

USH-12/18 Interchange


Town of Blooming Grove, Dane County, Wisconsin

WisDOT State ID 1007-10-02/05

12939.3

FIGURE 2

PARTICLE SIZE DISTRIBUTION ANALYSIS REPORT



	COBBLES (%)	GRAVEL (%)		SAND (%)			FINES (%)	
		coarse	fine	coarse	medium	fine	SILT (%)	CLAY (%)
●	0	7		64			29.1	
☒	0	6		47			47.4	

Sieve Size	Percent Finer		
	●	☒	
$\frac{3}{4}$ -inch	100		
$\frac{1}{2}$ -inch	99	100	
$\frac{3}{8}$ -inch	98	98	
#4	93	94	
#8	89	91	
#10	89	90	
#16	87	88	
#30	84	85	
#40	79	82	
#50	69	76	
#60	62	72	
#80	47	63	

Sieve Size	Percent Finer	
	●	☒
#100	41	59
#200	29.1	47.4

		Grain Size (mm)			Coefficients	
		D ₆₀	D ₃₀	D ₁₀	C _c	C _u
●	0.24	0.079				
☒	0.16					

Sample Information	
●	Boring SB-7, 14'-9" Depth: SILTY SAND (SM) — <i>fine to medium grained, non-plastic fines (LL=NP, PL=NP), light brown, wet, loose relative density, GLACIAL TILL, few gravel</i>
✕	Boring SB-8, 69'-7" Depth: SILTY CLAYEY SAND (SC-SM) — <i>fine grained, low plasticity fines (LL=17, PL=10), grayish-brown, moist, GLACIAL TILL, few gravel</i>

Soils & Engineering Services, Inc.

1102 STEWART STREET • MADISON, WISCONSIN 53713

Phone: 608-274-7600 • 888-866-SOIL (7645)

Fax: 608-274-7511 • Email: soils@soils.ws

CONSULTING CIVIL ENGINEERS SINCE 1966

LABORATORY TEST RESULT RECORD

IH-39 North Segment

IH-39/90 NB Bridge over NB Exit to USH-12/18 WB


Illinois State Line - Madison

USH-12/18 Interchange

Town of Blooming Grove, Dane County, Wisconsin

WisDOT State ID 1007-10-02/05

PARTICLE SIZE DISTRIBUTION ANALYSIS REPORT



COBBLES (%)	GRAVEL (%)		SAND (%)			FINES (%)	
	coarse	fine	coarse	medium	fine	SILT (%)	CLAY (%)
● 0	49		44			6.8	

Sieve Size	Percent Finer
1 1/2-inch	100
1-inch	97
3/4-inch	85
1/2-inch	76
3/8-inch	67
#4	51
#8	40
#10	38
#16	33
#30	28
#40	23
#50	18

Sieve Size	Percent Finer
#60	15
#80	11
#100	10
#200	6.8

Grain Size (mm)			Coefficients	
D ₆₀	D ₃₀	D ₁₀	C _u	C _c
● 7.0	0.78	0.15	0.58	47

Sample Information	
● Boring SB-8, 83'-9" Depth: POORLY-GRADED GRAVEL WITH SILT AND SAND (GP-GM) — fine to coarse grained, non-plastic to low plasticity fines, brown, wet, very dense relative density	



Soils & Engineering Services, Inc.

1102 STEWART STREET • MADISON, WISCONSIN 53713

Phone: 608-274-7600 • 888-866-SOIL (7645)

Fax: 608-274-7511 • Email: soils@soils.ws

CONSULTING CIVIL ENGINEERS SINCE 1966

LABORATORY TEST RESULT RECORD

IH-39 North Segment

IH-39/90 NB Bridge over NB Exit to USH-12/18 WB

Illinois State Line - Madison

USH-12/18 Interchange

Town of Blooming Grove, Dane County, Wisconsin

WisDOT State ID 1007-10-02/05

12939.3

FIGURE 4

Appendix C

Table 7-1: Recommended Soil Design Parameters

Table 7-2: Deep Driven Pile Foundation Analyses' Results; *APILE* Static Analyses'
Average Unfactored Soil Design Parameters

Table 7-3: Deep Driven Pile Foundation Analyses' Results; *APILE* Static and
GRLWEAP Drivability Analyses' Results



Table 7-1: RECOMMENDED SOIL DESIGN PARAMETERS

IH-39 North Segment
IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
Illinois State Line - Madison
USH-12/18 Interchange
Town of Blooming Grove, Dane County, Wisconsin
WisDOT State ID 1007-10-02/05

Elevation (feet)	Material Type	Estimated Soil Parameters*			Driven Pile Parameters	
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***
----- Boring SB-7 located in the vicinity of South Abutment of Bridge Structure B-13-731 -----						
889.0 to 887.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	----	----
887.7 to 879.2	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	----	----
879.2 to 870.2	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	----	----
870.2 to 870.0	Replace existing dark brown LEAN CLAY WITH SAND (CL) FILL TOPSOIL with MSE Retaining Wall Backfill	120.0	30	0	----	----
870.0 to 868.9	Replace existing brown fine to coarse SILTY SAND WITH GRAVEL (SM) FILL with MSE Retaining Wall Backfill	120.0	30	0	----	----
868.9 to 867.4	SANDY LEAN CLAY (CL) — medium plasticity, brown, moist, medium consistency, FILL	120.0	31	0	----	----
867.4 to 867.2		120.0	31	0	33 [67]	0.45
867.2 to 867.0		125.0	0	800	50 [83]	0.35
867.0 to 866.2	SILTY SAND WITH GRAVEL (SM) — fine to coarse grained, non-plastic to low plasticity fines, brown, moist, very loose to loose relative density, FILL	125.0	0	800	50 [83]	0.35
866.2 to 865.7		120.0	31	0	33 [67]	0.45
865.7 to 859.2		SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, wet, loose to very loose relative density, GLACIAL TILL , trace to some gravel	152.0	29	0	33 [67]
859.2 to 853.2	CLAYEY SAND WITH GRAVEL (SC) — fine grained, medium plasticity fines, reddish-brown to light brown, wet, medium dense relative density, GLACIAL TILL , trace to some gravel	152.0	29	0	33 [67]	0.45
853.2 to 848.2		152.0	31	0	33 [67]	0.45
848.2 to 838.2		152.0	29	0	33 [67]	0.45
838.2 to 830.7		152.0	29	0	33 [67]	0.45
830.7 to 823.2		152.0	29	0	33 [67]	0.45
823.2 to 813.2		146.0	31	0	33 [67]	0.45

Table Notes

- * The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- ** The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ 's greater than 36° are reduced to 36° or 40° depending upon the N_{100} -value for the indicated stratum/sub-stratum. The reduced driven pile ϕ 's are shown in brackets ([]). Please refer to geotechnical report for further explanation.
- *** The presented Driving SSL values from Table 11.3-4 of the WisDOT Bridge Manual are used for driven cast-in-place, steel pipe piles. The increased Driving SSL values shown in brackets ([]) are used for driven steel H-piles based on feedback from pile driving contractors.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets ([]). Please see report for further definition of the LRFD Factors presented.

Table Abbreviations and Symbols

pcf = pounds per cubic foot
SSL = soil strength loss.
NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Bot = Cohesion @ bottom of stratum/sub-stratum.

Table 7-1: RECOMMENDED SOIL DESIGN PARAMETERS
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

Elevation (feet)	Material Type	Estimated Soil Parameters*			Driven Pile Parameters	
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***
813.2 to 803.2	<i>SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist to wet, medium dense relative density, GLACIAL TILL, trace to some gravel</i>	152.0	32	0	33 [67]	0.45
803.2 to 800.7	<i>POORLY-GRADED SAND WITH GRAVEL (SP) — fine grained, light grayish-brown and brown, wet, medium dense relative density</i>	125.0	31	0	17 [50]	0.45
800.7 to 798.2	<i>SANDY LEAN CLAY (CL) — medium plasticity, grayish-brown, moist, hard to very stiff consistency</i>	132.0	0	3,800	50 [83]	0.35
798.2 to 788.2	<i>SILTY SAND WITH GRAVEL (SM) — fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist, dense to very dense relative density, GLACIAL TILL, trace to some gravel, with few irregular gray CLAYEY SAND (SC) lenses</i>	152.0	34	0	33 [67]	0.45
788.2 to 783.2		152.0	38 [36]	0	33 [67]	0.45
783.2 to 774.2		152.0	45 [36]	0	17 [50]	0.45
774.2 to 771.1		152.0	45 [40]	0	17 [17]	0.45
	----- End of Boring SB-7 @ Elevation 771.1 feet -----					

Table Notes

- * The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- ** The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° or 40° depending upon the N_{100} -value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- *** The presented Driving SSL values from Table 11.3-4 of the WisDOT Bridge Manual are used for driven cast-in-place, steel pipe piles. The increased Driving SSL values shown in brackets (II) are used for driven steel H-piles based on feedback from pile driving contractors.
- **** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.

Table Abbreviations and Symbols

pcf = pounds per cubic foot
 psf = pounds per square foot
 NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Bot = Cohesion @ bottom of stratum/sub-stratum.



Table 7-1: RECOMMENDED SOIL DESIGN PARAMETERS

IH-39 North Segment
IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
Illinois State Line - Madison
USH-12/18 Interchange
Town of Blooming Grove, Dane County, Wisconsin
WisDOT State ID 1007-10-02/05

WISDOT State ID 1007-10-02103

Elevation (feet)	Material Type	Estimated Soil Parameters*			Driven Pile Parameters	
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***
----- Boring SB-8 located in the vicinity of North Abutment of Bridge Structure B-13-731 -----						
889.0 to 887.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---
887.7 to 879.7	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---
879.7 to 871.5	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---
871.5 to 870.9	Construct new embankment with MSE Retaining Wall Backfill	120.0	30	0	---	---
870.9 to 870.3	Replace existing dark brown LEAN CLAY WITH SAND (CL) FILL TOPSOIL with MSE Retaining Wall Backfill	120.0	30	0	---	---
870.3 to 868.0	Replace existing brown fine to medium SILTY SAND WITH GRAVEL (SM) GLACIAL TILL trace to some gravel with MSE Retaining Wall Backfill	120.0	30	0	---	---
868.0 to 867.0		152.0	30	0	33 [67]	0.45
867.0 to 858.9		152.0	30	0	33 [67]	0.45
858.9 to 848.9	SILTY SAND WITH GRAVEL (SM) --- fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, wet, loose to medium dense relative density, GLACIAL TILL, trace to some gravel	152.0	29	0	33 [67]	0.45
848.9 to 843.9		152.0	31	0	33 [67]	0.45
843.9 to 836.4		152.0	29	0	33 [67]	0.45
836.4 to 828.9		152.0	29	0	33 [67]	0.45
828.9 to 818.9		152.0	31	0	33 [67]	0.45
818.9 to 808.9		152.0	29	0	33 [67]	0.45
808.9 to 803.9		152.0	31	0	33 [67]	0.45
803.9 to 798.9	SILTY CLAYEY SAND (SC-SM) --- fine grained, low plasticity fines, brown, moist, dense relative density, GLACIAL TILL, trace to some gravel	146.0	35	0	33 [67]	0.45
798.9 to 788.9	SILTY SAND WITH GRAVEL (SM) --- fine to medium grained, non-plastic to low plasticity fines, brown to reddish-brown, moist, very dense relative density, GLACIAL TILL, trace to some gravel	152.0	42 [36]	0	33 [67]	0.45

Table Notes

- * The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N'_{60} -value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets ([]). Please refer to geotechnical report for further explanation.
- ** The presented Driving SSL values from Table 11.3-4 of the WisDOT Bridge Manual are used for driven cast-in-place, steel pipe piles. The increased Driving SSL values shown in brackets ([]) are used for driven steel H-piles based on feedback from pile driving contractors.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets ([]). Please see report for further definition of the LRFD Factors presented.

Table Abbreviations and Symbols

pcf = pounds per cubic foot
SSL = soil strength loss.

Top = Cohesion @ top of stratum/sub-stratum.

Bot = Cohesion @ bottom of stratum/sub-stratum.



Table 7-1: RECOMMENDED SOIL DESIGN PARAMETERS
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

Elevation (feet)	Material Type	Estimated Soil Parameters*			Driven Pile Parameters	
		Moist Density, γ (pcf)	Angle of Internal Friction, ϕ^* (degrees)	Cohesion, c (psf)	Driving SSL** (%)	LRFD Factors***
788.9 to 781.4	POORLY-GRADED GRAVEL WITH SILT AND SAND (GP-GM) — <i>fine to coarse grained, non-plastic to low plasticity fines, brown, wet, very dense relative density</i>	120.0	45 [40]	0	0 [0]	0.45
	----- End of Boring SB-8 @ Elevation 781.4 feet -----					

Table Notes

- * The Moist Density, Angle of Internal Friction, Cohesion, Driving SSL, and LRFD Static Resistance Factor values are considered estimates based on the soils encountered at the indicated boring.
- * The computed Angle of Internal Friction, ϕ , for each soil stratum or sub-stratum is presented. For driven pile computations, computed ϕ s greater than 36° are reduced to 36° or 40° depending upon the N_{160} -value for the indicated stratum/sub-stratum. The reduced driven pile ϕ s are shown in brackets (I). Please refer to geotechnical report for further explanation.
- ** The presented Driving SSL values from Table 11.3-4 of the WisDOT Bridge Manual are used for driven cast-in-place, steel pipe piles. The increased Driving SSL values shown in brackets (II) are used for driven steel H-piles based on feedback from pile driving contractors.
- *** LRFD Static Resistance Factors and LRFD Load Factors are presented in this column. The LRFD Static Resistance Factors from the WisDOT Bridge Manual Table 11.3-1 or Table 11.3-8 are presented. For soil strata contributing to downdrag, LRFD Load Factors from the AASHTO LRFD Bridge Design Specifications Table 3.4.1-2 are presented in brackets (I). Please see report for further definition of the LRFD Factors presented.

Table Abbreviations and Symbols

pcf = pounds per cubic foot.
 SSL = soil strength loss.
 NA = Not applicable.

Top = Cohesion @ top of stratum/sub-stratum.

Bot = Cohesion @ bottom of stratum/sub-stratum.



Table 7-2: DEEP PILE FOUNDATION ANALYSES' RESULTS
 Static Analyses' Average Unfactored Soil Design Parameters
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

Boring ==> SB-7 located in the vicinity of South Abutment of Bridge Structure B-13-731										
Substructure Unit Foundation Bottom Elev ==> 887.7 feet				Design Ultimate GWL Elev ==> 867.0 feet				Design Contraction Scour Elev ==> NA		
Design Driving GS Elev ==> 867.4 feet				Design Driving/Restrike GWL Elev ==> 867.0 feet				Design Local Scour Elev ==> NA		
Design Ultimate GS Elev ==> 868.9 feet				Design Pre-Boring Elev ==> NA						
Pile Type and Size ==> 10 3/4" CIP HP 10x42										
Elevation (feet)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)
889.0 to 887.7	0	0	0	0						
887.7 to 879.2	230	0	230	0						
879.2 to 870.2	460	0	460	0						
870.2 to 869.9	540	0	540	0						
869.9 to 868.9	590	0	590	0						
868.9 to 867.4	1,170	0	1,170	0						
867.4 to 867.2	70	4,100	90	3,800						
867.2 to 867.0	70	5,900	90	5,600						
867.0 to 866.2	70	5,700	100	5,900						
866.2 to 865.7	90	6,700	120	6,800						
865.7 to 859.2	140	10,300	190	10,300						
859.2 to 853.2	240	13,600	310	13,600						
853.2 to 848.2	390	19,600	510	19,400						
848.2 to 838.2	460	13,600	610	13,700						
838.2 to 830.7	620	13,300	830	13,300						
830.7 to 823.2	760	13,500	1,010	13,500						
823.2 to 813.2	1,080	20,500	1,410	20,500						
813.2 to 803.2	1,410	32,100	1,830	32,000						
803.2 to 800.7	1,420	24,800	1,860	25,400						
800.7 to 798.2	3,680	36,400	3,770	36,900						
798.2 to 788.2	2,050	72,800	2,630	72,800						
788.2 to 783.2	2,770	144,000	3,480	143,000						
783.2 to 774.2	3,010	157,000	3,780	158,000						

Table Abbreviations and Symbols

HP = Steel H-pile.
 NA = Not applicable.
 NR = Not recommended.
 psf = pounds per square foot.

Ø CIP = inch-outside-diameter, cast-in-place, steel pipe pile.
 Ø PCP = inch-square, precast concrete pile.
 Refusal = Steel pile will obtain capacity in indicated layer due to very dense soil or bedrock.

Elev = Elevation.
 GS = Ground Surface.
 GWL = Groundwater Level.

The End Bearing & Skin Friction values presented above are the computed unfactored average for the indicated stratum.

Table 7-2: DEEP PILE FOUNDATION ANALYSES' RESULTS
 Static Analyses' Average Unfactored Soil Design Parameters
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

		Boring ==> SB-7 located in the vicinity of South Abutment of Bridge Structure B-13-731									
Substructure Unit Foundation Bottom Elev ==>		887.7 feet		Design Ultimate GWL Elev ==>		867.0 feet		Design Contraction Scour Elev ==>		NA	
Design Driving GS Elev ==>		867.4 feet		Design Driving/Restrike GWL Elev ==>		867.0 feet		Design Local Scour Elev ==>		NA	
Design Ultimate GS Elev ==>		868.9 feet		Design Pre-Boring Elev ==>		NA					
Pile Type and Size ==>		10 3/4" CIP		HP 10x42							
Elevation (feet)		Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)
		4,730	371,000	5,760	365,000						
774.2 to 771.1											

Table Abbreviations and Symbols

HP = Steel H-pile.
 NA = Not applicable.
 NR = Not recommended.
 psf = pounds per square foot.

Elev = Elevation.
 GS = Ground Surface.
 GWL = Groundwater Level.

The End Bearing & Skin Friction values presented above are the computed unfactored average for the indicated stratum.



Table 7-2: DEEP PILE FOUNDATION ANALYSES' RESULTS
 Static Analyses' Average Unfactored Soil Design Parameters
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

		Boring ==> SB-8 located in the vicinity of North Abutment of Bridge Structure B-13-731									
Substructure Unit Foundation Bottom Elev ==>		Design Driving GS Elev ==>		Design Ultimate GS Elev ==>		Design Driving/Restrike GWL Elev ==>		Design Ultimate GWL Elev ==>		Design Contraction Scour Elev ==>	
Design Driving GS Elev ==>		Design Driving GS Elev ==>		Design Ultimate GS Elev ==>		Design Driving/Restrike GWL Elev ==>		Design Ultimate GWL Elev ==>		Design Local Scour Elev ==>	
Design Ultimate GS Elev ==>		Design Ultimate GS Elev ==>		Design Ultimate GS Elev ==>		Design Driving/Restrike GWL Elev ==>		Design Ultimate GWL Elev ==>		Design Local Scour Elev ==>	
Pile Type and Size ==>		10%/40 CIP		HP 10x42							
Elevation (feet)		Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)	Skin Friction (psf)	End Bearing (psf)
889.0 to 887.7		0	0	0	0						
887.7 to 879.7		230	0	230	0						
879.7 to 871.5		450	0	450	0						
871.5 to 870.9		510	0	510	0						
870.9 to 870.3		530	0	530	0						
870.3 to 868.0		600	0	600	0						
868.0 to 867.0		10	1,000	10	900						
867.0 to 858.9		80	6,600	110	6,600						
858.9 to 848.9		250	13,400	330	13,500						
848.9 to 843.9		460	19,700	600	19,500						
843.9 to 836.4		500	13,600	670	13,700						
836.4 to 828.9		640	13,600	850	13,600						
828.9 to 818.9		940	20,100	1,230	20,100						
818.9 to 808.9		980	13,700	1,300	13,800						
808.9 to 803.9		1,320	23,400	1,730	23,700						
803.9 to 798.9		1,990	103,000	2,550	102,000						
798.9 to 788.9		2,510	156,000	3,150	157,000						
788.9 to 781.4		4,070	404,000	4,960	403,000						

Table Abbreviations and Symbols

HP = Steel H-pile.
 NA = Not applicable.
 NR = Not recommended.
 psf = pounds per square foot.

Elev = Elevation.
 GS = Ground Surface.
 GWL = Groundwater Level.

The End Bearing & Skin Friction values presented above are the computed unfactored average for the indicated stratum.



Table 7-3: DEEP DRIVEN PILE FOUNDATION ANALYSES' RESULTS
 APILE Static and GRLWEAP Drivability Analyses' Results
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

Boring ==> SB-7 located in the vicinity of South Abutment of Bridge Structure B-13-731									
Substructure Unit Foundation Bottom Elev ==>		887.7 feet		Design Ultimate GWL Elev ==>		867.0 feet		Design Contraction Scour Elev ==>	
Design Driving GS Elev ==>		867.4 feet		Design Driving/Restrike GWL Elev ==>		867.0 feet		Design Local Scour Elev ==>	
Design Ultimate GS Elev ==>		868.9 feet		Design Pre-Boring Elev ==>		NA			
Pile Type and Size	WisDOT Maximum R _{n,dyn} (kips)	Design Steel Yield Stress (ksi)	Design R _{n,dyn} (kips)	Design P _r (kips)	Design Pile Tip Elevation* (feet)	Vertical Piles Driven to Design R _{n,dyn} At Time of Installation			
						Pile Driving Hammer	Pile Tip Elevation* (feet)	Pile Refusal** (Yes/No)	Soil Resistance During Driving* (kips)
Factored Embankment Settlement Downdrag Load = 54 kips for 10¼Ø CIP.									
Per WBM Chapter 11.3.1.17.1, the Design P _r should be reduced by the Factored Embankment Settlement Downdrag Load for 10¼Ø CIP unless countermeasures are taken.									
10¼Ø CIP 0.250 †	260	35	260	130	781.4	D16-32	783.4	Yes	Not recommended. Pile refused above the design pile tip elevation.
10¼Ø CIP 0.250 †	260	35	260	130	781.4	D30-32	781.4	No	260
10¼Ø CIP 0.250 †	260	45†	260	130	781.4	D30-32	781.4	No	260
10¼Ø CIP 0.365 †	300	35	300	150	775.4	D16-32	775.4	Yes	300
10¼Ø CIP 0.365 †	300	45†	300	150	775.4	D16-32	775.4	Yes	300
10¼Ø CIP 0.500 †	300	35	300	150	775.4	D16-32	775.4	No	29.2
10¼Ø CIP 0.500 †	300	45†	300	150	775.4	D16-32	775.4	No	29.2
Factored Embankment Settlement Downdrag Load = 81 kips for 10x42 HP.									
Per WBM Chapter 11.3.1.17.1, the Design P _r should be reduced by the Factored Embankment Settlement Downdrag Load for 10x42 HP unless countermeasures are taken.									
10x42 HP	360	50	360	180	769.8	D16-32	769.8	No	360
									712

Table Notes

- * Elevation, Soil Resistance During Driving, and Maximum Steel Stress During Driving values are considered estimates based on the soils encountered at the indicated boring.
- ** Pile Refusal = Specified pile driving hammer is estimated to require more than 120 blows per foot to drive the indicated steel pile.
- *** Ultimate Static Capacity is the estimated capacity using static analyses that the indicated pile could achieve after pile set-up. The Design R_{n, dyn} and Design P_r should be used for design.
- † Pile driven through upper dense layer(s) to reach design pile tip elevation. Maximum Computed Driving R_{n, dyn} {shown within brackets} for the upper dense layer(s) is less than or equal to the WisDOT Maximum R_{n, dyn} for the indicated pile.
- ★ Pile Tip Elevation for indicated pile was controlled by recommended 10-foot minimum pile embedment below pre-bore depth.
- † Per Mr. Jeff Horsfall with WisDOT, the use of steel with a yield stress of 45 ksi for the shell of CIP pipe piles is acceptable to WisDOT.
- ✱ Design P_r was reduced due to low strength soil strata below the Design Pile Tip Elevation or due to a Design Ultimate GS Elevation that is less than the Design Driving GS Elevation.

Table Abbreviations and Symbols

- NA = Not applicable.
- ksi = kips per square inch.
- HP = Steel H-pile.
- f_c = ultimate concrete strength in ksi.
- † = -inch wall thickness.
- P_r = Factored Axial Compression Resistance.
- Ø CIP = -inch-outside-diameter, cast-in-place, steel pipe pile.
- Ø PCP = -inch-square, precast concrete pile.
- R_{n, dyn} = Required Driving Resistance.



Table 7-3: DEEP DRIVEN PILE FOUNDATION ANALYSES' RESULTS
 APILE Static and GRLWEAP Drivability Analyses' Results
 IH-39 North Segment
 IH-39/90 NB Bridge over NB Exit to USH-12/18 WB
 Illinois State Line - Madison
 USH-12/18 Interchange
 Town of Blooming Grove, Dane County, Wisconsin
 WisDOT State ID 1007-10-02/05

Boring ==> SB-8 located in the vicinity of North Abutment of Bridge Structure B-13-731									
Substructure Unit Foundation Bottom Elev ==>		887.7 feet		Design Ultimate GWL Elev ==>		867.0 feet		Design Contraction Scour Elev ==>	
Design Driving GS Elev ==>		868.0 feet		Design Driving/Restrike GWL Elev ==>		867.0 feet		Design Local Scour Elev ==>	
Design Ultimate GS Elev ==>		871.5 feet		Design Pre-Boring Elev ==>		NA			
Pile Type and Size	WisDOT Maximum R _{n_{dyn}} (kips)	Design Steel Yield Stress (ksi)	Design R _{n_{dyn}} (kips)	Design P _r (kips)	Design Pile Tip Elevation* (feet)	Vertical Piles Driven to Design R _{n_{dyn}} At Time of Installation			
						Pile Driving Hammer	Pile Tip Elevation* (feet)	Pile Refusal** (Yes/No)	Soil Resistance During Driving* (kips)
Factored Embankment Settlement Downdrag Load = 60 kips for 10¾Ø CIP.									
Per WBM Chapter 11.3.1.17.1, the Design P _r should be reduced by the Factored Embankment Settlement Downdrag Load for 10¾Ø CIP unless countermeasures are taken.									
10¾Ø CIP 0.250 †	260	35	260	130	786.2	D16-32	786.2	No	260
10¾Ø CIP 0.250 †	260	45 [†]	260	130	786.2	D16-32	786.2	No	260
10¾Ø CIP 0.365 †	300	35	300	150	785.6	D16-32	785.6	No	300
10¾Ø CIP 0.365 †	300	45 [†]	300	150	785.6	D16-32	785.6	No	300
10¾Ø CIP 0.500 †	300	35	300	150	785.6	D16-32	785.6	No	300
10¾Ø CIP 0.500 †	300	45 [†]	300	150	785.6	D16-32	785.6	No	300
Factored Embankment Settlement Downdrag Load = 85 kips for 10x42 HP.									
Per WBM Chapter 11.3.1.17.1, the Design P _r should be reduced by the Factored Embankment Settlement Downdrag Load for 10x42 HP unless countermeasures are taken.									
10x42 HP	360	50	360	180	778.4	D16-32	778.4	No	360
									613

Table Notes

- * Elevation, Soil Resistance During Driving, and Maximum Steel Stress During Driving values are considered estimates based on the soils encountered at the indicated boring.
- ** Pile Refusal = Specified pile driving hammer is estimated to require more than 120 blows per foot to drive the indicated steel pile.
- *** Ultimate Static Capacity is the estimated capacity using static analyses that the indicated pile could achieve after pile set-up. The Design R_{n, dyn} and Design P_r should be used for design.
- † Pile driven through upper dense layer(s) to reach design pile tip elevation. Maximum Computed Driving R_{n, dyn} {shown within brackets} for the upper dense layer(s) is less than or equal to the WisDOT Maximum R_{n, dyn} for the indicated pile.
- ★ Pile Tip Elevation for indicated pile was controlled by recommended 10-foot minimum pile embedment below pre-bore depth.
- † Per Mr. Jeff Horsfall with WisDOT, the use of steel with a yield stress of 45 ksi for the shell of CIP pipe piles is acceptable to WisDOT.
- ✱ Design P_r was reduced due to low strength soil strata below the Design Pile Tip Elevation or due to a Design Ultimate GS Elevation that is less than the Design Driving GS Elevation.

Table Abbreviations and Symbols

- NA = Not applicable.
- ksi = kips per square inch.
- HP = Steel H-pile.
- f_c = ultimate concrete strength in ksi.
- † = -inch wall thickness.
- P_r = Factored Axial Compression Resistance.
- Ø CIP = -inch-outside-diameter, cast-in-place, steel pipe pile.
- Ø PCP = -inch-square, precast concrete pile.
- R_{n, dyn} = Required Driving Resistance.

