

REHABILITATION STRUCTURE SURVEY REPORT

DT1696 6/2012

Wisconsin Department of Transportation

- ☒ **Grade Separation**
☐ **Stream Crossing**
☐ **Culvert**
☐ **Railroad**
☐ **Retaining Wall**
☐ **Noise Barrier**
☐ **Sign Structure**
☐ **Other:** _____

RECEIVED
5/15/2019
BUREAU OF STRUCTURES

For guidance see: http://dotnet/dtid_bos/extranet/structures/reports-checklists.htm

Design Project ID 1090-05-02		Construction Project ID 1090-05-72		Highway (Project Name) Rock Freeway IH 43	
Final Plan Due Date 12/1/2019		Preliminary Plan Due Date 5/15/2019		<input type="checkbox"/> Town <input type="checkbox"/> Village <input checked="" type="checkbox"/> City Greenfield	
PS&E Date 2/1/2020		Letting Date 5/12/2020		County Milwaukee	
Structure Number B-40-376		Section S30	Town T06N	Range R21E	
Station 23+63.50	Latitude: 42°57'26.39" Longitude: 88°04'08.99"		<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO Structure Located on National Highway System		
For Survey and CADD Files Horizontal Coordinate System: WCCS Milwaukee County Zone, NAD 83 (2011) Vertical Datum: NAVD88 (2012)		Traffic Forecast Data			
		Design Year	Average Daily Traffic (ADT)	Roadway Design Speed	Functional Class
		Feature On 2042	11,100	40 mph	Minor Art-Urban (16)
		Feature Under 2042	55,000	60 mph	Interstate-Urban (11)
Region Contact: Lance Parve (Area Code) Telephone Number(s): (414) 731-5375 Email: lance.parve@dot.wi.gov		Consultant Contact: Mohammed Zagloul, PE, SE (Area Code) Telephone Number(s): (414) 751-7223 Email: mzagloul@kapurinc.com			

Work To Be Performed

Field Information Required Item Number (see Pages 2-4)

- ☐ A. Structural Repair 1-3, 22
☒ B. Overlay 1-3, 10-22, 26-28, 32, 34
 ☐ Concrete Overlay ☐ Asphalt Overlay
 ☐ Polymer Modified Asphalt Overlay ☒ Thin Bonded Polymer Overlay
 ☐ Other: _____
☐ C. New Bearings 3, 8, 9, 22
☐ D. New Railings 15-17, 20-23
☐ E. Curb and Sidewalk Repair 2, 3, 16, 22, 23
☐ F. Abutment Repair 2, 3, 12, 16
☐ G. Pier Repair 2, 3, 12, 16
☐ H. New Deck 1-6, 9, 10, 13-28, 32-34
☐ I. Widening 1-28, 30, 32-35
☐ J. Joint Repair 2, 3, 8, 16, 19, 22
☒ K. Surface Repair 2, 3, 22
☐ L. Raising Bridge 3, 6, 9, 16, 20-24
☐ M. Slope Stabilization 1-3, 30
☐ N. Scour Repair 1, 2 or 3, 16, 19, 21, 27, 29, 31-35
☐ O. Painting 16, 22, 24
☐ P. Other: _____

Field Information Required

If no structure number exists provide the following: Small County Map on which the location of proposed structure is shown in red and any highway relocation in green. In addition, provide Location Map of scale not less than 1" = 2000' showing the structure location and number.

- ☒ 1. Most recent inspection report, brief history of bridge construction date, and description of repairs with dates.
- ☒ 2. Outline deficient areas on existing structure plan or drawing.
- ☒ 3. Photographs of details requiring repairs or modifications, such as: bearings, x-frames, joints, etc. Photograph all deficient areas. Clearly label all photographs.
- ☐ 4. Provide proposed typical section for roadway and structure showing dimensions and cross slopes.
- ☐ 5. Survey beam seat or girder elevations at both sides of bridge at all substructure units.
- ☐ 6. Provide cross-section elevations at 10 foot intervals extending across the structure and a minimum of 100 feet beyond each end. Sections should be normal to centerline and show elevations at centerline roadway and gutter line. Take elevations along joints and at floor drains.
- ☐ 7. Show and identify starting stationing on bridge.
- ☐ 8. Record measurement, temperature of the structure, and date taken for each of the following:
 - (a) Joint opening measured normal to joint at centerline of roadway and both curb lines.
 - (b) Clearance between girder ends at piers.
 - (c) Distance from front face of abutment backwall to closest point of girder end measured parallel to girder.
 - (d) Temperature of structure determined by averaging top and under deck (if accessible) readings.
- ☐ 9. Fixed and expansion bearings - condition and orientation.
- ☒ 10. Number and width of proposed pours including construction staging sequence.
- ☐ 11. Location of existing construction joints in the deck.
- ☒ 12. Estimated Quantities:

Preparation, Decks, Type 1	Sq. Yd. <u>TBD</u>	
Preparation, Decks, Type 2	Sq. Yd. <u>TBD</u>	
Full Depth Deck Repair	Sq. Yd. <u>TBD</u>	Galvanic Anodes? <u>TBD</u>
Concrete Surface Repair Superstructure	Sq. Ft. <u>20</u>	Galvanic Anodes? <u>TBD</u>
Concrete Surface Repair Substructure	Sq. Ft. <u>20</u>	Galvanic Anodes? <u>TBD</u>
Curb Repair	LF. <u>N/A</u>	Galvanic Anodes? <u>N/A</u>

☒ 13. Sufficiency number: 95.9 (obtain from HSI Bridge Inventory System)

☒ 14. Appraisal and Condition Rating

	Deck Condition	Superstructure Condition	Substructure Condition	Load Capacity Appraisal	Structural EVAL Appraisal
Current	6 Satisfactory	6 Satisfactory	7 Good	5-Legal Load Stress Not Exceeded	6-Condition Equal to Min. Criteria

☒ 15. Load Ratings

	Inventory	Operational
Current Calculated Date: 08/21/2013	HS19	HS39
After Completed by Bridge Designer	To Be Completed During Final Design	To Be Completed During Final Design

- ☒ 16. Utilities on/near Structure. (WisDOT policy is to avoid placing utilities on the structure.)

☐ Yes ☒ No

Type	Owner and Contact Information	Size	Opening at Abutment	Weight	Pressure

- ☒ 17. Is existing bridge railing deficient?

☐ Yes ☒ No If Yes – Replacement Rail Type:

- ☐ 18. Drains to be:

☐ Raised ☐ Closed ☐ Downspouted ☐ New

- ☒ 19. Traffic maintained on bridge during work?

☒ Yes ☐ No If Yes – Include sketches

- ☒ 20. Will guard rail be attached?

☐ Yes ☒ No If Yes – Which corners?

- ☒ 21. Will work to be performed eliminate all deficiencies?

☒ Yes ☐ No If No – Explain: See notes in the additional information below

- ☒ 22. Hazardous waste (asbestos) to be removed?

☐ Yes ☒ No If Yes – Explain: See notes in the additional information below

- ☐ 23. Wing location(s) for surface drain anchors:

- ☐ 24. Painting?

☐ Yes ☐ No If Yes – Explain on Page 4
(all, part, railing, color system, containment, bid items)

- ☐ 25. Desired roadway width: (new deck / widening) _____ Ft.

Desired sidewalk clear width: Left: _____ Ft. Right: _____ Ft.

- ☒ 26. Maximum increase in grade line elevation 0.25 In.

- ☐ 27. Benchmark description to be shown

- ☒ 28. Desired final cross slopes on bridge 0.02 Ft./Ft.

- ☐ 29. Underwater Inspection Report including:

- Streambed Cross Section With Pier, Footing and Seal Elevations
- Pier Elevation Drawings
- Pier Layout
- Hydrographic Survey

- ☐ 30. Slope stabilization, provide:

Type: _____ Quantity: _____ CY.

Slope: _____ Ft./Ft. Fill: _____ CY.

- ☐ 31. Preliminary layout of grout bags or proposed scour repair.

C.I.P. Articulated Mats (for Scour) _____ CY.

Grout Bags (for Scour) _____ CY.

Heavy Riprap _____ CY.

Extra Heavy Riprap _____ CY.

- ☒ 32. Report submitted with Preliminary Plan requires **no** CADD file submittal (*See ESubmittal instructions*).
- ☐ 33. Report submitted for development of Preliminary Plan to structure design engineer requires CADD file (if available) submittal and Report submittal to Soils Engineer if project involves foundation modifications.
- ☒ 34. Coordinate with structure design engineer **before** going into the field if existing structure has no available plans, if staged construction is planned, or if there are adjoining/adjacent structures that will remain in place.
- ☐ 35. If project involves substructure widening coordinate with structure and/or hydraulic design engineer to determine if information on the separation and/or stream crossing SSR will be required.

Additional Information

Elaborate on other concerns such as: DNR, Local, Utility Conflicts, Aesthetics, Railing Type and Staged Construction.

Please be as detailed and specific as possible.

WisDOT SE Region advanced Let from 9/2021 to 5/2020 developing the roadway plans.

Item #10: Deck repairs and polymer overlay to be done during short term (e.g. overnight or weekend) lane closures. At the end of each work zone closure, the bridge deck must be suitable for opening to traffic. The contractor should not begin work that cannot be completed within the closure period.

Item #12: Quantities for Deck Preparation Type 1 and Type 2 and Full Depth Deck Repair to be determined in final design. Quantities for superstructure and substructure Concrete Surface Repair will be included in the final plan submittal.

Item #13, 14, 15: These values were taken from the HSI system on 03/06/2019.

Item #15: Existing bridge rating values and reporting date are shown below:

- Inpsection Report Dated May 28, 2014 (Inventory = HS24, Operating = HS48)
- Inspection Report Dated April 29, 2016 (Inventory = HS19, Operating = HS32)
- Inspection Report Dated March 28, 2018 and HSI (Inventory = HS19, Operating = HS39)

Item #16: Utilites on B-40-376. Per the existing plans, no utilities are located on the structure.

Item #18: No drains on the structure.

Item #21: Based upon the most recent inspection report dated March 28, 2018 the following deficiencies are noted:

- Repair shoulder at NW wing tip (not on the bridge, roadway item)
- Place AC curb at SW wing tip (not on the bridge, roadway item)

Item #22: The caulk located in the abutment, parapet and sidewalk joints contains <1% asbestos and is not regulated ACM per the bridge asbestos inspection report. The overlay on the bridge can proceed as planned and the Standard Special Provision (STSP) 107-125 should be included in the specifications.

Other:

Related roadway work at the approaches will be included in roadway plans.

Current repair assumptions based upon most recent inspection report dated March 28, 2018.

Concrete surface repair includes repairs to girders, piers, abutments and wingwalls. Girder surface repairs shall not include spalls to the webs per SE maintenance recommendation. Pier repairs includes both the pier cap and columns. Loose concrete around spalls shall be removed and spalls to be patched.

Cracks in the existing girders are to be filled as necessary with "epoxy". Special provision "epoxy crack injection" for prestressed girders will be developed during final design. The use of epoxy crack injection is requested by the SE maintenance.

The concrete deck should be repaired as necessary per item "deck preparation", with "concrete masonry deck repair".

Per the SE maintenance, the separation between the abutment and slope paving is to be filled with a filler.
See B-40-376_oth file for list of maintenance items.

