

PROJECT ID: 1660-03-67 & 1660-03-68
WITH: 5580-00-82

COUNTY: CRAWFORD

ORDER OF SHEETS

Section No.	1	Title
Section No.	2	Typical Sections and Details
Section No.	3	Estimate of Quantities
Section No.	3	Miscellaneous Quantities
Section No.	4	Right of Way Plat
Section No.	5	Plan and Profile
Section No.	6	Standard Detail Drawings
Section No.	7	Sign Plates
Section No.	8	Structure Plans
Section No.	9	Computer Earthwork Data
Section No.	9	Cross Sections

TOTAL SHEETS =



DESIGN DESIGNATION 1660-03-67 & 1660-03-68

A.A.D.T.	2016	=	6800
A.A.D.T.	2026	=	7660 - 8160
D.H.V.		=	N/A
D.D.		=	N/A
T.		=	15%
DESIGN SPEED		=	55 MPH
ESALS		=	N/A


CONVENTIONAL SYMBOLS

PLAN

CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE

GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	



END PROJECT
1660-03-68
STA 176+25 EB
STA 179+50 WB
BEGIN PROJECT
1660-03-68
STA 141+25 EB
STA 161+00 WB
Y = 119,872.80
X = 313,215.69

END PROJECT
1660-03-37
STA 122+00 EB

BEGIN PROJECT
1660-03-37
STA 94+50 EB
Y = 119,327.19
X = 308,609.05

B-12-27
B-12-28
B-12-30
B-12-29

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


STATE HIGHWAY REHABILITATION-MAINTENANCE PROJECT

USH 18
MARQUETTE - PRAIRE DU CHIEN
B-12-27
CRAWFORD COUNTY

STATE PROJECT NUMBER
1660-03-67

USH 18
MARQUETTE - PRAIRE DU CHIEN
B-12-28, 29, 30
CRAWFORD COUNTY

STATE PROJECT NUMBER
1660-03-68



LAYOUT
SCALE 0 2 MI

TOTAL NET LENGTH OF CENTERLINE = 0.0 MI (1660-03-67)
TOTAL NET LENGTH OF CENTERLINE = 0.0 MI (1660-03-68)

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COUNTY COORDINATES, CRAWFORD COUNTY, NAD83 (YEAR), IN U.S. SURVEY FEET. VALUES ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.

STATE PROJECT

1660-03-67

1660-03-68

FEDERAL PROJECT

PROJECT

CONTRACT

TRANS 220
PROJECT PLAN
FOR
DESIGN OF UTILITY FACILITY
ALTERATIONS OR RELOCATIONS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY	
Surveyor	WISDOT - SW REGION
Designer	SHANE PETERSON
Project Manager	TIMOTHY MAEDKE
Regional Examiner	REGIONAL EXAMINER
Regional Supervisor	REINY YAHNKE

APPROVED FOR THE DEPARTMENT
DATE: _____ (Signature)

E



UTILITY CONTACTS

Michael Brolin
Alliant Energy – Electricity
4902 North Biltmore Ln.
Madison, WI 53713
608-458-4871
michaelbrolin@alliantenergy.com

Craig Eggert
Mediacom Wisconsin LLC – Communication Line
207 W Pearle St.
P.O. Box 226
Decorah, IA 52101-0226
563-419-5160
ceggert@mediacomcc.com

Mike Adams
Wisconsin DOT RWIS Program – Communication Tower
Rm 501
P.O. Box 7986
Madison, WI 53707-7986
608-266-5004
Michael.adams@dot.wi.gov

DESIGN CONTACTS

TIMOTHY MAEDKE	SHANE PETERSON
PROJECT MANAGER	PROJECT DESIGNER
PROJECT DEVELOPMENT	PROJECT DEVELOPMENT
WISDOT SW REGION	WISDOT SW REGION
3550 MORMON COULEE ROAD	3550 MORMON COULEE ROAD
LA CROSSE, WI 54601	LA CROSSE, WI 54601
(608) 789-6317	(608) 386-1898

DNR LIAISON

KAREN KALVELAGE
ENVIRONMENTAL ANALYSIS & REVIEW SPECIALIST
WISCONSIN DEPT. OF NATURAL RESOURCES
WEST CENTRAL REGION
3550 MORMON COULEE ROAD
LA CROSSE, WI 54601
608-785-9115

ORDER OF SECTION 2 SHEETS


GENERAL NOTES
PROJECT OVERVIEW
TYPICAL SECTIONS
CONSTRUCTION DETAILS
EROSION CONTROL AND DRAINAGE
PAVEMENT MARKING
TRAFFIC CONTROL AND CONSTRUCTION STAGING

GENERAL NOTES

- THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
- THERE ARE UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN ON THE PLANS. THE CONTRACTOR SHALL COORDINATE HIS CONSTRUCTION ACTIVITIES WITH A CALL TO DIGGERS HOTLINE AND/OR A DIRECT CALL TO THE UTILITIES THAT HAVE FACILITIES IN THE AREA. NOT ALL UTILITIES ARE MEMBERS OF DIGGERS HOTLINE.
- THE ENGINEER SHALL ADJUST THE LOCATIONS OF ITEMS UNDER THIS CONTRACT TO AVOID CONFLICT WITH THE EXISTING UTILITY FACILITIES.
- PRIOR TO THE PLACEMENT OF STEEL PLATE BEAM GUARD OR MGS GUARDRAIL, THE SHOULDERS SHALL BE IN PLACE, SHAPED AND COMPACTED UNLESS SHOWN OTHERWISE.
- THE CONTRACTOR'S PAVING OPERATIONS SHALL BE CONSISTENT WITH THE PLAN TYPICAL SECTIONS AND CONSTRUCTED TO PREVENT HMA LONGITUDINAL JOINTS FROM BEING LOCATED WITHIN A DRIVING, TURNING, BIKE OR PARKING LANE.
- HMA PAVEMENT WEIGHT CALCULATIONS ARE BASED ON 112 LB/SY/IN.
- ASPHALT MATERIAL FOR PLANT MIXES HAS BEEN ESTIMATED AT 5.5% OF THE HMA PAVEMENT.
- "X" INCH HMA PAVEMENT TYPE "XX", SHALL BE CONSTRUCTED WITH "X" INCH UPPER LAYER AND "X" INCH LOWER LAYER.
- CONTRACTOR WILL BE RESPONSIBLE FOR RESHAPING AND SEEDING ANY PREVIOUSLY GRASSED AREAS WHICH ARE DISTURBED BY HIS OPERATION OUTSIDE OF THE NORMAL CONSTRUCTION LIMITS.
- TOPSOIL SHALL BE PLACED 1 INCH BELOW THE TOP OF ADJACENT CONCRETE CURBS OR SIDEWALKS.
- THE QUANTITY OF THE ITEMS FOR EROSION PROTECTION INCLUDES AN UNDISTRIBUTED AMOUNT FOR PROTECTION, CONTROL AND ABATEMENT OF WATER POLLUTION RESULTING FROM SOIL EROSION. THE DISTRIBUTION AND LOCATION OF THESE MATERIALS ARE TO BE DETERMINED BY THE ENGINEER.
- DISTURBED AREAS WITHIN THE RIGHT OF WAY ARE TO BE TOPSOILED (SALVAGED), FERTILIZED, SEEDED, AND MULCHED OR SODDED AS DIRECTED BY THE ENGINEER.
- (SALVAGED) TOPSOIL AND MULCH HAS BEEN COMPUTED BY DIRECT MEASUREMENTS ON THE CROSS SECTIONS PLUS 5 FT BEYOND THE TOE OF SLOPE. SEEDING AND FERTILIZER HAS BEEN COMPUTED BY DIRECT MEASUREMENTS ON THE CROSS SECTIONS PLUS 10 FT.


STANDARD ABBREVIATIONS

AC	ACRE	LC.	LONG CHORD
AGG	AGGREGATE	LS	LUMP SUM
<	ANGLE	M.P.	MARKER POST
AE, AEW	APRON ENDWALL	MGAL	1000 GALLONS
ASPH.	ASPHALTIC	N.C.	NORMAL CROWN
A.D.T.	AVERAGE DAILY TRAFFIC	N	NORTH
A.A.D.T.	ANNUAL AVERAGE DAILY TRAFFIC	NB	NORTHBOUND
B.F.	BACK FACE	NOR	NORMAL
BM	BENCHMARK	NO.	NUMBER
BTWN	BETWEEN	PAV'T	PAVEMENT
CTR.	CENTER	P.L.E.	PERMANENT LIMITED EASEMENT
C/L	CENTER LINE	P.C.	POINT OF CURVATURE
Δ	CENTRAL ANGLE OR DELTA	P.I.	POINT OF INTERSECTION
C.E.	COMMERCIAL ENTRANCE	P.T.	POINT OF TANGENCY
CONST.	CONSTRUCTION	PCC	PORTLAND CEMENT CONCRETE
CMCP	CORRUGATED METAL CULVERT PIPE	P.E.	PRIVATE ENTRANCE
CMP	CORRUGATED METAL PIPE	PGL	PROFILE GRADE LINE
CO.	COUNTY	P.L.	PROPERTY LINE
CTH	COUNTY TRUNK HIGHWAY	R	RADIUS OR RANGE
CR.	CREEK	R/L	REFERENCE LINE
CABC	CRUSHED AGGREGATE BASE COURSE	R.C.C.P.	REINFORCED CONCRETE CULVERT PIPE
CY	CUBIC YARD	REQ'D	REQUIRED
CP	CONTROL POINT OR CULVERT PIPE	RT	RIGHT
C&G	CURB AND GUTTER	R.H.F.	RIGHT HAND FORWARD
D	DEGREE OF CURVE	R/W	RIGHT OF WAY
D.H.V.	DESIGN HOURLY VOLUME	RD.	ROAD
DIA.	DIAMETER	SHLD.	SHOULDER(S)
D.D.	DIRECTIONAL DISTRIBUTION	SHR.	SHRINKAGE
DISCH.	DISCHARGE	S	SOUTH
DMS	DYNAMIC MESSAGE SIGN	SB	SOUTHBOUND
EA	EACH	S.F.	SQUARE FOOT (FEET)
E	EAST	SDD	STANDARD DETAIL DRAWING(S)
EB	EASTBOUND	STH	STATE TRUNK HIGHWAY
ELEC.	ELECTRIC(AL), ELEC. CABLE	STA.	STATION
EL., ELEV.	ELEVATION	S.E.	SUPERELEVATION
ESALS	EQUIVALENT SINGLE AXLE LOADS	S/L	SURVEY LINE
EXC.	EXCAVATION	SYM	SYMMETRICAL
EXIST	EXISTING	T.	PERCENT TRUCKS
F.F.	FACE TO FACE	TEL.	TELEPHONE
FERT.	FERTILIZER	TEMP.	TEMPORARY
F.E.	FIELD ENTRANCE	T.L.E.	TEMPORARY LIMITED EASEMENT
F/L, F.L.	FLOW LINE	T.O.C.	TOP OF CURB
GALV.	GALVANIZE	TYP	TYPICAL
H.S.	HIGH STRENGTH	UNCL.	UNCLASSIFIED
CWT	HUNDRED WEIGHT	U.G.	UNDERGROUND (CABLE)
INL	INLET	VAR	VARIABLE
INTER.	INTERSECTION	V.C.	VERTICAL CURVE
IH	INTERSTATE HIGHWAY	V.P.C.	VERTICAL POINT OF CURVATURE
JT.	JOINT	V.P.I.	VERTICAL POINT OF INTERSECTION
LT	LEFT	V.P.T.	VERTICAL POINT OF TANGENCY
L.H.F.	LEFT HAND FORWARD	Wt.	WEIGHT
L.	LENGTH OF CURVE	W	WEST
L.F.	LINEAR FOOT(FEET)	WB	WESTBOUND



PROJECT NO: 1660-03-67/68	HWY: USH 18	COUNTY: CRAWFORD	PROJECT OVERVIEW	SHEET	E
---------------------------	-------------	------------------	------------------	-------	---


2



EXISTING TYPICAL SECTION - USH 18


STA 121+46 TO STA 122+00
STA 141+25 TO STA 141+80
STA 160+97 TO STA 161+25

2




EXISTING TYPICAL SECTION - USH 18

WEST OF B-12-30
(LOOKING EAST)



PROPOSED TYPICAL SECTION - USH 18

SHOULDER WIDENING WEST OF B-12-30
CONSTRUCTED DURING STAGE A
REQUIRED DURING STAGE B
(LOOKING EAST)




TYPICAL WORK AREA SECTION - STAGE 1

LOOKING EAST, STRUCTURE B-12-27 & B-12-28


CONSTRUCTION STAGING DESCRIPTIONS

STAGE 1 = DECK PREP, DECK REPAIR & PARAPET REPAIR ON NORTHERN PORTION
 STAGE 2 = DECK PREP, DECK REPAIR ON MIDDLE PORTION
 STAGE 3 = DECK PREP, DECK REPAIR & PARAPET REPAIR ON SOUTHERN PORTION
 STAGE 4 = POLYMER MODIFIED ASPHALT OVERLAY ON NORTHERN HALF
 STAGE 5 = POLYMER MODIFIED ASPHALT OVERLAY ON SOUTHERN HALF




TYPICAL WORK AREA SECTION - STAGE 2

LOOKING EAST, STRUCTURE B-12-27 & B-12-28



TYPICAL WORK AREA SECTION - STAGE 3

LOOKING EAST, STRUCTURE B-12-27 & B-12-28



TYPICAL WORK AREA SECTION - STAGE 4/5

LOOKING EAST, STRUCTURE B-12-27 & B-12-28
 STAGE 5 IS REVERSE OF STAGE 4

PROJECT NO: 1660-03-67/68


HWY: USH 18

COUNTY: CRAWFORD

TYPICAL SECTIONS: TRAFFIC CONTROL & STAGING B-12-27 & 28


SHEET

E




TYPICAL TRAFFIC CONTROL - STAGE A: B-12-30 CONCRETE OVERLAY


SPANS 2, 3, 4, & 5 LOOKING EAST, STRUCTURE B-12-29






TYPICAL TRAFFIC CONTROL - STAGE B: B-12-29 CONCRETE OVERLAY

LOOKING EAST, STRUCTURE B-12-30









NOTES:

- PORTABLE CHANGEABLE MESSAGE SIGNS (PCMS) SHALL BE OPERATIONAL FOR A MINIMUM OF ONE WEEK PRIOR TO THE START OF CONSTRUCTION.
- PCMS MESSAGE SCHEDULE MAY REQUIRE ADJUSTMENT TO ACCOMMODATE CONSTRUCTION SCHEDULE. MESSAGES MUST BE APPROVED BY THE ENGINEER.
- ALL PCMS BOARDS SHALL REMAIN OPERATIONAL UNTIL PROJECT BEGINS, AS APPROVED BY THE ENGINEER.

LEGEND:

- **MB** PORTABLE CHANGEABLE MESSAGE SIGN


PCMS MESSAGE SCHEDULE


PRECONSTRUCTION



PANEL 1	PANEL 2
ROADWORK	EXPECT
STARTING	DELAYS
X/XX/XX	

STAGE A: B-12-30 OVERLAY	
PANEL 1	PANEL 2
BRIDGE CLOSED	FOLLOW
STARTING	DETOUR
X/XX/XX	

STAGE B: B-12-29 OVERLAY	
PANEL 1	PANEL 2
BRIDGE CLOSED	FOLLOW
STARTING	DETOUR
X/XX/XX	










PROJECT NO: 1660-03-67/68	HWY: USH 18	COUNTY: CRAWFORD	PLAN: STRUCTURE B-12-27	SHEET	E
---------------------------	-------------	------------------	-------------------------	-------	---

5




PROJECT NO: 1660-03-67/68	HWY: USH 18	COUNTY: CRAWFORD	PLAN: STRUCTURE B-12-28	SHEET	E
---------------------------	-------------	------------------	-------------------------	-------	---

5



5

PROJECT NO: 1660-03-67/68	HWY: USH 18	COUNTY: CRAWFORD	PLAN: STAGE A - SHOULDER WIDENING FOR STAGE B	SHEET	E
---------------------------	-------------	------------------	---	-------	---



PROJECT NO: 1660-03-67/68


HWY: USH 18

COUNTY: CRAWFORD


PLAN: STRUCTURES B-12-29 & 30

SHEET


E



PLAN



ELEVATION



CROSS SECTION THRU RDWY. LOOKING EAST

REHABILITATION LEGEND

- P1 SPOT CLEAN AND PAINT STEEL SUPERSTRUCTURE, EXTERIOR
- P2 SPOT CLEAN AND PAINT STEEL SUPERSTRUCTURE, INTERIOR (INSIDE ARCH TIE-GIRDER & ARCH RIB)
- CR CONCRETE SURFACE REPAIRS
- PR PARAPET RESURFACING
- EP EPOXY CRACK INJECTION AT PIER WALLS
- CP REPLACE PARAPET COVER PLATES
- PR PIER CAP CLEANING, REPAIR GROUTING, & SEALING
- LC REMOVE LOOSE CONCRETE AT UNDERSIDE OF DECK
- FB CLEAN & CAULK TOP OF EXPOSED FLOOR BEAMS
- BR BEARING REPAIRS
- TB TEMPORARY BRACING OF GIRDER TOP FLANGE
- SS REMOVE AND REPLACE TORN STRIP SEAL GLAND BTWN. PARAPETS (EXISTING SEAL IS D.S. BROWN- A2R-400, 41'-0"± LENGTH @ E. ABUT.) (EXISTING SEAL IS WATSON-BOWMAN-ACME SE-300, 41'-0"± LENGTH @ MODULAR JOINT IN SPAN 7)

LIST OF DRAWINGS

1. PMA OVERLAY
2. REMOVAL AND STAGING DETAILS 1
3. REMOVAL AND STAGING DETAILS 2
4. QUANTITIES AND NOTES
5. SURFACE REPAIR DETAILS
6. PARAPET RESURFACING 1
7. PARAPET RESURFACING 2
8. PARAPET COVER PLATES
9. FULL DEPTH DECK REPAIR DETAILS
10. BEARING REPAIR DETAILS
11. PIER CAP REPAIRS
12. CLEANING AND CAULKING FLOOR BEAMS
13. DECK CONDITION SURVEY - SPANS 1 TO 5
14. DECK CONDITION SURVEY - SPANS 6 TO 13

DESIGN DATA

LIVE LOAD:
DESIGN RATING: HS-20
INVENTORY RATING: HS-17
OPERATIONAL RATING: HS- 28
MAXIMUM STANDARD PERMIT VEHICLE LOAD: 230 (KIPS)


MATERIAL PROPERTIES:
CONCRETE MASONRY $f'_c = 4,000$ P.S.I.
BAR STEEL REINFORCEMENT: GRADE 60 $f_y = 60,000$ P.S.I.
STRUCTURAL CARBON STEEL: ASTM A709, GRADE 36 $F_y = 36,000$ P.S.I.
HIGH STRENGTH STRUCTURAL STEEL: ASTM A709, GRADE 50 $F_y = 50,000$ P.S.I.

TRAFFIC VOLUME


USH 18
ADT = 6,800 (2016)
R.D.S. = 50 M.P.H.

STRUCTURE DESIGN CONTACTS:


CHRISTOPHER DOLL (608) 266-3229
LAURA SHADEWALD (608) 267-9592

NO.	DATE	REVISION	BY
 BUREAU OF STRUCTURES			
ACCEPTED CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
STRUCTURE B-12-27			
USH 18-STH 60 OVER IA-76/CP RR/MISSISSIPPI RIVER			
COUNTY	CRAWFORD	TOWN	BRIDGEPORT
DESIGN SPEC. REHABILITATION - N/A			
DESIGNED BY	DESIGNED CK'D.	DRAWN BY	PLANS CK'D.
CAD		CAD	
PMA OVERLAY			SHEET 1 OF 14


** MIN./VARIES IN SPANS 1 & 2



STAGE 1 - REMOVAL SECTION




PARAPET PARTIAL REMOVAL DETAIL




DELAMINATED HAUNCH REMOVAL


NOTE:
HAUNCH REMOVAL MAY OCCUR IN ANY STAGE,
PROVIDED REMOVAL OPERATIONS DO NOT
INTERFERE WITH THE MAINTENANCE OF TRAFFIC.




DETAIL A



DETAIL B




STAGE 1 - OVERLAY/CONSTRUCTION



PART FRAMING PLAN SHOWING LOCATION
OF TEMPORARY BRACING IN SPAN 3


REVISION			
NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-27			
DRAWN BY		CAD	PLANS CK'D.
REMOVAL AND STAGING DETAILS			SHEET 2
1			

** MIN./VARIES IN SPANS 1 & 2



STAGE 2 - REMOVAL SECTION


★ LONGITUDINAL CONSTRUCTION JOINT AND JOINTS BETWEEN APPROACH AND BRIDGE P.M.A. OVERLAY SHALL BE SEALED WITH AN APPROVED ASPHALTIC SEALER. JOINT SEALING SHALL BE CONSIDERED INCIDENTAL TO BID ITEM "HMA OVERLAY POLYMER-MODIFIED".




STAGE 2 - OVERLAY/CONSTRUCTION

STATE PROJECT NUMBER

1660-03-67



STAGE 3 - REMOVAL SECTION



STAGE 3 - OVERLAY/CONSTRUCTION

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-27			
DRAWN BY		CAD	PLANS CK'D.
REMOVAL AND STAGING DETAILS		SHEET 3	
2			

SCALE = 3:50

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER.	WEST ABUT.	PIER 4	PIER 5	EAST ABUT.	TOTALS
203.0600.S	REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS STA. 95+85	LS	—	—	—	—	—	1
502.0100	CONCRETE MASONRY BRIDGES	CY	—	—	—	—	—	
502.3210	PIGMENTED SURFACE SEALER	SY						
502.4205	ADHESIVE ANCHORS NO. 5 BAR	EACH						
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB						
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB						
506.0105	STRUCTURAL STEEL CARBON	LB						
★ 509.0301	PREPARATION DECKS TYPE 1	SY						
★ 509.0302	PREPARATION DECKS TYPE 2	SY						
★ 509.1500	CONCRETE SURFACE REPAIR	SF						
★ 509.2000	FULL-DEPTH DECK REPAIR	SY						
509.2100.S	CONCRETE MASONRY DECK REPAIR	CY						
509.3500.S	HMA OVERLAY POLYMER-MODIFIED	TON						
★ 509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY B-12-27	SY						
509.9025.S	EPOXY INJECTION CRACK REPAIR AND CORED HOLES	LF						
★ 509.9050.S	CLEANING PARAPETS	LF						
SPV.0060	BEARINGS REPAIRS B-12-27	EACH						
SPV.0060	PARAPET COVER PLATES	EACH						
SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF						
SPV.0105	STRUCTURE SPOT CLEANING AND PAINTING B-12-27	LS						
SPV.0105	STRIP SEAL GLAND REPLACEMENT B-12-27	LS						
★ SPV.0105	PIER CAP REPAIRS B-12-27	LS						
★ SPV.0105	CLEANING AND CAULKING FLOOR BEAMS B-12-27	LS						
	NON-BID ITEMS							
	FILLER	SIZE						

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE ¾"UNLESS OTHERWISE NOTED.

PIGMENTED SURFACE SEALER TO BE APPLIED TO THE FRONT FACE AND THE TOP OF THE PARAPETS.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.

THE COLOR OF THE FINISH EPOXY TOP COAT SHALL BE BLUE, (FEDERAL STANDARD COLOR NO. 25240) OR SIMILAR COLOR APPROVED BY THE ENGINEER.

ALL FIELD CONNECTIONS SHALL BE MADE WITH ¾" DIAMETER A325 HIGH-TENSILE STRENGTH BOLTS UNLESS OTHERWISE SHOWN OR NOTED.

AREAS OF "PREPARATION DECKS TYPE 1" SHALL BE DEFINED BY A SAW CUT.

PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2, AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION AND FULL-DEPTH DECK REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY DECK REPAIR".

ANY EXCAVATION REQUIRED TO COMPLETE THE OVERLAY AT THE ABUTMENTS IS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "HMA OVERLAY POLYMER-MODIFIED".

THE PLAN QUANTITY FOR THE BID ITEM "HMA OVERLAY POLYMER-MODIFIED" IS BASED ON THE AVERAGE OVERLAY THICKNESS.

CONTACT THE BUREAU OF STRUCTURES BEFORE PLACEMENT OF OVERLAY IF THE AVERAGE THICKNESS OF THE NEW OVERLAY WILL EXCEED THE AVERAGE OVERLAY SHOWN ON THE PLANS BY MORE THAN 1/2".

THE EXISTING OVERLAY SHALL BE REMOVED FROM THE BRIDGE DECK UNDER BID ITEM "REMOVING CONCRETE MASONRY DECK OVERLAY".

★ REMOVAL, DEBRIS CONTAINMENT, AND DISPOSAL OF EXISTING STRUCTURE INCLUDED WITHIN THESE ITEMS SHALL CONFORM TO THE REQUIREMENTS SET FORTH IN SPECIAL PROVISION "REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS STA. 95+85".


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-27			
		DRAWN BY	PLANS CK'D.
QUANTITES AND NOTES		SHEET 4	



PIER 5

PARAPETS ABOVE TO BE REMOVED FOR COVERPLATE INSTALLATION, SEE 'PARAPET COVER PLATES' SHT. FOR DETAILS.

"CONCRETE SURFACE REPAIR" AT ABUTMENT BACKWALL



SOUTH CORNER OF WEST ABUTMENT BACKWALL

EXISTING STEEL TROUGH/GUTTER TO REMAIN. TAKE CARE PREVENT DAMAGE TO DRAIN SYSTEM DURING REMOVAL OPERATIONS

PARAPETS ABOVE TO BE REMOVED FOR COVERPLATE INSTALLATION, SEE 'PARAPET COVER PLATES' SHT. FOR DETAILS.

"CONCRETE SURFACE REPAIR" AT ABUTMENT BACKWALL




NORTH CORNER OF WEST ABUTMENT BACKWALL

REMOVE AND REPLACE EXISTING DOWNSPOUT AS REQ'D TO PERFORM SURFACE REPAIRS. INCIDENTAL TO "CONCRETE SURFACE REPAIR" ITEM.




PIER 4

"CONCRETE SURFACE REPAIR" AT ABUTMENT BACKWALL



NORTH CORNER OF EAST ABUTMENT BACKWALL

"CONCRETE SURFACE REPAIR" AT ABUTMENT BACKWALL



SOUTH CORNER OF EAST ABUTMENT BACKWALL

NOTES

THIS SHEET DEPICTS THE GENERAL TYPES AND LOCATIONS OF REPAIRS, AND MAY NOT BE ALL INCLUSIVE. QUANTITIES SHOWN ON SHT. 4 ARE APPROXIMATE. ADDITIONAL REPAIRS MAY BE REQUIRED DURING CONSTRUCTION AND SHOULD BE PERFORMED AS DIRECTED BY THE FIELD ENGINEER.


ALL SURFACE REPAIR AREAS SHALL BE DEFINED BY 1/2" MIN. SAWCUT.

CONTRACTOR SHALL EMPLOY METHODS TO PREVENT REMOVED CONCRETE MATERIAL FROM ENTERING THE WATERWAY.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-27			
DRAWN BY		CAD	PLANS CK'D.
SURFACE REPAIR DETAILS			SHEET 5

EPOXY CRACK SEALING AT PIERS 4 & 5

SURFACE REPAIRS AT ABUTMENTS




ELEVATION AT WINGS- WEST ABUTMENT




RESURFACING DETAIL SECTION

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-27			
		DRAWN BY	PLANS CK'D.
PARAPET RESURFACING 1		SHEET 6	

SCALE = 1:100



PLAN



ELEVATION

DESIGN DATA

LIVE LOAD:
INVENTORY RATING; HS-17
OPERATIONAL RATING; HS-28
MAXIMUM STANDARD PERMIT VEHICLE LOAD = 230 KIPS.


ULTIMATE DESIGN STRESSES:
CONCRETE MASONRY SLAB — $f'_c = 4,000$ P.S.I.
ALL OTHER — $f'_c = 3,500$ P.S.I.
BAR STEEL REINFORCEMENT, GRADE 60 — $f_y = 60,000$ P.S.I.

REHABILITATION LEGEND


- P1 SPOT CLEAN AND PAINT STEEL SUPERSTRUCTURE
- CR CONCRETE SURFACE REPAIRS
- EP EPOXY CRACK INJECTION AT PIER WALLS
- CP REPLACE/TIGHTEN PARAPET COVER PLATE BOLTS
- PR PIER CAP CLEANING, REPAIR GROUTING, & SEALING
- LC REMOVE LOOSE CONCRETE AT UNDERSIDE OF DECK
- HG REPLACE ACCESS HATCH GASKETS NEAR PIERS 6 & 7
-EXISTING ACCESS HATCHES/MANHOLES ARE CATALOG NO. R-6665-3CH BY NEENAH FOUNDRY COMPANY


LIST OF DRAWINGS

- PMA OVERLAY
- REMOVAL AND STAGING DETAILS 1
- REMOVAL AND STAGING DETAILS 2
- QUANTITIES AND NOTES
- SURFACE REPAIR DETAILS
- PIER CAP REPAIRS
- DECK CONDITION SURVEY - SPANS 1 TO 5
- DECK CONDITION SURVEY - SPANS 6 TO 13




CROSS SECTION THRU RDWY. LOOKING EAST

NO.	DATE	REVISION	BY
 BUREAU OF STRUCTURES			
ACCEPTED CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
STRUCTURE B-12-28			
USH 18 - STH 60 OVER CP RR & MISSISSIPPI RIVER			
COUNTY	CRAWFORD	CITY	PRAIRIE DU CHIEN
DESIGN SPEC. REHABILITATION - N/A			
DESIGNED BY	CAD	DESIGNED CK'D.	DRAWN BY
PMA OVERLAY		SHEET 1 OF XX	



STAGE 1 - REMOVAL SECTION



STAGE 1 - OVERLAY/CONSTRUCTION


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-28			
		DRAWN BY	PLANS CK'D.
		CAD	
REMOVAL AND STAGING DETAILS 1		SHEET 2	

SCALE = 3/50


☆ LONGITUDINAL CONSTRUCTION JOINT AND JOINTS BETWEEN APPROACH AND BRIDGE P.M.A. OVERLAY SHALL BE SEALED WITH AN APPROVED ASPHALTIC SEALER. JOINT SEALING SHALL BE CONSIDERED INCIDENTAL TO BID ITEM "HMA OVERLAY POLYMER-MODIFIED".

STATE PROJECT NUMBER


1660-03-68




STAGE 2 - REMOVAL SECTION



STAGE 2 - OVERLAY/CONSTRUCTION



STAGE 3 - REMOVAL SECTION



STAGE 3 - OVERLAY/CONSTRUCTION

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-28			
		DRAWN BY	CAD PLANS CK'D.
REMOVAL AND STAGING DETAILS 2		SHEET 3	


GENERAL NOTES

*ESTIMATED SQUARE FOOT QUANTITIES SHOWN FOR INFORMATION ONLY. ITEM TO BE BID AS A SINGLE LUMP SUM AMOUNT FOR ALL PAINTING ON THE STRUCTURE. QUANTITIES SHOWN ARE APPROXIMATE AND ADDITIONAL CLEANING/PAINTING MAY BE REQUIRED DURING CONSTRUCTION AND SHOULD BE PERFORMED AS DIRECTED BY THE FIELD ENGINEER.


★ REMOVAL, DEBRIS CONTAINMENT, AND DISPOSAL OF EXISTING STRUCTURE INCLUDED WITHIN THESE ITEMS SHALL CONFORM TO THE REQUIREMENTS SET FORTH IN SPECIAL PROVISION "REMOVING OLD STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS STA. 141+80".




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-28			
		DRAWN BY	PLANS C'K'D.
QUANTITIES AND NOTES		SHEET 4	



PIER 6



TYPICAL AT ALL ABUTMENT BACKWALL CORNERS
(4 CORNERS TOTAL)




EAST ABUTMENT BODY

SURFACE REPAIRS AT ABUTMENTS



PIER 7



PARAPET SURFACE REPAIR

NOTES


THIS SHEET DEPICTS THE GENERAL TYPES AND LOCATIONS OF REPAIRS, AND MAY NOT BE ALL INCLUSIVE. QUANTITIES SHOWN ON SHT. 4 ARE APPROXIMATE. ADDITIONAL REPAIRS MAY BE REQUIRED DURING CONSTRUCTION AND SHOULD BE PERFORMED AS DIRECTED BY THE FIELD ENGINEER.

ALL SURFACE REPAIR AREAS SHALL BE DEFINED BY 1/2" MIN. SAWCUT.

CONTRACTOR SHALL EMPLOY METHODS TO PREVENT REMOVED CONCRETE MATERIAL FROM ENTERING THE WATERWAY.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-28			
DRAWN BY		CAD	PLANS CK'D.
SURFACE REPAIR DETAILS			SHEET 5

SURFACE REPIARS & EPOXY CRACK SEALING AT PIERS 6 & 7



CURVE DATA

USH 18 EB
P.I. = 167+92.32
Δ = 27° 42' 52"
D = 3° 0' 0"
T = 471.16
L = 923.87'
R = 1909.86'
S.E. = 4.5 %

CONCRETE OVERLAY PLAN

(5 SPAN - 45" PRESTRESSED CONCRETE GIRDER BRIDGE)

DESIGN DATA

LIVE LOAD:
DESIGN RATING: HS-20
INVENTORY RATING: HS-22
OPERATIONAL RATING: HS- 37
MAXIMUM STANDARD PERMIT VEHICLE LOAD: 250 (KIPS)

MATERIAL PROPERTIES:


CONCRETE MASONRY f'c = 4,000 P.S.I.
BAR STEEL REINFORCEMENT:
GRADE 60 fy = 60,000 P.S.I.
STRUCTURAL CARBON STEEL:
ASTM A709, GRADE 36 Fy = 36,000 P.S.I.
HIGH STRENGTH STRUCTURAL STEEL:
ASTM A709, GRADE 50 Fy = 50,000 P.S.I.

TRAFFIC VOLUME

USH 18 EB
ADT = 5,500 (2010)
R.D.S. = 50 M.P.H.

STRUCTURE DESIGN CONTACTS:

CHRISTOPHER DOLL (608) 266-3229
LAURA SHADEWALD (608) 267-9592




TYPICAL CROSS SECTION THRU BRIDGE

(LOOKING EAST)

LIST OF DRAWINGS

1. GENERAL PLAN
2. QUANTITIES & NOTES
3. REPLACEMENT BEARINGS
4. JOINT REPAIR DETAILS - W. ABUT.
5. JOINT REPAIR DETAILS - E. ABUT.
6. EXPANSION DEVICE
7. COVER PLATE DETAILS
8. DOWNSPOUT DETAILS
9. DECK CONDITION SURVEY

NO.	DATE	REVISION	BY
 BUREAU OF STRUCTURES			
ACCEPTED CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
STRUCTURE B-12-29			
USH 18/STH 60 EB OVER MARAIS DE SAINT FERIOLE			
COUNTY	CRAWFORD	CITY	PRAIRIE DU CHIEN
DESIGN SPEC. N/A REHABILITATION			
DESIGNED BY	DESIGNED CK'D.	DRAWN BY	PLANS CK'D.
CAD	CK'D.	CAD	CK'D.
GENERAL PLAN			SHEET 1 OF 9

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER.	EAST ABUT.	WEST ABUT.	TOTALS
502.3100	EXPANSION DEVICE B-12-29	LS	—	—	1	1
502.3200	PROTECTIVE SURFACE TREATMENT	SY	1774	—	—	1774
502.4110	ADHESIVE ANCHORS 1 1/4-INCH	EACH	—	—	12	12
502.4205	ADHESIVE ANCHORS NO. 5 BAR	EACH	—	—	38	38
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	—	725	1,235	1,960
506.6000	BEARING ASSEMBLIES EXPANSION B-12-29	EACH	—	—	6	6
506.7050.S	REMOVING BEARINGS B-12-29	EACH	—	—	6	6
509.0301	PREPARATION DECKS TYPE 1	SY	107	—	—	107
509.0302	PREPARATION DECKS TYPE 2	SY	191	—	—	191
509.1000	JOINT REPAIR	SY	—	209	169	378
509.1500	CONCRETE SURFACE REPAIR	SF	19	—	40	59
509.2000	FULL-DEPTH DECK REPAIR	SY	2	—	—	2
509.2500	CONCRETE MASONRY OVERLAY DECKS	CY	110	—	—	110
509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY B-12-29	SY	1774	—	—	1774
SPV.0060	DOWNSPOUT REPAIR	EACH	3	—	—	3
	NON-BID ITEMS					
	BRIDGE SEAT PROTECTION	L.S.	—	—	—	1
	FILLER	SIZE	—	—	—	1/2", 3/4", 1 1/2"

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE 3/4" UNLESS OTHERWISE NOTED.


PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE ENTIRE EXPOSED TOP OF DECK/OVERLAY.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.


ANY EXCAVATION NECESSARY TO COMPLETE THE OVERLAY OR JOINT REPAIR AT THE ABUTMENTS IS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "CONCRETE MASONRY OVERLAY DECKS".

CONTACT THE BUREAU OF STRUCTURES BEFORE PLACEMENT OF OVERLAY IF THE AVERAGE THICKNESS OF THE NEW OVERLAY WILL EXCEED THE AVERAGE OVERLAY SHOWN ON THE PLANS BY MORE THAN 1/2".

THE EXISTING OVERLAY SHALL BE REMOVED FROM THE BRIDGE DECK UNDER BID ITEM "REMOVING CONCRETE MASONRY DECK OVERLAY B-12-29".



WEST ABUTMENT SURFACE REPAIRS



BEARING REMOVAL DETAIL AT WEST ABUTMENT


NOTE:
REMOVAL AND DISPOSAL OF EXISTING BEARINGS AND SHIMS AS SHOWN, INCLUDING JACKING OF THE BRIDGE AS REQUIRED TO REMOVE AND REPLACE THE BEARINGS, SHALL BE INCLUDED IN BID ITEM "REMOVING BEARINGS B-12-29".

SURFACE REPAIR NOTES

SURFACE REPAIR DETAILS DEPICT THE GENERAL TYPES AND LOCATIONS OF REPAIRS, AND MAY NOT BE ALL INCLUSIVE. QUANTITIES SHOWN ON ARE APPROXIMATE. ADDITIONAL REPAIRS MAY BE REQUIRED DURING CONSTRUCTION AND SHOULD BE PERFORMED AS DIRECTED BY THE FIELD ENGINEER.

ALL SURFACE REPAIR AREAS SHALL BE DEFINED BY 1/2" MIN. SAWCUT.

CONTRACTOR SHALL EMPLOY METHODS TO PREVENT REMOVED CONCRETE MATERIAL FROM ENTERING THE WATERWAY.




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
		DRAWN BY	PLANS CK'D.
		CAD	
QUANTITIES & NOTES		SHEET 2	


SCALE = 1:00

BEARING NOTES

- ALL BEARINGS ARE SYMMETRICAL ABOUT ϕ OF GIRDER AND ϕ OF BEARING.
- ALL MATERIAL IN BEARINGS, BUT EXCLUDING STAINLESS STEEL SHEET, TEFLON SURFACE, PINTLES, ANCHOR BOLTS, NUTS AND WASHERS, SHALL CONFORM TO ASTM A709 GRADE 50W.
- STAINLESS STEEL SHEET SHALL CONFORM TO ASTM A240, TYPE 304.
- STEEL PINTLES SHALL CONFORM TO ASTM A449 OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 36, OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ALL STRUCTURAL STEEL BEARING PLATES SHALL BE FLAT ROLLED STEEL PLATES WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT, AND VERTICAL.
- ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUTS.
- ALL FINISHED SURFACES SHALL BE MACHINE FINISHED BY AN AUTOMATIC PROCESS.
- ANCHOR BOLTS SHALL BE FULLY THREADED. PROVIDE ONE STANDARD WROUGHT WASHER AND ONE HEX NUT PER BOLT. PROJECT ANCHOR BOLTS, MASONRY PLATE "D" THICKNESS + 2 1/4", ABOVE TOP OF CONCRETE. ANCHOR BOLTS SHALL BE PAID FOR AS "ADHESIVE ANCHORS 1 1/4-INCH" AND BE EPOXY ANCHORED. CHAMFER ANCHOR BOLTS PRIOR TO THREADING.
- MASONRY PLATE "D", ROCKER PLATE "C", ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153, CLASS "C". TOP PLATE "A" AND STEEL PLATE "B" SHALL BE SHOP PAINTED. USE A WELDABLE PRIMER ON TOP PLATE "A". DO NOT PAINT TEFLON OR STAINLESS STEEL SURFACES.
- ALL MATERIAL IN BEARING ASSEMBLIES, INCLUDING BEARING PADS, SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "BEARING ASSEMBLIES EXPANSION B-12-29", EACH.
- DRILLED HOLES FOR ANCHOR BOLTS IN MASONRY PLATE "D" SHALL HAVE A DIAMETER 3/8" LARGER THAN ANCHOR BOLT.
- TEFLON SURFACE, USE UNFILLED WITH MINIMUM 1/16" THICKNESS. PLACE WITH SCRIBE MARKS IN DIRECTION OF MOVEMENT. BOND STEEL PLATE "B" AND TEFLON WITH ADHESIVE MATERIAL MEETING THE REQUIREMENTS FOUND IN THE STANDARD SPECIFICATION.
- PROVIDE A METHOD FOR HANDLING ROCKER PLATE "C" DURING GALVANIZING.
- AT INSTALLATION, ENSURE STAINLESS STEEL SLIDING FACE OF THE UPPER ELEMENT AND THE TFE SLIDING FACE OF THE LOWER ELEMENT HAVE THE SURFACE FINISH SPECIFIED AND ARE CLEAN AND FREE OF ALL DUST, MOISTURE, AND OTHER FOREIGN MATTER.



EXPANSION BEARING ASSEMBLY





TEMPERATURE	W. ABUT. IN.
10°	-1 1/16"
20°	-3/4"
30°	-7/16"
40°	-1/8"
50°	1/8"
60°	7/16"
70°	3/4"
80°	1 1/16"
90°	1 3/8"

TEMPERATURE TABLE

AT THE WEST ABUTMENT, NEGATIVE VALUE INDICATES PINTLES ARE LOCATED WEST OF THE ϕ OF TOP PLATE "A" AND POSITIVE VALUE INDICATES PINTLES ARE LOCATED EAST OF THE ϕ OF TOP PLATE "A".

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
DRAWN BY		CAD	PLANS CK'D.
REPLACEMENT BEARINGS		SHEET 3	




JOINT REPAIR
DETAILS -
W. ABUT.

BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S501	X	23	39'-9"			DECK TRANS. @ JOINT REPAIRS
S402	X	10	5'-9"			DECK TRANS. THRU EXP. DEVICE ANCHORS
S603	X	30	5'-1"			W. ABUT. DIAPH. BTM.
S404	X	35	5'-2"	X		W. ABUT. DIAPH. STIRRUPS
S505	X	30	7'-2"			W. ABUT. PAVING BLOCK
S406	X	38	3'-6"	X		W. ABUT. PAVING BLOCK STIRRUPS
S507	X	38	3'-0"	X		W. ABUT. PAVING BLOCK MASONRY ANCHOR
S508	X	20	5'-0"	X		PARAPET VERT.
S509	X	16	4'-9"	X		DECK TO PARAPET VERT. DOWEL



S406


INCORPORATE EXISTING LONGITUDINAL DECK STEEL



JOINT REPAIR SECTION


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
DRAWN BY		CAD	PLANS CK'D.
JOINT REPAIR DETAILS - E. ABUT.		SHEET 5	

SCALE = 4,00




REMOVAL PLAN

REMOVAL AREAS




JOINT REMOVAL SECTION
NORMAL TO CL SUBSTRUCTURE




JOINT REPAIR PLAN

PRESERVE ALL EXISTING LONGITUDINAL STEEL IN DECK AND PARAPETS, TYP.




PARTIAL TRANS. SECTION AT JOINT REMOVAL




* POUR CONCRETE ABOVE THIS JOINT AFTER SUPERSTRUCTURE IS IN PLACE. STRIKE OFF AND LEAVE ROUGH.

SECTION THRU JOINT AT ABUTMENT
NORMAL TO ϕ SUBSTRUCTURE




SECTION THRU JOINT

EXTERIOR GIRDER TO EDGE OF DECK AND AT PARAPETS, MEDIANS AND SIDEWALKS




ALTERNATE STRIP SEAL ANCHOR



SECTION THRU JOINT

ROADWAY TRAFFIC AREA BETWEEN EXTERIOR GIRDERS.



PART PLAN

LEGEND

- ① NEOPRENE STRIP SEAL (4- INCH) AND STEEL EXTRUSIONS.
- ② STUDS $\frac{5}{8}$ " ϕ X $6\frac{3}{8}$ " LONG AT 6" ALTERNATE CENTERS. WELD TO EXTRUSIONS AND BEND AS SHOWN AFTER WELDING.
- ②A $\frac{1}{2}$ " THICK ANCHOR PLATE WITH $\frac{5}{8}$ " ϕ ROD (OR ALTERNATE STRIP SEAL ANCHOR). WELD ROD TO ANCHOR PLATE, WELD ANCHOR PLATE TO NO. 1 AT 1'-6" CENTERS BETWEEN GIRDERS.
- ③ $\frac{3}{4}$ " ϕ THREADED ROD WITH 2 NUTS AND PLATE WASHERS. GROUT THREADED ROD INTO FIELD DRILLED HOLES ON ϕ OF GIRDER. ON ABUTMENT SIDE GROUT THREADED ROD INTO FIELD DRILLED HOLES IN ABUTMENT BACKWALL AS SHOWN.
- ④ $\frac{3}{4}$ " ϕ THREADED ROD WITH NUT. TACK WELD NUT TO NO. 5.
- ⑤ FABRICATE SUPPORT FROM 3" X $\frac{1}{2}$ " BAR AS SHOWN OR EQUIVALENT, ONE PER GIRDER PER SIDE. SHOP OR FIELD WELD TO NO. 1. IF FIELD WELDED, COVER WELDED AREAS WITH EPOXY-COATING MATERIAL. PROVIDE $1\frac{1}{2}$ " ϕ HOLE FOR NO. 3 AND 1" ϕ HOLE FOR NO. 4.
- ⑥ GALVANIZED PLATE $\frac{3}{8}$ " X 1'-5" X 2'-0" LONG WITH HOLES FOR NO. 7. BEND AS SHOWN.
- ⑦ $\frac{3}{4}$ " ϕ X $1\frac{1}{2}$ " STAINLESS STEEL SOCKET FLAT HEAD SCREWS WITH ANTI-SEIZE LUBRICANT. PLACE IN COUNTERSUNK HOLE. RECESS $\frac{1}{16}$ " BELOW PLATE SURFACE.
- ⑧ $\frac{3}{4}$ " ϕ X 4" GALVANIZED HEX HEAD BOLT. BEND 45°.
- ⑨ $\frac{3}{4}$ " ϕ X $2\frac{1}{4}$ " GALVANIZED THREADED COUPLING.
- ⑩ 1" X 5" SLOTTED COUNTERSUNK HOLE FOR NO. 7. PLACE SLOT PARALLEL TO DIRECTION OF MOVEMENT.

TEMPERATURE TABLE

SHADED UNDERSIDE DECK TEMP. (°F)	JOINT OPENING (NORMAL TO JT.)
85°	$\frac{3}{4}$ "
75°	$\frac{1}{16}$ "
65°	$\frac{13}{8}$ "
55°	$\frac{11}{16}$ "
45°	2"
35°	$2\frac{5}{16}$ "
25°	$2\frac{9}{16}$ "
15°	$2\frac{15}{16}$ "
5°	$3\frac{1}{4}$ "

A SMALL JOINT OPENING DUE TO A HIGH TEMPERATURE AT TIME OF CONSTRUCTION MAY REQUIRE NEOPRENE STRIP SEAL INSTALLATION INTO STEEL EXTRUSIONS PRIOR TO SETTING THE EXPANSION JOINT.

NOTES

ONE FIELD SPlice PERMITTED IN STEEL EXTRUSIONS, UNLESS MORE ARE REQUIRED FOR STAGED CONSTRUCTION, HANDLING OR GALVANIZING REQUIREMENTS. IF USED, DETAILS SHALL BE SUBMITTED FOR APPROVAL. NO SPlicing PERMITTED IN NEOPRENE STRIP SEAL.

AFTER FABRICATION, BUT BEFORE SHIPMENT, STRAIGHTEN STEEL EXTRUSIONS SUCH THAT THEY SHALL BE FREE FROM WARP, TWIST AND SWEEP.


FABRICATOR SHALL PROVIDE MEANS OF KEEPING GALVANIZED EXTRUSIONS CLEAN AND SMOOTH DURING SHIPMENT AND PRIOR TO APPLYING LUBRICANT ADHESIVE FOR NEOPRENE GLAND INSTALLATION.

SANDBLAST PLATES, SUPPORTS AND EXTRUSIONS AFTER FABRICATION IN ACCORDANCE WITH SSPC SP. #6 "COMMERCIAL BLAST CLEANING". AFTER BLAST CLEANING, THE PLATES, SUPPORTS AND EXTRUSIONS SHALL BE HOT DIPPED GALVANIZED.

ANCHOR SYSTEM NO. 8 AND NO. 9 SHALL CONFORM TO ASTM A307 & SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153 CLASS C AND D.


STRIP SEAL EXPANSION JOINT ASSEMBLY, INCLUDING ANCHOR STUDS AND HARDWARE WILL BE PAID FOR AT THE LUMP SUM PRICE BID FOR "EXPANSION DEVICE B-1-1".

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
DRAWN BY		CAD	PLANS CKD.
EXPANSION DEVICE		SHEET 6	



■ JOINT OPENING DIMENSION ALONG SKEW PLUS 1/2".

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
		DRAWN BY	CAD
		PLANS CK'D.	
COVER PLATE DETAILS		SHEET 7	




NOTES

- BID ITEM SHALL BE "DOWNSPOUT REPAIR", WHICH INCLUDES ALL ITEMS SHOWN.
- ROUND HSS TUBE MATERIAL SHALL CONFORM TO ASTM A500-GRADE B.
- NEW STEEL TUBES SHALL BE SHOP PAINTED. BLAST CLEAN TO SSPC SP-6 AND USE A WELDABLE PRIMER. DO NOT APPLY FINISH COATS TO SURFACES TO BE FIELD WELDED.
- THE COLOR OF THE FINISH TOP COAT SHALL BE "GRAY", FEDERAL COLOR NO. 26293
- BOLTS AND NUTS SHALL CONFORM TO ASTM F3125, GRADE A325.

DOWNSPOUT EXTENSION DETAIL
(TYPICAL AT ALL (3) FLOOR DRAIN LOCATIONS)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
		DRAWN BY	PLANS CK'D.
DOWNSPOUT DETAILS		SHEET 8	

SCALE = 0.50




Conditions Legend		Orientation	Quantity Summary			General Information	
Rebar-level deterioration detected by GPR		 	Estimate Deck Prep Items	sq. ft.	%	Bridge ID: B-12-029	
Increasing severity -->			Type 1	878	5.4	USH 18 EB-STH 60 EB over Marais De St	
IE (delam)	Delamination detected by IR		Type 2	1563	9.7	Analyzed by: SB/RG	
IE (no delam)	Patching		Full-Depth	0	0.0	Reviewed by: AC	
	Full Depth					Completed: 09/22/17	
						Sheet 1 of 1	

NOTES

DECK SURVEY IS SHOWN FOR INFORMATION PURPOSES ONLY AND MAY NOT BE ALL INCLUSIVE. ADDITIONAL PATCHING/PREPARATION MAY BE REQUIRED AND SHALL BE PERFORMED AS DIRECTED BY THE ENGINEER.

GPR= GROUND PENETRATING RADAR
IR = INFRARED (THERMOGRAPHY)
IE = IMPACT ECHO

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-29			
DRAWN BY		CAD	PLANS CK'D.
DECK CONDITION SURVEY			SHEET 9



CURVE DATA

US 18 EB
P.I. = 167+92.32
Δ = 27° 42' 52"
D = 3° 0' 0"
T = 471.16
L = 923.87'
R = 1909.86'
S.E. = 4.5 %

CONCRETE OVERLAY PLAN

(5 SPAN - 45" PRESTRESSED CONCRETE GIRDER BRIDGE)

DESIGN DATA


LIVE LOAD:
DESIGN RATING: HS-20
INVENTORY RATING: HS-20
OPERATIONAL RATING: HS- 31
MAXIMUM STANDARD PERMIT VEHICLE LOAD: 250 (KIPS)

MATERIAL PROPERTIES:

CONCRETE MASONRY ————— f'c = 4,000 P.S.I.
BAR STEEL REINFORCEMENT:
GRADE 60 ————— fy = 60,000 P.S.I.
STRUCTURAL CARBON STEEL:
ASTM A709, GRADE 36 ————— Fy = 36,000 P.S.I.
HIGH STRENGTH STRUCTURAL STEEL:
ASTM A709, GRADE 50 ————— Fy = 50,000 P.S.I.

TRAFFIC VOLUME

US 18 WB
ADT = 4,600 (2010)
R.D.S. = 50 M.P.H.




TYPICAL CROSS SECTION THRU BRIDGE

(LOOKING EAST)

SPAN 1	5'-8"
SPAN 2	5'-9"
SPAN 3	5'-10"
SPAN 4	5'-10 3/4"
SPAN 5	5'-11 1/2"


LIST OF DRAWINGS

1. GENERAL PLAN
2. QUANTITIES & NOTES
3. REPLACEMENT BEARINGS
4. JOINT REPAIR DETAILS - W. ABUT.
5. EXPANSION DEVICE
6. COVER PLATE DETAILS
7. DOWNSPOT DETAILS
8. DECK CONDITION SURVEY

NO.	DATE	REVISION	BY
 BUREAU OF STRUCTURES			
ACCEPTED CHIEF STRUCTURES DESIGN ENGINEER _____ DATE _____			
STRUCTURE B-12-30			
USH 18/STH 60 EB OVER MARAIS DE SAINT FERIOLE			
COUNTY	CRAWFORD	CITY	PRAIRIE DU CHIEN
DESIGN SPEC. N/A REHABILITATION			
DESIGNED BY	DESIGNED CK'D.	DRAWN BY	PLANS CK'D.
CAD	CK'D.	CAD	CK'D.
GENERAL PLAN			SHEET 1 OF 8

GENERAL NOTES

THE EXISTING OVERLAY SHALL BE REMOVED FROM THE BRIDGE DECK UNDER BID ITEM "REMOVING CONCRETE MASONRY DECK OVERLAY B-12-30".




NOTE:
REMOVAL AND DISPOSAL OF EXISTING BEARINGS AS SHOWN, INCLUDING JACKING OF THE BRIDGE AS REQUIRED TO REMOVE AND REPLACE THE BEARINGS, SHALL BE INCLUDED IN BID ITEM "REMOVING BEARINGS B-12-30".

PARAPET SURFACE REPAIR WITH FULL DEPTH DECK REPAIR


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-30			
DRAWN BY		CAD	PLANS CK'D.
QUANTITIES & NOTES		SHEET 2	

BEARING NOTES

- ALL BEARINGS ARE SYMMETRICAL ABOUT ϕ OF GIRDER AND ϕ OF BEARING.
- ALL MATERIAL IN BEARINGS, BUT EXCLUDING STAINLESS STEEL SHEET, TEFLON SURFACE, PINTLES, ANCHOR BOLTS, NUTS AND WASHERS, SHALL CONFORM TO ASTM A709 GRADE 50W.
- STAINLESS STEEL SHEET SHALL CONFORM TO ASTM A240, TYPE 304.
- STEEL PINTLES SHALL CONFORM TO ASTM A449 OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 36, OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ALL STRUCTURAL STEEL BEARING PLATES SHALL BE FLAT ROLLED STEEL PLATES WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT, AND VERTICAL.
- ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUTS.
- ALL FINISHED SURFACES SHALL BE MACHINE FINISHED BY AN AUTOMATIC PROCESS.
- ANCHOR BOLTS SHALL BE FULLY THREADED. PROVIDE ONE STANDARD WROUGHT WASHER AND ONE HEX NUT PER BOLT. PROJECT ANCHOR BOLTS, MASONRY PLATE "D" THICKNESS + 2 1/4", ABOVE TOP OF CONCRETE. ANCHOR BOLTS SHALL BE PAID FOR AS "ADHESIVE ANCHORS 1 1/4-INCH" AND BE EPOXY ANCHORED. CHAMFER ANCHOR BOLTS PRIOR TO THREADING.
- MASONRY PLATE "D", ROCKER PLATE "C", ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153, CLASS "C". TOP PLATE "A" AND STEEL PLATE "B" SHALL BE SHOP PAINTED. USE A WELDABLE PRIMER ON TOP PLATE "A". DO NOT PAINT TEFLON OR STAINLESS STEEL SURFACES.
- ALL MATERIAL IN BEARING ASSEMBLIES, INCLUDING BEARING PADS, SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "BEARING ASSEMBLIES EXPANSION B-12-30", EACH.
- DRILLED HOLES FOR ANCHOR BOLTS IN MASONRY PLATE "D" SHALL HAVE A DIAMETER 3/8" LARGER THAN ANCHOR BOLT.
- TEFLON SURFACE, USE UNFILLED WITH MINIMUM 1/16" THICKNESS. PLACE WITH SCRIBE MARKS IN DIRECTION OF MOVEMENT. BOND STEEL PLATE "B" AND TEFLON WITH ADHESIVE MATERIAL MEETING THE REQUIREMENTS FOUND IN THE STANDARD SPECIFICATION.
- PROVIDE A METHOD FOR HANDLING ROCKER PLATE "C" DURING GALVANIZING.
- AT INSTALLATION, ENSURE STAINLESS STEEL SLIDING FACE OF THE UPPER ELEMENT AND THE TFE SLIDING FACE OF THE LOWER ELEMENT HAVE THE SURFACE FINISH SPECIFIED AND ARE CLEAN AND FREE OF ALL DUST, MOISTURE, AND OTHER FOREIGN MATTER.



EXPANSION BEARING ASSEMBLY




TEMPERATURE	W. ABUT. IN.
10°	-1/16"
20°	-3/4"
30°	-7/16"
40°	-1/8"
50°	1/8"
60°	7/16"
70°	3/4"
80°	1 1/16"
90°	1 3/8"


TEMPERATURE TABLE

AT THE WEST ABUTMENT, NEGATIVE VALUE INDICATES PINTLES ARE LOCATED WEST OF THE ϕ OF TOP PLATE "A" AND POSITIVE VALUE INDICATES PINTLES ARE LOCATED EAST OF THE ϕ OF TOP PLATE "A".


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-30			
DRAWN BY		CAD	PLANS CK'D.
REPLACEMENT BEARINGS		SHEET 3	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-30			
DRAWN BY		CAD	PLANS CK'D.
JOINT REPAIR DETAILS - W. ABUT.			SHEET 4



NORMAL TO \mathbb{C} SUBSTRUCTURE




STRIP SEAL EXPANSION JOINT ASSEMBLY, INCLUDING ANCHOR STUDS AND HARDWARE
WILL BE PAID FOR AT THE LUMP SUM PRICE BID FOR "EXPANSION DEVICE B-12-30".

(10) 1" X 5" SLOTTED COUNTERSUNK HOLE FOR NO. 7. PLACE SLOT PARALLEL TO DIRECTION OF MOVEMENT.

NO.	DATE	REVISION			BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION					
STRUCTURE B-12-30					
		DRAWN BY	CAD	PLANS CK'D.	
EXPANSION DEVICE				SHEET 5	



- | | | | |
|--|------|----------|-------------|
| | | | |
| NO. | DATE | REVISION | BY |
| STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DESIGN SECTION | | | |
| STRUCTURE B-12-30 | | | |
| DRAWN BY | | CAD | PLANS CK'D. |
| COVER PLATE
DETAILS | | SHEET 6 | |
| | | | |



DOWNSPOUT EXTENSION DETAIL
(TYPICAL AT (2) FLOOR DRAIN LOCATIONS)

NOTES

BID ITEM SHALL BE "DOWNSPOUT REPAIR", WHICH INCLUDES ALL ITEMS SHOWN.

ROUND HSS TUBE MATERIAL SHALL CONFORM TO ASTM A500-GRADE B.


NEW STEEL TUBES SHALL BE SHOP PAINTED. BLAST CLEAN TO SSPC SP-6 AND USE A WELDABLE PRIMER. DO NOT APPLY FINISH COATS TO SURFACES TO BE FIELD WELDED.








THE COLOR OF THE FINISH TOP COAT SHALL BE "GRAY", FEDERAL COLOR NO. 26293

BOLTS AND NUTS SHALL CONFORM TO ASTM F3125, GRADE A325.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-30			
		DRAWN BY	PLANS CK'D.
DOWNSPOUT DETAILS		SHEET 7	

SCALE = 0.50



Conditions Legend		Orientation	Quantity Summary			General Information	
Rebar-level deterioration detected by GPR			Estimate Deck Prep Items	sq. ft.	%	Bridge ID: B-12-030	
 Increasing severity -->			Type 1	2389	14.1	Analyzed by: SB/RG	
 IE (delam)			Type 2	3943	23.3	Reviewed by: AC	
 IE (no delam)			Full-Depth	0	0.0	Completed: 09/22/17	
						Sheet 1 of 1	


NOTES

DECK SURVEY IS SHOWN FOR INFORMATION PURPOSES ONLY AND MAY NOT BE ALL INCLUSIVE. ADDITIONAL PATCHING/PREPARATION MAY BE REQUIRED AND SHALL BE PERFORMED AS DIRECTED BY THE ENGINEER.


GPR= GROUND PENETRATING RADAR
IR = INFRARED (THERMOGRAPHY)
IE = IMPACT ECHO

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-12-30			
		DRAWN BY	CAD PLANS CK'D.
DECK CONDITION SURVEY		SHEET 8	


Transitions




Posts 5



Posts 1




Posts 9



9

9




9

9

PROJECT NO: 1660-03-67/68	HWY: USH 18	COUNTY: CRAWFORD	CROSS SECTIONS: B-12-29 MGS GUARDRAIL EAT	SHEET	E
---------------------------	-------------	------------------	---	-------	---


Post 9

Post 1




Post 5

Transition



9

9



PROJECT NO: 1660-03-67/68

HWY: USH 18

COUNTY: CRAWFORD

CROSS SECTIONS: B-12-30 MGS GUARDRAIL EAT RT

SHEET

E

FILE NAME : N:\PDS\C3D\16600337\SHEETS\PLAN\090201-XS.DWG
LAYOUT NAME - 090203-xs-B-12-30 RT

PLOT DATE : 1/26/2018 8:28 AM


PLOT BY : PETERSON, SHANE J

PLOT NAME :


PLOT SCALE : 1 IN:20 FT HORZ. / 1 IN:10 FT VERT.

WISDOT/CADDs SHEET 49


Post 9




Post 1



Post 5




Transition



9

1



PROJECT NO: 1660-03-67/68

HWY: USH 18

COUNTY: CRAWFORD

CROSS SECTIONS: B-12-30 MGS GUARDRAIL EAT LT

SHEET

--	--

FILE NAME : N:\PDS\C3D\16600337\SHEETSPLAN\090201-XS.DWG
LAYOUT NAME - 090204-xs-B-12-30 LT

PLOT DATE : 1/26/2018 8:28 AM

PLOT BY : PETERSON, SHANE J

PLOT NAME :

PLOT SCALE : 1 IN:20 FT HORZ. / 1 IN:10 FT VERT.

WISDOT/CADDS SHEET 49