## FLASHING BEACON INSTALLATION APPLICATION/PERMIT DT1877 6/2010 s.86.19(3) Wis. Stats.

Wisconsin Department of Transportation

Submit application in triplicate to Wisconsin Department of Transportation, Regional office. Make separate application for each flasher or associated pair of flashers desired. See conditions for installation of flashing beacon on next page(s).

Applicant - Munici					Unit of Govern	nent (C	ounty, Town, Ci	ty, Village)
Village of Saul	c City c/o Vick	Breunig			Village			
Mailing Address 726 Water St.						Date 06/29/2017		
Name of 24/7 Emergency Contact Marv Dolphin				Contact Area Code – Telephone Number 608-643-3932			Cell or Pager Number 608-963-8707	
Description of Bea						Mounting Height		Lateral Setback
Red	Incandescent  165 w	LED*	☐ Single ☐ Pair-as separate installation		tallation	8 Feet		2 Feet From ☐ Edge of Pavement
Yellow	□ 116 w □		☐ Pair-as same installation for school speed limit signs only				☑ Face or Top of Curb	
RRFB Yellow	RRFB Yellow Solar LED w Hardware LED w		Single RRFB Indication Dual RRFB Indication					
* If LED indications	s are used, they s	nall have an equi	valent outp	out to incandes	cent indications.			
Location of Beacon Facing STH 78/ Water St		]E ]W			•	et and Webster Street		
Associated Sign  Stop  Warning			Speed Lir	mit [	Scho	ool	Other W11-15 & W1	
Reason for Erectin Great Sauk Sta		ng						,
Application is ma installation and o State Electrical C	peration of the	lashing beacor	will com	ply with the re	equiations of the	e Wisco	nsin Departm	greed that the design, ent of Transportation, the age(s).
The undersigned	certifies that he	/she is authoriz	zed to sig	n this applica	tion on behalf o	f the na	amed unit of g	overnment.
(Authorized Representative) (Date)  Character (Ottle)								
PERMIT APPROVAL  Permission is granted for the installation described above in compliance with the conditions specified.								
Permit Number	Date Iss				r Wisconsin D			
FB-	***************************************					-		
				X	/Traffic	Engine	er)	(Date)
	<u> </u>		i		(TIRIIIC	- IIAIIIC	U1 }	(Date)

## CONDITIONS FOR INSTALLATION OF FLASHING BEACON

- 1. WisDOT's policy on Beacons, General Provisions per TGM 4-5-1 is made part of this policy (copy attached).
- 2. The design, installation and operation of the flashing beacon shall comply with, the state Electrical Code, Chapter 4L of the Wisconsin Manual on Uniform Traffic Control Devices, FHWA's July 16, 2008 Interim Approval Memo (IA-11) for Rectangular Rapid Flashing Beacons (RRFBs), and local ordinances and regulations.
- 3. During the installation and subsequent maintenance, the permittee shall follow all pertinent provisions for work zone traffic control provided in Part 6 of the Wisconsin Manual of Uniform Traffic Control Devices.
- 4. The beacon may be mounted on a post, pole, or other suitable rigid support. The supports shall be outside of the curb line or on rural type highways at or beyond the shoulder line.
- 5. The beacon shall be mounted on the same support as the sign that it is to supplement.
- 6. The beacon lens shall have a diameter of 12", unless an RRFB or otherwise approved by the Department.
- 7. The support for the beacon shall be so designed and constructed that the associated sign specified may be erected on the same support immediately below the beacon, except in the case of an RRFB. For an RRFB, the associated sign should be mounted above the beacon. The beacon shall be maintained in proper working order and condition.
- 8. The permittee shall maintain the equipment in proper working order, and coordinate the installation with other right-of-way users (i.e., utilities, adjacent property owners, etc.). If not already, the permittee shall become a member of Diggers Hotline. Failure to do so will result in permit revocation.
- 9. It is the responsibility of the permittee to maintain locational information or locating flashing beacon facilities in the field for the purposes of avoiding utility conflicts.
- 10. All costs of design, installation, operation, maintenance and relocation or removal of flashing beacons installations due to road construction shall be the responsibility of the permittee.
- 11. It is the responsibility of the permittee to identify upcoming highway improvement projects that will affect flashing beacon installations and appropriately coordinate with WisDOT staff. WisDOT will not participate in sharing costs related to removal or relocation of flashing beacon facilities due to improvement projects.
- 12. The permit may be revoked upon notice in writing for failure to comply with these conditions, or upon a finding by the Department that the continued operation of the flashing beacon is not warranted.
- 13. The final location of the flashing beacon shall have the approval of the Traffic Engineer or his authorized representative.
- 14. At schools or school crossings, unless an RRFB is installed, the installation shall be equipped with an automatic time switch which shall cause the flashing beacon to operate only during the following periods:
  - a. For three-quarters of an hour before school begins in the morning;
  - b. Between the end of the morning and the beginning of the afternoon session:
  - c. For three-quarters of an hour after the end of the afternoon session.
  - d. The beacon shall operate only on school days and arrangements shall be made so that the beacon will not operate on holidays.
- 15. A concrete base, if used, shall not extend more than four (4) inches above ground level at any point.
- 16. Subsequent maintenance of In-Roadway Lights that require the permittee to access public right-of-way may require a Work on Highway Right-of-Way Permit (DT1812). Should any of these selected maintenance activities encroach in the STH traveled way, or if activities impact the free flow of traffic on the STH highway (closure of a travel lane, diversion of traffic, etc.), a permit shall first be obtained from the Department. The following are examples of work, which does not require a permit:
  - a. Buried cable locates and facility marking.
  - b. Reading electrical service meters.
  - c. Repair to electrical service.
  - d. Land surveys.
  - e. Controller programming.
  - f. Connect and test wiring of cable at pull box and pedestal locations.
  - g. Pedestal base, standard, bracket, and hardware repair/replacement.

	h.	Remove debris from warning devices.
	i.	Repair cable bonding or grounds.
	j.	Visual condition surveys.
	k.	Trim trees or remove brush for vision of warning devices.
	١.	Fuse replacement.
	m.	Replace overhead highway lighting lamps and cleaning glass.
	n.	Repair or replace outdoor lighting control.
	0.	Reset time clock or control switches.
	p.	Replace equipment tags or identifiers.
	q.	Minor repair of electrical cable (splices, etc.).
7.	Other o	onditions: □ □No □ Yes – Specify below:
		•



